

Nano Bottom Sheet — Specs (field-ds)

Oct 1, 2026 · @Anmol

Overview

Use the field-ds `BottomSheet` as it is: it is already a React Native component (Reanimated + PanResponder), and Nano's sheet copies its numbers. This page is its spec, plus the content Nano puts in it.

Component	<code>packages/components/src/BottomSheet/BottomSheet.tsx</code> in <code>field-design-system</code>
Figma (field-ds)	<code>M-BottomSheet</code> 3207:15
Figma (Nano)	<code>M-BottomSheet</code> 1015:45419 in parent-flow frame 4 (1015:45373)
Used in Nano	Parent flow → Email ID → Continue opens the "Confirm email" sheet (Yes, use this email / Edit email)
Footer	field-ds <code>ActionBar</code> ; Nano puts the Button v3 pair in it (see the Button v3 handoff)
Tokens	<code>packages/tokens</code> (<code>semantic.ts</code> , <code>base.ts</code> , raw JSON)

Visual specs

The sheet floats: a white card inset 12pt from each side, all four corners rounded 16pt, with the grabber inside its top and the home indicator below it, outside the card.

Sheet (field-ds)

Token	Value	field-ds source
Horizontal inset	12pt each side	<code>space["12"]</code>
Corner radius	16pt, all four corners	<code>radius["16"]</code>
Background	<code>#FFFFFF</code>	<code>colour.surface.primary</code>

Token	Value	field-ds source
Shadow	#000000 at 12%, offset y -2, radius 16; Android elevation 16	<code>SHADOW_TINT</code>
Max height	680pt, no detents; content scrolls inside if taller	<code>SHEET_MAX_HEIGHT</code>
Overflow	hidden	
Header slot	min height 48pt	<code>HEADER_MIN_H</code>
Footer	<code>ActionBar</code> (layout single, tone action, label Continue by default)	

Grabber and home indicator

Token	Value
Grabber bar	36 × 4pt, radius 2, rgba(255, 255, 255, 0.64)
Grabber hit area	full sheet width, 12pt above and below the bar
Home indicator	134 × 5pt, fully rounded, #FFFFFF; stays still while the sheet drags
Home indicator block	20 + 5 + 8 = 33pt without a safe-area inset; with one, 20 + 5 + inset.bottom
Sheet bottom	sits on top of the home indicator block

Scrim

Token	Value
Colour	#000000CC (black at 80%), <code>colour.surface["overlay-bold"]</code>
Opacity	animated 0 → 1 on top of the 80% colour
Tap	dismisses the sheet (<code>accessibilityLabel="Dismiss bottom sheet"</code>)

Nano's content (Confirm email sheet, 1015:45419)

Element	Spec
Art	Lottie, 235 × 125pt, 24pt above, 12pt below
Title	Noontree Bold 20, tracking -0.25, line height 28, #1D2539
Text block	12pt horizontal, 8pt vertical padding; secondary text #666D85
Email pill	height 48, 24pt horizontal padding, capsule, 1pt #F2F3F7 border; 12pt horizontal, 20pt vertical margin
Buttons	Button v3: dark "Yes, use this email" over white "Edit email", 52pt each, 12pt gap, 12pt padding

Motion timesheet

One shared value, `progress` (0 hidden → 1 shown), drives both the sheet and the scrim on the field-ds `springLight` spring; it settles in about 330 ms. Drag adds a second value, `dragOffsetY`.

Present (`open = true`)

#	Track	Property	From → To	Start	Duration	Curve
1	Sheet + grabber	<code>translateY</code>	<code>slideDistance</code> → 0	0 ms	~330 ms to settle	<code>springLight</code>
2	Scrim	<code>opacity</code>	0 → 1 (of the 80% black)	0 ms	same spring, linear in <code>progress</code>	<code>springLight</code>
3	Home indicator	—	static	—	—	—

`slideDistance` = window height in `modal` mode, the measured container height in `inline` mode. `translateY` = $(1 - \text{progress}) \times \text{slideDistance} + \text{dragOffsetY}$.

Dismiss (`open = false`, scrim tap, Android back, or drag past threshold)

#	Track	Property	From → To	Start	Duration	Curve
1	Sheet	<code>translateY</code>	current → <code>slideDistance</code>	0 ms	~330 ms	<code>springLight</code>

#	Track	Property	From → To	Start	Duration	Curve
2	Drag offset	dragOffsetY	current → 0	0 ms	~330 ms	springLight (springs, never snaps, so a drag-close does not jump)
3	Stretch	expansionProgress	current → 0	0 ms	~330 ms	springLight
4	Scrim	opacity	current → 0	0 ms	follows progress	springLight
5	Component	unmount	—	when the spring finishes	—	—

Drag (grabber only)

Gesture	Effect	Formula
Pull down	Sheet follows the finger 1:1, no rubber-band	<code>dragOffsetY = dy</code>
Pull down	Scrim fades out over a 200pt pull	<code>scrim = progress × (1 - min(1, dragOffsetY / 200))</code>
Pull up	Stretch: gaps open between sections; the sheet does not grow	<code>expansion = clamp(0, 1, -dy / 80) ; gap = expansion × 16pt</code> after the header and after the body
Release, $dy > 60pt$	Close	<code>onClose()</code> → Dismiss above
Release, $dy \leq 60pt$	Settle back	<code>dragOffsetY</code> → 0 on springLight; <code>expansion</code> → 0 on springBouncy (~510 ms, a small bounce)
Gesture terminated	Settle back	both on springLight

No velocity or fling check and no snap points: only the 60pt distance decides.

Springs (Reanimated `withSpring` configs, mass 1, `overshootClamping: false`, rest thresholds 0.01)

Token	Stiffness	Damping	Damping ratio	Settles in
springLight	300	28	0.81	~330 ms

Token	Stiffness	Damping	Damping ratio	Settles in
springBouncy	280	18	0.54	~510 ms

Reduced motion (`useReducedMotion`): every value snaps; no springs.

Behaviour and React Native notes

- 1. Mount it as-is.** `<BottomSheet open onClose presentation="modal" headerSlot bodySlot footer />`. Modal mode renders a transparent RN `Modal` (`animationType="none"`), so Android back calls `onClose`.
- 2. Gestures live on the grabber only.** The body does not drag; content can scroll inside it up to the 680pt max height.
- 3. Keyboard.** The sheet has no keyboard handling. Nano dismisses the keyboard before raising the sheet; on Edit email it refocuses the field 300 ms after the sheet starts closing.
- 4. Haptics.** The sheet has none. The only haptics are the Button v3 taps on its buttons (see the Button v3 handoff).
- 5. Nano's flow around it.**
 - Continue on Email ID opens it. "Yes, use this email" confirms and pushes the next page; the sheet leaves with the page crossfade (0.35 s ease-in-out).
 - "Edit email" or a drag past 60pt closes it. The parent progress bar returns 400 ms later, once the scrim has faded.
 - The stretch opens three gaps in Nano's content (after the art, the text and the pill), each 16pt × expansion. field-ds opens two (after header, after body); use field-ds.

Where the iOS prototype differs from field-ds (follow field-ds):

	iOS prototype	field-ds
Shadow radius	8	16
Hidden position	fixed 520pt offset	full window height
Home strip	fixed 33pt	33pt, or 25pt + safe-area inset
Open/close trigger	spring 320 / 28	springLight 300 / 28
Android elevation	—	16