

GENERATION OF SINE WAVE USING DSP KIT

Aim

To generate a sine wave using DSP kit.

Theory

Sinusoidal are the most smooth signals with no abrupt variation in their amplitude, the amplitude witnesses gradual change with time. Sinusoidal signals can be defined as a periodic signal with waveform as that of a sine wave. The amplitude of sine wave increase from a value of 0 at 0° angle to a maximum value of 1 at 90° , it further reaches its minimum value of -1 at 270° and then return to 0 at 360° . After any angle greater than 360° , the sinusoidal signal repeats the values so we can say that time period of sinusoidal signal is 2π i.e. 360° . If we observe the graph, we can see that the amplitude varying gradually with a maximum value of 1 and a minimum value of -1. We can also observe that the wave begins to repeat its value after a time period or angle value of 2π hence periodicity of sinusoidal signal is 2π .

These are sinusoidal signal parameters:

- Graph: It is a plot used to depict the relation between quantities. Depending upon the number of variables, we can decide to number of axes each perpendicular to the other.
- Time period: The period for a signal can be defined as the time taken by a periodic signal to complete one cycle.
- Amplitude: Amplitude can be defined as the maximum distance between the horizontal axis and the vertical position of any signal.
- Frequency: This can be defined as the number of times a signal oscillates in one second. It can be mathematically defined as the reciprocal of a period.
- Phase: It can be defined as the horizontal position of a waveform in one oscillation. The symbol θ is used to indicate the phase.

If we consider a sinusoidal signal $y(t)$ having an amplitude A , frequency f , and of quantity then we can represent the signal as

$$y(t) = A \sin(2\pi ft + \theta)$$

If we denote $2\pi f$ as an angular frequency ω then we can re-write the signal as

$$y(t) = A \sin(\omega t + \theta)$$

Procedure

1. Open Code Composer Studio,
Click on File - New – CCS Project
Select the Target – C674X Floating point DSP , TMS320C6748 , and
Connection – Texas Instruments XDS 100v2 USB Debug Probe and Verify.
Give the project name and select Finish.
2. Type the code program for generating the sine wave and choose File – Save As and then
save the program with a name including ‘main.c’.
Delete the already existing main.c program.
3. Select Debug and once finished, select the Run option.
4. From the Tools Bar, select Graphs – Single Time.
Select the DSP Data Type as 32-bit Floating point and time display unit as second(s).
Change the Start address with the array name used in the program(here,a).
5. Click OK to apply the settings and Run the program or click Resume in CCS.

Program

```
#include<stdio.h>

#include <math.h>

#define pi 3.1415625

float a[200];

voidmain()
{
    int i;

    float f=100,Fs=10000;

    for(i=0;i<100;i++)
a[i]=sin(2*pi*f*i/Fs);
}
```

Result

Generated a sine wave using DSP kit.

Observation

