

2 UML for OOAD

2.1 What is UML?

2.2 Classes in UML

2.3 Relations in UML

2.4 Static and Dynamic Design with UML

2.1 UML Background

”The Unified Modelling Language (UML) is a graphical language for visualizing, specifying, constructing, and documenting the artifacts of a software-intensive system. The UML offers a standard way to write a systems blueprints, including conceptual things like such as business processes and system functions as well as concrete things such as programming language statements, database schemas, and reusable software components.”

Grady Booch, Ivar Jacobsen, Jim Rumbaugh
Rational Software

[OMG Unified Modelling Language Specification, Version 1.3, March 2000]

2.1 Brief UML History

- Around 1980
 - first OO modelling languages
 - other techniques
- Around 1990
 - "OO method wars"
 - many modelling languages
- End of 90's
 - UML appears as combination of best practices


2.1 Why UML?

- Physicists know formal graphical modelling
 - Mathematics to describe nature
 - Feynman graphs to calculate particle reaction rates
- We need a common language
 - discuss software systems at a black- (white-) board
 - document software systems
 - UML is an important part of that language
 - UML provides the "words and grammar"

2.2 Classes in UML

- Classes describe objects
 - Interfaces (member function signature)
 - Behaviour (member function implementation)
 - State bookkeeping (values of data members)
 - Creation and destruction
- Objects described by classes collaborate
 - Relations between classes (objects)
 - Dependencies between classes

2.2 UML Class



Data members, arguments and methods are specified by
visibility **name** : **type**


2.2 Class Name

The top compartment contains the class name

Abstract classes have italicised names

Abstract methods also have italicised names

Stereotypes are used to identify groups of classes, e.g interfaces or persistent (storeable) classes



2.2 Class Attributes

Attributes are the instance
and class data members


Class data members (underlined)
are shared between all instances
(objects) of a given class

Data types shown after ":"

Visibility shown as

- + public
- private
- # protected

Attribute
compartment




visibility name : type

2.2 Class Operations (Interface)

Operations are the class methods with their argument and return types

Public (+) operations define the class interface

Class methods (underlined) have only access to class data members, no need for a class instance (object)



visibility name : type

Operations
compartment

2.2 Visibility

+

public

Anyone can access

Interface operations

Not data members

—

private

Noone can access

Data members

Helper functions

”Friends” are allowed
in though

#

protected

Subclasses can access

Operations where sub-
classes collaborate


Not data members
(creates dependency
off subclass on im-
plementation of parent)

2.3 Relations

- Association
- Aggregation
- Composition
- Dependence
- Inheritance

2.3 Binary Association

Binary association: both classes know each other




Usually "knows about" means a pointer or reference

Other methods possible: method argument, tables, database, ...

Implies dependency cycle


2.3 Unary Association

A knows about B, but B knows nothing about A




2.3 Aggregation

Aggregation = Association with "whole-part" relationship



2.3 Composition

Composition = Aggregation with lifetime control



```
double mInv() {
    double minv2= momentum.magSquared();
    return minv2<0?-sqrt(-minv2):sqrt(minv2);
}
```

Shown by filled diamond at the "owner" side

Lifetime control implied


Lifetime control can be tranferred

Lifetime control: construction and destruction controlled by "owner"
→ call constructors and destructors (or have somebody else do it)

2.3 Association Details

Name gives details of association

Name can be viewed as verb of a sentence




Notes at association ends
explain "roles" of classes (objects)

Multiplicities show number of
objects which participate in the
association

2.3 Friendship

Friends are granted access to private data members and member functions

Friendship is given to other classes, never taken



Bob Martin:

More like lovers than friends


You can have many friends

You should not have many lovers

Friendship breaks data hiding, use carefully


2.3 Parametric Association

Association mediated by a parameter (function call argument)



A depends upon B, because it uses B
No data member of type B in A


2.3 Inheritance



2.3 Associations Summary

- Can express different kinds of associations between classes/objects with UML
 - Association, aggregation, composition, inheritance
 - Friendship, parametric association
- Can go from simple sketches to more detailed design by adding *adornments*
 - Name, roles, multiplicities
 - lifetime control

2.3 Multiple Inheritance




The derived class inherits interface, behaviour and data members of all its base classes

Extension and overriding works as before

B implements the interface A and is also a "countable" class

2.3 Deadly Diamond of Death



Now the @*#! hits the %&\$

Data members of **TObject** are inherited twice in **B**, which ones are valid?

Fortunately, there is a solution to this problem:

→ virtual inheritance
only one copy of a multiply inherited structure will be created


2.4 Static and Dynamic Design

- Static design describes code structure and object relations
 - Class relations
 - Objects at a given time
- Dynamic design shows communication between objects
 - Similarity to class relations
 - can follow sequences of events


2.4 Class Diagram

- Show static relations between classes
 - we have seen them already
 - interfaces, data members
 - associations
- Subdivide into diagrams for specific purpose
 - showing all classes usually too much
 - ok to show only relevant class members
 - set of all diagrams should describe system

2.4 Object Diagram



Class diagram
never changes




Object diagram shows
relations at instant in time
(snapshot)


Object relations are drawn
using the class association
lines

2.4 Sequence Diagram


Show sequence of events for a particular use case



2.4 Sequence Diagram




2.4 Sequence Diagram



Slanted messages take some time

Can model real-time systems


2.4 Sequence Diagram



Crossing message lines
are a bad sign

→ race conditions

2.4 Collaboration Diagram



Object diagram with
numbered messages

Sequence numbers of messages
are nested by procedure call

2.4 Static and Dynamic Design Summary

- Class diagrams → object diagrams
 - classes → objects; associations → links
- Dynamic models show how system works
 - Sequence and collaboration diagram
- There are tools for this process
 - UML syntax and consistency checks
- Rough sketches by hand or with simple tools
 - aid in design discussions

Some Comments

- Design-heavy development processes
 - several 10% of person-power/time spent on design with formal UML from requirements
 - start coding when the design is consistent
 - large software houses may work this way
- Lighter processes
 - a few % of person-power/time spent with UML
 - UML as a discussion and documentation aid
 - probably more adequate in HEP