

# Nu Html Checker

This tool is an ongoing experiment in better HTML checking, and its behavior remains subject to change

## Showing results for contents of text-input area

Checker Input

Show

☒ source

☐ outline

☐ image report

Options...

Check by

text input

☐ CSS

```
<!DOCTYPE html>
<html lang="fr">
  <head>
    <meta charset="utf-8" />
    <link rel="icon" href="./favicon.png" />
    <meta name="viewport" content="width=device-width, initial-scale=1" />
    <meta name="theme-color" content="#000000" />
    <meta
      name="description"
      content="Web site created using create-react-app"
    />
    <link rel="apple-touch-icon" href="%PUBLIC_URL%/logo192.png" />
    <link rel="manifest" href="%PUBLIC_URL%/manifest.json" />

    <link
```

Check

Press the Message Filtering button to collapse the filtering options and error/warning/info counts.

### Message Filtering

Errors (487) · [Hide all errors](#) · [Show all errors](#)

- 1 Bad value  for attribute  on element : Percentage ("%") is not followed by two hexadecimal digits. (2) · [Hide all](#) · [Show all](#)
  - 1.1 ☒ Bad value  for attribute  on element : Percentage ("%") is not followed by two hexadecimal digits.
  - 1.2 ☒ Bad value  for attribute  on element : Percentage ("%") is not followed by two hexadecimal digits.

2 Attribute `___` not allowed on element `___` at this point. (285) · [Hide all](#) · [Show all](#)

- 2.1 ☒ Attribute `to` not allowed on element `link` at this point. (22)
- 2.2 ☒ Attribute `classname` not allowed on element `link` at this point. (21)
- 2.3 ☒ Attribute `${location.pathname}` not allowed on element `link` at this point. (5)
- 2.4 ☒ Attribute `'` not allowed on element `link` at this point. (5)
- 2.5 ☒ Attribute `?` not allowed on element `link` at this point. (5)
- 2.6 ☒ Attribute `'active'` not allowed on element `link` at this point. (5)
- 2.7 ☒ Attribute `:` not allowed on element `link` at this point. (5)
- 2.8 ☒ Attribute `""} }` not allowed on element `link` at this point. (5)
- 2.9 ☒ Attribute `service'` not allowed on element `link` at this point.
- 2.10 ☒ Attribute `realisations'` not allowed on element `link` at this point.
- 2.11 ☒ Attribute `blog'` not allowed on element `link` at this point.
- 2.12 ☒ Attribute `contact'` not allowed on element `link` at this point.
- 2.13 ☒ Attribute `classname` not allowed on element `div` at this point. (68)
- 2.14 ☒ Attribute `classname` not allowed on element `button` at this point. (5)
- 2.15 ☒ Attribute `classname` not allowed on element `h5` at this point. (8)
- 2.16 ☒ Attribute `classname` not allowed on element `p` at this point. (20)
- 2.17 ☒ Attribute `classname` not allowed on element `img` at this point. (7)
- 2.18 ☒ Attribute `width:` not allowed on element `div` at this point. (5)
- 2.19 ☒ Attribute `"90%"` not allowed on element `div` at this point.
- 2.20 ☒ Attribute `}}` not allowed on element `div` at this point. (5)
- 2.21 ☒ Attribute `"80%"` not allowed on element `div` at this point.
- 2.22 ☒ Attribute `"70%"` not allowed on element `div` at this point.
- 2.23 ☒ Attribute `"60%"` not allowed on element `div` at this point.
- 2.24 ☒ Attribute `"50%"` not allowed on element `div` at this point.
- 2.25 ☒ Attribute `htmlfor` not allowed on element `label` at this point. (5)
- 2.26 ☒ Attribute `classname` not allowed on element `input` at this point. (4)
- 2.27 ☒ Attribute `classname` not allowed on element `i` at this point. (20)
- 2.28 ☒ Attribute `border:` not allowed on element `iframe` at this point.
- 2.29 ☒ Attribute `0` not allowed on element `iframe` at this point.
- 2.30 ☒ Attribute `}}` not allowed on element `iframe` at this point.
- 2.31 ☒ Attribute `classname` not allowed on element `h2` at this point. (3)
- 2.32 ☒ Attribute `classname` not allowed on element `a` at this point. (5)

- 2.33 ☒ Attribute `color:` not allowed on element `i` at this point. (14)
- 2.34 ☒ Attribute `"#000000"` not allowed on element `i` at this point. (3)
- 2.35 ☒ Attribute `}}` not allowed on element `i` at this point. (14)
- 2.36 ☒ Attribute `classname` not allowed on element `u1` at this point. (3)
- 2.37 ☒ Attribute `"#0d6efd"` not allowed on element `i` at this point. (11)
- 3 ☒ Element `link` is missing one or more of the following attributes: `href`, `itemprop`, `property`, `rel`, `resource`. (22)
- 4 ☒ A `link` element must have an `href` or `imagesrcset` attribute, or both. (25)
- 5 ☒ A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`. (25)
- 6 ☒ Stray end tag `link`. (25)
- 7 ☒ ``` in an unquoted attribute value. Probable cause: Using the wrong character as a quote. (5)
- 8 ☒ `=` at the start of an unquoted attribute value. Probable cause: Stray duplicate equals sign. (5)
- 9 ☒ `=` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value. (5)
- 10 ☒ Saw `'` when expecting an attribute name. Probable cause: `=` missing immediately before. (6)
- 11 ☒ A slash was not immediately followed by `>`. (5)
- 12 ☒ Duplicate attribute `'`.
- 13 Quote `___` in attribute name. Probable cause: Matching quote missing somewhere earlier. (62) · [Hide all](#) · [Show all](#)
- 13.1 ☒ Quote `'` in attribute name. Probable cause: Matching quote missing somewhere earlier. (14)
- 13.2 ☒ Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier. (48)
- 14 Bad value `___` for attribute `___` on element `___`: Illegal character in path segment: `___` is not allowed. (7) · [Hide all](#) · [Show all](#)
- 14.1 ☒ Bad value `{photoProfil}` for attribute `src` on element `img`: Illegal character in path segment: `{` is not allowed.
- 14.2 ☒ Bad value `{blog1}` for attribute `src` on element `img`: Illegal character in path segment: `{` is not allowed.
- 14.3 ☒ Bad value `{blog2}` for attribute `src` on element `img`: Illegal character in path segment: `{` is not allowed.
- 14.4 ☒ Bad value `{blog3}` for attribute `src` on element `img`: Illegal character in path segment: `{` is not allowed.
- 14.5 ☒ Bad value `{blog4}` for attribute `src` on element `img`: Illegal character in path segment: `{` is not allowed.
- 14.6 ☒ Bad value `{blog5}` for attribute `src` on element `img`: Illegal character in path segment: `{` is not allowed.
- 14.7 ☒ Bad value `{blog6}` for attribute `src` on element `img`: Illegal character in path segment: `{` is not allowed.
- 15 Element `___` not allowed as child of element `___` in this context. (Suppressing further errors from this subtree.) (2) · [Hide all](#) · [Show all](#)

- 15.1 ☒ Element `imagedynamic` not allowed as child of element `main` in this context. (Suppressing further errors from this subtree.)
- 15.2 ☒ Element `adress` not allowed as child of element `div` in this context. (Suppressing further errors from this subtree.)
- 16 ☒ Self-closing syntax (`/>`) used on a non-void HTML element. Ignoring the slash and treating as a start tag. (2)
- 17 ☒ End tag `main` seen, but there were open elements.
- 18 ☒ Unclosed element `imagedynamic`. (2)

**Warnings (95)** · [Hide all warnings](#) · [Show all warnings](#)

- 1 Attribute `___` is not serializable as XML 1.0. (94) · [Hide all](#) · [Show all](#)
  - 1.1 ☒ Attribute `${location.pathname}` is not serializable as XML 1.0. (5)
  - 1.2 ☒ Attribute `'` is not serializable as XML 1.0. (5)
  - 1.3 ☒ Attribute `?` is not serializable as XML 1.0. (5)
  - 1.4 ☒ Attribute `'active'` is not serializable as XML 1.0. (5)
  - 1.5 ☒ Attribute `:` is not serializable as XML 1.0. (5)
  - 1.6 ☒ Attribute `""}~}` is not serializable as XML 1.0. (5)
  - 1.7 ☒ Attribute `service'` is not serializable as XML 1.0.
  - 1.8 ☒ Attribute `realisations'` is not serializable as XML 1.0.
  - 1.9 ☒ Attribute `blog'` is not serializable as XML 1.0.
  - 1.10 ☒ Attribute `contact'` is not serializable as XML 1.0.
  - 1.11 ☒ Attribute `width:` is not serializable as XML 1.0. (5)
  - 1.12 ☒ Attribute `"90%"` is not serializable as XML 1.0.
  - 1.13 ☒ Attribute `}}` is not serializable as XML 1.0. (20)
  - 1.14 ☒ Attribute `"80%"` is not serializable as XML 1.0.
  - 1.15 ☒ Attribute `"70%"` is not serializable as XML 1.0.
  - 1.16 ☒ Attribute `"60%"` is not serializable as XML 1.0.
  - 1.17 ☒ Attribute `"50%"` is not serializable as XML 1.0.
  - 1.18 ☒ Attribute `border:` is not serializable as XML 1.0.
  - 1.19 ☒ Attribute `0` is not serializable as XML 1.0.
  - 1.20 ☒ Attribute `color:` is not serializable as XML 1.0. (14)
  - 1.21 ☒ Attribute `"#000000"` is not serializable as XML 1.0. (3)
  - 1.22 ☒ Attribute `"#0d6efd"` is not serializable as XML 1.0. (11)
- 2 ☒ Section lacks heading. Consider using `h2` - `h6` elements to add identifying headings to all sections, or else use a `div` element instead for any cases where no heading is needed.

**Info messages (28)** · [Hide all info messages](#) · [Show all info messages](#)

- 1 ☒ Trailing slash on void elements has no effect and interacts badly with unquoted attribute values. (28)

1. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 4, column 5; to line 4, column 28](#)

```
head>↵    <meta charset="utf-8" />↵    <
```

2. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 5, column 5; to line 5, column 44](#)

```
8" />↵    <link rel="icon" href="./favicon.png" />↵    <
```

3. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 6, column 5; to line 6, column 74](#)

```
g" />↵    <meta name="viewport" content="width=device-width, initial-scale=1" />↵    <
```

4. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 7, column 5; to line 7, column 49](#)

```
1" />↵    <meta name="theme-color" content="#000000" />↵    <
```

5. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 8, column 5; to line 11, column 6](#)

```
0" />↵    <meta↵        name="description"↵        content="Web site created using create-react-app"↵    />↵    <
```

6. **Error** Bad value `%PUBLIC_URL%/logo192.png` for attribute `href` on element [link](#): Percentage ("%") is not followed by two hexadecimal digits.

[From line 12, column 5; to line 12, column 67](#)

```
/>↵    <link rel="apple-touch-icon" href="%PUBLIC_URL%/logo192.png" />↵    <
```

7. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 12, column 5; to line 12, column 67](#)

```
/>↵ <link rel="apple-touch-icon" href="%PUBLIC_URL%/logo192.png" />↵ <
```

8. **Error** Bad value `%PUBLIC_URL%/manifest.json` for attribute `href` on element [link](#): Percentage ("%") is not followed by two hexadecimal digits.

[From line 13, column 5; to line 13, column 61](#)

```
g" />↵ <link rel="manifest" href="%PUBLIC_URL%/manifest.json" />↵↵
```

9. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 13, column 5; to line 13, column 61](#)

```
g" />↵ <link rel="manifest" href="%PUBLIC_URL%/manifest.json" />↵↵
```

10. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 15, column 5; to line 20, column 6](#)

```
" />↵ <link↵ href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"↵  
rel="stylesheet"↵ integrity="sha384-  
QWTKZyjpPEjISv5WaRU90FeRpok6YctnYmDr5pNlyT2bRjXh0JMhJy6hW+ALEwIH"↵ crossorigin="anonymous"↵ />↵
```

11. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 21, column 5; to line 24, column 6](#)

```
/>↵ <link↵ rel="stylesheet"↵ href="https://cdnjs.cloudflare.com/ajax/libs/font-  
awesome/6.0.0-beta3/css/all.min.css"↵ />↵ <
```

12. **Error** Attribute `to` not allowed on element [link](#) at this point.

[From line 40, column 11; to line 40, column 44](#)

```
<Link class="navbar-brand" to="/">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

13. **Error** Element [link](#) is missing one or more of the following attributes: `href`, `itemprop`, `property`, `rel`, `resource`.

[From line 40, column 11; to line 40, column 44](#)

```
<Link class="navbar-brand" to="/">
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)



[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

14. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 40, column 11; to line 40, column 44](#)

```
<Link class="navbar-brand" to="/">
```

15. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 40, column 11; to line 40, column 44](#)

```
<Link class="navbar-brand" to="/">
```

16. **Error** Stray end tag `link`.

[From line 42, column 11; to line 42, column 17](#)

```
</Link><␣
```

17. **Error** ``` in an unquoted attribute value. Probable cause: Using the wrong character as a quote.

[At line 57, column 41](#)

```
"/" className={`nav-link ${loc
```

18. **Error** `=` at the start of an unquoted attribute value. Probable cause: Stray duplicate equals sign.

[At line 57, column 72](#)

```
tion.pathname === '/' ? 'activ
```

19. **Error** `=` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

[At line 57, column 73](#)

```
ion.pathname === '/' ? 'active
```

20. **Error** Saw `'` when expecting an attribute name. Probable cause: `=` missing immediately before.

[At line 57, column 75](#)

```
n.pathname === '/' ? 'active'
```

21. **Error** A slash was not immediately followed by `>`.

[At line 57, column 77](#)

```
pathname === '/' ? 'active' :
```

22. **Error** Saw `'` when expecting an attribute name. Probable cause: `=` missing immediately before.

[At line 57, column 77](#)

```
pathname === '/' ? 'active' :
```

23. **Error** Duplicate attribute `'`.

[At line 57, column 78](#)

```
athname === '/' ? 'active' :
```

24. **Error** Quote `'` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 57, column 81](#)

```
name === '/' ? 'active' : ""}`
```

25. **Error** Quote `'` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 57, column 88](#)

```
= '/' ? 'active' : ""}`}>
```

26. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 57, column 92](#)

```
' ? 'active' : ""}`}>
```

27. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 57, column 93](#)

```
? 'active' : ""}`}>
```

28. **Warning** Attribute `${location.pathname}` is not serializable as XML 1.0.

[From line 57, column 17; to line 57, column 97](#)

```
<Link to="/" className={`nav-link ${location.pathname === '/' ? 'active' : ""}`}>
```

29. **Warning** Attribute `'` is not serializable as XML 1.0.

[From line 57, column 17; to line 57, column 97](#)

```
<Link to="/" className={`nav-link ${location.pathname === '/' ? 'active' : ""}`}>
```

30. **Warning** Attribute `?` is not serializable as XML 1.0.

[From line 57, column 17; to line 57, column 97](#)

```
<Link to="/" className={`nav-link ${location.pathname === '/' ? 'active' : ""}`}>
```

31. **Warning** Attribute `'active'` is not serializable as XML 1.0.

[From line 57, column 17; to line 57, column 97](#)

```
<Link to="/" className={`nav-link ${location.pathname === '/' ? 'active' : ""}`}>
```

32. **Warning** Attribute `:` is not serializable as XML 1.0.

[From line 57, column 17; to line 57, column 97](#)

```
<Link to="/" className={`nav-link ${location.pathname === '/' ? 'active' : ""}`}>
```

33. **Warning** Attribute `""}``}` is not serializable as XML 1.0.

[From line 57, column 17; to line 57, column 97](#)

```
<Link to="/" className={`nav-link ${location.pathname === '/' ? 'active' : ""}`}>
```

34. **Error** Attribute `to` not allowed on element `link` at this point.

[From line 57, column 17; to line 57, column 97](#)

```
<Link to="/" className={`nav-link ${location.pathname === '/' ? 'active' : ""}`}>
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

35. **Error** Attribute `classname` not allowed on element `link` at this point.

[From line 57, column 17; to line 57, column 97](#)

```
<Link to="/" classname={`nav-link ${location.pathname === '/' ? 'active' : ''}`}>↵
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

36. **Error** Attribute `${location.pathname}` not allowed on element [link](#) at this point.

[From line 57, column 17; to line 57, column 97](#)

```
<Link to="/" className={`nav-link ${location.pathname === '/' ? 'active' : ""}`}><
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

37. **Error** Attribute `'` not allowed on element `link` at this point.

[From line 57, column 17; to line 57, column 97](#)

```
<Link to="/" className={` nav-link ${location.pathname === '/' ? 'active' : ""}`}><
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

38. **Error** Attribute `?` not allowed on element `link` at this point.

[From line 57, column 17; to line 57, column 97](#)

```
<Link to="/" className={`nav-link ${location.pathname === '/' ? 'active' : ''}`}>↵
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled



[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

39. **Error** Attribute `'active'` not allowed on element [link](#) at this point.

[From line 57, column 17; to line 57, column 97](#)

```
<Link to="/" className={`nav-link ${location.pathname === '/' ? 'active' : ""}`}><
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

40. **Error** Attribute `:` not allowed on element `link` at this point.

[From line 57, column 17; to line 57, column 97](#)

```
<Link to="/" className={`nav-link ${location.pathname === '/' ? 'active' : ""}`}>
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

41. **Error** Attribute `""}``` not allowed on element `link` at this point.

[From line 57, column 17; to line 57, column 97](#)

```
<Link to="/" className={`nav-link ${location.pathname === '/' ? 'active' : ""}`}>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

42. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

[From line 57, column 17; to line 57, column 97](#)

```
<Link to="/" className={`nav-link ${location.pathname === '/' ? 'active' : ''}`}><
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

43. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 57, column 17; to line 57, column 97](#)

```
<Link to="/" className={`nav-link ${location.pathname === '/' ? 'active' : ''}`}>↵
```

44. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 57, column 17; to line 57, column 97](#)

```
<Link to="/" className={`nav-link ${location.pathname === '/' ? 'active' : ''}`}>↵
```

45. **Error** Stray end tag `link`.

[From line 59, column 17; to line 59, column 23](#)

```
</Link><␣
```

46. **Error** ``` in an unquoted attribute value. Probable cause: Using the wrong character as a quote.

[At line 62, column 48](#)

```
ce" className={`nav-link ${loc
```

47. **Error** `=` at the start of an unquoted attribute value. Probable cause: Stray duplicate equals sign.

[At line 62, column 79](#)

```
tion.pathname === '/service' ?
```

48. **Error** `=` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

[At line 62, column 80](#)

```
ion.pathname === '/service' ?
```

49. **Error** Saw `'` when expecting an attribute name. Probable cause: `=` missing immediately before.

[At line 62, column 82](#)

```
n.pathname === '/service' ? 'a
```

50. **Error** A slash was not immediately followed by `>`.

[At line 62, column 84](#)

```
pathname === '/service' ? 'act
```

51. **Error** Quote `'` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 62, column 91](#)

```
e === '/service' ? 'active' :
```

52. **Error** Quote `'` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 62, column 95](#)

```
= '/service' ? 'active' : ""}`
```

53. **Error** Quote `'` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 62, column 102](#)

```
vice' ? 'active' : ""}`>
```

54. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 62, column 106](#)

```
' ? 'active' : ""}`>
```

55. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 62, column 107](#)

```
? 'active' : ""}`>
```

56. **Warning** Attribute `${location.pathname}` is not serializable as XML 1.0.

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ""}`}>
```

57. **Warning** Attribute `'` is not serializable as XML 1.0.

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ""}`}>
```

58. **Warning** Attribute `service` is not serializable as XML 1.0.

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ''}`}>
```

><

59. **Warning** Attribute `?` is not serializable as XML 1.0.

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ''}`}>
```

><

60. **Warning** Attribute `'active'` is not serializable as XML 1.0.

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ''}`}>
```

><

61. **Warning** Attribute `:` is not serializable as XML 1.0.

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ''}`}>
```

><

62. **Warning** Attribute `""}``` is not serializable as XML 1.0.

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ''}`}>
```

><

63. **Error** Attribute `to` not allowed on element `link` at this point.

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ''}`}>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

64. **Error** Attribute `classname` not allowed on element [link](#) at this point.

From line 62, column 17; to line 62, column 111

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ''}`}>
```

Attributes for element [link](#):



[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

65. **Error** Attribute `${location.pathname}` not allowed on element [link](#) at this point.

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ''}`
```

>

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

66. **Error** Attribute `'` not allowed on element `link` at this point.

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ''}`}>  
</>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

67. **Error** Attribute `service` not allowed on element [link](#) at this point.

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ''}}`
```



Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

68. **Error** Attribute `?` not allowed on element `link` at this point.

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ''}`}  
>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

69. **Error** Attribute 'active' not allowed on element [link](#) at this point.

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ""}`}  
>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="[preload](#)")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="[preload](#)")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="[preload](#)" and [rel](#)="[modulepreload](#)")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

70. **Error** **Attribute** `:` **not allowed on element** `link` **at this point.**

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ''}`}
>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="[icon](#)")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="[preload](#)")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="[preload](#)")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

71. **Error** Attribute `""`}`` not allowed on element [link](#) at this point.

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ""}`}
><
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

72. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ''}`}
></>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")



[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

73. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ''}`}>
```

74. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 62, column 17; to line 62, column 111](#)

```
<Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' : ''}`}>
```

75. **Error** Stray end tag `link`.

[From line 64, column 17; to line 64, column 23](#)

```
</Link>
```

76. **Error** ``` in an unquoted attribute value. Probable cause: Using the wrong character as a quote.

[At line 67, column 54](#)

```
ns" className={`nav-link ${loc
```

77. **Error** `=` at the start of an unquoted attribute value. Probable cause: Stray duplicate equals sign.

[At line 67, column 85](#)

```
tion.pathname === '/realisatio
```

78. **Error** `=` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

[At line 67, column 86](#)

```
ion.pathname === '/realisation'
```

79. **Error** Saw `'` when expecting an attribute name. Probable cause: `=` missing immediately before.

[At line 67, column 88](#)

```
n.pathname === '/realisations'
```

80. **Error** A slash was not immediately followed by `>`.

[At line 67, column 90](#)

```
pathname === '/realisations' ?
```

81. **Error** Quote `'` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 67, column 102](#)

```
'/realisations' ? 'active' :
```

82. **Error** Quote `'` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 67, column 106](#)

```
ealisations' ? 'active' : ""}`
```

83. **Error** Quote `'` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 67, column 113](#)

```
ions' ? 'active' : ""}`}>↵
```

84. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 67, column 117](#)

```
' ? 'active' : ""}``}><
```

85. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 67, column 118](#)

```
? 'active' : ""}``}><
```

86. **Warning** Attribute `${location.pathname}` is not serializable as XML 1.0.

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname} === '/realisations' ?  
'active' : ""}``}><
```

87. **Warning** Attribute `'` is not serializable as XML 1.0.

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname} === '/realisations' ?  
'active' : ""}``}><
```

88. **Warning** Attribute `realisations'` is not serializable as XML 1.0.

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname} === '/realisations' ?  
'active' : ""}``}><
```

89. **Warning** Attribute `?` is not serializable as XML 1.0.

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname} === '/realisations' ?  
'active' : ""}``}><
```

90. **Warning** Attribute `'active'` is not serializable as XML 1.0.

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname === '/realisations' ?  
'active' : ""}`}>
```

91. **Warning** Attribute `:` is not serializable as XML 1.0.

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname === '/realisations' ?  
'active' : ""}`}>
```

92. **Warning** Attribute `""}`` is not serializable as XML 1.0.

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname === '/realisations' ?  
'active' : ""}`}>
```

93. **Error** Attribute `to` not allowed on element `link` at this point.

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname === '/realisations' ?  
'active' : ""}`}>
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

94. **Error** Attribute `classname` not allowed on element `link` at this point.

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname === '/realisations' ?  
'active' : ""}`}><
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)=[preload](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)=[preload](#))

[as](#) — [Potential destination](#) for a preload request (for [rel](#)=[preload](#) and [rel](#)=[modulepreload](#))

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)=[mask-icon](#))

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

95. **Error** **Attribute** `${location.pathname}` **not allowed on element** [link](#) **at this point.**

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname === '/realisations' ?  
'active' : ""}`}><
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)=[icon](#))

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)=[preload](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)=[preload](#))

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

96. **Error** Attribute `'` not allowed on element `link` at this point.

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname === '/realisations' ?  
'active' : ""}`}><
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

97. **Error** **Attribute** `realisations'` **not allowed on element** `link` **at this point.**

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname === '/realisations' ?  
'active' : ""}`}>
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled



[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

98. **Error** Attribute `?` not allowed on element `link` at this point.

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname === '/realisations' ?  
'active' : ""}`}>↵
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

99. **Error** Attribute `'active'` not allowed on element `link` at this point.

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname === '/realisations' ?  
'active' : ""}`}><
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="[icon](#)")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="[preload](#)")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="[preload](#)")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="[preload](#)" and [rel](#)="[modulepreload](#)")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="[mask-icon](#)")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

100. **Error** Attribute `:` not allowed on element `link` at this point.

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname === '/realisations' ?
'active' : ""}`}>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

101. **Error** Attribute `""}`` }` not allowed on element [link](#) at this point.

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname === '/realisations' ?
'active' : ""}`}>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

102. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname === '/realisations' ?  
'active' : ""}`} ><
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

103. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname === '/realisations' ?  
'active' : ""}`}><
```

104. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 67, column 17; to line 67, column 122](#)

```
<Link to="/realisations" className={`nav-link ${location.pathname === '/realisations' ?  
'active' : ""}`}>
```

105. **Error** Stray end tag `link`.

[From line 69, column 17; to line 69, column 23](#)

```
</Link>
```

106. **Error** ``` in an unquoted attribute value. Probable cause: Using the wrong character as a quote.

[At line 72, column 44](#)

```
og" className={`nav-link ${loc
```

107. **Error** `=` at the start of an unquoted attribute value. Probable cause: Stray duplicate equals sign.

[At line 72, column 75](#)

```
tion.pathname === '/blog' ? 'a
```

108. **Error** `=` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

[At line 72, column 76](#)

```
ion.pathname === '/blog' ? 'ac
```

109. **Error** Saw `'` when expecting an attribute name. Probable cause: `=` missing immediately before.

[At line 72, column 78](#)

```
n.pathname === '/blog' ? 'acti
```

110. **Error** A slash was not immediately followed by `>`.

[At line 72, column 80](#)

```
pathname === '/blog' ? 'active'
```

111. **Error** Quote `'` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 72, column 84](#)

```
name === '/blog' ? 'active' :
```

112. **Error** Quote `'` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 72, column 88](#)

```
=== '/blog' ? 'active' : ""}`
```

113. **Error** Quote `'` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 72, column 95](#)

```
blog' ? 'active' : ""}`}>↵
```

114. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 72, column 99](#)

```
' ? 'active' : ""}`}>↵
```

115. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 72, column 100](#)

```
? 'active' : ""}`}>↵
```

116. **Warning** Attribute `${location.pathname}` is not serializable as XML 1.0.

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ""}`}>↵
```

117. **Warning** Attribute `'` is not serializable as XML 1.0.

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ""}`}>
```

118. **Warning** Attribute `blog` is not serializable as XML 1.0.

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ""}`}>
```

119. **Warning** Attribute `?` is not serializable as XML 1.0.

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ""}`}>
```

120. **Warning** Attribute `'active'` is not serializable as XML 1.0.

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ""}`}>
```

121. **Warning** Attribute `:` is not serializable as XML 1.0.

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ""}`}>
```

122. **Warning** Attribute `""}`}`` is not serializable as XML 1.0.

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ""}`}>
```

123. **Error** Attribute `to` not allowed on element `link` at this point.

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ""}`}>
```

Attributes for element `link`:

[Global attributes](#)



[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

124. **Error** Attribute `classname` not allowed on element `link` at this point.

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" classname={`nav-link ${location.pathname === '/blog' ? 'active' : ''}`}></pre>
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

125. **Error** **Attribute** `${location.pathname}` **not allowed on element** [link](#) **at this point.**

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ''}`}>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

126. **Error** Attribute `'` not allowed on element `link` at this point.

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ''}`}><
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

127. **Error** Attribute `blog` not allowed on element `link` at this point.

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ''}`}>
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

128. **Error** Attribute `?` not allowed on element `link` at this point.

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ''}`}>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

129. **Error** Attribute `'active'` not allowed on element [link](#) at this point.

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ''}`}><
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="[icon](#)")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="[preload](#)")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="[preload](#)")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="[preload](#)" and [rel](#)="[modulepreload](#)")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="[mask-icon](#)")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

130. **Error** Attribute `:` not allowed on element `link` at this point.

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ''}`}>
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

131. **Error** Attribute `""}``` not allowed on element `link` at this point.

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ''}`}>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

132. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ''}`}>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)



[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

133. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ""}`}></pre>
```

134. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 72, column 15; to line 72, column 104](#)

```
<Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ""}`}></pre>
```

135. **Error** Stray end tag `link`.

[From line 74, column 17; to line 74, column 23](#)

```
</Link><␣
```

136. **Error** ``` in an unquoted attribute value. Probable cause: Using the wrong character as a quote.

[At line 77, column 47](#)

```
ct" className={`nav-link ${loc
```

137. **Error** `=` at the start of an unquoted attribute value. Probable cause: Stray duplicate equals sign.

[At line 77, column 78](#)

```
tion.pathname === '/contact' ?
```

138. **Error** `=` in an unquoted attribute value. Probable causes: Attributes running together or a URL query string in an unquoted attribute value.

[At line 77, column 79](#)

```
ion.pathname === '/contact' ?
```

139. **Error** Saw `'` when expecting an attribute name. Probable cause: `=` missing immediately before.

[At line 77, column 81](#)

```
n.pathname === '/contact' ? 'a
```

140. **Error** A slash was not immediately followed by `>`.

[At line 77, column 83](#)

```
pathname === '/contact' ? 'act
```

141. **Error** Quote `'` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 77, column 90](#)

```
e === '/contact' ? 'active' :
```

142. **Error** Quote `'` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 77, column 94](#)

```
= '/contact' ? 'active' : ""}`
```

143. **Error** Quote `'` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 77, column 101](#)

```
tact' ? 'active' : ""}`>
```

144. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 77, column 105](#)

```
' ? 'active' : ""}`>
```

145. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 77, column 106](#)

```
? 'active' : ""}`>
```

146. **Warning** Attribute `${location.pathname}` is not serializable as XML 1.0.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ""}}`>
```

147. **Warning** Attribute `'` is not serializable as XML 1.0.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ""}}`>
```

148. **Warning** Attribute `contact'` is not serializable as XML 1.0.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ''}`}>
```

149. **Warning** Attribute `?` is not serializable as XML 1.0.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ''}`}>
```

150. **Warning** Attribute `'active'` is not serializable as XML 1.0.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ''}`}>
```

151. **Warning** Attribute `:` is not serializable as XML 1.0.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ''}`}>
```

152. **Warning** Attribute `""}``` is not serializable as XML 1.0.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ''}`}>
```

153. **Error** Attribute `to` not allowed on element `link` at this point.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ""}
`}>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

154. **Error** Attribute `classname` not allowed on element [link](#) at this point.

From line 77, column 15; to line 77, column 110

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ""}
`}>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

155. **Error** Attribute `${location.pathname}` not allowed on element [link](#) at this point.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ""}`}>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

156. **Error** Attribute `'` not allowed on element `link` at this point.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ""}
`}><
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

157. **Error** Attribute `contact` not allowed on element `link` at this point.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ""}
`}>
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)



[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

158. **Error** Attribute `?` not allowed on element `link` at this point.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ""}
`}><
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SR\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

159. **Error** Attribute 'active' not allowed on element [link](#) at this point.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ""}
`}><
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)=[preload](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)=[preload](#))

[as](#) — [Potential destination](#) for a preload request (for [rel](#)=[preload](#) and [rel](#)=[modulepreload](#))

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)=[mask-icon](#))

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

160. **Error** Attribute `:` not allowed on element `link` at this point.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ""}
`}>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)=[icon](#))

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)=[preload](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)=[preload](#))

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

161. **Error** Attribute `""`}`` not allowed on element [link](#) at this point.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ""}
`}>
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

162. **Error** Element [link](#) is missing one or more of the following attributes: `href`, `itemprop`, `property`, `rel`, `resource`.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={` nav-link ${location.pathname === '/contact' ? 'active' : ""}
`}><
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

163. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ""}
`}>
```

164. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 77, column 15; to line 77, column 110](#)

```
<Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' : ""}
`}>
```

165. **Error** Stray end tag `link`.

[From line 79, column 17; to line 79, column 23](#)

```
</Link>
```

166. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 87, column 9; to line 87, column 48](#)

```
><div className="home-container-accueil">
```

Attributes for element `div`:

[Global attributes](#)

167. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 88, column 11; to line 88, column 52](#)

```
<div className="background-image-accueil">↵
```

Attributes for element [div](#):

[Global attributes](#)

168. **Error** Attribute `classname` not allowed on element [div](#) at this point.

[From line 89, column 13; to line 89, column 45](#)

```
<div className="overlay-accueil">↵
```

Attributes for element [div](#):

[Global attributes](#)

169. **Error** Attribute `classname` not allowed on element [button](#) at this point.

[From line 92, column 15; to line 92, column 90](#)

```
<button type="button" className="btn btn-primary" onClick={scrollToAPropos}>↵
```

Attributes for element [button](#):

[Global attributes](#)

[disabled](#) — Whether the form control is disabled

[form](#) — Associates the element with a [form](#) element

[formaction](#) — [URL](#) to use for [form submission](#)

[formenctype](#) — [Entry list](#) encoding type to use for [form submission](#)

[formmethod](#) — Variant to use for [form submission](#)

[formnovalidate](#) — Bypass form control validation for [form submission](#)

[formtarget](#) — [Navigable](#) for [form submission](#)

[name](#) — Name of the element to use for [form submission](#) and in the [form.elements](#) API

[popovertarget](#) — Targets a popover element to toggle, show, or hide

[popovertargetaction](#) — Indicates whether a targeted popover element is to be toggled, shown, or hidden

[type](#) — Type of button

[value](#) — Value to be used for [form submission](#)

170. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 99, column 9; to line 99, column 40](#)

```
>↵      <div classname="container mt-5">↵
```

Attributes for element `div`:

[Global attributes](#)

171. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 100, column 11; to line 100, column 40](#)

```
<div classname="card-accueil">↵
```

Attributes for element `div`:

[Global attributes](#)

172. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 101, column 13; to line 101, column 44](#)

```
<div classname="row no-gutters">↵
```

Attributes for element `div`:

[Global attributes](#)

173. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 103, column 15; to line 103, column 50](#)

```
<div classname="col-md-6 col-sm-12">↵
```

Attributes for element `div`:

[Global attributes](#)

174. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 104, column 17; to line 104, column 51](#)



```
<div className="card-body-accueil">↵
```

Attributes for element [div](#):

[Global attributes](#)

175. **Error** Attribute `classname` not allowed on element `h5` at this point.

[From line 105, column 19; to line 105, column 53](#)

```
<h5 className="card-title-accueil">À prop
```

176. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 106, column 19; to line 106, column 24](#)

```
<br />↵
```

177. **Error** Attribute `classname` not allowed on element `p` at this point.

[From line 107, column 19; to line 107, column 43](#)

```
<p className="card-text">↵
```

Attributes for element `p`:

[Global attributes](#)

178. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 115, column 19; to line 115, column 24](#)

```
<br />↵
```

179. **Error** Attribute `classname` not allowed on element `p` at this point.

[From line 116, column 19; to line 116, column 43](#)

```
<p className="card-text">↵
```

Attributes for element `p`:

[Global attributes](#)

180. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).  
[From line 121, column 19; to line 121, column 24](#)

```
<br />↵
```

181. **Error** Attribute `classname` not allowed on element `p` at this point.  
[From line 122, column 19; to line 122, column 43](#)

```
<p classname="card-text">↵
```

Attributes for element `p`:

[Global attributes](#)

182. **Error** Attribute `classname` not allowed on element `div` at this point.  
[From line 129, column 15; to line 129, column 50](#)

```
<div classname="col-md-6 col-sm-12">↵
```

Attributes for element `div`:

[Global attributes](#)

183. **Error** Attribute `classname` not allowed on element `div` at this point.  
[From line 130, column 17; to line 130, column 51](#)

```
<div classname="card-body-accueil">↵
```

Attributes for element `div`:

[Global attributes](#)

184. **Error** Bad value `{photoProfil}` for attribute `src` on element `img`: Illegal character in path segment: `{`  
**is not allowed.**

[From line 131, column 19; to line 131, column 80](#)

```
<img src={photoProfil} classname="img-fluid" alt="John Doe" />↵
```

185. **Error** Attribute `classname` not allowed on element `img` at this point.

[From line 131, column 19; to line 131, column 80](#)

```
<img src={photoProfil} className="img-fluid" alt="John Doe" />
```

Attributes for element `img`:

[Global attributes](#)

[alt](#) — Replacement text for use when images are not available

[src](#) — Address of the resource

[srcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc.

[sizes](#) — Image sizes for different page layouts

[crossorigin](#) — How the element handles crossorigin requests

[usemap](#) — Name of [image map](#) to use

[ismap](#) — Whether the image is a server-side image map

[width](#) — Horizontal dimension

[height](#) — Vertical dimension

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[decoding](#) — Decoding hint to use when processing this image for presentation

[loading](#) — Used when determining loading deferral

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

186. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 131, column 19; to line 131, column 80](#)

```
<img src={photoProfil} className="img-fluid" alt="John Doe" />
```

187. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 132, column 19; to line 132, column 50](#)

```
<div className="card-text mt-3">
```

Attributes for element [div](#):

[Global attributes](#)

188. **Error** Attribute `classname` not allowed on element `h5` at this point.

[From line 133, column 21; to line 133, column 48](#)

```
<h5 classname="card-title2">Mes co
```

189. **Error** Attribute `classname` not allowed on element `p` at this point.

[From line 134, column 21; to line 134, column 52](#)

```
<p classname="card-competences">HTML5
```

Attributes for element `p`:

[Global attributes](#)

190. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 145, column 41](#)

```
tyle={{ width: "90%" }}↵
```

191. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 145, column 45](#)

```
={{ width: "90%" }}↵
```

192. **Warning** Attribute `width:` is not serializable as XML 1.0.

[From line 143, column 23; to line 146, column 23](#)

```
<div↵                               classname="progress-bar bg-danger"↵
style={{ width: "90%" }}↵                               ></div>
```

193. **Warning** Attribute `"90%"` is not serializable as XML 1.0.

[From line 143, column 23; to line 146, column 23](#)

```
<div↵                               className="progress-bar bg-danger"↵
style={{ width: "90%" }}↵                               ></div>
```

194. **Warning** Attribute `}}` is not serializable as XML 1.0.

[From line 143, column 23; to line 146, column 23](#)

```
<div↵                               className="progress-bar bg-danger"↵
style={{ width: "90%" }}↵                               ></div>
```

195. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 143, column 23; to line 146, column 23](#)

```
<div↵                               className="progress-bar bg-danger"↵
style={{ width: "90%" }}↵                               ></div>
```

Attributes for element `div`:

[Global attributes](#)

196. **Error** Attribute `width`: not allowed on element `div` at this point.

[From line 143, column 23; to line 146, column 23](#)

```
<div↵                               className="progress-bar bg-danger"↵
style={{ width: "90%" }}↵                               ></div>
```

Attributes for element `div`:

[Global attributes](#)

197. **Error** Attribute `"90%"` not allowed on element `div` at this point.

[From line 143, column 23; to line 146, column 23](#)

```
<div↵                               className="progress-bar bg-danger"↵
style={{ width: "90%" }}↵                               ></div>
```

Attributes for element `div`:

[Global attributes](#)

198. **Error** Attribute `}}` not allowed on element `div` at this point.

[From line 143, column 23; to line 146, column 23](#)

```
<div className="progress-bar bg-danger" style={{ width: "90%" }}></div>
```

Attributes for element `div`:

[Global attributes](#)

199. **Error** Attribute `classname` not allowed on element `p` at this point.

[From line 148, column 21; to line 148, column 52](#)

```
<p classname="card-competences">CSS3 8
```

Attributes for element `p`:

[Global attributes](#)

200. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 159, column 41](#)

```
tyle={{ width: "80%" }}
```

201. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 159, column 45](#)

```
={{ width: "80%" }}
```

202. **Warning** Attribute `width:` is not serializable as XML 1.0.

[From line 157, column 23; to line 160, column 23](#)

```
<div className="progress-bar bg-info" style={{ width: "80%" }}></div>
```

203. **Warning** Attribute `"80%"` is not serializable as XML 1.0.

```
<div className="progress-bar bg-info" style={{
width: "80%" }}>
</div>
```

```
<div className="progress-bar bg-info" style={{
width: "80%" }}>
</div>
```

```
<div className="progress-bar bg-info" style={{ width: "80%" }}></div>
```

## Global attributes

```
<div className="progress-bar bg-info" style={{ width: "80%" }}>
```

## Global attributes

```
<div className="progress-bar bg-info" style={{ width: "80%" }}></div>
```

Attributes for element `div`:

[Global attributes](#)

208. **Error** Attribute `}}` not allowed on element `div` at this point.

[From line 157, column 23; to line 160, column 23](#)

```
<div↵                               className="progress-bar bg-info"↵
style={{ width: "80%" }}↵                               ></div>
```

Attributes for element `div`:

[Global attributes](#)

209. **Error** Attribute `classname` not allowed on element `p` at this point.

[From line 162, column 21; to line 162, column 52](#)

```
<p className="card-competences">JAVASC
```

Attributes for element `p`:

[Global attributes](#)

210. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 173, column 41](#)

```
tyle={{ width: "70%" }}↵
```

211. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 173, column 45](#)

```
={{ width: "70%" }}↵
```

212. **Warning** Attribute `width:` is not serializable as XML 1.0.

[From line 171, column 23; to line 174, column 23](#)

```
<div↵                               className="progress-bar bg-warning"↵
style={{ width: "70%" }}↵                               ></div>
```



**Warning** Attribute "70%" is not serializable as XML 1.0.

From line 171, column 23; to line 174, column 23

```
<div className="progress-bar bg-warning" style={{ width: "70%" }}>
```

**Warning** **Attribute {}** is not serializable as XML 1.0.

From line 171, column 23; to line 174, column 23

```
<div className="progress-bar bg-warning" style={{ width: "70%" }}>
```

**Error** Attribute `classname` not allowed on element `div` at this point.

From line 171, column 23; to line 174, column 23

```
<div className="progress-bar bg-warning" style={{ width: "70%" }}>
```

Attributes for element `div`:

## Global attributes

**Error** Attribute width: not allowed on element div at this point.

From line 171, column 23; to line 174, column 23

```
<div className="progress-bar bg-warning" style={{ width: "70%" }}>
```

Attributes for element `div`:

## Global attributes

**Error** Attribute "70%" not allowed on element `div` at this point.

From line 171, column 23; to line 174, column 23

```
<div↵      className="progress-bar bg-warning"↵
```

```
style={{ width: "70%" }}<div>
```

Attributes for element [div](#):

[Global attributes](#)

218. **Error** Attribute `}}` not allowed on element [div](#) at this point.

[From line 171, column 23; to line 174, column 23](#)

```
<div className="progress-bar bg-warning" style={{ width: "70%" }}>
```

Attributes for element [div](#):

[Global attributes](#)

219. **Error** Attribute `classname` not allowed on element [p](#) at this point.

[From line 176, column 21; to line 176, column 52](#)

```
<p classname="card-competences">PHP 60
```

Attributes for element [p](#):

[Global attributes](#)

220. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 187, column 41](#)

```
tyle={{ width: "60%" }}
```

221. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 187, column 45](#)

```
={{ width: "60%" }}
```

222. **Warning** Attribute `width:` is not serializable as XML 1.0.

[From line 185, column 23; to line 188, column 23](#)

```
<div className="progress-bar bg-success">
```

></div>

**Warning** Attribute "60%" is not serializable as XML 1.0.

From line 185, column 23; to line 188, column 23

<div↵

```
className="progress-bar bg-success"↵
```

></div>

**Warning** **Attribute {} is not serializable as XML 1.0.**

From line 185, column 23; to line 188, column 23

<div↵

```
className="progress-bar bg-success"↵
```

></div>

**Error** **Attribute** `classname` **not allowed on element** `div` **at this point.**

From line 185, column 23; to line 188, column 23

<div←

```
className="progress-bar bg-success"↵
```

></div>

Attributes for element `div`:

## Global attributes

**Error** Attribute width: not allowed on element div at this point.

From line 185, column 23; to line 188, column 23

<div↵

```
className="progress-bar bg-success"↵
```

></div>

Attributes for element `div`:

## Global attributes

**Error** Attribute "60%" not allowed on element `div` at this point.

From line 185, column 23; to line 188, column 23

```
<div className="progress-bar bg-success" style={{ width: "60%" }}></div>
```

Attributes for element [div](#):

[Global attributes](#)

228. **Error** Attribute `}}` not allowed on element [div](#) at this point.

[From line 185, column 23; to line 188, column 23](#)

```
<div className="progress-bar bg-success" style={{ width: "60%" }}></div>
```

Attributes for element [div](#):

[Global attributes](#)

229. **Error** Attribute `classname` not allowed on element [p](#) at this point.

[From line 190, column 21; to line 190, column 52](#)

```
<p classname="card-competences">REACT
```

Attributes for element [p](#):

[Global attributes](#)

230. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 201, column 41](#)

```
tyle={{ width: "50%" }}
```

231. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 201, column 45](#)

```
={{ width: "50%" }}
```

232. **Warning** Attribute `width:` is not serializable as XML 1.0.

[From line 199, column 23; to line 202, column 23](#)

```
<div className="progress-bar" style={{ width:
"50%" }}>
</div>
```

233. **Warning** Attribute `"50%"` is not serializable as XML 1.0.

[From line 199, column 23; to line 202, column 23](#)

```
<div className="progress-bar" style={{ width:
"50%" }}>
</div>
```

234. **Warning** Attribute `}}` is not serializable as XML 1.0.

[From line 199, column 23; to line 202, column 23](#)

```
<div className="progress-bar" style={{ width:
"50%" }}>
</div>
```

235. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 199, column 23; to line 202, column 23](#)

```
<div className="progress-bar" style={{ width:
"50%" }}>
</div>
```

Attributes for element `div`:

[Global attributes](#)

236. **Error** Attribute `width:` not allowed on element `div` at this point.

[From line 199, column 23; to line 202, column 23](#)

```
<div className="progress-bar" style={{ width:
"50%" }}>
</div>
```

Attributes for element `div`:

[Global attributes](#)

237. **Error** Attribute `"50%"` not allowed on element `div` at this point.

[From line 199, column 23; to line 202, column 23](#)

```
<div className="progress-bar" style={{ width:
"50%" }}></div>
```

Attributes for element [div](#):

[Global attributes](#)

238. **Error** Attribute `}}` not allowed on element [div](#) at this point.

[From line 199, column 23; to line 202, column 23](#)

```
<div className="progress-bar" style={{ width:
"50%" }}></div>
```

Attributes for element [div](#):

[Global attributes](#)

239. **Error** Attribute `classname` not allowed on element [div](#) at this point.

[From line 211, column 17; to line 211, column 49](#)

```
<div classname="container-fluid"></div>
```

Attributes for element [div](#):

[Global attributes](#)

240. **Error** Attribute `classname` not allowed on element [div](#) at this point.

[From line 212, column 9; to line 212, column 29](#)

```
><div classname="row"></div>
```

Attributes for element [div](#):

[Global attributes](#)

241. **Error** Attribute `classname` not allowed on element [div](#) at this point.

[From line 213, column 11; to line 213, column 45](#)

```
<div classname="col-12 titre-blog"></div>
```

Attributes for element [div](#):

[Global attributes](#)

242. **Error** Attribute `classname` not allowed on element [div](#) at this point.

[From line 217, column 11; to line 217, column 67](#)

```
<div className="col-12 col-md-6 col-lg-4 container-card">↵
```

Attributes for element [div](#):

[Global attributes](#)

243. **Error** Attribute `classname` not allowed on element [div](#) at this point.

[From line 218, column 13; to line 218, column 34](#)

```
<div className="card">↵
```

Attributes for element [div](#):

[Global attributes](#)

244. **Error** Bad value `{blog1}` for attribute `src` on element [img](#): Illegal character in path segment: `{` is not allowed.

[From line 219, column 15; to line 223, column 16](#)

```
<img src={blog1} className="card-img-top" alt="coder" />↵
```

245. **Error** Attribute `classname` not allowed on element [img](#) at this point.

[From line 219, column 15; to line 223, column 16](#)

```
<img src={blog1} className="card-img-top" alt="coder" />↵
```

Attributes for element [img](#):

[Global attributes](#)

[alt](#) — Replacement text for use when images are not available

[src](#) — Address of the resource

[srcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc.

[sizes](#) — Image sizes for different page layouts

[crossorigin](#) — How the element handles crossorigin requests

[usemap](#) — Name of [image map](#) to use

[ismap](#) — Whether the image is a server-side image map

[width](#) — Horizontal dimension

[height](#) — Vertical dimension

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[decoding](#) — Decoding hint to use when processing this image for presentation

[loading](#) — Used when determining loading deferral

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

246. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 219, column 15; to line 223, column 16](#)

```
<img src={blog1} className="card-img-top"
alt="coder" />
```

247. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 224, column 15; to line 224, column 41](#)

```
<div classname="card-body">
```

Attributes for element `div`:

[Global attributes](#)

248. **Error** Attribute `classname` not allowed on element `h5` at this point.

[From line 225, column 17; to line 225, column 43](#)

```
<h5 classname="card-title">Coder
```



249. **Error** Attribute `classname` not allowed on element `p` at this point.

[From line 226, column 17; to line 226, column 41](#)

```
<p classname="card-text">↵
```

Attributes for element `p`:

[Global attributes](#)

250. **Error** Attribute `to` not allowed on element `link` at this point.

[From line 229, column 17; to line 229, column 65](#)

```
<Link to="#" classname="btn btn-outline-primary">↵
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="[icon](#)")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="[preload](#)")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="[preload](#)")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="[preload](#)" and [rel](#)="[modulepreload](#)")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="[mask-icon](#)")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

251. **Error** Attribute `classname` not allowed on element `link` at this point.

[From line 229, column 17; to line 229, column 65](#)

```
<Link to="#" classname="btn btn-outline-primary"></>
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="[icon](#)")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="[preload](#)")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="[preload](#)")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="[preload](#)" and [rel](#)="[modulepreload](#)")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="[mask-icon](#)")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

252. **Error** Element `link` is missing one or more of the following attributes: `href`, `itemprop`, `property`, `rel`, `resource`.

[From line 229, column 17; to line 229, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

253. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 229, column 17; to line 229, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

254. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 229, column 17; to line 229, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

255. **Error** Stray end tag `link`.

[From line 231, column 17; to line 231, column 23](#)

```
</Link>↵
```

256. **Error** Attribute `classname` not allowed on element `p` at this point.

[From line 233, column 15; to line 233, column 41](#)

```
<p className="card-footer">Publié
```

Attributes for element `p`:

[Global attributes](#)

257. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 236, column 11; to line 236, column 67](#)

```
<div className="col-12 col-md-6 col-lg-4 container-card">↵
```

Attributes for element `div`:

[Global attributes](#)

258. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 237, column 13; to line 237, column 34](#)

```
<div className="card">↵
```

Attributes for element `div`:

[Global attributes](#)

259.

**Error**

**Bad value {blog2} for attribute src on element [img](#): Illegal character in path segment: { is not allowed.**

[From line 238, column 15; to line 242, column 16](#)

```
<img src={blog2} className="card-img-top" alt="croissance" />
```

260. **Error** Attribute `classname` not allowed on element `img` at this point.

[From line 238, column 15; to line 242, column 16](#)

```
<img src={blog2} className="card-img-top" alt="croissance" />
```

Attributes for element `img`:

[Global attributes](#)

[alt](#) — Replacement text for use when images are not available

[src](#) — Address of the resource

[srcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc.

[sizes](#) — Image sizes for different page layouts

[crossorigin](#) — How the element handles crossorigin requests

[usemap](#) — Name of [image map](#) to use

[ismap](#) — Whether the image is a server-side image map

[width](#) — Horizontal dimension

[height](#) — Vertical dimension

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[decoding](#) — Decoding hint to use when processing this image for presentation

[loading](#) — Used when determining loading deferral

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

261. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 238, column 15; to line 242, column 16](#)

```
<img src={blog2} className="card-img-top" alt="croissance" />
```

262. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 243, column 15; to line 243, column 41](#)

```
<div className="card-body">↵
```

Attributes for element [div](#):

[Global attributes](#)

263. **Error** Attribute `classname` not allowed on element `h5` at this point.

[From line 244, column 17; to line 244, column 43](#)

```
<h5 className="card-title">Vendre
```

264. **Error** Attribute `classname` not allowed on element `p` at this point.

[From line 245, column 17; to line 245, column 41](#)

```
<p className="card-text">Some q
```

Attributes for element `p`:

[Global attributes](#)

265. **Error** Attribute `to` not allowed on element `link` at this point.

[From line 246, column 17; to line 246, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

266. **Error** Attribute `classname` not allowed on element `link` at this point.

[From line 246, column 17; to line 246, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")



[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

267. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

[From line 246, column 17; to line 246, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

268. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 246, column 17; to line 246, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

269. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 246, column 17; to line 246, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

270. **Error** Stray end tag `link`.

[From line 248, column 17; to line 248, column 23](#)

```
</Link>↵
```

271. **Error** Attribute `classname` not allowed on element `p` at this point.

[From line 250, column 15; to line 250, column 41](#)

```
<p classname="card-footer">Publié
```

Attributes for element `p`:

[Global attributes](#)

272. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 253, column 11; to line 253, column 67](#)

```
<div className="col-12 col-md-6 col-lg-4 container-card">
```

Attributes for element [div](#):

[Global attributes](#)

273. **Error** Attribute `classname` not allowed on element [div](#) at this point.

[From line 254, column 13; to line 254, column 34](#)

```
<div className="card">
```

Attributes for element [div](#):

[Global attributes](#)

274. **Error** Bad value `{blog3}` for attribute `src` on element [img](#): Illegal character in path segment: `{` is not allowed.

[From line 255, column 15; to line 259, column 16](#)

```
<img src={blog3} className="card-img-top" alt="google" />
```

275. **Error** Attribute `classname` not allowed on element [img](#) at this point.

[From line 255, column 15; to line 259, column 16](#)

```
<img src={blog3} className="card-img-top" alt="google" />
```

Attributes for element [img](#):

[Global attributes](#)

[alt](#) — Replacement text for use when images are not available

[src](#) — Address of the resource

[srcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc.

[sizes](#) — Image sizes for different page layouts

[crossorigin](#) — How the element handles crossorigin requests

[usemap](#) — Name of [image map](#) to use

[ismap](#) — Whether the image is a server-side image map

[width](#) — Horizontal dimension

[height](#) — Vertical dimension

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[decoding](#) — Decoding hint to use when processing this image for presentation

[loading](#) — Used when determining loading deferral

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

276. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 255, column 15; to line 259, column 16](#)

```
<img src={blog3} className="card-img-top"
alt="google" />
```

277. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 260, column 15; to line 260, column 41](#)

```
<div classname="card-body"></div>
```

Attributes for element `div`:

[Global attributes](#)

278. **Error** Attribute `classname` not allowed on element `h5` at this point.

[From line 261, column 17; to line 261, column 43](#)

```
<h5 classname="card-title">Se pos
```

279. **Error** Attribute `classname` not allowed on element `p` at this point.

[From line 262, column 17; to line 262, column 41](#)

```
<p className="card-text">↵
```

Attributes for element [p](#):

[Global attributes](#)

280. **Error** Attribute [to](#) not allowed on element [link](#) at this point.

[From line 265, column 17; to line 265, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

281. **Error** Attribute `classname` not allowed on element `link` at this point.

[From line 265, column 17; to line 265, column 65](#)

```
<Link to="#" className="btn btn-outline-primary"></>
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

282. **Error** Element `link` is missing one or more of the following attributes: `href`, `itemprop`, `property`, `rel`, `resource`.

[From line 265, column 17; to line 265, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

283. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 265, column 17; to line 265, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

284. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has

an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 265, column 17; to line 265, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

285. **Error** Stray end tag `link`.

[From line 267, column 17; to line 267, column 23](#)

```
</Link>↵
```

286. **Error** Attribute `classname` not allowed on element `p` at this point.

[From line 269, column 15; to line 269, column 41](#)

```
<p className="card-footer">Publié
```

Attributes for element `p`:

[Global attributes](#)

287. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 272, column 11; to line 272, column 67](#)

```
<div className="col-12 col-md-6 col-lg-4 container-card">↵
```

Attributes for element `div`:

[Global attributes](#)

288. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 273, column 13; to line 273, column 34](#)

```
<div className="card">↵
```

Attributes for element `div`:

[Global attributes](#)

289. **Error** Bad value `{blog4}` for attribute `src` on element `img`: Illegal character in path segment: `{` is not



**allowed.**

[From line 274, column 15; to line 278, column 16](#)

```
<img↵                               src={blog4}↵                               className="card-img-top"↵
alt="screens"↵                       />↵
```

290.

**Error** **Attribute** `classname` **not allowed on element** `img` **at this point.**

[From line 274, column 15; to line 278, column 16](#)

```
<img↵                               src={blog4}↵                               className="card-img-top"↵
alt="screens"↵                       />↵
```

Attributes for element `img`:

[Global attributes](#)

[alt](#) — Replacement text for use when images are not available

[src](#) — Address of the resource

[srcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc.

[sizes](#) — Image sizes for different page layouts

[crossorigin](#) — How the element handles crossorigin requests

[usemap](#) — Name of [image map](#) to use

[ismap](#) — Whether the image is a server-side image map

[width](#) — Horizontal dimension

[height](#) — Vertical dimension

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[decoding](#) — Decoding hint to use when processing this image for presentation

[loading](#) — Used when determining loading deferral

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

291.

**Info** **Trailing slash on void elements** [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 274, column 15; to line 278, column 16](#)

```
<img src={blog4} className="card-img-top" alt="screens" />
```

292. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 279, column 15; to line 279, column 41](#)

```
<div className="card-body">
```

Attributes for element `div`:

[Global attributes](#)

293. **Error** Attribute `classname` not allowed on element `h5` at this point.

[From line 280, column 17; to line 280, column 43](#)

```
<h5 className="card-title">Coder
```

294. **Error** Attribute `classname` not allowed on element `p` at this point.

[From line 281, column 17; to line 281, column 41](#)

```
<p className="card-text">
```

Attributes for element `p`:

[Global attributes](#)

295. **Error** Attribute `to` not allowed on element `link` at this point.

[From line 284, column 17; to line 284, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

296. **Error** Attribute `classname` not allowed on element `link` at this point.

[From line 284, column 17; to line 284, column 65](#)

```
<Link to="#" classname="btn btn-outline-primary"></>
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

297. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

[From line 284, column 17; to line 284, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

298. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 284, column 17; to line 284, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

299. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 284, column 17; to line 284, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

300. **Error** Stray end tag `link`.

[From line 286, column 17; to line 286, column 23](#)

```
</Link>↵
```

301. **Error** Attribute `classname` not allowed on element `p` at this point.

[From line 288, column 15; to line 288, column 41](#)

```
<p classname="card-footer">Publié
```

Attributes for element `p`:

[Global attributes](#)

302. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 291, column 11; to line 291, column 67](#)

```
<div className="col-12 col-md-6 col-lg-4 container-card">
```

Attributes for element `div`:

[Global attributes](#)

303. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 292, column 13; to line 292, column 34](#)

```
<div className="card">
```

Attributes for element `div`:

[Global attributes](#)

304. **Error** Bad value `{blog5}` for attribute `src` on element `img`: Illegal character in path segment: `{` is not allowed.

[From line 293, column 15; to line 297, column 16](#)

```
<img src={blog5} className="card-img-top" alt="SEO" />
```

305. **Error** Attribute `classname` not allowed on element `img` at this point.

[From line 293, column 15; to line 297, column 16](#)

```
<img src={blog5} className="card-img-top" alt="SEO" />
```

Attributes for element `img`:

[Global attributes](#)

`alt` — Replacement text for use when images are not available

`src` — Address of the resource

**fetchpriority** — Sets the **priority** for **fetches** initiated by the element

```
<h5 className="card-title">Techni
```

309. **Error** Attribute `classname` not allowed on element `p` at this point.

[From line 300, column 17; to line 300, column 41](#)

```
<p classname="card-text">↵
```

Attributes for element `p`:

[Global attributes](#)

310. **Error** Attribute `to` not allowed on element `link` at this point.

[From line 303, column 17; to line 303, column 65](#)

```
<Link to="#" classname="btn btn-outline-primary">↵
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="[icon](#)")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="[preload](#)")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="[preload](#)")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="[preload](#)" and [rel](#)="[modulepreload](#)")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="[mask-icon](#)")

[disabled](#) — Whether the link is disabled



[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

311. **Error** Attribute `classname` not allowed on element `link` at this point.

[From line 303, column 17; to line 303, column 65](#)

```
<Link to="#" classname="btn btn-outline-primary"></>
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

312. **Error** Element `link` is missing one or more of the following attributes: `href`, `itemprop`, `property`, `rel`, `resource`.

[From line 303, column 17; to line 303, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

313. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 303, column 17; to line 303, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

314. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 303, column 17; to line 303, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

315. **Error** Stray end tag `link`.

[From line 305, column 17; to line 305, column 23](#)

```
</Link>↵
```

316. **Error** Attribute `classname` not allowed on element `p` at this point.

[From line 307, column 15; to line 307, column 41](#)

```
<p className="card-footer">Publié
```

Attributes for element `p`:

[Global attributes](#)

317. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 310, column 11; to line 310, column 67](#)

```
<div className="col-12 col-md-6 col-lg-4 container-card">↵
```

Attributes for element `div`:

[Global attributes](#)

318. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 311, column 13; to line 311, column 34](#)

```
<div className="card">↵
```

Attributes for element `div`:

[Global attributes](#)

319.

**Error**

**Bad value {blog6} for attribute src on element [img](#): Illegal character in path segment: { is not allowed.**

[From line 312, column 15; to line 316, column 16](#)

```
<img src={blog6} className="card-img-top" alt="technos" />
```

320. **Error** Attribute `classname` not allowed on element `img` at this point.

[From line 312, column 15; to line 316, column 16](#)

```
<img src={blog6} className="card-img-top" alt="technos" />
```

Attributes for element `img`:

[Global attributes](#)

[alt](#) — Replacement text for use when images are not available

[src](#) — Address of the resource

[srcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc.

[sizes](#) — Image sizes for different page layouts

[crossorigin](#) — How the element handles crossorigin requests

[usemap](#) — Name of [image map](#) to use

[ismap](#) — Whether the image is a server-side image map

[width](#) — Horizontal dimension

[height](#) — Vertical dimension

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[decoding](#) — Decoding hint to use when processing this image for presentation

[loading](#) — Used when determining loading deferral

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

321. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 312, column 15; to line 316, column 16](#)

```
<img src={blog6} className="card-img-top" alt="technos" />
```

322. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 317, column 15; to line 317, column 41](#)

```
<div className="card-body">↵
```

Attributes for element [div](#):

[Global attributes](#)

323. **Error** Attribute `classname` not allowed on element `h5` at this point.

[From line 318, column 17; to line 318, column 43](#)

```
<h5 className="card-title">Appren
```

324. **Error** Attribute `classname` not allowed on element `p` at this point.

[From line 319, column 17; to line 319, column 41](#)

```
<p className="card-text">↵
```

Attributes for element `p`:

[Global attributes](#)

325. **Error** Attribute `to` not allowed on element `link` at this point.

[From line 322, column 17; to line 322, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

326. **Error** Attribute `classname` not allowed on element `link` at this point.

[From line 322, column 17; to line 322, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

327. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

[From line 322, column 17; to line 322, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")



[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

328. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 322, column 17; to line 322, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

329. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 322, column 17; to line 322, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

330. **Error** Stray end tag `link`.

[From line 324, column 17; to line 324, column 23](#)

```
</Link>↵
```

331. **Error** Attribute `classname` not allowed on element `p` at this point.

[From line 326, column 15; to line 326, column 41](#)

```
<p className="card-footer">Publié
```

Attributes for element `p`:

[Global attributes](#)

332. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 331, column 9; to line 331, column 48](#)

```
><div className="home-container-contact"><
```

Attributes for element [div](#):

[Global attributes](#)

333. **Error** Attribute `classname` not allowed on element [div](#) at this point.

[From line 332, column 11; to line 332, column 52](#)

```
<div className="background-image-contact"><
```

Attributes for element [div](#):

[Global attributes](#)

334. **Error** Attribute `classname` not allowed on element [div](#) at this point.

[From line 333, column 13; to line 333, column 45](#)

```
<div className="overlay-contact"><
```

Attributes for element [div](#):

[Global attributes](#)

335. **Error** Attribute `classname` not allowed on element [div](#) at this point.

[From line 334, column 15; to line 334, column 45](#)

```
<div className="titre-contact"><
```

Attributes for element [div](#):

[Global attributes](#)

336. **Error** Attribute `classname` not allowed on element [div](#) at this point.

[From line 340, column 15; to line 340, column 47](#)

```
<div className="contact-content"><
```

Attributes for element [div](#):

[Global attributes](#)

337. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 341, column 17; to line 341, column 46](#)

```
<div classname="contact-form">↵
```

Attributes for element `div`:

[Global attributes](#)

338. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 344, column 21; to line 344, column 48](#)

```
<div classname="form-group">↵
```

Attributes for element `div`:

[Global attributes](#)

339. **Error** Attribute `htmlfor` not allowed on element `label` at this point.

[From line 345, column 23; to line 345, column 44](#)

```
<label htmlFor="name"></labe
```

Attributes for element `label`:

[Global attributes](#)

[for](#) — Associate the label with form control

340. **Error** Attribute `classname` not allowed on element `input` at this point.

[From line 346, column 23; to line 351, column 24](#)

```
<input↵                                type="text"↵                                classname="name"↵
id="name"↵                                placeholder="Votre nom"↵                                />↵
```

Attributes for element `input`:

[Global attributes](#)

[accept](#) when type is [file](#)

[alt](#) when type is [image](#)

<a href="#">autocomplete</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">password</a> , <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , <a href="#">range</a> , or <a href="#">color</a>
<a href="#">autofocus</a>	
<a href="#">checked</a>	when type is <a href="#">checkbox</a> or <a href="#">radio</a>
<a href="#">dirname</a>	when type is <a href="#">text</a> or <a href="#">search</a>
<a href="#">disabled</a>	
<a href="#">form</a>	
<a href="#">formaction</a>	when type is <a href="#">submit</a> or <a href="#">image</a>
<a href="#">formenctype</a>	when type is <a href="#">submit</a> or <a href="#">image</a>
<a href="#">formmethod</a>	when type is <a href="#">submit</a> or <a href="#">image</a>
<a href="#">formnovalidate</a>	when type is <a href="#">submit</a> or <a href="#">image</a>
<a href="#">formtarget</a>	when type is <a href="#">submit</a> or <a href="#">image</a>
<a href="#">height</a>	when type is <a href="#">image</a>
<a href="#">list</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , <a href="#">range</a> , or <a href="#">color</a>
<a href="#">max</a>	when type is <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , or <a href="#">range</a>
<a href="#">maxlength</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , or <a href="#">password</a>
<a href="#">min</a>	when type is <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , or <a href="#">range</a>
<a href="#">multiple</a>	when type is <a href="#">email</a> or <a href="#">file</a>
<a href="#">name</a>	
<a href="#">pattern</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , or <a href="#">password</a>
<a href="#">placeholder</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">password</a> , or <a href="#">number</a>
<a href="#">readonly</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">password</a> , <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , or <a href="#">number</a>
<a href="#">required</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">password</a> , <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , <a href="#">checkbox</a> , <a href="#">radio</a> , or <a href="#">file</a>
<a href="#">size</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , or <a href="#">password</a>
<a href="#">src</a>	when type is <a href="#">image</a>

[step](#) when type is [date](#), [month](#), [week](#), [time](#), [datetime-local](#), [number](#), or [range](#)

[type](#)

[value](#) when type is not [file](#) or [image](#)

[width](#) when type is [image](#)

341. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 346, column 23; to line 351, column 24](#)

```
<input type="text" className="name"
id="name" placeholder="Votre nom" />
```

342. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 353, column 21; to line 353, column 48](#)

```
<div classname="form-group">
```

Attributes for element `div`:

[Global attributes](#)

343. **Error** Attribute `htmlfor` not allowed on element `label` at this point.

[From line 354, column 23; to line 354, column 45](#)

```
<label htmlFor="email"></labe
```

Attributes for element `label`:

[Global attributes](#)

[for](#) — Associate the label with form control

344. **Error** Attribute `classname` not allowed on element `input` at this point.

[From line 355, column 23; to line 360, column 24](#)

```
<input type="email" className="email"
id="email" placeholder="Votre adresse email" />
```

Attributes for element [input](#):

[Global attributes](#)

<a href="#">accept</a>	when type is <a href="#">file</a>
<a href="#">alt</a>	when type is <a href="#">image</a>
<a href="#">autocomplete</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">password</a> , <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , <a href="#">range</a> , or <a href="#">color</a>
<a href="#">autofocus</a>	
<a href="#">checked</a>	when type is <a href="#">checkbox</a> or <a href="#">radio</a>
<a href="#">dirname</a>	when type is <a href="#">text</a> or <a href="#">search</a>
<a href="#">disabled</a>	
<a href="#">form</a>	
<a href="#">formaction</a>	when type is <a href="#">submit</a> or <a href="#">image</a>
<a href="#">formenctype</a>	when type is <a href="#">submit</a> or <a href="#">image</a>
<a href="#">formmethod</a>	when type is <a href="#">submit</a> or <a href="#">image</a>
<a href="#">formnovalidate</a>	when type is <a href="#">submit</a> or <a href="#">image</a>
<a href="#">formtarget</a>	when type is <a href="#">submit</a> or <a href="#">image</a>
<a href="#">height</a>	when type is <a href="#">image</a>
<a href="#">list</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , <a href="#">range</a> , or <a href="#">color</a>
<a href="#">max</a>	when type is <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , or <a href="#">range</a>
<a href="#">maxlength</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , or <a href="#">password</a>
<a href="#">min</a>	when type is <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , or <a href="#">range</a>
<a href="#">multiple</a>	when type is <a href="#">email</a> or <a href="#">file</a>
<a href="#">name</a>	
<a href="#">pattern</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , or <a href="#">password</a>
<a href="#">placeholder</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">password</a> , or <a href="#">number</a>
<a href="#">readonly</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">password</a> , <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , or <a href="#">number</a>

<a href="#">required</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">password</a> , <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , <a href="#">checkbox</a> , <a href="#">radio</a> , or <a href="#">file</a>
<a href="#">size</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , or <a href="#">password</a>
<a href="#">src</a>	when type is <a href="#">image</a>
<a href="#">step</a>	when type is <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , or <a href="#">range</a>
<a href="#">type</a>	
<a href="#">value</a>	when type is not <a href="#">file</a> or <a href="#">image</a>
<a href="#">width</a>	when type is <a href="#">image</a>

345. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 355, column 23; to line 360, column 24](#)

```
<input type="email" className="email" id="email" placeholder="Votre adresse email" />
```

346. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 362, column 21; to line 362, column 48](#)

```
<div className="form-group">
```

Attributes for element `div`:

[Global attributes](#)

347. **Error** Attribute `htmlfor` not allowed on element `label` at this point.

[From line 363, column 23; to line 363, column 49](#)

```
<label htmlFor="telephone"></label>
```

Attributes for element `label`:

[Global attributes](#)

[for](#) — Associate the label with form control

348. **Error** **Attribute** `classname` **not allowed on element** `input` **at this point.**

[From line 364, column 23; to line 369, column 24](#)

```
<input type="tel" classname="téléphone" id="telephone" placeholder="Votre numéro de téléphone" />
```

Attributes for element `input`:

[Global attributes](#)

<a href="#">accept</a>	when type is <a href="#">file</a>
<a href="#">alt</a>	when type is <a href="#">image</a>
<a href="#">autocomplete</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">password</a> , <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , <a href="#">range</a> , or <a href="#">color</a>
<a href="#">autofocus</a>	
<a href="#">checked</a>	when type is <a href="#">checkbox</a> or <a href="#">radio</a>
<a href="#">dirname</a>	when type is <a href="#">text</a> or <a href="#">search</a>
<a href="#">disabled</a>	
<a href="#">form</a>	
<a href="#">formaction</a>	when type is <a href="#">submit</a> or <a href="#">image</a>
<a href="#">formenctype</a>	when type is <a href="#">submit</a> or <a href="#">image</a>
<a href="#">formmethod</a>	when type is <a href="#">submit</a> or <a href="#">image</a>
<a href="#">formnovalidate</a>	when type is <a href="#">submit</a> or <a href="#">image</a>
<a href="#">formtarget</a>	when type is <a href="#">submit</a> or <a href="#">image</a>
<a href="#">height</a>	when type is <a href="#">image</a>
<a href="#">list</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , <a href="#">range</a> , or <a href="#">color</a>
<a href="#">max</a>	when type is <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , or <a href="#">range</a>
<a href="#">maxlength</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , or <a href="#">password</a>
<a href="#">min</a>	when type is <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , or <a href="#">range</a>



<a href="#">multiple</a>	when type is <a href="#">email</a> or <a href="#">file</a>
<a href="#">name</a>	
<a href="#">pattern</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , or <a href="#">password</a>
<a href="#">placeholder</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">password</a> , or <a href="#">number</a>
<a href="#">readonly</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">password</a> , <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , or <a href="#">number</a>
<a href="#">required</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">password</a> , <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , <a href="#">checkbox</a> , <a href="#">radio</a> , or <a href="#">file</a>
<a href="#">size</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , or <a href="#">password</a>
<a href="#">src</a>	when type is <a href="#">image</a>
<a href="#">step</a>	when type is <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , or <a href="#">range</a>
<a href="#">type</a>	
<a href="#">value</a>	when type is not <a href="#">file</a> or <a href="#">image</a>
<a href="#">width</a>	when type is <a href="#">image</a>

349. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 364, column 23; to line 369, column 24](#)

```
<input type="tel" className="téléphone" id="telephone" placeholder="Votre numéro de téléphone" />
```

350. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 371, column 21; to line 371, column 48](#)

```
<div classname="form-group">
```

Attributes for element `div`:

[Global attributes](#)

351. **Error** Attribute `htmlfor` not allowed on element `label` at this point.

[From line 372, column 23; to line 372, column 45](#)

```
<label htmlFor="sujet"></labe
```

Attributes for element [label](#):

[Global attributes](#)

[for](#) — Associate the label with form control

352. **Error** **Attribute** `classname` **not allowed on element** [input](#) **at this point.**

[From line 373, column 23; to line 378, column 24](#)

```
<input type="text" className="sujet"
id="sujet" placeholder="Sujet" />
```

Attributes for element [input](#):

[Global attributes](#)

[accept](#)

when type is [file](#)

[alt](#)

when type is [image](#)

[autocomplete](#)

when type is [text](#), [search](#), [url](#), [tel](#), [email](#), [password](#), [date](#), [month](#), [week](#), [time](#), [datetime-local](#), [number](#), [range](#), or [color](#)

[autofocus](#)

[checked](#)

when type is [checkbox](#) or [radio](#)

[dirname](#)

when type is [text](#) or [search](#)

[disabled](#)

[form](#)

[formaction](#)

when type is [submit](#) or [image](#)

[formenctype](#)

when type is [submit](#) or [image](#)

[formmethod](#)

when type is [submit](#) or [image](#)

[formnovalidate](#)

when type is [submit](#) or [image](#)

[formtarget](#)

when type is [submit](#) or [image](#)

[height](#)

when type is [image](#)

<a href="#">list</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , <a href="#">range</a> , or <a href="#">color</a>
<a href="#">max</a>	when type is <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , or <a href="#">range</a>
<a href="#">maxlength</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , or <a href="#">password</a>
<a href="#">min</a>	when type is <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , or <a href="#">range</a>
<a href="#">multiple</a>	when type is <a href="#">email</a> or <a href="#">file</a>
<a href="#">name</a>	
<a href="#">pattern</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , or <a href="#">password</a>
<a href="#">placeholder</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">password</a> , or <a href="#">number</a>
<a href="#">readonly</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">password</a> , <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , or <a href="#">number</a>
<a href="#">required</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , <a href="#">password</a> , <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , <a href="#">checkbox</a> , <a href="#">radio</a> , or <a href="#">file</a>
<a href="#">size</a>	when type is <a href="#">text</a> , <a href="#">search</a> , <a href="#">url</a> , <a href="#">tel</a> , <a href="#">email</a> , or <a href="#">password</a>
<a href="#">src</a>	when type is <a href="#">image</a>
<a href="#">step</a>	when type is <a href="#">date</a> , <a href="#">month</a> , <a href="#">week</a> , <a href="#">time</a> , <a href="#">datetime-local</a> , <a href="#">number</a> , or <a href="#">range</a>
<a href="#">type</a>	
<a href="#">value</a>	when type is not <a href="#">file</a> or <a href="#">image</a>
<a href="#">width</a>	when type is <a href="#">image</a>

353. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 373, column 23; to line 378, column 24](#)

```
<input type="text" className="sujet"
id="sujet" placeholder="Sujet" />
```

354. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 380, column 21; to line 380, column 48](#)

```
<div classname="form-group">
```

Attributes for element `div`:

[Global attributes](#)

355. **Error** Attribute `htmlfor` not allowed on element `label` at this point.

[From line 381, column 23; to line 381, column 47](#)

```
<label htmlFor="message"></labe
```

Attributes for element `label`:

[Global attributes](#)

[for](#) — Associate the label with form control

356. **Error** Attribute `classname` not allowed on element `button` at this point.

[From line 388, column 21; to line 388, column 66](#)

```
<button type="submit" className="btn-contact"><stron
```

Attributes for element `button`:

[Global attributes](#)

[disabled](#) — Whether the form control is disabled

[form](#) — Associates the element with a [form](#) element

[formaction](#) — [URL](#) to use for [form submission](#)

[formenctype](#) — [Entry list](#) encoding type to use for [form submission](#)

[formmethod](#) — Variant to use for [form submission](#)

[formnovalidate](#) — Bypass form control validation for [form submission](#)

[formtarget](#) — [Navigable](#) for [form submission](#)

[name](#) — Name of the element to use for [form submission](#) and in the [form.elements](#) API

[popovertarget](#) — Targets a popover element to toggle, show, or hide

[popovertargetaction](#) — Indicates whether a targeted popover element is to be toggled, shown, or hidden

[type](#) — Type of button

[value](#) — Value to be used for [form submission](#)

357. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 391, column 17; to line 391, column 46](#)

```
<div classname="contact-info">↵
```

Attributes for element `div`:

[Global attributes](#)

358. **Error** Attribute `classname` not allowed on element `i` at this point.

[From line 394, column 21; to line 394, column 60](#)

```
<i classname="fa-solid fa-location-dot">↵
```

Attributes for element `i`:

[Global attributes](#)

359. **Error** Attribute `classname` not allowed on element `i` at this point.

[From line 398, column 21; to line 398, column 68](#)

```
<i classname="fa-solid fa-mobile-screen-button">↵
```

Attributes for element `i`:

[Global attributes](#)

360. **Warning** Attribute `border:` is not serializable as XML 1.0.

[From line 403, column 19; to line 414, column 19](#)

```
<iframe↵ src="https://www.google.com/maps/embed?pb=!1m18!1m12!1m3!
1d2782.626965754099!2d4...e2b9!2s40%20Rue%20Laure%20Diebold%2C%2069009%20Lyon!5e0!3m2!1sfr!2sfr!
4v1719059881625!5m2!1sfr!2sfr"↵ width="600"↵ height="450"↵
```

361. **Warning** Attribute `0` is not serializable as XML 1.0.

[From line 403, column 19; to line 414, column 19](#)

```
<iframe↵ src="https://www.google.com/maps/embed?pb=!1m18!1m12!1m3!
```

```
1d2782.626965754099!2d4...e2b9!2s40%20Rue%20Laure%20Diebold%2C%2069009%20Lyon!5e0!3m2!1sfr!2sfr!
```

362. **Warning** Attribute `}}` is not serializable as XML 1.0.

[From line 403, column 19; to line 414, column 19](#)

```
<iframe↵ src="https://www.google.com/maps/embed?pb=!1m18!1m12!1m3!
1d2782.626965754099!2d4...e2b9!2s40%20Rue%20Laure%20Diebold%2C%2069009%20Lyon!5e0!3m2!1sfr!2sfr!
4v1719059881625!5m2!1sfr!2sfr"↵ width="600"↵ height="450"↵
```

363. **Error** Attribute `border:` not allowed on element `iframe` at this point.

[From line 403, column 19; to line 414, column 19](#)

```
<iframe↵ src="https://www.google.com/maps/embed?pb=!1m18!1m12!1m3!
1d2782.626965754099!2d4...e2b9!2s40%20Rue%20Laure%20Diebold%2C%2069009%20Lyon!5e0!3m2!1sfr!2sfr!
4v1719059881625!5m2!1sfr!2sfr"↵ width="600"↵ height="450"↵
```

Attributes for element `iframe`:

[Global attributes](#)

[src](#) — Address of the resource

[srcdoc](#) — A document to render in the `iframe`

[name](#) — Name of [content navigable](#)

[sandbox](#) — Security rules for nested content

[allow](#) — [Permissions policy](#) to be applied to the `iframe`'s contents

[allowfullscreen](#) — Whether to allow the `iframe`'s contents to use [requestFullscreen\(\)](#)

[width](#) — Horizontal dimension

[height](#) — Vertical dimension

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[loading](#) — Used when determining loading deferral

364. **Error** Attribute `0` not allowed on element `iframe` at this point.

[From line 403, column 19; to line 414, column 19](#)

```
<iframe src="https://www.google.com/maps/embed?pb=!1m18!1m12!1m3!1d2782.626965754099!2d4...e2b9!2s40%20Rue%20Laure%20Diebold%2C%2069009%20Lyon!5e0!3m2!1sfr!2sfr!4v1719059881625!5m2!1sfr!2sfr" width="600" height="450">
```

Attributes for element [iframe](#):

[Global attributes](#)

[src](#) — Address of the resource

[srcdoc](#) — A document to render in the [iframe](#)

[name](#) — Name of [content navigable](#)

[sandbox](#) — Security rules for nested content

[allow](#) — [Permissions policy](#) to be applied to the [iframe](#)'s contents

[allowfullscreen](#) — Whether to allow the [iframe](#)'s contents to use [requestFullscreen\(\)](#)

[width](#) — Horizontal dimension

[height](#) — Vertical dimension

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[loading](#) — Used when determining loading deferral

365. **Error** Attribute `}}` not allowed on element `iframe` at this point.

[From line 403, column 19; to line 414, column 19](#)

```
<iframe src="https://www.google.com/maps/embed?pb=!1m18!1m12!1m3!1d2782.626965754099!2d4...e2b9!2s40%20Rue%20Laure%20Diebold%2C%2069009%20Lyon!5e0!3m2!1sfr!2sfr!4v1719059881625!5m2!1sfr!2sfr" width="600" height="450">
```

Attributes for element [iframe](#):

[Global attributes](#)

[src](#) — Address of the resource

[srcdoc](#) — A document to render in the [iframe](#)

[name](#) — Name of [content navigable](#)

[sandbox](#) — Security rules for nested content

[allow](#) — [Permissions policy](#) to be applied to the [iframe](#)'s contents

[allowfullscreen](#) — Whether to allow the [iframe](#)'s contents to use [requestFullscreen\(\)](#)

[width](#) — Horizontal dimension

[height](#) — Vertical dimension

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[loading](#) — Used when determining loading deferral

366. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 421, column 7; to line 421, column 39](#)

```
iv>↵      <div classname="container-fluid">↵
```

Attributes for element `div`:

[Global attributes](#)

367. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 422, column 9; to line 422, column 29](#)

```
>↵      <div className="row">↵
```

Attributes for element `div`:

[Global attributes](#)

368. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 423, column 11; to line 423, column 49](#)

```
<div classname="col-12 titre-mentions">↵
```

Attributes for element `div`:

[Global attributes](#)

369. **Error** Attribute `classname` not allowed on element `div` at this point.



[From line 427, column 11; to line 427, column 59](#)

```
<div className="accordion" id="accordionExample">
```

Attributes for element [div](#):

[Global attributes](#)

370. **Error** Attribute `classname` not allowed on element [div](#) at this point.

[From line 428, column 13; to line 428, column 44](#)

```
<div className="accordion-item">
```

Attributes for element [div](#):

[Global attributes](#)

371. **Error** Attribute `classname` not allowed on element [h2](#) at this point.

[From line 429, column 15; to line 429, column 47](#)

```
<h2 className="accordion-header">
```

372. **Error** Attribute `classname` not allowed on element [button](#) at this point.

[From line 430, column 17; to line 437, column 17](#)

```
<button                                className="accordion-button"                                type="button"
data-bs-toggle="collapse"                                data-bs-target="#collapseOne"                                aria-
expanded="true"                                aria-controls="collapseOne"                                >
```

Attributes for element [button](#):

[Global attributes](#)

[disabled](#) — Whether the form control is disabled

[form](#) — Associates the element with a [form](#) element

[formaction](#) — [URL](#) to use for [form submission](#)

[formenctype](#) — [Entry list](#) encoding type to use for [form submission](#)

[formmethod](#) — Variant to use for [form submission](#)

[formnovalidate](#) — Bypass form control validation for [form submission](#)

[formtarget](#) — [Navigable](#) for [form submission](#)

[name](#) — Name of the element to use for [form submission](#) and in the [form.elements](#) API

[popovertarget](#) — Targets a popover element to toggle, show, or hide

[popovertargetaction](#) — Indicates whether a targeted popover element is to be toggled, shown, or hidden

[type](#) — Type of button

[value](#) — Value to be used for [form submission](#)

373. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 441, column 15; to line 445, column 15](#)

```
<div id="collapseOne" className="accordion-collapse collapse
show" data-bs-parent="#accordionExample">
```

Attributes for element `div`:

[Global attributes](#)

374. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 446, column 17; to line 446, column 48](#)

```
<div className="accordion-body">
```

Attributes for element `div`:

[Global attributes](#)

375. **Error** Attribute `classname` not allowed on element `i` at this point.

[From line 450, column 23; to line 450, column 62](#)

```
<i className="fa-solid fa-location-dot"> </i>
```

Attributes for element `i`:

[Global attributes](#)

376. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 452, column 23; to line 452, column 28](#)

```
<br /> 69009
```

377. **Error** Attribute `classname` not allowed on element `a` at this point.

[From line 455, column 23; to line 455, column 69](#)

```
<a href="tel:0620304050" className="telephone">↵
```

Attributes for element `a`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[target](#) — [Navigable](#) for [hyperlink navigation](#)

[download](#) — Whether to download the resource instead of navigating to it, and its filename if so

[ping](#) — [URLs](#) to ping

[rel](#) — Relationship between the location in the document containing the [hyperlink](#) and the destination resource

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

378. **Error** Attribute `classname` not allowed on element `i` at this point.

[From line 456, column 25; to line 456, column 72](#)

```
<i className="fa-solid fa-mobile-screen-button"> </i>↵
```

Attributes for element `i`:

[Global attributes](#)

379. **Error** Attribute `classname` not allowed on element `a` at this point.

[From line 460, column 21; to line 460, column 73](#)

```
<a href="mailto:john.doe@gmail.com" className="mail">↵
```

Attributes for element [a](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[target](#) — [Navigable](#) for [hyperlink navigation](#)

[download](#) — Whether to download the resource instead of navigating to it, and its filename if so

[ping](#) — [URLs](#) to ping

[rel](#) — Relationship between the location in the document containing the [hyperlink](#) and the destination resource

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

380. **Error** Attribute `classname` not allowed on element `i` at this point.

[From line 461, column 23; to line 461, column 58](#)

```
<i classname="fa-solid fa-envelope"></i>jo
```

Attributes for element `i`:

[Global attributes](#)

381. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 467, column 13; to line 467, column 44](#)

```
<div classname="accordion-item"></div>
```

Attributes for element `div`:

[Global attributes](#)

382. **Error** Attribute `classname` not allowed on element `h2` at this point.

[From line 468, column 15; to line 468, column 47](#)

```
<h2 classname="accordion-header"></h2>
```

383. **Error** Attribute `classname` not allowed on element `button` at this point.

[From line 469, column 17; to line 476, column 17](#)

```
<button          className="accordion-button collapsed"
type="button"    data-bs-toggle="collapse"    data-bs-
target="#collapseTwo"    aria-expanded="false"    aria-
```

Attributes for element `button`:

[Global attributes](#)

[disabled](#) — Whether the form control is disabled

[form](#) — Associates the element with a [form](#) element

[formaction](#) — [URL](#) to use for [form submission](#)

[formenctype](#) — [Entry list](#) encoding type to use for [form submission](#)

[formmethod](#) — Variant to use for [form submission](#)

[formnovalidate](#) — Bypass form control validation for [form submission](#)

[formtarget](#) — [Navigable](#) for [form submission](#)

[name](#) — Name of the element to use for [form submission](#) and in the [form.elements](#) API

[popovertarget](#) — Targets a popover element to toggle, show, or hide

[popovertargetaction](#) — Indicates whether a targeted popover element is to be toggled, shown, or hidden

[type](#) — Type of button

[value](#) — Value to be used for [form submission](#)

384. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 480, column 15; to line 484, column 15](#)

```
<div          id="collapseTwo"          className="accordion-collapse
collapse"    data-bs-parent="#accordionExample"    >
```

Attributes for element `div`:

[Global attributes](#)

385. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 490, column 23; to line 490, column 28](#)

```
<br /> 75008
```

386. **Error** Attribute `classname` not allowed on element `a` at this point.

[From line 492, column 21; to line 496, column 21](#)

```
<a href="https://www.alwaysdata.com/fr/"
target="blank"
className="always">
```

Attributes for element `a`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[target](#) — [Navigable](#) for [hyperlink navigation](#)

[download](#) — Whether to download the resource instead of navigating to it, and its filename if so

[ping](#) — [URLs](#) to ping

[rel](#) — Relationship between the location in the document containing the [hyperlink](#) and the destination resource

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

387. **Error** Attribute `classname` not allowed on element `i` at this point.

[From line 497, column 23; to line 497, column 64](#)

```
<i classname="fa-sharp fa-solid fa-globe"></i>
```

Attributes for element `i`:

[Global attributes](#)

388. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 504, column 13; to line 504, column 44](#)

```
<div className="accordion-item">↵
```

Attributes for element [div](#):

[Global attributes](#)

389. **Error** Attribute `classname` not allowed on element `h2` at this point.

[From line 505, column 15; to line 505, column 47](#)

```
<h2 className="accordion-header">↵
```

390. **Error** Attribute `classname` not allowed on element `button` at this point.

[From line 506, column 17; to line 513, column 17](#)

```
<button                                className="accordion-button collapsed"↵
type="button"↵                        data-bs-toggle="collapse"↵                data-bs-
target="#collapseThree"↵              aria-expanded="false"↵                aria-
```

Attributes for element [button](#):

[Global attributes](#)

[disabled](#) — Whether the form control is disabled

[form](#) — Associates the element with a [form](#) element

[formaction](#) — [URL](#) to use for [form submission](#)

[formenctype](#) — [Entry list](#) encoding type to use for [form submission](#)

[formmethod](#) — Variant to use for [form submission](#)

[formnovalidate](#) — Bypass form control validation for [form submission](#)

[formtarget](#) — [Navigable](#) for [form submission](#)

[name](#) — Name of the element to use for [form submission](#) and in the [form.elements](#) API

[popovertarget](#) — Targets a popover element to toggle, show, or hide

[popovertargetaction](#) — Indicates whether a targeted popover element is to be toggled, shown, or hidden

[type](#) — Type of button

[value](#) — Value to be used for [form submission](#)

391. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 517, column 15; to line 521, column 15](#)

```
<div id="collapseThree" className="accordion-collapse  
collapse" data-bs-parent="#accordionExample">
```

Attributes for element `div`:

[Global attributes](#)

392. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 522, column 17; to line 522, column 48](#)

```
<div className="accordion-body">
```

Attributes for element `div`:

[Global attributes](#)

393. **Error** Attribute `classname` not allowed on element `a` at this point.

[From line 527, column 21; to line 531, column 21](#)

```
<a href="https://pixabay.com/fr/"  
target="blank" className="pixabay">
```

Attributes for element `a`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[target](#) — [Navigable](#) for [hyperlink navigation](#)

[download](#) — Whether to download the resource instead of navigating to it, and its filename if so

[ping](#) — [URLs](#) to ping

[rel](#) — Relationship between the location in the document containing the [hyperlink](#) and the destination resource

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element



394. **Error** Element `imagedynamic` not allowed as child of element `main` in this context. (Suppressing further errors from this subtree.)

[From line 542, column 9; to line 542, column 24](#)

```
>↵      <ImageDynamic />↵
```

Content model for element `main`:

[Flow content](#).

395. **Error** Self-closing syntax (`/>`) used on a non-void HTML element. Ignoring the slash and treating as a start tag.

[From line 542, column 9; to line 542, column 24](#)

```
>↵      <ImageDynamic />↵
```

396. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 551, column 15; to line 555, column 16](#)

```
      <img↵                src={real1}↵                className="card-img-top"↵
alt="fresh food"↵                />↵
```

397. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 561, column 17; to line 561, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

398. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 561, column 17; to line 561, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

399. **Error** Stray end tag `link`.

[From line 563, column 17; to line 563, column 23](#)

```
</Link>
```

400. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 570, column 15; to line 574, column 16](#)

```
<img src={real2} className="card-img-top"
alt="restaurant japonais" />
```

401. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 578, column 17; to line 578, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">
```

402. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 578, column 17; to line 578, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">
```

403. **Error** Stray end tag `link`.

[From line 580, column 17; to line 580, column 23](#)

```
</Link>
```

404. **Info** Trailing slash on void elements [has no effect](#) and [interacts badly with unquoted attribute values](#).

[From line 587, column 15; to line 591, column 16](#)

```
<img src={real3} className="card-img-top"
alt="espace bien etre" />
```

405. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 597, column 17; to line 597, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

406. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 597, column 17; to line 597, column 65](#)

```
<Link to="#" className="btn btn-outline-primary">↵
```

407. **Error** Stray end tag `link`.

[From line 599, column 17; to line 599, column 23](#)

```
</Link>↵
```

408. **Error** Self-closing syntax (`/>`) used on a non-void HTML element. Ignoring the slash and treating as a start tag.

[From line 606, column 21; to line 606, column 36](#)

```
<ImageDynamic />↵
```

409. **Warning** Section lacks heading. Consider using `h2` - `h6` elements to [add identifying headings to all sections](#), or else use a `div` element instead for any cases where no heading is needed.

[From line 613, column 29; to line 613, column 69](#)

```
<section className="row container-offre">↵
```

410. **Error** End tag `main` seen, but there were open elements.

[From line 634, column 1; to line 634, column 7](#)

```
</div></main><
```

411. **Error** Unclosed element `imagedynamic`.

[From line 606, column 21; to line 606, column 36](#)

```
<ImageDynamic />
```

412. **Error** Unclosed element `imagedynamic`.

[From line 542, column 9; to line 542, column 24](#)

```
><ImageDynamic />
```

413. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 636, column 7; to line 636, column 39](#)

```
er><div className="container-fluid">
```

Attributes for element `div`:

[Global attributes](#)

414. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 637, column 9; to line 637, column 36](#)

```
><div className="row d-flex">
```

Attributes for element `div`:

[Global attributes](#)

415. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 638, column 11; to line 638, column 52](#)

```
<div className="col-12 col-md-6 col-lg-3">
```

Attributes for element [div](#):

[Global attributes](#)

416. **Error** Element `adress` not allowed as child of element `div` in this context. (Suppressing further errors from this subtree.)

[From line 640, column 13; to line 640, column 20](#)

```
<adress><␣
```

Content model for element [div](#):

If the element is a child of a [dl](#) element: one or more [dt](#) elements followed by one or more [dd](#) elements, optionally intermixed with [script-supporting elements](#).

If the element is not a child of a [dl](#) element: [flow content](#).

417. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 653, column 35](#)

```
tyle={{ color: "#000000" }}<␣
```

418. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 653, column 43](#)

```
color: "#000000" }}<␣
```

419. **Warning** Attribute `color:` is not serializable as XML 1.0.

[From line 651, column 17; to line 654, column 17](#)

```
<i␣                               className="fa-brands fa-github"␣                               style={{ color:
"#000000" }}<␣                               ></i><␣
```

420. **Warning** Attribute `"#000000"` is not serializable as XML 1.0.

[From line 651, column 17; to line 654, column 17](#)

```
<i␣                               className="fa-brands fa-github"␣                               style={{ color:
```

```
"#000000" }}<br></i><br>
```

421. **Warning** Attribute `}}` is not serializable as XML 1.0.

[From line 651, column 17; to line 654, column 17](#)

```
<i><br>className="fa-brands fa-github"<br>style={{ color:<br>"#000000" }}<br></i><br>
```

422. **Error** Attribute `classname` not allowed on element `i` at this point.

[From line 651, column 17; to line 654, column 17](#)

```
<i><br>className="fa-brands fa-github"<br>style={{ color:<br>"#000000" }}<br></i><br>
```

Attributes for element `i`:

[Global attributes](#)

423. **Error** Attribute `color:` not allowed on element `i` at this point.

[From line 651, column 17; to line 654, column 17](#)

```
<i><br>className="fa-brands fa-github"<br>style={{ color:<br>"#000000" }}<br></i><br>
```

Attributes for element `i`:

[Global attributes](#)

424. **Error** Attribute `"#000000"` not allowed on element `i` at this point.

[From line 651, column 17; to line 654, column 17](#)

```
<i><br>className="fa-brands fa-github"<br>style={{ color:<br>"#000000" }}<br></i><br>
```

Attributes for element `i`:

[Global attributes](#)

425. **Error** Attribute `}}` not allowed on element `i` at this point.

[From line 651, column 17; to line 654, column 17](#)

```
<i className="fa-brands fa-github" style={{ color:
"#000000" }}>
</i>
```

Attributes for element `i`:

[Global attributes](#)

426. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 663, column 35](#)

```
tyle={{ color: "#000000" }}
```

427. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 663, column 43](#)

```
color: "#000000" }}
```

428. **Warning** Attribute `color:` is not serializable as XML 1.0.

[From line 661, column 17; to line 664, column 17](#)

```
<i className="fa-brands fa-x-twitter" style={{ color:
"#000000" }}>
</i>
```

429. **Warning** Attribute `"#000000"` is not serializable as XML 1.0.

[From line 661, column 17; to line 664, column 17](#)

```
<i className="fa-brands fa-x-twitter" style={{ color:
"#000000" }}>
</i>
```

430. **Warning** Attribute `}}` is not serializable as XML 1.0.

[From line 661, column 17; to line 664, column 17](#)

```
<i      className="fa-brands fa-x-twitter"      style={{ color:
"#000000" }}>
></i>
```

431. **Error** Attribute `classname` not allowed on element `i` at this point.

[From line 661, column 17; to line 664, column 17](#)

```
<i      className="fa-brands fa-x-twitter"      style={{ color:
"#000000" }}>
></i>
```

Attributes for element `i`:

[Global attributes](#)

432. **Error** Attribute `color:` not allowed on element `i` at this point.

[From line 661, column 17; to line 664, column 17](#)

```
<i      className="fa-brands fa-x-twitter"      style={{ color:
"#000000" }}>
></i>
```

Attributes for element `i`:

[Global attributes](#)

433. **Error** Attribute `"#000000"` not allowed on element `i` at this point.

[From line 661, column 17; to line 664, column 17](#)

```
<i      className="fa-brands fa-x-twitter"      style={{ color:
"#000000" }}>
></i>
```

Attributes for element `i`:

[Global attributes](#)

434. **Error** Attribute `}}` not allowed on element `i` at this point.

[From line 661, column 17; to line 664, column 17](#)

```
<i      className="fa-brands fa-x-twitter"      style={{ color:
"#000000" }}>
></i>
```



Attributes for element [i](#):

[Global attributes](#)

435. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 673, column 35](#)

```
tyle={{ color: "#000000" }}↵
```

436. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 673, column 43](#)

```
color: "#000000" }}↵
```

437. **Warning** Attribute `color:` is not serializable as XML 1.0.

[From line 671, column 17; to line 674, column 17](#)

```
<i↵                               className="fa-brands fa-linkedin"↵                               style={{ color:
"#000000" }}↵                               ></i>↵
```

438. **Warning** Attribute `"#000000"` is not serializable as XML 1.0.

[From line 671, column 17; to line 674, column 17](#)

```
<i↵                               className="fa-brands fa-linkedin"↵                               style={{ color:
"#000000" }}↵                               ></i>↵
```

439. **Warning** Attribute `}}` is not serializable as XML 1.0.

[From line 671, column 17; to line 674, column 17](#)

```
<i↵                               className="fa-brands fa-linkedin"↵                               style={{ color:
"#000000" }}↵                               ></i>↵
```

440. **Error** Attribute `classname` not allowed on element [i](#) at this point.

[From line 671, column 17; to line 674, column 17](#)

```
<i className="fa-brands fa-linkedin" style={{ color:
"#000000" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

441. **Error** Attribute `color:` not allowed on element [i](#) at this point.

[From line 671, column 17; to line 674, column 17](#)

```
<i className="fa-brands fa-linkedin" style={{ color:
"#000000" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

442. **Error** Attribute `"#000000"` not allowed on element [i](#) at this point.

[From line 671, column 17; to line 674, column 17](#)

```
<i className="fa-brands fa-linkedin" style={{ color:
"#000000" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

443. **Error** Attribute `}}` not allowed on element [i](#) at this point.

[From line 671, column 17; to line 674, column 17](#)

```
<i className="fa-brands fa-linkedin" style={{ color:
"#000000" }}></i>
```

Attributes for element [i](#):

[Global attributes](#)

444. **Error** Attribute `classname` not allowed on element [div](#) at this point.

[From line 678, column 11; to line 678, column 52](#)

```
<div className="col-12 col-md-6 col-lg-3">↵
```

Attributes for element [div](#):

[Global attributes](#)

445. **Error** Attribute `classname` not allowed on element [ul](#) at this point.

[From line 680, column 13; to line 680, column 42](#)

```
<ul className="list-unstyled">↵
```

Attributes for element [ul](#):

[Global attributes](#)

446. **Error** Attribute `to` not allowed on element [link](#) at this point.

[From line 682, column 17; to line 682, column 52](#)

```
<Link to="/" className="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="[icon](#)")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="[preload](#)")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="[preload](#)")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="[preload](#)" and [rel](#)="[modulepreload](#)")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

447. **Error** Attribute `classname` not allowed on element `link` at this point.

[From line 682, column 17; to line 682, column 52](#)

```
<Link to="/" classname="text-black">↵
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

448. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

[From line 682, column 17; to line 682, column 52](#)

```
<Link to="/" className="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

449. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 682, column 17; to line 682, column 52](#)

```
<Link to="/" className="text-black">
```

450. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 682, column 17; to line 682, column 52](#)

```
<Link to="/" className="text-black">
```

451. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 685, column 37](#)

```
tyle={{ color: "#0d6efd" }}
```

452. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 685, column 45](#)

```
color: "#0d6efd" }}
```

453. **Warning** Attribute `color:` is not serializable as XML 1.0.

[From line 683, column 19; to line 686, column 19](#)

```
<i                                className="fas fa-chevron-right me-1"                                style={{
color: "#0d6efd" }}>                                ></i>
```

454. **Warning** Attribute `"#0d6efd"` is not serializable as XML 1.0.

[From line 683, column 19; to line 686, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

455. **Warning** Attribute `}}` is not serializable as XML 1.0.

[From line 683, column 19; to line 686, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

456. **Error** Attribute `classname` not allowed on element `i` at this point.

[From line 683, column 19; to line 686, column 19](#)

```
<i classname="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element `i`:

[Global attributes](#)

457. **Error** Attribute `color:` not allowed on element `i` at this point.

[From line 683, column 19; to line 686, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element `i`:

[Global attributes](#)

458. **Error** Attribute `"#0d6efd"` not allowed on element `i` at this point.

[From line 683, column 19; to line 686, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
```

```
color: "#0d6efd" }}</i>
```

Attributes for element [i](#):

[Global attributes](#)

459. **Error** Attribute `}}` not allowed on element [i](#) at this point.

[From line 683, column 19; to line 686, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
```

Attributes for element [i](#):

[Global attributes](#)

460. **Error** Stray end tag `link`.

[From line 688, column 17; to line 688, column 23](#)

```
</Link>
```

461. **Error** Attribute `classname` not allowed on element [a](#) at this point.

[From line 691, column 17; to line 691, column 59](#)

```
<a href="/#aPropos" classname="text-black">
```

Attributes for element [a](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[target](#) — [Navigable](#) for [hyperlink navigation](#)

[download](#) — Whether to download the resource instead of navigating to it, and its filename if so

[ping](#) — [URLs](#) to ping

[rel](#) — Relationship between the location in the document containing the [hyperlink](#) and the destination resource

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource



[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

462. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 694, column 37](#)

```
tyle={{ color: "#0d6efd" }}↵
```

463. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 694, column 45](#)

```
color: "#0d6efd" }}↵
```

464. **Warning** Attribute `color:` is not serializable as XML 1.0.

[From line 692, column 19; to line 695, column 19](#)

```
      <i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

465. **Warning** Attribute `"#0d6efd"` is not serializable as XML 1.0.

[From line 692, column 19; to line 695, column 19](#)

```
      <i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

466. **Warning** Attribute `}}` is not serializable as XML 1.0.

[From line 692, column 19; to line 695, column 19](#)

```
      <i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

467. **Error** Attribute `classname` not allowed on element `i` at this point.

[From line 692, column 19; to line 695, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

468. **Error** Attribute `color:` not allowed on element [i](#) at this point.

[From line 692, column 19; to line 695, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

469. **Error** Attribute `"#0d6efd"` not allowed on element [i](#) at this point.

[From line 692, column 19; to line 695, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

470. **Error** Attribute `}}` not allowed on element [i](#) at this point.

[From line 692, column 19; to line 695, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

471. **Error** Attribute `to` not allowed on element [link](#) at this point.

[From line 700, column 17; to line 700, column 59](#)

```
<Link to="/service" className="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

472. **Error** Attribute `classname` not allowed on element [link](#) at this point.

[From line 700, column 17; to line 700, column 59](#)

```
<Link to="/service" className="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

473. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

[From line 700, column 17; to line 700, column 59](#)

```
<Link to="/service" className="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

474. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 700, column 17; to line 700, column 59](#)

```
<Link to="/service" className="text-black">↵
```

475. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 700, column 17; to line 700, column 59](#)

```
<Link to="/service" className="text-black">↵
```

476. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 703, column 37](#)

```
type={{ color: "#0d6efd" }}↵
```

477. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 703, column 45](#)

```
color: "#0d6efd" }}↵
```

478. **Warning** Attribute `color:` is not serializable as XML 1.0.

[From line 701, column 19; to line 704, column 19](#)

```
      <i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

479. **Warning** Attribute `"#0d6efd"` is not serializable as XML 1.0.

[From line 701, column 19; to line 704, column 19](#)

```
      <i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

480. **Warning** Attribute `}}` is not serializable as XML 1.0.

[From line 701, column 19; to line 704, column 19](#)

```
      <i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

481. **Error** Attribute `classname` not allowed on element `i` at this point.

[From line 701, column 19; to line 704, column 19](#)

```
      <i↵                               classname="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

Attributes for element [i](#):

[Global attributes](#)

482. **Error** Attribute `color`: not allowed on element [i](#) at this point.

[From line 701, column 19; to line 704, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

483. **Error** Attribute `"#0d6efd"` not allowed on element [i](#) at this point.

[From line 701, column 19; to line 704, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

484. **Error** Attribute `}}` not allowed on element [i](#) at this point.

[From line 701, column 19; to line 704, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

485. **Error** Stray end tag `link`.

[From line 706, column 17; to line 706, column 23](#)

```
</Link>
```

486. **Error** Attribute `to` not allowed on element `link` at this point.

[From line 709, column 17; to line 709, column 59](#)

```
<Link to="/contact" className="text-black">↵
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="[icon](#)")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="[preload](#)")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="[preload](#)")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="[preload](#)" and [rel](#)="[modulepreload](#)")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="[mask-icon](#)")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

487. **Error** Attribute `classname` not allowed on element `link` at this point.

[From line 709, column 17; to line 709, column 59](#)

```
<Link to="/contact" classname="text-black">↵
```



Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

488. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

[From line 709, column 17; to line 709, column 59](#)

```
<Link to="/contact" className="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

489. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 709, column 17; to line 709, column 59](#)

```
<Link to="/contact" className="text-black">↵
```

490. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 709, column 17; to line 709, column 59](#)

```
<Link to="/contact" className="text-black">↵
```

491. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 712, column 37](#)

```
type={{ color: "#0d6efd" }}↵
```

492. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 712, column 45](#)

```
color: "#0d6efd" }}↵
```

493. **Warning** Attribute `color:` is not serializable as XML 1.0.

[From line 710, column 19; to line 713, column 19](#)

```
      <i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

494. **Warning** Attribute `"#0d6efd"` is not serializable as XML 1.0.

[From line 710, column 19; to line 713, column 19](#)

```
      <i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

495. **Warning** Attribute `}}` is not serializable as XML 1.0.

[From line 710, column 19; to line 713, column 19](#)

```
      <i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

496. **Error** Attribute `classname` not allowed on element `i` at this point.

[From line 710, column 19; to line 713, column 19](#)

```
      <i↵                               classname="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

Attributes for element [i](#):

[Global attributes](#)

497. **Error** Attribute `color`: not allowed on element [i](#) at this point.

[From line 710, column 19; to line 713, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

498. **Error** Attribute `"#0d6efd"` not allowed on element [i](#) at this point.

[From line 710, column 19; to line 713, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

499. **Error** Attribute `}}` not allowed on element [i](#) at this point.

[From line 710, column 19; to line 713, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

500. **Error** Stray end tag `link`.

[From line 715, column 17; to line 715, column 23](#)

```
</Link>
```

501. **Error** Attribute `to` not allowed on element `link` at this point.

[From line 718, column 17; to line 718, column 60](#)

```
<Link to="/mentions" className="text-black">↵
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="[icon](#)")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="[preload](#)")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="[preload](#)")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="[preload](#)" and [rel](#)="[modulepreload](#)")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="[mask-icon](#)")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

502. **Error** Attribute `classname` not allowed on element `link` at this point.

[From line 718, column 17; to line 718, column 60](#)

```
<Link to="/mentions" classname="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

503. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

[From line 718, column 17; to line 718, column 60](#)

```
<Link to="/mentions" className="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

504. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 718, column 17; to line 718, column 60](#)

```
<Link to="/mentions" className="text-black">↵
```

505. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 718, column 17; to line 718, column 60](#)

```
<Link to="/mentions" className="text-black">↵
```

506. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 721, column 37](#)

```
tyle={{ color: "#0d6efd" }}↵
```

507. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 721, column 45](#)

```
color: "#0d6efd" }}↵
```

508. **Warning** Attribute `color:` is not serializable as XML 1.0.

[From line 719, column 19; to line 722, column 19](#)

```
      <i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

509. **Warning** Attribute `"#0d6efd"` is not serializable as XML 1.0.

[From line 719, column 19; to line 722, column 19](#)

```
      <i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

510. **Warning** Attribute `}}` is not serializable as XML 1.0.

[From line 719, column 19; to line 722, column 19](#)

```
      <i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

511. **Error** Attribute `classname` not allowed on element `i` at this point.

[From line 719, column 19; to line 722, column 19](#)

```
      <i↵                               classname="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```



Attributes for element [i](#):

[Global attributes](#)

512. **Error** Attribute `color`: not allowed on element [i](#) at this point.

[From line 719, column 19; to line 722, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

513. **Error** Attribute `"#0d6efd"` not allowed on element [i](#) at this point.

[From line 719, column 19; to line 722, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

514. **Error** Attribute `}}` not allowed on element [i](#) at this point.

[From line 719, column 19; to line 722, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

515. **Error** Stray end tag `link`.

[From line 724, column 17; to line 724, column 23](#)

```
</Link>
```

516. **Error** Attribute `classname` not allowed on element `div` at this point.

[From line 729, column 11; to line 729, column 52](#)

```
<div classname="col-12 col-md-6 col-lg-3">↵
```

Attributes for element `div`:

[Global attributes](#)

517. **Error** Attribute `classname` not allowed on element `ul` at this point.

[From line 731, column 13; to line 731, column 42](#)

```
<ul classname="list-unstyled">↵
```

Attributes for element `ul`:

[Global attributes](#)

518. **Error** Attribute `to` not allowed on element `link` at this point.

[From line 733, column 17; to line 733, column 64](#)

```
<Link to="/realisations" classname="text-black">↵
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

519. **Error** Attribute `classname` not allowed on element `link` at this point.

[From line 733, column 17; to line 733, column 64](#)

```
<Link to="/realisations" className="text-black">↵
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

520. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

[From line 733, column 17; to line 733, column 64](#)

```
<Link to="/realisations" className="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

521. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 733, column 17; to line 733, column 64](#)

```
<Link to="/realisations" className="text-black">↵
```

522. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 733, column 17; to line 733, column 64](#)

```
<Link to="/realisations" className="text-black">↵
```

523. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 736, column 37](#)

```
tyle={{ color: "#0d6efd" }}↵
```

524. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 736, column 45](#)

```
color: "#0d6efd" }}↵
```

525. **Warning** Attribute `color:` is not serializable as XML 1.0.

[From line 734, column 19; to line 737, column 19](#)

```
<i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

526. **Warning** Attribute `"#0d6efd"` is not serializable as XML 1.0.

[From line 734, column 19; to line 737, column 19](#)

```
<i                                     className="fas fa-chevron-right me-1"      style={{
color: "#0d6efd" }}>                                     ></i>
```

527. **Warning** Attribute `}}` is not serializable as XML 1.0.[From line 734, column 19; to line 737, column 19](#)

```
<i                                     className="fas fa-chevron-right me-1"      style={{
color: "#0d6efd" }}>                                     ></i>
```

528. **Error** Attribute `classname` not allowed on element `i` at this point.[From line 734, column 19; to line 737, column 19](#)

```
<i                                     className="fas fa-chevron-right me-1"      style={{
color: "#0d6efd" }}>                                     ></i>
```

Attributes for element `i`:[Global attributes](#)529. **Error** Attribute `color:` not allowed on element `i` at this point.[From line 734, column 19; to line 737, column 19](#)

```
<i                                     className="fas fa-chevron-right me-1"      style={{
color: "#0d6efd" }}>                                     ></i>
```

Attributes for element `i`:[Global attributes](#)530. **Error** Attribute `"#0d6efd"` not allowed on element `i` at this point.[From line 734, column 19; to line 737, column 19](#)

```
<i                                     className="fas fa-chevron-right me-1"      style={{
color: "#0d6efd" }}>                                     ></i>
```

Attributes for element `i`:

[Global attributes](#)

531. **Error** Attribute `}}` not allowed on element `i` at this point.

[From line 734, column 19; to line 737, column 19](#)

```
<i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

Attributes for element `i`:

[Global attributes](#)

532. **Error** Stray end tag `link`.

[From line 739, column 17; to line 739, column 23](#)

```
</Link>↵
```

533. **Error** Attribute `to` not allowed on element `link` at this point.

[From line 742, column 17; to line 742, column 64](#)

```
<Link to="/realisations" className="text-black">↵
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SR!\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="[icon](#)")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)=[preload](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)=[preload](#))

[as](#) — [Potential destination](#) for a preload request (for [rel](#)=[preload](#) and [rel](#)=[modulepreload](#))

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)=[mask-icon](#))

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

534. **Error** Attribute `classname` not allowed on element [link](#) at this point.

[From line 742, column 17; to line 742, column 64](#)

```
<Link to="/realisations" className="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)=[icon](#))

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)=[preload](#))

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)=[preload](#))

[as](#) — [Potential destination](#) for a preload request (for [rel](#)=[preload](#) and [rel](#)=[modulepreload](#))



[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

535. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

[From line 742, column 17; to line 742, column 64](#)

```
<Link to="/realisations" className="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

536. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 742, column 17; to line 742, column 64](#)

```
<Link to="/realisations" className="text-black">↵
```

537. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 742, column 17; to line 742, column 64](#)

```
<Link to="/realisations" className="text-black">↵
```

538. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 745, column 37](#)

```
tyle={{ color: "#0d6efd" }}↵
```

539. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 745, column 45](#)

```
color: "#0d6efd" }}↵
```

540. **Warning** Attribute `color:` is not serializable as XML 1.0.

[From line 743, column 19; to line 746, column 19](#)

```
<i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

541. **Warning** Attribute `"#0d6efd"` is not serializable as XML 1.0.

[From line 743, column 19; to line 746, column 19](#)

```
<i↵          className="fas fa-chevron-right me-1"↵          style={{
color: "#0d6efd" }}↵        ></i>↵
```

542. **Warning** Attribute `}}` is not serializable as XML 1.0.

[From line 743, column 19; to line 746, column 19](#)

```
<i↵          className="fas fa-chevron-right me-1"↵          style={{
color: "#0d6efd" }}↵        ></i>↵
```

543. **Error** Attribute `classname` not allowed on element `i` at this point.

[From line 743, column 19; to line 746, column 19](#)

```
<i↵          className="fas fa-chevron-right me-1"↵          style={{
color: "#0d6efd" }}↵        ></i>↵
```

Attributes for element `i`:

[Global attributes](#)

544. **Error** Attribute `color:` not allowed on element `i` at this point.

[From line 743, column 19; to line 746, column 19](#)

```
<i↵          className="fas fa-chevron-right me-1"↵          style={{
color: "#0d6efd" }}↵        ></i>↵
```

Attributes for element `i`:

[Global attributes](#)

545. **Error** Attribute `"#0d6efd"` not allowed on element `i` at this point.

[From line 743, column 19; to line 746, column 19](#)

```
<i↵          className="fas fa-chevron-right me-1"↵          style={{
```

```
color: "#0d6efd" }}</i>
```

Attributes for element [i](#):

[Global attributes](#)

546. **Error** Attribute `}}` not allowed on element [i](#) at this point.

[From line 743, column 19; to line 746, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
```

Attributes for element [i](#):

[Global attributes](#)

547. **Error** Stray end tag `link`.

[From line 748, column 17; to line 748, column 23](#)

```
</Link>
```

548. **Error** Attribute `to` not allowed on element [link](#) at this point.

[From line 751, column 17; to line 751, column 64](#)

```
<Link to="/realisations" className="text-black">
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

549. **Error** Attribute `classname` not allowed on element `link` at this point.

[From line 751, column 17; to line 751, column 64](#)

```
<Link to="/realisations" className="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

550. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

[From line 751, column 17; to line 751, column 64](#)

```
<Link to="/realisations" className="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

551. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 751, column 17; to line 751, column 64](#)

```
<Link to="/realisations" className="text-black">↵
```

552. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 751, column 17; to line 751, column 64](#)

```
<Link to="/realisations" className="text-black">↵
```

553. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 754, column 37](#)

```
tyle={{ color: "#0d6efd" }}↵
```

554. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 754, column 45](#)

```
color: "#0d6efd" }}↵
```

555. **Warning** Attribute `color:` is not serializable as XML 1.0.

[From line 752, column 19; to line 755, column 19](#)

```
<i↵                className="fas fa-chevron-right me-1"↵                style={{
```

```
color: "#0d6efd" }}↵></
```

556. **Warning** Attribute `"#0d6efd"` is not serializable as XML 1.0.

[From line 752, column 19; to line 755, column 19](#)

```
<i↵className="fas fa-chevron-right me-1"↵style={{color: "#0d6efd" }}↵></
```

557. **Warning** Attribute `}}` is not serializable as XML 1.0.

[From line 752, column 19; to line 755, column 19](#)

```
<i↵className="fas fa-chevron-right me-1"↵style={{color: "#0d6efd" }}↵></
```

558. **Error** Attribute `classname` not allowed on element `i` at this point.

[From line 752, column 19; to line 755, column 19](#)

```
<i↵className="fas fa-chevron-right me-1"↵style={{color: "#0d6efd" }}↵></
```

Attributes for element `i`:

[Global attributes](#)

559. **Error** Attribute `color:` not allowed on element `i` at this point.

[From line 752, column 19; to line 755, column 19](#)

```
<i↵className="fas fa-chevron-right me-1"↵style={{color: "#0d6efd" }}↵></
```

Attributes for element `i`:

[Global attributes](#)

560. **Error** Attribute `"#0d6efd"` not allowed on element `i` at this point.

[From line 752, column 19; to line 755, column 19](#)



```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}></
```

Attributes for element [i](#):

[Global attributes](#)

561. **Error** Attribute `}}` not allowed on element [i](#) at this point.

[From line 752, column 19; to line 755, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}></
```

Attributes for element [i](#):

[Global attributes](#)

562. **Error** Stray end tag `link`.

[From line 757, column 17; to line 757, column 23](#)

```
</Link>
```

563. **Error** Attribute `classname` not allowed on element [div](#) at this point.

[From line 761, column 11; to line 761, column 52](#)

```
<div className="col-12 col-md-6 col-lg-3">
```

Attributes for element [div](#):

[Global attributes](#)

564. **Error** Attribute `classname` not allowed on element [ul](#) at this point.

[From line 763, column 13; to line 763, column 42](#)

```
<ul className="list-unstyled">
```

Attributes for element [ul](#):

[Global attributes](#)

565. **Error** Attribute `to` not allowed on element `link` at this point.

[From line 765, column 17; to line 765, column 56](#)

```
<Link to="/blog" className="text-black">↵
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="[icon](#)")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="[preload](#)")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="[preload](#)")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="[preload](#)" and [rel](#)="[modulepreload](#)")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="[mask-icon](#)")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

566. **Error** Attribute `classname` not allowed on element `link` at this point.

[From line 765, column 17; to line 765, column 56](#)

```
<Link to="/blog" classname="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

567. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

[From line 765, column 17; to line 765, column 56](#)

```
<Link to="/blog" className="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

568. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 765, column 17; to line 765, column 56](#)

```
<Link to="/blog" className="text-black">↵
```

569. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 765, column 17; to line 765, column 56](#)

```
<Link to="/blog" className="text-black">↵
```

570. **Error** Quote " in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 768, column 37](#)

```
type={{ color: "#0d6efd" }}↵
```

571. **Error** Quote " in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 768, column 45](#)

```
color: "#0d6efd" }}↵
```

572. **Warning** Attribute color: is not serializable as XML 1.0.

[From line 766, column 19; to line 769, column 19](#)

```
<i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

573. **Warning** Attribute "#0d6efd" is not serializable as XML 1.0.

[From line 766, column 19; to line 769, column 19](#)

```
<i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

574. **Warning** Attribute }} is not serializable as XML 1.0.

[From line 766, column 19; to line 769, column 19](#)

```
<i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

575. **Error** Attribute classname not allowed on element i at this point.

[From line 766, column 19; to line 769, column 19](#)

```
<i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

Attributes for element [i](#):

[Global attributes](#)

576. **Error** Attribute `color`: not allowed on element [i](#) at this point.

[From line 766, column 19; to line 769, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

577. **Error** Attribute `"#0d6efd"` not allowed on element [i](#) at this point.

[From line 766, column 19; to line 769, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

578. **Error** Attribute `}}` not allowed on element [i](#) at this point.

[From line 766, column 19; to line 769, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

579. **Error** Stray end tag `link`.

[From line 771, column 17; to line 771, column 23](#)

```
</Link>
```

580. **Error** Attribute `to` not allowed on element `link` at this point.

[From line 774, column 17; to line 774, column 56](#)

```
<Link to="/blog" className="text-black">↵
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="[icon](#)")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="[preload](#)")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="[preload](#)")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="[preload](#)" and [rel](#)="[modulepreload](#)")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="[mask-icon](#)")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

581. **Error** Attribute `classname` not allowed on element `link` at this point.

[From line 774, column 17; to line 774, column 56](#)

```
<Link to="/blog" classname="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

582. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

[From line 774, column 17; to line 774, column 56](#)

```
<Link to="/blog" className="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)



[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

583. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 774, column 17; to line 774, column 56](#)

```
<Link to="/blog" className="text-black">↵
```

584. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 774, column 17; to line 774, column 56](#)

```
<Link to="/blog" className="text-black">↵
```

585. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 777, column 37](#)

```
type={{ color: "#0d6efd" }}↵
```

586. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 777, column 45](#)

```
color: "#0d6efd" }}↵
```

587. **Warning** Attribute `color:` is not serializable as XML 1.0.

[From line 775, column 19; to line 778, column 19](#)

```
<i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

588. **Warning** Attribute `"#0d6efd"` is not serializable as XML 1.0.

[From line 775, column 19; to line 778, column 19](#)

```
<i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

589. **Warning** Attribute `}}` is not serializable as XML 1.0.

[From line 775, column 19; to line 778, column 19](#)

```
<i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

590. **Error** Attribute `classname` not allowed on element `i` at this point.

[From line 775, column 19; to line 778, column 19](#)

```
<i↵                               classname="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

Attributes for element [i](#):

[Global attributes](#)

591. **Error** Attribute `color`: not allowed on element [i](#) at this point.

[From line 775, column 19; to line 778, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

592. **Error** Attribute `"#0d6efd"` not allowed on element [i](#) at this point.

[From line 775, column 19; to line 778, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

593. **Error** Attribute `}}` not allowed on element [i](#) at this point.

[From line 775, column 19; to line 778, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

594. **Error** Stray end tag `link`.

[From line 780, column 17; to line 780, column 23](#)

```
</Link>
```

595. **Error** Attribute `to` not allowed on element `link` at this point.

[From line 783, column 17; to line 783, column 56](#)

```
<Link to="/blog" className="text-black">↵
```

Attributes for element `link`:

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="[icon](#)")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="[preload](#)")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="[preload](#)")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="[preload](#)" and [rel](#)="[modulepreload](#)")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="[mask-icon](#)")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

596. **Error** Attribute `classname` not allowed on element `link` at this point.

[From line 783, column 17; to line 783, column 56](#)

```
<Link to="/blog" classname="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

597. **Error** Element [link](#) is missing one or more of the following attributes: [href](#), [itemprop](#), [property](#), [rel](#), [resource](#).

[From line 783, column 17; to line 783, column 56](#)

```
<Link to="/blog" className="text-black">↵
```

Attributes for element [link](#):

[Global attributes](#)

[href](#) — Address of the [hyperlink](#)

[crossorigin](#) — How the element handles crossorigin requests

[rel](#) — Relationship between the document containing the [hyperlink](#) and the destination resource

[media](#) — Applicable media

[integrity](#) — Integrity metadata used in *Subresource Integrity* checks [\[SRI\]](#)

[hreflang](#) — Language of the linked resource

[type](#) — Hint for the type of the referenced resource

[referrerpolicy](#) — [Referrer policy](#) for [fetches](#) initiated by the element

[sizes](#) — Sizes of the icons (for [rel](#)="icon")

[imagesrcset](#) — Images to use in different situations, e.g., high-resolution displays, small monitors, etc. (for [rel](#)="preload")

[imagesizes](#) — Image sizes for different page layouts (for [rel](#)="preload")

[as](#) — [Potential destination](#) for a preload request (for [rel](#)="preload" and [rel](#)="modulepreload")

[blocking](#) — Whether the element is [potentially render-blocking](#)

[color](#) — Color to use when customizing a site's icon (for [rel](#)="mask-icon")

[disabled](#) — Whether the link is disabled

[fetchpriority](#) — Sets the [priority](#) for [fetches](#) initiated by the element

Also, the [title](#) attribute [has special semantics](#) on this element: Title of the link; [CSS style sheet set name](#)

598. **Error** A `link` element must have an `href` or `imagesrcset` attribute, or both.

[From line 783, column 17; to line 783, column 56](#)

```
<Link to="/blog" className="text-black">↵
```

599. **Error** A `link` element must not appear as a descendant of a `body` element unless the `link` element has an `itemprop` attribute or has a `rel` attribute whose value contains `dns-prefetch`, `modulepreload`, `pingback`, `preconnect`, `prefetch`, `preload`, `prerender`, or `stylesheet`.

[From line 783, column 17; to line 783, column 56](#)

```
<Link to="/blog" className="text-black">↵
```

600. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 786, column 37](#)

```
type={{ color: "#0d6efd" }}↵
```

601. **Error** Quote `"` in attribute name. Probable cause: Matching quote missing somewhere earlier.

[At line 786, column 45](#)

```
color: "#0d6efd" }}↵
```

602. **Warning** Attribute `color:` is not serializable as XML 1.0.

[From line 784, column 19; to line 787, column 19](#)

```
      <i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

603. **Warning** Attribute `"#0d6efd"` is not serializable as XML 1.0.

[From line 784, column 19; to line 787, column 19](#)

```
      <i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

604. **Warning** Attribute `}}` is not serializable as XML 1.0.

[From line 784, column 19; to line 787, column 19](#)

```
      <i↵                               className="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

605. **Error** Attribute `classname` not allowed on element `i` at this point.

[From line 784, column 19; to line 787, column 19](#)

```
      <i↵                               classname="fas fa-chevron-right me-1"↵                               style={{
color: "#0d6efd" }}↵                               ></i>↵
```

Attributes for element [i](#):

[Global attributes](#)

606. **Error** Attribute `color`: not allowed on element [i](#) at this point.

[From line 784, column 19; to line 787, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

607. **Error** Attribute `"#0d6efd"` not allowed on element [i](#) at this point.

[From line 784, column 19; to line 787, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

608. **Error** Attribute `}}` not allowed on element [i](#) at this point.

[From line 784, column 19; to line 787, column 19](#)

```
<i className="fas fa-chevron-right me-1" style={{
color: "#0d6efd" }}>
</i>
```

Attributes for element [i](#):

[Global attributes](#)

609. **Error** Stray end tag `link`.

[From line 789, column 17; to line 789, column 23](#)

```
</Link>
```



610. **Error** **Attribute** `classname` **not allowed on element** `div` **at this point.**

[From line 795, column 7; to line 795, column 33](#)

```
iv><div className="copyright">
```

Attributes for element `div`:

[Global attributes](#)

Document checking completed.

## Source

```
1. <!DOCTYPE html>
2. <html lang="fr">
3.   <head>
4.     <meta charset="utf-8" />
5.     <link rel="icon" href="./favicon.png" />
6.     <meta name="viewport" content="width=device-width, initial-scale=1" />
7.     <meta name="theme-color" content="#000000" />
8.     <meta
9.       name="description"
10.      content="Web site created using create-react-app"
11.    />
12.     <link rel="apple-touch-icon" href="%PUBLIC_URL%/logo192.png" />
13.     <link rel="manifest" href="%PUBLIC_URL%/manifest.json" />
14.   <link
15.     href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
16.     rel="stylesheet"
17.     integrity="sha384-QWTKZyjpPEjISv5WaRU90FeRpok6YctnYmDr5pNlyT2bRjXh0JMhJy6hW+ALEwIH"
18.     crossorigin="anonymous"
19.   />
20.   <link
21.     rel="stylesheet"
22.     href="https://cdnjs.cloudflare.com/ajax/libs/font-awesome/6.0.0-beta3/css/all.min.css"
23.   />
24.   <!-- lien font -->
25.   <link rel="preconnect" href="https://fonts.googleapis.com">
26.   <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
27.   <link href="https://fonts.googleapis.com/css2?
28.     family=Nunito+Sans:ital,opsz,wght@0,6..12,200..1000;1,6..12,200..1000&display=swap" rel="stylesheet">
29.   <title>React App</title>
```

```
30. </head>↵
31. <body>↵
32.   <noscript>You need to enable JavaScript to run this app.</noscript>↵
33.   <div id="root"></div>↵
34.   <header>↵
35.     <nav↵
36.       class="navbar bg-dark navbar-expand-lg bg-body-tertiary"↵
37.       data-bs-theme="dark"↵
38.     >↵
39.     <div class="container-fluid">↵
40.       <Link class="navbar-brand" to="/">↵
41.         John Doe↵
42.       </Link>↵
43.       <button↵
44.         class="navbar-toggler"↵
45.         type="button"↵
46.         data-bs-toggle="collapse"↵
47.         data-bs-target="#navbarNav"↵
48.         aria-controls="navbarNav"↵
49.         aria-expanded="false"↵
50.         aria-label="Toggle navigation"↵
51.       >↵
52.         <span class="navbar-toggler-icon"></span>↵
53.       </button>↵
54.       <div class="collapse navbar-collapse" id="navbarNav">↵
55.         <ul class="navbar-nav ms-auto">↵
56.           <li class="nav-item">↵
57.             <Link to="/" className={`nav-link ${location.pathname === '/' ? 'active' : ""}`}>↵
58.               Accueil↵
59.             </Link>↵
60.           </li>↵
61.           <li class="nav-item">↵
62.             <Link to="/service" className={`nav-link ${location.pathname === '/service' ? 'active' :
63.               ""}`}>↵
64.               Services↵
65.             </Link>↵
66.           </li>↵
67.           <li class="nav-item">↵
68.             <Link to="/realisations" className={`nav-link ${location.pathname === '/realisations' ?
69.               'active' : ""}`}>↵
70.               Réalisations↵
71.             </Link>↵
72.           </li>↵
73.           <li class="nav-item">↵
74.             <Link to="/blog" className={`nav-link ${location.pathname === '/blog' ? 'active' : ""}`}>↵
75.               Blog↵
76.             </Link>↵
77.           </li>↵
78.           <li class="nav-item">↵
79.             <Link to="/contact" className={`nav-link ${location.pathname === '/contact' ? 'active' :
```

```
78.         Me contacter↵
79.         </Link>↵
80.     </li>↵
81. </ul>↵
82. </div>↵
83. </div>↵
84. </nav>↵
85. </header>↵
86. <main>↵
87.     <div className="home-container-accueil">↵
88.         <div className="background-image-accueil">↵
89.             <div className="overlay-accueil">↵
90.                 <h2>Bonjour, je suis John Doe</h2>↵
91.                 <h1>Développeur web full stack</h1>↵
92.                 <button type="button" className="btn btn-primary" onClick={scrollToAPropos}>↵
93.                     En savoir plus↵
94.                 </button>↵
95.             </div>↵
96.         </div>↵
97.     </div>↵
98.     <section id="aPropos">↵
99.         <div className="container mt-5">↵
100.             <div className="card-accueil">↵
101.                 <div className="row no-gutters">↵
102.                     { /* Première colonne */ }↵
103.                     <div className="col-md-6 col-sm-12">↵
104.                         <div className="card-body-accueil">↵
105.                             <h5 className="card-title-accueil">À propos</h5>↵
106.                             <br />↵
107.                             <p className="card-text">↵
108.                                 Passionné par l'informatique et les nouvelles technologies,↵
109.                                 j'ai suivi une formation d'↵
110.                                 <strong>intégrateur-développeur web</strong> au CEF. Au↵
111.                                 cours de cette formation, j'ai pu acquérir des bases solides↵
112.                                 pour travailler dans le domaine du{" "}↵
113.                                 <strong>développement web</strong>.↵
114.                             </p>↵
115.                             <br />↵
116.                             <p className="card-text">↵
117.                                 Basé à Lyon, je suis en recherche d'une alternance au sein↵
118.                                 d'une agence digitale pour consolider ma formation de{" "}↵
119.                                 <strong>développeur web full stack</strong>.↵
120.                             </p>↵
121.                             <br />↵
122.                             <p className="card-text">↵
123.                                 J'accorde une attention particulière à la qualité du code↵
124.                                 que l'écris et je respecte les bonnes pratiques du web↵
125.                             </p>↵
126.                         </div>↵
```

```
127.     </div>↵
128.     { /* Deuxième colonne */ }↵
129.     <div className="col-md-6 col-sm-12">↵
130.       <div className="card-body-accueil">↵
131.         <img src={photoProfil} className="img-fluid" alt="John Doe" />↵
132.         <div className="card-text mt-3">↵
133.           <h5 className="card-title2">Mes compétences</h5>↵
134.           <p className="card-competences">HTML5 90%</p>↵
135.           <div↵
136.             class="progress"↵
137.             role="progressbar"↵
138.             aria-label="Basic example"↵
139.             aria-valuenow="90"↵
140.             aria-valuemin="0"↵
141.             aria-valuemax="100"↵
142.           >↵
143.             <div↵
144.               className="progress-bar bg-danger"↵
145.               style={{ width: "90%" }}↵
146.             ></div>↵
147.           </div>↵
148.           <p className="card-competences">CSS3 80%</p>↵
149.           <div↵
150.             class="progress"↵
151.             role="progressbar"↵
152.             aria-label="Basic example"↵
153.             aria-valuenow="80"↵
154.             aria-valuemin="0"↵
155.             aria-valuemax="100"↵
156.           >↵
157.             <div↵
158.               className="progress-bar bg-info"↵
159.               style={{ width: "80%" }}↵
160.             ></div>↵
161.           </div>↵
162.           <p className="card-competences">JAVASCRIPT 70%</p>↵
163.           <div↵
164.             class="progress"↵
165.             role="progressbar"↵
166.             aria-label="Basic example"↵
167.             aria-valuenow="70"↵
168.             aria-valuemin="0"↵
169.             aria-valuemax="100"↵
170.           >↵
171.             <div↵
172.               className="progress-bar bg-warning"↵
173.               style={{ width: "70%" }}↵
174.             ></div>↵
175.           </div>↵
176.           <p className="card-competences">PHP 60%</p>↵
```

```
177.         <div↵
178.             class="progress"↵
179.             role="progressbar"↵
180.             aria-label="Basic example"↵
181.             aria-valuenow="60"↵
182.             aria-valuemin="0"↵
183.             aria-valuemax="100"↵
184.         >↵
185.         <div↵
186.             className="progress-bar bg-success"↵
187.             style={{ width: "60%" }}↵
188.         ></div>↵
189.     </div>↵
190.     <p className="card-competences">REACT 50%</p>↵
191.     <div↵
192.         class="progress"↵
193.         role="progressbar"↵
194.         aria-label="Basic example"↵
195.         aria-valuenow="50"↵
196.         aria-valuemin="0"↵
197.         aria-valuemax="100"↵
198.     >↵
199.     <div↵
200.         className="progress-bar"↵
201.         style={{ width: "50%" }}↵
202.     ></div>↵
203. </div>↵
204. </div>↵
205. </div>↵
206. </div>↵
207. </div>↵
208. </div>↵
209. </div>↵
210. </section>↵
211.     <div className="container-fluid">↵
212. <div className="row">↵
213.     <div className="col-12 titre-blog">↵
214.         <h2>Blog</h2>↵
215.         <p>Retrouvez ici quelques articles sur le développement web.</p>↵
216.     </div>↵
217.     <div className="col-12 col-md-6 col-lg-4 container-card">↵
218.         <div className="card">↵
219.             <img↵
220.                 src={blog1}↵
221.                 className="card-img-top"↵
222.                 alt="coder"↵
223.             />↵
224.             <div className="card-body">↵
225.                 <h5 className="card-title">Coder son site en HTML/CSS</h5>↵
226.                 <p className="card-text">
```

```
227.         Some quick example text to build on the card title and make up the bulk of the card's
content.↵
228.         </p>↵
229.         <Link to="#" className="btn btn-outline-primary">↵
230.             Lire la suite↵
231.         </Link>↵
232.     </div>↵
233.     <p className="card-footer">Publié le 22 août 2022</p>↵
234. </div>↵
235. </div>↵
236. <div className="col-12 col-md-6 col-lg-4 container-card">↵
237.     <div className="card">↵
238.         <img↵
239.             src={blog2}↵
240.             className="card-img-top"↵
241.             alt="croissance"↵
242.         />↵
243.         <div className="card-body">↵
244.             <h5 className="card-title">Vendre ses produits sur le web</h5>↵
245.             <p className="card-text">Some quick example text to build on the card title and make up
the bulk of the card's content.</p>↵
246.             <Link to="#" className="btn btn-outline-primary">↵
247.                 Lire la suite↵
248.             </Link>↵
249.         </div>↵
250.         <p className="card-footer">Publié le 20 août 2022</p>↵
251.     </div>↵
252. </div>↵
253. <div className="col-12 col-md-6 col-lg-4 container-card">↵
254.     <div className="card">↵
255.         <img↵
256.             src={blog3}↵
257.             className="card-img-top"↵
258.             alt="google"↵
259.         />↵
260.         <div className="card-body">↵
261.             <h5 className="card-title">Se positionner sur Google</h5>↵
262.             <p className="card-text">↵
263.                 Some quick example text to build on the card title and make up the bulk of the card's
content.↵
264.             </p>↵
265.             <Link to="#" className="btn btn-outline-primary">↵
266.                 Lire la suite↵
267.             </Link>↵
268.         </div>↵
269.         <p className="card-footer">Publié le 1 août 2022</p>↵
270.     </div>↵
271. </div>↵
272. <div className="col-12 col-md-6 col-lg-4 container-card">↵
273.     <div className="card">↵
```

```
274.         <img↵
275.             src={blog4}↵
276.             className="card-img-top"↵
277.             alt="screens"↵
278.         />↵
279.         <div className="card-body">↵
280.             <h5 className="card-title">Coder en responsive design</h5>↵
281.             <p className="card-text">↵
282.                 Some quick example text to build on the card title and make up the bulk of the card's
content.↵
283.             </p>↵
284.             <Link to="#" className="btn btn-outline-primary">↵
285.                 Lire la suite↵
286.             </Link>↵
287.         </div>↵
288.         <p className="card-footer">Publié le 31 juillet 2022</p>↵
289.     </div>↵
290. </div>↵
291. <div className="col-12 col-md-6 col-lg-4 container-card">↵
292.     <div className="card">↵
293.         <img↵
294.             src={blog5}↵
295.             className="card-img-top"↵
296.             alt="SEO"↵
297.         />↵
298.         <div className="card-body">↵
299.             <h5 className="card-title">Techniques de référencement</h5>↵
300.             <p className="card-text">↵
301.                 Some quick example text to build on the card title and make up the bulk of the card's
content.↵
302.             </p>↵
303.             <Link to="#" className="btn btn-outline-primary">↵
304.                 Lire la suite↵
305.             </Link>↵
306.         </div>↵
307.         <p className="card-footer">Publié le 30 juillet 2022</p>↵
308.     </div>↵
309. </div>↵
310. <div className="col-12 col-md-6 col-lg-4 container-card">↵
311.     <div className="card">↵
312.         <img↵
313.             src={blog6}↵
314.             className="card-img-top"↵
315.             alt="technos"↵
316.         />↵
317.         <div className="card-body">↵
318.             <h5 className="card-title">Apprendre à coder</h5>↵
319.             <p className="card-text">↵
320.                 Some quick example text to build on the card title and make up the bulk of the card's
content.↵
```

```
321.         </p><br>
322.         <Link to="#" className="btn btn-outline-primary"><br>
323.             Lire la suite<br>
324.         </Link><br>
325.     </div><br>
326.     <p className="card-footer">Publié le 12 juillet 2022</p><br>
327. </div><br>
328. </div><br>
329. </div><br>
330. </div><br>
331. <div className="home-container-contact"><br>
332.     <div className="background-image-contact"><br>
333.         <div className="overlay-contact"><br>
334.             <div className="titre-contact"><br>
335.                 <h2>Me contacter</h2><br>
336.                 <p><br>
337.                     Pour me contacter en vue d'un ensemble ou d'une future<br>
338.                     collaboration, merci de remplir le formulaire de contact.<br>
339.                 </p><br>
340.             <div className="contact-content"><br>
341.                 <div className="contact-form"><br>
342.                     <h3>Formulaire de contact</h3><br>
343.                     <form><br>
344.                         <div className="form-group"><br>
345.                             <label htmlFor="name"></label><br>
346.                             <input<br>
347.                                 type="text"<br>
348.                                 className="name"<br>
349.                                 id="name"<br>
350.                                 placeholder="Votre nom"<br>
351.                             /><br>
352.                         </div><br>
353.                         <div className="form-group"><br>
354.                             <label htmlFor="email"></label><br>
355.                             <input<br>
356.                                 type="email"<br>
357.                                 className="email"<br>
358.                                 id="email"<br>
359.                                 placeholder="Votre adresse email"<br>
360.                             /><br>
361.                         </div><br>
362.                         <div className="form-group"><br>
363.                             <label htmlFor="telephone"></label><br>
364.                             <input<br>
365.                                 type="tel"<br>
366.                                 className="téléphone"<br>
367.                                 id="telephone"<br>
368.                                 placeholder="Votre numéro de téléphone"<br>
369.                             /><br>
370.                         </div><br>
```



```
371.         <div className="form-group">↵
372.             <label htmlFor="sujet"></label>↵
373.             <input↵
374.                 type="text"↵
375.                 className="sujet"↵
376.                 id="sujet"↵
377.                 placeholder="Sujet"↵
378.             />↵
379.         </div>↵
380.         <div className="form-group">↵
381.             <label htmlFor="message"></label>↵
382.             <textarea↵
383.                 id="message"↵
384.                 name="message"↵
385.                 placeholder="Votre message"↵
386.             ></textarea>↵
387.         </div>↵
388.         <button type="submit" className="btn-contact"><strong>Envoyer</strong></button>↵
389.     </form>↵
390. </div>↵
391. <div className="contact-info">↵
392.     <h3>Mes coordonnées</h3>↵
393.     <address>↵
394.         <i className="fa-solid fa-location-dot">↵
395.             {" "}↵
396.             <span>40 Rue Laure Diebold, 69009 Lyon, France</span>↵
397.         </i>↵
398.         <i className="fa-solid fa-mobile-screen-button">↵
399.             {" "}↵
400.             <span>06 20 30 40 50</span>↵
401.         </i>↵
402.     </address>↵
403.     <iframe↵
404.         src="https://www.google.com/maps/embed?pb=!1m18!1m12!1m3!1d2782.626965754099!
2d4.796403976643226!3d45.77866571240162!2m3!1f0!2f0!3f0!3m2!1i1024!2i768!4f13.1!3m3!1m2!
1s0x47f4eb65edac5b3f%3A0xe01c47049cb2e2b9!2s40%20Rue%20Laure%20Diebold%2C%2069009%20Lyon!5e0!3m2!1sfr!
2sfr!4v1719059881625!5m2!1sfr!2sfr"↵
405.         width="600"↵
406.         height="450"↵
407.         style={{ border: 0 }}↵
408.         allowfullscreen=""↵
409.         aria-hidden="false"↵
410.         tabIndex="0"↵
411.         loading="lazy"↵
412.         referrerpolicy="no-referrer-when-downgrade"↵
413.         title="Localisation adresse John Doe"↵
414.     ></iframe>↵
415. </div>↵
416. </div>↵
417. </div>↵
```

```
418.         </div><br>
419.     </div><br>
420. </div><br>
421. <div className="container-fluid"><br>
422.     <div className="row"><br>
423.         <div className="col-12 titre-mentions"><br>
424.             <h2>Mentions légales</h2><br>
425.             <p></p><br>
426.         </div><br>
427.         <div className="accordion" id="accordionExample"><br>
428.             <div className="accordion-item"><br>
429.                 <h2 className="accordion-header"><br>
430.                     <button<br>
431.                         className="accordion-button"<br>
432.                         type="button"<br>
433.                         data-bs-toggle="collapse"<br>
434.                         data-bs-target="#collapseOne"<br>
435.                         aria-expanded="true"<br>
436.                         aria-controls="collapseOne"<br>
437.                     ><br>
438.                         Éditeur du site<br>
439.                     </button><br>
440.                 </h2><br>
441.                 <div<br>
442.                     id="collapseOne"<br>
443.                     className="accordion-collapse collapse show"<br>
444.                     data-bs-parent="#accordionExample"<br>
445.                 ><br>
446.                     <div className="accordion-body"><br>
447.                         <h3>John Doe</h3><br>
448.                         <address><br>
449.                             <p><br>
450.                                 <i className="fa-solid fa-location-dot"> </i><br>
451.                                 40 Rue Laure Diebold<br>
452.                                 <br /> 69009 Lyon, France<br>
453.                             </p><br>
454.                             <p><br>
455.                                 <a href="tel:0620304050" className="telephone"><br>
456.                                     <i className="fa-solid fa-mobile-screen-button"> </i><br>
457.                                     06 20 30 40 50<br>
458.                                 </a><br>
459.                             </p><br>
460.                                 <a href="mailto:john.doe@gmail.com" className="mail"><br>
461.                                     <i className="fa-solid fa-envelope"></i>john.doe@gmail.com<br>
462.                                 </a><br>
463.                             </address><br>
464.                         </div><br>
465.                     </div><br>
466.                 </div><br>
467.             <div className="accordion-item"><br>
```

```
468.      <h2 className="accordion-header">↵
469.        <button↵
470.          className="accordion-button collapsed"↵
471.          type="button"↵
472.          data-bs-toggle="collapse"↵
473.          data-bs-target="#collapseTwo"↵
474.          aria-expanded="false"↵
475.          aria-controls="collapseTwo"↵
476.        >↵
477.        Hébergeur↵
478.      </button>↵
479.    </h2>↵
480.    <div↵
481.      id="collapseTwo"↵
482.      className="accordion-collapse collapse"↵
483.      data-bs-parent="#accordionExample"↵
484.    >↵
485.      <div class="accordion-body">↵
486.        <h3>Always Data</h3>↵
487.        <address>↵
488.          <p>↵
489.            91 rue du Faubourg Saint Honoré↵
490.            <br /> 75008 Paris↵
491.          </p>↵
492.          <a↵
493.            href="https://www.alwaysdata.com/fr/"↵
494.            target="blank"↵
495.            className="always"↵
496.          >↵
497.            <i className="fa-sharp fa-solid fa-globe"></i>↵
498.            www.alwaysdata.com↵
499.          </a>↵
500.        </address>↵
501.      </div>↵
502.    </div>↵
503.  </div>↵
504.  <div className="accordion-item">↵
505.    <h2 className="accordion-header">↵
506.      <button↵
507.        className="accordion-button collapsed"↵
508.        type="button"↵
509.        data-bs-toggle="collapse"↵
510.        data-bs-target="#collapseThree"↵
511.        aria-expanded="false"↵
512.        aria-controls="collapseThree"↵
513.      >↵
514.      Crédits↵
515.    </button>↵
516.  </h2>↵
517.  <div>
```

```
518.         id="collapseThree"<↵
519.         className="accordion-collapse collapse"<↵
520.         data-bs-parent="#accordionExample"<↵
521.     >↵
522.     <div className="accordion-body">↵
523.         <h3>Crédits</h3>↵
524.         <p>Site développé par John Doe, étudiant du CEF.</p>↵
525.         <p>↵
526.             Les images libres sont issues du site{" "}↵
527.             <a↵
528.                 href="https://pixabay.com/fr/"↵
529.                 target="blank"↵
530.                 className="pixabay"<↵
531.             >↵
532.                 <strong>Pixabay</strong>↵
533.             </a>↵
534.             .↵
535.         </p>↵
536.     </div>↵
537. </div>↵
538. </div>↵
539. </div>↵
540. </div>↵
541. </div>↵
542. <ImageDynamic />↵
543. <div className="container-fluid">↵
544.     <div className="row">↵
545.         <div className="col-12 titre-realisation">↵
546.             <h2>Portfolio</h2>↵
547.             <p>Voici quelques-unes de mes réalisations.</p>↵
548.         </div>↵
549.         <div className="col-12 col-md-6 col-lg-4 container-card">↵
550.             <div className="card">↵
551.                 <img↵
552.                     src={real1}<↵
553.                     className="card-img-top"<↵
554.                     alt="fresh food"<↵
555.                 />↵
556.                 <div className="card-body">↵
557.                     <h5 className="card-title">Fresh food</h5>↵
558.                     <p className="card-text">↵
559.                         Réalisation d'un site avec commande en ligne.↵
560.                     </p>↵
561.                     <Link to="#" className="btn btn-outline-primary">↵
562.                         Voir↵
563.                     </Link>↵
564.                 </div>↵
565.                 <p className="card-footer">Site réalisé avec PHP et MySQL</p>↵
566.             </div>↵
567.         </div>↵
```

```
568.     <div className="col-12 col-md-6 col-lg-4 container-card">↵
569.         <div className="card">↵
570.             <img↵
571.                 src={real2}↵
572.                 className="card-img-top"↵
573.                 alt="restaurant japonais"↵
574.             />↵
575.             <div className="card-body">↵
576.                 <h5 className="card-title">Restaurant akira</h5>↵
577.                 <p className="card-text">Réalisation d'un site vitrine.</p>↵
578.                 <Link to="#" className="btn btn-outline-primary">↵
579.                     Voir↵
580.                 </Link>↵
581.             </div>↵
582.             <p className="card-footer">Site réalisé avec WordPress</p>↵
583.         </div>↵
584.     </div>↵
585.     <div className="col-12 col-md-6 col-lg-4 container-card">↵
586.         <div className="card">↵
587.             <img↵
588.                 src={real3}↵
589.                 className="card-img-top"↵
590.                 alt="espace bien etre"↵
591.             />↵
592.             <div className="card-body">↵
593.                 <h5 className="card-title">Espace bien-être</h5>↵
594.                 <p className="card-text">↵
595.                     Réalisation d'un site vitrine pour un praticien de bien-être.↵
596.                 </p>↵
597.                 <Link to="#" className="btn btn-outline-primary">↵
598.                     Voir↵
599.                 </Link>↵
600.             </div>↵
601.             <p className="card-footer">Site réalisé en HTML/CSS</p>↵
602.         </div>↵
603.     </div>↵
604. </div>↵
605. </div>↵
606.     <ImageDynamic />↵
607.     <div className="container-fluid-service">↵
608.         <div className="row offre">↵
609.             <div className="col-12 titre-offre">↵
610.                 <h2 className="text-center">Mon offre de services</h2>↵
611.                 <p className="text-center">Voici les prestations sur lesquelles je peux
612. intervenir</p>↵
613.             </div>↵
614.             <section className="row container-offre">↵
615.                 <article className="col-12 col-md-4 col-lg-4">↵
616.                     <i className="fa-solid fa-display icone"></i>↵
                     <h2>ux design</h2>↵
```

```
617.             <p>L'<strong>UX Design</strong> est une méthode de conception centrée
sur l'utilisateur.</p>
618.             Son but est d'offrir une expérience de navigation optimale à
l'internaute.</p>
619.             </article>
620.             <article className="col-12 col-md-4 col-lg-4">
621.               <i className="fa-solid fa-file-code icone"></i>
622.               <h2>développement web</h2>
623.               <p>Le <strong>développement de sites web</strong> repose sur
l'utilisation des langages HTML, CSS, JavaScript et PHP.</p>
624.             </article>
625.             <article className="col-12 col-md-4 col-lg-4">
626.               <i className="fa-solid fa-magnifying-glass-dollar icone"></i>
627.               <h2>référencement</h2>
628.               <p>Le <strong>référencement naturel d'un site</strong>, aussi appelé
SEO, consiste à mettre des techniques en oeuvre pour <em>améliorer</em> sa <em>position</em>
dans les résultats des moteurs de recherche.</p>
629.             </article>
630.           </section>
631.         </div>
632.       </div>
633.     </div>
634. </main>
635.   <footer>
636.     <div className="container-fluid">
637.       <div className="row d-flex">
638.         <div className="col-12 col-md-6 col-lg-3">
639.           <h5>John Doe</h5>
640.           <adress>
641.             <p>40 Rue Laure Diebold</p>
642.             <p>69009 Lyon, France</p>
643.             <p>Téléphone : 06 20 30 40 50</p>
644.           </adress>
645.           <div class="reseaux-sociaux">
646.             <a
647.               href="https://github.com/github-john-doe"
648.               target="_blank"
649.               rel="noopener noreferrer nofollow"
650.             >
651.               <i
652.                 className="fa-brands fa-github"
653.                 style={{ color: "#000000" }}
654.               ></i>
655.             </a>
656.             <a
657.               href="https://x.com/twitter-john-doe"
658.               target="_blank"
659.               rel="noopener noreferrer nofollow"
660.             >
661.               <i
662.                 className="fa-brands fa-x-twitter"
```

```
663.         style={{ color: "#000000" }}<↵
664.     ></i><↵
665. </a><↵
666. <a↵
667.     href="https://linkedin.com/linkedin-john-doe"<↵
668.     target="_blank"<↵
669.     rel="noopener noreferrer nofollow"<↵
670. ><↵
671.     <i↵
672.         className="fa-brands fa-linkedin"<↵
673.         style={{ color: "#000000" }}<↵
674.     ></i><↵
675. </a><↵
676. </div><↵
677. </div><↵
678. <div className="col-12 col-md-6 col-lg-3"><↵
679.     <h5>Liens utiles</h5><↵
680.     <ul className="list-unstyled"><↵
681.         <li><↵
682.             <Link to="/" className="text-black"><↵
683.                 <i↵
684.                     className="fas fa-chevron-right me-1"<↵
685.                     style={{ color: "#0d6efd" }}<↵
686.                 ></i><↵
687.                 Accueil<↵
688.             </Link><↵
689.         </li><↵
690.         <li><↵
691.             <a href="/#aPropos" className="text-black"><↵
692.                 <i↵
693.                     className="fas fa-chevron-right me-1"<↵
694.                     style={{ color: "#0d6efd" }}<↵
695.                 ></i><↵
696.                 À propos<↵
697.             </a><↵
698.         </li><↵
699.         <li><↵
700.             <Link to="/service" className="text-black"><↵
701.                 <i↵
702.                     className="fas fa-chevron-right me-1"<↵
703.                     style={{ color: "#0d6efd" }}<↵
704.                 ></i><↵
705.                 Services<↵
706.             </Link><↵
707.         </li><↵
708.         <li><↵
709.             <Link to="/contact" className="text-black"><↵
710.                 <i↵
711.                     className="fas fa-chevron-right me-1"<↵
712.                     style={{ color: "#0d6efd" }}<↵
```

```
713.         ></i><br>
714.         Me contacter<br>
715.     </Link><br>
716. </li><br>
717. <li><br>
718.     <Link to="/mentions" className="text-black"><br>
719.         <i><br>
720.             className="fas fa-chevron-right me-1"<br>
721.             style={{ color: "#0d6efd" }}<br>
722.         ></i><br>
723.         Mentions légales<br>
724.     </Link><br>
725. </li><br>
726. <li></li><br>
727. </ul><br>
728. </div><br>
729. <div className="col-12 col-md-6 col-lg-3"><br>
730.     <h5>Mes dernières réalisations</h5><br>
731.     <ul className="list-unstyled"><br>
732.         <li><br>
733.             <Link to="/realisations" className="text-black"><br>
734.                 <i><br>
735.                     className="fas fa-chevron-right me-1"<br>
736.                     style={{ color: "#0d6efd" }}<br>
737.                 ></i><br>
738.                 Fresh Food<br>
739.             </Link><br>
740.         </li><br>
741.         <li><br>
742.             <Link to="/realisations" className="text-black"><br>
743.                 <i><br>
744.                     className="fas fa-chevron-right me-1"<br>
745.                     style={{ color: "#0d6efd" }}<br>
746.                 ></i><br>
747.                 Restaurant Akira<br>
748.             </Link><br>
749.         </li><br>
750.         <li><br>
751.             <Link to="/realisations" className="text-black"><br>
752.                 <i><br>
753.                     className="fas fa-chevron-right me-1"<br>
754.                     style={{ color: "#0d6efd" }}<br>
755.                 ></i><br>
756.                 Espace bien-être<br>
757.             </Link><br>
758.         </li><br>
759.     </ul><br>
760. </div><br>
761. <div className="col-12 col-md-6 col-lg-3"><br>
762.     <h5>Mes derniers articles</h5><br>
```



```
763.         <ul className="list-unstyled">↵
764.             <li>↵
765.                 <Link to="/blog" className="text-black">↵
766.                     <i↵
767.                         className="fas fa-chevron-right me-1"↵
768.                         style={{ color: "#0d6efd" }}↵
769.                     ></i>↵
770.                     Coder son site en HTML/CSS↵
771.                 </Link>↵
772.             </li>↵
773.             <li>↵
774.                 <Link to="/blog" className="text-black">↵
775.                     <i↵
776.                         className="fas fa-chevron-right me-1"↵
777.                         style={{ color: "#0d6efd" }}↵
778.                     ></i>↵
779.                     Vendre ses produits sur le web↵
780.                 </Link>↵
781.             </li>↵
782.             <li>↵
783.                 <Link to="/blog" className="text-black">↵
784.                     <i↵
785.                         className="fas fa-chevron-right me-1"↵
786.                         style={{ color: "#0d6efd" }}↵
787.                     ></i>↵
788.                     Se positionner sur Google↵
789.                 </Link>↵
790.             </li>↵
791.         </ul>↵
792.     </div>↵
793. </div>↵
794. </div>↵
795. <div className="copyright">↵
796.     <p>&copy; Designed by John Doe</p>↵
797. </div>↵
798. </footer>↵
799. ↵
800. <script↵
801.     src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"↵
802.     integrity="sha384-YvpcrYf0tY3lHB60NNkmXc5s9fDVZLESaAA55NDz0xhy9GkcIdslK1eN7N6jIeHz"↵
803.     crossorigin="anonymous"↵
804. ></script>↵
805. </body>↵
806. </html>↵
807.
```

Used the HTML parser.

Total execution time 416 milliseconds.

[About this checker](#) • [Report an issue](#) • Version: 24.5.11