Nummernschilderkennung mit Python

Anne-Sophie Bollmann, Susanne Klöcker, Pia von Kolken, Christian Peters 18. Februar 2021

Pipeline

Pipeline






Image Segmentation

Trainingseingaben





(a) Eingabe

(b) Ziel

Modellarchitektur






Abbildung 2: Das Ergebnis nach wochenlangem Ausprobieren.


Modellvorhersage




Schwellenwert



Umschließendes Rechteck



Resultat



Details zum Training

Implementierung in Tensorflow, Training auf Google Colab GPU

- 534 Zusätzliche Trainingsbilder hinzugefügt
- Data Augmentation: 949 ⇒ 22.776 Bilder
 - Horizontal Flip, Random Cropping, Random Contrast, Random Brightness
 - · Benötigt >14GB GPU Speicher!
- · Gradient Descent mit ADAM Optimizer
- · Loss: Binary cross entropy

$$-\sum_{\text{Pixel}} y_{\text{true}} \log(y_{\text{pred}}) + (1 - y_{\text{true}}) \log(1 - y_{\text{pred}})$$

- · Zur Validierung 20 Bilder aus EU/RO per Hand selektiert
- · "Early Stopping" nach 19 Epochen

Optical Character Recognition

Optical Character Recognition

Dies und das...

<u>Learnings</u>

Learnings

Dies und das...



Evaluator Results

Dies und das...

Literatur i



Systematic review on vehicular licence plate recognition framework in intelligent transport systems.

The Institution of Engineering and Technology, 2019.

T. P. I. P. Ltd.
Learn opencv, 2021.

J. Redmon and A. Farhadi. Yolov3: An incremental improvement. arXiv, 2018.

J. F. R. Rice, Stephen R. and T. A. Nartker.

The fifth annual test of ocr accuracy.

Information Science Research Institute, 1993.

Literatur ii



R. Smith.

An overview of the tesseract ocr engine.

Ninth International Conference on Document Analysis and Recognition (ICDAR 2007), 2:629–633, 2007.