

# Package ‘COMET’

October 28, 2023

**Title** COMET (Context-specific Optimization of EMT Trajectories)

**Version** 0.0.0.9000

**Maintainer** <annicenajafi@tamu.edu>

**Description** COMET is a computational framework for inferring EMT trajectories from time-course single cell RNA sequencing data.

**License** MIT

**Encoding** UTF-8

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.2.3

## R topics documented:

calculate_conf_intervals . . . . .	1
DTW_calculate . . . . .	2
find.min.alpha . . . . .	2
find.optimal.cutoff . . . . .	3
fit.all.data . . . . .	4
fit.CTMC . . . . .	4
generate_pipeline_files . . . . .	5
KS.label.me . . . . .	5
run.CTMC . . . . .	6
run_pipeline . . . . .	6
start_pipeline . . . . .	7
transition_matrix . . . . .	7
<b>Index</b>	<b>8</b>

---

calculate\_conf\_intervals

*This function calculates confidence intervals for every sample over 10 runs*

---

## Description

This function calculates confidence intervals for every sample over 10 runs

**Usage**

```
calculate_conf_intervals(data.inputs)
```

**Arguments**

`data.inputs`      the input datasheet stored in a csv file in the tables dir

**Value**

nothing, saves results within the Confidence\_Interval\_Calculations dir

---

DTW_calculate	<i>This function calculates the DTW distance bewteen the inferred trajectories for every cutoff and the flow cytometry data</i>
---------------	---

---

**Description**

This function calculates the DTW distance bewteen the inferred trajectories for every cutoff and the flow cytometry data

**Usage**

```
DTW_calculate(data.inputs, MET.range)
```

**Arguments**

`data.inputs`      the input datasheet stored in a csv file in the tables dir  
`MET.range`        range of time for MET to take place

**Value**

nothing, saves the matrix in the DTW\_Matrix dir

---

find.min.alpha	<i>This function finds the mse_total given a certain alpha</i>
----------------	--

---

**Description**

This function finds the mse\_total given a certain alpha

**Usage**

```
find.min.alpha(
  alpha,
  E_cad,
  hybrid,
  ZEB,
  M_sc,
  Mu_sc,
  eq,
  ref_eq_day,
  timepoints
)
```

**Arguments**

alpha	parameter alpha
E_cad	Epithelial percentage, just named E_cad
hybrid	hybrid percentage
ZEB	Mesenchymal percentage, just named ZEB
M_sc	ratio of M/E at steady state
Mu_sc	ratio of H/E at steady state
eq	what timepoint to start
ref_eq_day	steady state timepoint
timepoints	total timepoints

**Value**

mse\_total

---

find.optimal.cutoff	<i>Find the optimal cutoff Finds the best number of highly variable EMT genes</i>
---------------------	---

---

**Description**

Find the optimal cutoff Finds the best number of highly variable EMT genes

**Usage**

```
find.optimal.cutoff(data.input)
```

**Arguments**

data.input	input data to use
------------	-------------------

**Value**

optimal cutoff of highly variable genes

---

fit.all.data	<i>This function fits optimal CTMC trajectories to timecourse data</i>
--------------	--

---

**Description**

This function fits optimal CTMC trajectories to timecourse data

**Usage**

```
fit.all.data(data.inputs, MET.range)
```

**Arguments**

data.inputs	the input datasheet stored in a csv file in the tables dir
MET.range	range of time for MET to take place

**Value**

the final dataframe with the optimal trajectories fitted to data

---

fit.CTMC	<i>This function optimally fits 3 CTMC models to data (1st phase, 2nd phase, MET range)</i>
----------	---

---

**Description**

This function optimally fits 3 CTMC models to data (1st phase, 2nd phase, MET range)

**Usage**

```
fit.CTMC(data.input, MET.range, opt.cutoff)
```

**Arguments**

data.input	input data to use
MET.range	range where MET takes place
opt.cutoff	optimal cutoff of highly variable genes

**Value**

final trajectories, lambda\_E, mu, and lambda\_M respectively

---

generate\_pipeline\_files

*This function is to be ran for all cutoffs, purpose is to find the optimal number of EMT genes to minimize the DTW distance between the flow cytometry trajectories and data*

---

### Description

This function is to be ran for all cutoffs, purpose is to find the optimal number of EMT genes to minimize the DTW distance between the flow cytometry trajectories and data

### Usage

```
generate_pipeline_files(data.inputs, tables.dir, input.data.dir)
```

### Arguments

data.inputs	the input datasheet stored in a csv file in the tables dir
tables.dir	directory with a csv file that had the address for the data and metadata
input.data.dir	this is the directory where the input file should be saved in

### Value

does not return, saves the files in the COMET\_populated\_files dir

---

KS.label.me

*This function perform Kolmogorov Smirnov scoring on data, credit given to Priyanka Chakraborty as the code was adapted from her work and modified*

---

### Description

This function perform Kolmogorov Smirnov scoring on data, credit given to Priyanka Chakraborty as the code was adapted from her work and modified

### Usage

```
KS.label.me(exp.mat, genes, topgenes)
```

### Arguments

exp.mat	gene expression matrix
genes	genes
top200	receives top 200 highly variable genes for scoring

### Value

KS score

---

run.CTMC	<i>This function generates trajectories for a CTMC model given parameters</i>
----------	---

---

### Description

This function generates trajectories for a CTMC model given parameters

### Usage

```
run.CTMC(alph_fun, time.range, M_sc_fun, Mu_sc_fun, p0_fun)
```

### Arguments

alph_fun	alpha parameter used in function
time.range	specific timerange to generate trajectory
M_sc_fun	ratio of M/E at steady state
Mu_sc_fun	ratio of H/E at steady state
p0_fun	initial state vector

### Value

trajectories along with the resulting p vector

---

run_pipeline	<i>This function runs the data driven pipeline for inferring trajectories</i>
--------------	---

---

### Description

This function runs the data driven pipeline for inferring trajectories

### Usage

```
run_pipeline(data.inputs, tables.dir, input.data.dir, cutoff)
```

### Arguments

data.inputs	the input datasheet stored in a csv file in the tables dir
tables.dir	directory with a csv file that had the address for the data and metadata
input.data.dir	this is the directory where the input file should be saved in
cutoff	of highly variable EMT genes to be considered

### Value

the inferred trajectories, also saves them within the COMET\_populated\_files directory

---

start_pipeline	<i>Read necessary files and parameters for pipeline to run This function reads all the necessary files to run this pipeline</i>
----------------	---

---

**Description**

Read necessary files and parameters for pipeline to run This function reads all the necessary files to run this pipeline

**Usage**

```
start_pipeline(tables.dir, input.data.dir)
```

**Arguments**

tables.dir      directory with a csv file that had the address for the data and metadata  
input.data.dir   this is the directory where the input file should be saved in

**Value**

nothing, stores necessary parameters for the model in global variables

---

transition_matrix	<i>This function finds the transition matrix given the parameters for the generator matrix</i>
-------------------	--

---

**Description**

This function finds the transition matrix given the parameters for the generator matrix

**Usage**

```
transition_matrix(lambda_E, lambda_M, mu_E, mu_M, t)
```

**Arguments**

lambda\_E      Rate of transition from H to E  
lambda\_M      Rate of transition from H to M  
mu\_E          Rate of transition from E to H  
mu\_M          Rate of transition from M to H  
t              time

**Value**

the probability transition matrix

# Index

`calculate_conf_intervals`, [1](#)

`DTW_calculate`, [2](#)

`find.min.alpha`, [2](#)

`find.optimal.cutoff`, [3](#)

`fit.all.data`, [4](#)

`fit.CTMC`, [4](#)

`generate_pipeline_files`, [5](#)

`KS.label.me`, [5](#)

`run.CTMC`, [6](#)

`run_pipeline`, [6](#)

`start_pipeline`, [7](#)

`transition_matrix`, [7](#)