

Research Endpoint

# Create Research Task

Copy page

Tavily Research performs comprehensive research on a given topic by conducting multiple searches, analyzing sources, and generating a detailed research report.

POST /research

JavaScript SDK

JavaScript



```
const { tavily } = require("@tavily/core");

const tvly = tavily({ apiKey: "tvly-YOUR_API_KEY" });
const response = await tvly.research("What are the latest developments in AI?");

console.log(response);
```

201 400 401 429 432 433 500



```
{
  "request_id": "123e4567-e89b-12d3-a456-426614174111",
  "created_at": "2025-01-15T10:30:00Z",
  "status": "pending",
  "input": "What are the latest developments in AI?",
  "model": "mini",
  "response_time": 1.23
}
```

## Files

Attach files to a research request and the agent uses their contents as a source alongside the web. Add a `files` array to the request body, where each entry carries a filename and its base64-encoded contents. The agent reads the relevant parts of each file, grounds its answer in them, and cites any file it draws from.

## Full Request

```
{
  "input": "Summarize the key risks in the attached report and compare them to",
  "files": [
    {
      "name": "q1-report.md",
      "data": "<base64-encoded file contents>",
      "type": "base64"
    }
  ]
}
```

## Limits

| Limit                                         | Value        |
|-----------------------------------------------|--------------|
| Max files per request                         | 5            |
| Max size per text file ( .txt , .md , .json ) | 80,000 words |
| Max combined size of all files                | 80,000 words |

## Authorizations

Authorization string header required

Bearer authentication header in the form Bearer , where is your Tavily API key (e.g., Bearer tvly-YOUR\_API\_KEY).

## Body

application/json

---

Example: "What are the latest developments in AI?"

---

model `enum<string>` `default:auto`

The model used by the research agent. "mini" is optimized for targeted, efficient research and works best for narrow or well-scoped questions. "pro" provides comprehensive, multi-angle research and is suited for complex topics that span multiple subtopics or domains

Available options: mini , pro , auto

---

stream `boolean` `default:false`

Whether to stream the research results as they are generated. When 'true', returns a Server-Sent Events (SSE) stream. See [Streaming documentation](#) for details.

---

output\_schema `object`

A JSON Schema object that defines the structure of the research output. When provided, the research response will be structured to match this schema, ensuring a predictable and validated output shape. Must include a 'properties' field, and may optionally include 'required' field.

Show child attributes

Example:

&gt;

```
    "description": "The name of the company"
  },
  "key_metrics": {
    "type": "array",
    "description": "List of key performance metrics",
    "items": { "type": "string" }
  },
  "financial_details": {
    "type": "object",
    "description": "Detailed financial breakdown",
    "properties": {
      "operating_income": {
        "type": "number",
        "description": "Operating income for the period"
      }
    }
  }
},
"required": ["company"]
}
```

`citation_format` `enum<string>` `default:numbered`

The format for citations in the research report.

Available options: `numbered` , `mla` , `apa` , `chicago`

`include_domains` `string[]`

Soft preference for sources. The research agent prioritizes these domains, but URLs from other domains can still appear in the final report. Matching is host-based and includes subdomains (e.g., `sec.gov` matches `sec.gov` and `data.sec.gov` ). Maximum 20 entries.

Maximum array length: 20

Example:

```
["sec.gov", "ec.europa.eu"]
```

>

Hard blacklist. No URL from a listed domain or any of its subdomains appears in the response.

Subdomain matching is downward only — blocking `medium.com` also blocks `blog.medium.com`, but blocking `blog.medium.com` leaves `medium.com` itself allowed. Maximum 20 entries.

Maximum array length: 20

Example:

```
["reddit.com", "quora.com"]
```

`output_length` `enum<string>` `default:standard`

Typed control over response size. Ranges are targets, not hard caps — individual responses can fall outside when the question requires it.

Available options: `short`, `standard`, `long`

## Response

201 ▾

application/json

Research task queued successfully (when not streaming)

`request_id` `string` `required`

A unique identifier for the research task.

Example: `"123e4567-e89b-12d3-a456-426614174111"`

`created_at` `string` `required`

Timestamp when the research task was created.

Example: `"2025-01-15T10:30:00Z"`

---

Example: "pending"

---

input string required

The research task or question investigated.

Example: "What are the latest developments in AI?"

---

model string required

The model used by the research agent.

Example: "mini"

---

response\_time integer required

Time in seconds it took to complete the request.

Example: 1.23

Tavily Map

< Previous

Get Research Task Status

Next >

---

---

Platform Terms of  
Use

Cookie Notice