

Core Endpoints

Tavily Crawl

 Copy page



Tavily Crawl is a graph-based website traversal tool that can explore hundreds of paths in parallel with built-in extraction and intelligent discovery.

POST /crawl

JavaScript SDK

 JavaScript



```
const { tavily } = require("@tavily/core");

const tvly = tavily({ apiKey: "tvly-YOUR_API_KEY" });
const response = await tvly.crawl("https://docs.tavily.com", { instructions: "Find all page:

console.log(response);
```

```
{
  "url": "https://docs.tavily.com/welcome",
  "raw_content": "Welcome - Tavily Docs\n\n[Tavily Docs home page! [light logo](https://i...)",
  "favicon": "https://mintlify.s3-us-west-1.amazonaws.com/tavilyai/_generated/favicon/a...",
},
{
  "url": "https://docs.tavily.com/documentation/api-credits",
  "raw_content": "Credits & Pricing - Tavily Docs\n\n[Tavily Docs home page! [light logo...]",
  "favicon": "https://mintlify.s3-us-west-1.amazonaws.com/tavilyai/_generated/favicon/a...",
},
{
  "url": "https://docs.tavily.com/documentation/about",
  "raw_content": "Who are we?\n-----\n\nWe're a team of AI researchers and develop...",
  "favicon": "https://mintlify.s3-us-west-1.amazonaws.com/tavilyai/_generated/favicon/a...",
}
],
"response_time": 1.23,
"usage": {
  "credits": 1
},
"request_id": "123e4567-e89b-12d3-a456-426614174111"
}
```

Authorizations

Authorization string header required

Bearer authentication header in the form Bearer , where is your Tavily API key (e.g., Bearer tvly-YOUR_API_KEY).

Body

application/json

Parameters for the Tavily Crawl request.

>

Example: "docs.tavily.com"

`instructions` `string`

Natural language instructions for the crawler. When specified, the mapping cost increases to 2 API credits per 10 successful pages instead of 1 API credit per 10 pages.

Example: "Find all pages about the Python SDK"

`chunks_per_source` `integer` `default:3`

Chunks are short content snippets (maximum 500 characters each) pulled directly from the source. Use `chunks_per_source` to define the maximum number of relevant chunks returned per source and to control the `raw_content` length. Chunks will appear in the `raw_content` field as: `<chunk 1> [...]` `<chunk 2> [...]` `<chunk 3>`. Available only when `instructions` are provided. Must be between 1 and 5.

Required range: $1 \leq x \leq 5$

`max_depth` `integer` `default:1`

Max depth of the crawl. Defines how far from the base URL the crawler can explore.

Required range: $1 \leq x \leq 5$

`max_breadth` `integer` `default:20`

Max number of links to follow per level of the tree (i.e., per page).

Required range: $1 \leq x \leq 500$

Required range: `x >= 1`

`select_paths` `string[]`

Regex patterns to select only URLs with specific path patterns (e.g., `/docs/.*` , `/api/v1.*`).

`select_domains` `string[]`

Regex patterns to select crawling to specific domains or subdomains (e.g., `^docs\.example\.com$`).

`exclude_paths` `string[]`

Regex patterns to exclude URLs with specific path patterns (e.g., `/private/.*` , `/admin/.*`).

`exclude_domains` `string[]`

Regex patterns to exclude specific domains or subdomains from crawling (e.g., `^private\.example\.com$`).

`allow_external` `boolean` `default:true`

Whether to include external domain links in the final results list.

`include_images` `boolean` `default:false`

Whether to include images in the crawl results.

>

vanced extraction costs 2 credits per 5 successful extractions.

Available options: basic , advanced

format `enum<string>` `default:markdown`

The format of the extracted web page content. `markdown` returns content in markdown format. `text` returns plain text and may increase latency.

Available options: markdown , text

include_favicon `boolean` `default:false`

Whether to include the favicon URL for each result.

timeout `number<float>` `default:150`

Maximum time in seconds to wait for the crawl operation before timing out. Must be between 10 and 150 seconds.

Required range: $10 \leq x \leq 150$

include_usage `boolean` `default:false`

Whether to include credit usage information in the response. NOTE: The value may be 0 if the total use of `/extract` and `/map` have not yet reached minimum requirements. See our [Credits & Pricing documentation](#) for details.

Response

200 ~

application/json

Crawl results returned successfully

Example: "docs.tavily.com"

results `object[]`

A list of extracted content from the crawled URLs.

Show child attributes

Example:

```
[
  {
    "url": "https://docs.tavily.com/welcome",
    "raw_content": "Welcome - Tavily Docs\n\n[Tavily Docs home page! [light logo](http:
    "favicon": "https://mintlify.s3-us-west-1.amazonaws.com/tavilyai/_generated/favico
  },
  {
    "url": "https://docs.tavily.com/documentation/api-credits",
    "raw_content": "Credits & Pricing - Tavily Docs\n\n[Tavily Docs home page! [light
    "favicon": "https://mintlify.s3-us-west-1.amazonaws.com/tavilyai/_generated/favico
  },
  {
    "url": "https://docs.tavily.com/documentation/about",
    "raw_content": "Who are we?\n-----\n\nWe're a team of AI researchers and de
    "favicon": "https://mintlify.s3-us-west-1.amazonaws.com/tavilyai/_generated/favico
  }
]
```

response_time `number<float>`

Time in seconds it took to complete the request.

Example: 1.23

usage `object`

```
{ "credits": 1 }
```

request_id `string`

A unique request identifier you can share with customer support to help resolve issues with specific requests.

Example: "123e4567-e89b-12d3-a456-426614174111"

Tavily Extract

[< Previous](#)

Tavily Map

[Next >](#)

Resources

[About](#)

[Tavily Search Crawler](#)

[Tavily Status](#)

Legal

[Security &
Compliance](#)

[Privacy Policy](#)

[Website Terms of Use](#)

[Platform Terms of
Use](#)

[Cookie Notice](#)

