

Core Endpoints

Tavily Extract

Copy page

Extract web page content from one or more specified URLs using Tavily Extract.

POST /extract

JavaScript SDK

JavaScript



```
const { tavily } = require("@tavily/core");

const tvly = tavily({ apiKey: "tvly-YOUR_API_KEY" });
const response = await tvly.extract("https://en.wikipedia.org/wiki/Artificial_intelligence");

console.log(response);
```

200 400 401 429 432 433 500



```
{
  "results": [
    {
      "url": "https://en.wikipedia.org/wiki/Artificial_intelligence",
      "raw_content": "\\Jump to content\\nMain menu\\nSearch\\nAppearance\\nDonate\\nCreate",
      "images": [],
      "favicon": "https://en.wikipedia.org/static/favicon/wikipedia.ico"
    }
  ],
  "failed_results": [],
  "response_time": 0.02,
  "usage": {
    "credits": 1
  },
  "request_id": "123e4567-e89b-12d3-a456-426614174111"
}
```

>

Bearer authentication header in the form Bearer , where is your Tavily API key (e.g., Bearer tvly-YOUR_API_KEY).

Body

application/json

Parameters for the Tavily Extract request.

`urls` `string` required

The URL to extract content from.

Example: "https://en.wikipedia.org/wiki/Artificial_intelligence"

`query` `string`

User intent for reranking extracted content chunks. When provided, chunks are reranked based on relevance to this query.

`chunks_per_source` `integer` `default:3`

Chunks are short content snippets (maximum 500 characters each) pulled directly from the source. Use `chunks_per_source` to define the maximum number of relevant chunks returned per source and to control the `raw_content` length. Chunks will appear in the `raw_content` field as: `<chunk 1> [...]` `<chunk 2> [...]` `<chunk 3> [...]`. Available only when `query` is provided. Must be between 1 and 5.

Required range: $1 \leq x \leq 5$

successful URL extractions, while `advanced` extraction costs 2 credits per 5 successful URL extractions.

Available options: `basic` , `advanced`

`include_images` `boolean` `default:false`

Include a list of images extracted from the URLs in the response. Default is false.

`include_favicon` `boolean` `default:false`

Whether to include the favicon URL for each result.

`format` `enum<string>` `default:markdown`

The format of the extracted web page content. `markdown` returns content in markdown format. `text` returns plain text and may increase latency.

Available options: `markdown` , `text`

`timeout` `number<float>` `default:None`

Maximum time in seconds to wait for the URL extraction before timing out. Must be between 1.0 and 60.0 seconds. If not specified, default timeouts are applied based on `extract_depth`: 10 seconds for basic extraction and 30 seconds for advanced extraction.

Required range: `1 <= x <= 60`

`include_usage` `boolean` `default:false`

Whether to include credit usage information in the response. NOTE: The value may be 0 if the total successful URL extractions has not yet reached 5 calls. See our [Credits & Pricing documentation](#) for details.

>

`results` `object[]`

A list of extracted content from the provided URLs.

Show child attributes

`failed_results` `object[]`

A list of URLs that could not be processed.

Show child attributes

Example:

`[]`

`response_time` `number<float>`

Time in seconds it took to complete the request.

Example: `0.02`

`usage` `object`

Credit usage details for the request.

Example:

`{ "credits": 1 }`

Example: "123e4567-e89b-12d3-a456-426614174111"

Tavily Search

< Previous

Tavily Crawl

Next >

Resources

About

Tavily Search Crawler

Tavily Status

Legal

Security &
Compliance

Privacy Policy

Website Terms of Use

Platform Terms of
Use

Cookie Notice