

Core Endpoints

Tavily Map

Copy page

Tavily Map traverses websites like a graph and can explore hundreds of paths in parallel with intelligent discovery to generate comprehensive site maps.

POST /map

JavaScript SDK

JavaScript



```
const { tavily } = require("@tavily/core");

const tvly = tavily({ apiKey: "tvly-YOUR_API_KEY" });
const response = await tvly.map("https://docs.tavily.com");

console.log(response);
```

200 400 401 403 429 432 433 500



```
{
  "base_url": "docs.tavily.com",
  "results": [
    "https://docs.tavily.com/welcome",
    "https://docs.tavily.com/documentation/api-credits",
    "https://docs.tavily.com/documentation/about"
  ],
  "response_time": 1.23,
  "usage": {
    "credits": 1
  },
  "request_id": "123e4567-e89b-12d3-a456-426614174111"
}
```

Authorizations

Body

application/json

Parameters for the Tavily Map request.

`url` `string` `required`

The root URL to begin the mapping.

Example: `"docs.tavily.com"`

`instructions` `string`

Natural language instructions for the crawler. When specified, the cost increases to 2 API credits per 10 successful pages instead of 1 API credit per 10 pages.

Example: `"Find all pages about the Python SDK"`

`max_depth` `integer` `default:1`

Max depth of the mapping. Defines how far from the base URL the crawler can explore.

Required range: `1 <= x <= 5`

`max_breadth` `integer` `default:20`

Max number of links to follow per level of the tree (i.e., per page).

Required range: `1 <= x <= 500`

Required range: $x \geq 1$

`select_paths` `string[]`

Regex patterns to select only URLs with specific path patterns (e.g., `/docs/.*` , `/api/v1.*`).

`select_domains` `string[]`

Regex patterns to select crawling to specific domains or subdomains (e.g., `^docs\.example\.com$`).

`exclude_paths` `string[]`

Regex patterns to exclude URLs with specific path patterns (e.g., `/private/.*` , `/admin/.*`).

`exclude_domains` `string[]`

Regex patterns to exclude specific domains or subdomains from crawling (e.g., `^private\.example\.com$`).

`allow_external` `boolean` `default:true`

Whether to include external domain links in the final results list.

`timeout` `number<float>` `default:150`

Maximum time in seconds to wait for the map operation before timing out. Must be between 10 and 150 seconds.

Required range: $10 \leq x \leq 150$

Response

200 ▾

application/json

Map results returned successfully

`base_url` `string`

The base URL that was mapped.

Example: `"docs.tavily.com"`

`results` `string[]`

A list of URLs that were discovered during the mapping.

Example:

```
[  
  "https://docs.tavily.com/welcome",  
  "https://docs.tavily.com/documentation/api-credits",  
  "https://docs.tavily.com/documentation/about"  
]
```

`response_time` `number<float>`

Time in seconds it took to complete the request.

Example: `1.23`

`usage` `object`

Credit usage details for the request.

request_id `string`

A unique request identifier you can share with customer support to help resolve issues with specific requests.

Example: "123e4567-e89b-12d3-a456-426614174111"

Tavily Crawl

< Previous

Create Research Task

Next >

