

@id Maps

```
{
  "@context": {
    "@version": 1.1,
    "schema": "http://schema.org/",
    "name": "schema:name",
    "body": "schema:articleBody",
    "words": "schema:wordCount",
    "post": {
      "@id": "schema:blogPost",
      "@container": "@id"
    }
  },
  "@id": "http://example.com/",
  "@type": "schema:Blog",
  "name": "World Financial News",
  "post": {
    "http://example.com/posts/1/en": {
      "body": "World commodities were up today with heavy trading of crude oil...",
      "words": 1539
    },
    "http://example.com/posts/1/de": {
      "body": "Die Werte an Warenbörsen stiegen im Sog eines starken Handels von Rohöl...",
      "words": 1204
    }
  }
}
```

- Also @type maps and @graph/@id maps.
- Keys may include @none.

Scoped Contexts

```
{
  "@context": {
    "@version": 1.1,
    "@vocab": "http://schema.org/",
    "interest": {
      "@id": "http://xmlns.com/foaf/0.1/interest",
      "@context": {"@vocab": "http://xmlns.com/foaf/0.1/"}
    }
  },
  "name": "Manu Sporny",
  "interest": {
    "@id": "https://www.w3.org/TR/json-ld/",
    "name": "JSON-LD",
    "topic": "Linking Data"
  }
}
```

```
@prefix foaf: <http://xmlns.com/foaf/0.1/> .
@prefix schema: <http://schema.org> .
@prefix xsd: <http://www.w3.org/2001/XMLSchema#> .
```

```
<https://www.w3.org/TR/json-ld/> foaf:name "JSON-LD";
  foaf:topic "Linking Data" .
```

```
[
  foaf:interest <https://www.w3.org/TR/json-ld/>;
  schema:name "Manu Sporny"
] .
```

- Terms can also be used as values of `@type`, with similar behavior.
- Type-scoped contexts do not propagate (by default), to sub-objects, unless set explicitly.