Heating ·(50Hz 230V)·

Outdoor unit	Indoor unit	Heating capacity [kW]					Total capacity [kW]			Power input [kW]			Total current [A]			Power factor [%]
		Room ·A·	Room ·B·	Room ·C·	Room ·D·	Room ·E·	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	Minimum	Nominal	Maximum	
5MXM90M2V1B 5MXM90N2V1B 5MXM90N2V1B9	1.5+1.5+1.5	1,83	1,83	1,83	---	---	1,88	5,50	9,97	0,44	1,20	2,28	2,02	5,50	10,43	95
	1.5+1.5+2.0	1,83	1,83	2,44	---	---	2,02	6,10	10,15	0,46	1,38	2,36	2,11	6,32	10,80	95
	1.5+1.5+2.5	1,83	1,83	3,05	---	---	2,17	6,70	10,23	0,48	1,59	2,39	2,19	7,28	10,94	95
	1.5+1.5+3.5	1,85	1,85	4,31	---	---	2,48	8,00	10,34	0,52	2,05	2,51	2,37	9,39	11,49	95
	1.5+1.5+4.2	1,81	1,81	5,08	---	---	2,68	8,70	10,34	0,56	2,29	2,51	2,58	10,49	11,49	95
	1.5+1.5+5.0	1,74	1,74	5,81	---	---	2,92	9,30	10,51	0,56	2,48	2,61	2,58	11,36	11,95	95
	1.5+1.5+6.0	1,58	1,58	6,33	---	---	3,20	9,50	11,14	0,57	2,48	2,80	2,62	11,36	12,81	95
	1.5+1.5+7.1	1,49	1,49	7,03	---	---	3,52	10,00	11,18	0,61	2,70	2,79	2,80	12,36	12,77	95
	1.5+2.0+2.0	1,83	2,44	2,44	---	---	2,17	6,70	10,31	0,48	1,60	2,43	2,19	7,33	11,12	95
	1.5+2.0+2.5	1,83	2,43	3,04	---	---	2,33	7,30	10,41	0,50	1,77	2,46	2,28	8,11	11,26	95
	1.5+2.0+3.5	1,82	2,43	4,25	---	---	2,63	8,50	10,50	0,54	2,21	2,60	2,45	10,12	11,90	95
	1.5+2.0+4.2	1,75	2,34	4,91	---	---	2,83	9,00	10,51	0,58	2,39	2,66	2,67	10,94	12,17	95
	1.5+2.0+5.0	1,76	2,35	5,88	---	---	3,06	10,00	10,93	0,58	2,77	2,66	2,67	12,68	12,17	95
	1.5+2.0+6.0	1,58	2,11	6,32	---	---	3,35	10,00	11,14	0,60	2,71	2,80	2,75	12,41	12,81	95
	1.5+2.0+7.1	1,42	1,89	6,70	---	---	3,66	10,00	11,18	0,64	2,69	2,79	2,93	12,32	12,77	95
	1.5+2.5+2.5	1,85	3,08	3,08	---	---	2,48	8,00	10,52	0,52	2,00	2,46	2,37	9,16	11,26	95
	1.5+2.5+3.5	1,80	3,00	4,20	---	---	2,77	9,00	10,63	0,56	2,35	2,66	2,58	10,76	12,17	95
	1.5+2.5+4.2	1,83	3,05	5,12	---	---	2,97	10,00	10,63	0,60	2,74	2,66	2,75	12,55	12,17	95
	1.5+2.5+5.0	1,67	2,78	5,56	---	---	3,20	10,00	11,05	0,61	2,63	2,82	2,80	12,04	12,91	95
	1.5+2.5+6.0	1,50	2,50	6,00	---	---	3,49	10,00	11,14	0,62	2,58	2,80	2,84	11,81	12,81	95
	1.5+2.5+7.1	1,35	2,25	6,40	---	---	3,80	10,00	11,18	0,66	2,53	2,79	3,01	11,58	12,77	95
	1.5+3.5+3.5	1,76	4,12	4,12	---	---	3,06	10,00	10,64	0,60	2,74	2,66	2,75	12,55	12,17	95
	1.5+3.5+4.2	1,63	3,80	4,57	---	---	3,26	10,00	10,78	0,65	2,72	2,87	2,97	12,45	13,14	95
	1.5+3.5+5.0	1,50	3,50	5,00	---	---	3,49	10,00	10,98	0,66	2,61	2,82	3,01	11,95	12,91	95
	1.5+3.5+6.0	1,36	3,18	5,45	---	---	3,77	10,00	11,15	0,67	2,56	2,80	3,05	11,72	12,81	95
	1.5+3.5+7.1	1,24	2,89	5,87	---	---	4,09	10,00	11,18	0,73	2,51	2,79	3,36	11,49	12,77	95
	1.5+4.2+4.2	1,52	4,24	4,24	---	---	3,46	10,00	10,90	0,68	2,69	2,92	3,10	12,32	13,36	95
	1.5+4.2+5.0	1,40	3,93	4,67	---	---	3,69	10,00	11,03	0,71	2,59	2,82	3,23	11,86	12,91	95
	1.5+4.2+6.0	1,28	3,59	5,13	---	---	3,98	10,00	11,27	0,71	2,54	2,80	3,27	11,63	12,81	95
	1.5+4.2+7.1	1,17	3,28	5,55	---	---	4,29	10,00	11,30	0,76	2,49	2,78	3,48	11,40	12,72	95
	1.5+5.0+5.0	1,30	4,35	4,35	---	---	3,92	10,00	11,17	0,71	2,50	2,83	3,23	11,45	12,95	95
	1.5+5.0+6.0	1,20	4,00	4,80	---	---	4,21	10,00	11,41	0,71	2,46	2,75	3,27	11,26	12,59	95
	1.5+5.0+7.1	1,10	3,68	5,22	---	---	4,53	10,00	11,44	0,79	2,41	2,73	3,61	11,03	12,49	95
	1.5+6.0+6.0	1,11	4,44	4,44	---	---	4,50	10,00	11,65	0,72	2,42	2,67	3,31	11,08	12,22	95
	1.5+6.0+7.1	1,32	3,97	4,70	---	---	4,81	10,00	11,68	0,79	2,40	2,66	3,61	10,99	12,17	95
	2.0+2.0+2.0	2,50	2,50	2,50	---	---	2,33	7,50	10,49	0,50	1,77	2,50	2,28	8,11	11,44	95
	2.0+2.0+2.5	2,46	2,46	3,08	---	---	2,48	8,00	10,57	0,52	1,92	2,54	2,37	8,79	11,62	95
	2.0+2.0+3.5	2,40	2,40	4,20	---	---	2,77	9,00	10,68	0,56	2,27	2,66	2,58	10,39	12,17	95
	2.0+2.0+4.2	2,29	2,29	4,81	---	---	2,97	9,40	10,68	0,60	2,47	2,66	2,75	11,31	12,17	95
	2.0+2.0+5.0	2,22	2,22	5,56	---	---	3,20	10,00	10,90	0,61	2,76	2,82	2,80	12,64	12,91	95
	2.0+2.0+6.0	2,00	2,00	6,00	---	---	3,49	10,00	11,14	0,62	2,72	2,80	2,84	12,45	12,81	95
	2.0+2.0+7.1	1,80	1,80	6,40	---	---	3,80	10,00	11,18	0,66	2,67	2,79	3,01	12,22	12,77	95
	2.0+2.5+2.5	2,43	3,04	3,04	---	---	2,62	8,50	10,59	0,54	2,15	2,63	2,45	9,84	12,04	95
	2.0+2.5+3.5	2,33	2,91	4,07	---	---	2,92	9,30	10,68	0,58	2,45	2,66	2,67	11,22	12,17	95

Notes

1. The total capacity of each connected indoor unit is up to ·15.6·kW.
2. The values above are for connecting with the following indoor unit types:
   ·1.5, 2.0, 2.5, 3.5, 4.2, 5.0, 6.0, 7.1· kW class
   Wall-mounted ·FTXM-M, FTXM-N, FTXM-R· series
3. Heating capacity conditions
   Indoor temperature ·20·°C DB
   Outdoor temperature ·7·°C DB / ·6·°C WB
4. For additional information on the connection of the DHW generator for Multi and the Hybrid for Multi, see ·3D106169·.