

Estruturas de Linguagem

Tipos Abstratos de Dados

Francisco Sant'Anna

francisco@ime.uerj.br

<http://github.com/fsantanna/EDL>

O Conceito de Abstração

An **abstraction** is a view or representation of an entity that includes only the most significant attributes.

- Classes de abstrações

- processos

```
sortInt(list, listLen)
```

- dados

```
float d;
```

- Uma “arma” contra complexidade

- facilita no gerenciamento de programas

Abstração de Dados (definida pelo programador)

- Tipos de dados definidos pelo programador
- Invólucro que inclui
 - representação do tipo de dado
 - implementação das operações sobre o tipo de dado
- Detalhes desnecessários são escondidos
 - “information hiding”
- Interface de acesso
 - construtores (instâncias) + operações

Exemplo: Pilha

<code>create(stack)</code>	Creates and possibly initializes a stack object
<code>destroy(stack)</code>	Deallocates the storage for the stack
<code>empty(stack)</code>	A predicate (or Boolean) function that returns true if the specified stack is empty and false otherwise
<code>push(stack, element)</code>	Pushes the specified element on the specified stack
<code>pop(stack)</code>	Removes the top element from the specified stack
<code>top(stack)</code>	Returns a copy of the top element from the specified stack

```
. . .  
create(stk1);  
push(stk1, color1);  
push(stk1, color2);  
temp = top(stk1);  
. . .
```

```
Stack stk; /** Cre  
stk.push(42);  
stk.push(17);  
topOne = stk.top();  
stk.pop();  
. . .
```

- Vetor?
- Lista?

Considerações

- Como expor a interface sem expor a representação / implementação?
 - modificadores
 - private / protected
 - módulos
 - unidades de compilação
- Operações entre diferentes tipos abstratos?
 - “friend”
- Encapsulamento de nomes?
 - namespaces, packages, modules

Pilha em C++ e C

```
class Stack {  
    public:  
        Stack();  
        ~Stack();  
        int empty (void);  
        void push  (int);  
        void pop   (void);  
        int top    (void);  
    private:  
        int* stackPtr;  
        int  maxLen;  
        int  topSub;  
}
```

```
typedef struct Stack Stack;  
Stack* create (void);  
int     empty  (Stack*);  
void    push   (Stack*, int);  
void    pop    (Stack*);  
int     top    (Stack*);
```

define

Abstração de Dados

We now formally define an abstract data type in the context of user-defined types. An **abstract data type** is a data type that satisfies the following conditions:

- The representation of objects of the type is hidden from the program units that use the type, so the only direct operations possible on those objects are those provided in the type's definition.
- The declarations of the type and the protocols of the operations on objects of the type, which provide the type's interface, are contained in a single syntactic unit. The type's interface does not depend on the representation of the objects or the implementation of the operations. Also, other program units are allowed to create variables of the defined type.

Abstração de Dados

- Vantagens?
 - confiabilidade (reliability)
 - clientes não podem manipular as representações internas (conscientemente ou não)
 - legibilidade/redigibilidade (readability/writability)
 - menos código, mudanças centralizadas
- Getters and Setters?

1. Read-only access can be provided by having a getter method but no corresponding setter method.
2. Constraints can be included in setters. For example, if the data value should be restricted to a particular range, the setter can enforce that.
3. The actual implementation of the data member can be changed without affecting the clients if getters and setters are the only access.

Pilha em Elm

```
module Stack exposing (create, empty, top, push, pop)
```

```
type alias Stack = List Int
```

```
create : Stack  
create = []
```

```
empty : Stack -> Bool  
empty s = List.isEmpty s
```

```
top : Stack -> Maybe Int  
top s = List.head s
```

```
push : Int -> Stack -> Stack  
push x s = (x :: s)
```

```
pop : Stack -> Maybe Stack  
pop s = case s of  
    [] -> Nothing  
    _ :: rest -> Just rest
```


Abstração de Dados Parametrizada

- Os exemplos de pilha que mostramos foram sempre para guardar inteiros

```
typedef struct Stack Stack;
Stack* create (void);
int     empty  (Stack*);
void    push   (Stack*, int);
void    pop    (Stack*);
int     top    (Stack*);
```

```
type alias Stack = List Int
create : Stack
empty   : Stack -> Bool
top     : Stack -> Maybe Int
push    : Int -> Stack -> Stack
pop     : Stack -> Maybe Stack
```

```
typedef struct Stack Stack;
Stack* create (void);
int     empty  (Stack*);
void    push   (Stack*, void*);
void    pop    (Stack*);
void*   top    (Stack*);
```

```
type alias Stack a = List a
create : Stack a
empty   : Stack a -> Bool
top     : Stack a -> Maybe a
push    : a -> Stack a -> Stack a
pop     : Stack a -> Maybe (Stack a)
```

Abstração de Dados Parametrizada

- Os exemplos de pilha que mostramos foram sempre para guardar inteiros

```
template <typename Type>
class Stack {
    private:
        Type *stackPtr;
        ...
    public:
        Stack (int size) {
            stackPtr = new Type [size];
            ...
        }
        void push (Type number) { ... }
        Type top() { ... }
}
```

Abstração de Dados Parametrizada

- Linguagens dinâmicas?

```
function create ()      ... end
function empty  (s)     ... end
function push   (s, v)  ... end
function pop    (s)     ... end
function top    (s)     ... end
```

Abstração de Dados Parametrizada

- Lista
- Árvore
- Linguagem de Expressões