

Warning: could not find file /overview/overview/environments.md. Ignoring include statement. Error: [Errno 2] No such file or directory: u'/overview/overview/environments.md' Warning: could not find file /overview/overview/synchronous\_execution\_model.md. Ignoring include statement. Error: [Errno 2] No such file or directory: u'/overview/overview/synchronous\_execution\_model.md' Warning: could not find file /overview/overview/parallel\_compositions\_and\_abortion.md. Ignoring include statement. Error: [Errno 2] No such file or directory: u'/overview/overview/parallel\_compositions\_and\_abortion.md' Warning: could not find file /overview/overview/bounded\_execution.md. Ignoring include statement. Error: [Errno 2] No such file or directory: u'/overview/overview/bounded\_execution.md' Warning: could not find file /overview/overview/deterministic\_execution.md. Ignoring include statement. Error: [Errno 2] No such file or directory: u'/overview/overview/deterministic\_execution.md' Warning: could not find file /overview/overview/internal\_reactions.md. Ignoring include statement. Error: [Errno 2] No such file or directory: u'/overview/overview/internal\_reactions.md'

# Overview

## Overview

Céu provides *Structured Synchronous Reactive Programming* with the following general characteristics:

- *Reactive*: code executes in reactions to events.
- *Structured*: code uses structured control-flow mechanisms, such as **spawn** and **await** (to create and suspend lines of execution).
- *Synchronous*: event reactions run atomically and to completion on each line of execution.

The lines of execution in Céu, known as *trails*, react all together to input events one after another, in discrete steps. An input event is broadcast to all active trails, which share the event as an unique and global time reference.

The example in Céu that follows blinks a LED every second and terminates on a button press:

```
input none  BUTTON;
output on/off LED;
par/or do
    await BUTTON;
with
    loop do
        await 1s;
        emit LED(on);
        await 1s;
        emit LED(off);
```

```
end
end
```

The synchronous concurrency model of Céu greatly diverges from multithreaded and actor-based models (e.g. *threads* and *erlang*). On the one hand, there is no preemption or real parallelism at the synchronous core of the language (i.e., no multi-core execution). On the other hand, accesses to shared variables among trails are deterministic and do not require synchronization primitives (i.e., *locks* or *queues*).

Céu provides static memory management based on lexical scope and does not require a garbage collector.

Céu integrates safely with C, particularly when manipulating external resources (e.g., file handles). Programs can make native calls seamlessly while avoiding common pitfalls such as memory leaks and dangling pointers.

Céu is free software.

## Lexical Rules

### Lexical Rules

#### Keywords

Keywords in Céu are reserved names that cannot be used as identifiers (e.g., for variables and events):

and	as	async	atomic	await
bool	break	byte	call	code
const	continue	data	deterministic	do
dynamic	else	emit	end	escape
event	every	false	finalize	FOREVER
hold	if	in	input	int
integer	is	isr	kill	lock
loop	lua	native	NEVER	new
no	nohold	none	not	nothing

null	off	on	or	outer
output	par	pause	plain	pool
pos	pre	pure	r32	r64
real	recursive	request	resume	s16
s32	s64	s8	sizeof	spawn
ssize	static	then	thread	tight
traverse	true	u16	u32	u64
u8	uint	until	usize	val
var	watching	with	yes	

TODO: catch, throw, throws

## Identifiers

Céu uses identifiers to refer to *types* (ID\_type), *variables* (ID\_int), *vectors* (ID\_int), *pools* (ID\_int), *internal events* (ID\_int), *external events* (ID\_ext), *code abstractions* (ID\_abs), *data abstractions* (ID\_abs), *fields* (ID\_field), *native symbols* (ID\_nat), and *block labels* (ID\_int).

```

ID      ::= [a-z, A-Z, 0-9, _]+ // a sequence of letters, digits, and underscores
ID_int  ::= ID                  // ID beginning with lowercase
ID_ext  ::= ID                  // ID all in uppercase, not beginning with digit
ID_abs  ::= ID {`.´ ID}         // IDs beginning with uppercase, containing at least one
ID_field ::= ID                 // ID not beginning with digit
ID_nat  ::= ID                 // ID beginning with underscore

ID_type ::= ( ID_nat | ID_abs
              | none
              | bool  | on/off | yes/no
              | byte
              | r32   | r64    | real
              | s8    | s16    | s32      | s64
              | u8    | u16    | u32      | u64
              | int   | uint   | integer
              | ssize | usize )

```

Declarations for `code` and `data` abstractions create new types which can be used as type identifiers.

Examples:

```
var int a;                // "a" is a variable, "int" is a type

emit e;                   // "e" is an internal event

await I;                  // "I" is an external input event

spawn Move();             // "Move" is a code abstraction and a type

var Rect r;               // "Rect" is a data abstraction and a type

escape r.width;           // "width" is a field

_printf("hello world!\n"); // "_printf" is a native symbol
```

## Literals

Céu provides literals for *booleans*, *integers*, *reals*, *strings*, and *null pointers*.

## Booleans

The boolean type has only two possible values: `true` and `false`.

The boolean values `on` and `yes` are synonymous to `true` and can be used interchangeably. The boolean values `off` and `no` are synonymous to `false` and can be used interchangeably.

## Integers

Céu supports decimal and hexadecimal integers:

- Decimals: a sequence of digits (i.e., `[0-9]+`).
- Hexadecimals: a sequence of hexadecimal digits (i.e., `[0-9, a-f, A-F]+`) prefixed by `0x`.

Examples:

```
// both are equal to the decimal 127
v = 127;    // decimal
v = 0x7F;   // hexadecimal
```

## Floats

TODO (like C)

## Strings

A sequence of characters surrounded by the character " is converted into a *null-terminated string*, just like in C:

Example:

```
_printf("Hello World!\n");
```

## Null pointer

TODO (like C)

## Comments

Céu provides C-style comments:

- Single-line comments begin with `//` and run to end of the line.
- Multi-line comments use `/*` and `*/` as delimiters. Multi-line comments can be nested by using a different number of `*` as delimiters.

Examples:

```
var int a;    // this is a single-line comment
```

```
/** comments a block that contains comments
```

```
var int a;  
/* this is a nested multi-line comment  
a = 1;  
*/
```

```
**/
```

## Types

### Types

Céu is statically typed, requiring all variables, events, and other storage entities to be declared before they are used in programs.

A type is composed of a type identifier, followed by an optional sequence of pointer modifiers `&&`, followed by an optional option modifier `?`:

```
Type ::= ID_type {`&&`} [`?`]
```

Examples:

```

var  u8      v;    // "v" is of 8-bit unsigned integer type
var  _rect   r;    // "r" is of external native type "rect"
var  Tree    t;    // "t" is a data of type "Tree"
var  int?    ret;  // "ret" is either unset or is of integer type
input byte&& RECV; // "RECV" is an input event carrying a pointer to a "byte"

```

## Primitives

Céu has the following primitive types:

```

none           // void type
bool           // boolean type
on/off         // synonym to bool
yes/no         // synonym to bool
byte           // 1-byte type
int            uint    // platform dependent signed and unsigned integer
integer        // synonym to int
s8             u8      // signed and unsigned 8-bit integers
s16            u16     // signed and unsigned 16-bit integers
s32            u32     // signed and unsigned 32-bit integers
s64            u64     // signed and unsigned 64-bit integers
real           // platform dependent real
r32            r64     // 32-bit and 64-bit reals
ssize          usize   // signed and unsigned size types

```

## Natives

Types defined externally in C can be prefixed by `_` to be used in Céu programs.

Example:

```

var _message_t msg;    // "message_t" is a C type defined in an external library

```

Native types support modifiers to provide additional information to the compiler.

## Abstractions

See Abstractions.

## Modifiers

Types can be suffixed with the pointer modifier `&&` and the option modifier `?`.

## Pointer

TODO (like in C)

TODO cannot cross yielding statements

## Option

TODO (like "Maybe")

TODO: \_

# Storage Entities

## Storage Entities

Storage entities represent all objects that are stored in memory during execution. Céu supports *variables*, *vectors*, *events* (external and internal), and *pools* as entity classes.

An entity declaration consists of an entity class, a type, and an identifier.

Examples:

```
var    int    v;      // "v" is a variable of type "int"
var[9] byte   buf;    // "buf" is a vector with at most 9 values of type "byte"
input  none&& A;      // "A" is an input event that carries values of type "none&&"
event  bool   e;      // "e" is an internal event that carries values of type "bool"
pool[] Anim   anims;  // "anims" is a dynamic "pool" of instances of type "Anim"
```

A declaration binds the identifier with a memory location that holds values of the associated type.

## Lexical Scope

Storage entities have lexical scope, i.e., they are visible only in the block in which they are declared.

The lifetime of entities, which is the period between allocation and deallocation in memory, is also limited to the scope of the enclosing block. However, individual elements inside *vector* and *pool* entities have dynamic lifetime, but which never outlive the scope of the declaration.

## Entity Classes

### Variables

A variable in Céu holds a value of a declared type that may vary during program execution. The value of a variable can be read in expressions or written in assignments. The current value of a variable is preserved until the next assignment, during its whole lifetime.

Example:

```
var int v = _; // empty initialization
par/and do
  v = 1;       // write access
with
  v = 2;       // write access
end
escape v;      // read access (yields 2)
```

### Vectors

A vector in Céu is a dynamic and contiguous collection of variables of the same type.

A vector declaration specifies its type and maximum number of elements (possibly unlimited). The current length of a vector is dynamic and can be accessed through the operator \$.

Individual elements of a vector can be accessed through an index starting from 0. Céu generates an error for out-of-bounds vector accesses.

Example:

```
var[9] byte buf = [1,2,3]; // write access
buf = buf .. [4];          // write access
escape buf[1];             // read access (yields 2)
```

TODO: ring buffers

### Events

Events account for the reactive nature of Céu. Programs manipulate events through the **await** and **emit** statements. An **await** halts the running trail until the specified event occurs. An event occurrence is broadcast to the whole program and awakes trails awaiting that event to resume execution.

Unlike all other entity classes, the value of an event is ephemeral and does not persist after a reaction terminates. For this reason, an event identifier is not a variable: values can only be communicated through **emit** and **await** statements. A declaration includes the type of value the occurring event carries.



*Note: none is a valid type for signal-only events with no associated values.*

Example:

```
input  none I;           // "I" is an input event that carries no values
output int  0;           // "0" is an output event that carries values of type "int"
event  int  e;           // "e" is an internal event that carries values of type "int"
par/and do
    await I;             // awakes when "I" occurs
    emit e(10);          // broadcasts "e" passing 10, awakes the "await" below
with
    var int v = await e; // awaits "e" assigning the received value to "v"
    emit 0(v);           // emits "0" back to the environment passing "v"
end
```

As described in Internal Reactions, Céu supports external and internal events with different behavior.

### External Events

External events are used as interfaces between programs and devices from the real world:

- *input events* represent input devices such as a sensor, button, mouse, etc.
- *output events* represent output devices such as a LED, motor, screen, etc.

The availability of external events depends on the environment in use.

Programs can **emit** output events and **await** input events.

### Internal Events

Internal events, unlike external events, do not represent real devices and are defined by the programmer. Internal events serve as signalling and communication mechanisms among trails in a program.

Programs can **emit** and **await** internal events.

### Pools

A pool is a dynamic container to hold running code abstractions.

A pool declaration specifies the type of the abstraction and maximum number of concurrent instances (possibly unlimited). Individual elements of pools can only be accessed through iterators. New elements are created with **spawn** and are removed automatically when the code execution terminates.

Example:

```

code/await Anim (none) => none do      // defines the "Anim" code abstraction
  <...>                                // body of "Anim"
end
pool[] Anim as;                        // declares an unlimited container for "Anim" instan
loop i in [1->10] do
  spawn Anim() in as;                  // creates 10 instances of "Anim" into "as"
end

```

When a pool declaration goes out of scope, all running code abstractions are automatically aborted.

TODO: kill

## Locations

A location (aka *l-value*) is a path to a memory position holding a value.

The list that follows summarizes all valid locations:

- storage entity: variable, vector, internal event (but not external), or pool
- native expression or symbol
- data field
- vector index
- vector length \$
- pointer dereferencing \*
- option unwrapping !

Locations appear in assignments, event manipulation, iterators, and expressions. Locations are detailed in Locations and Expressions.

Examples:

```

emit e(1);          // "e" is an internal event
_UDR = 10;          // "_UDR" is a native symbol
person.age = 70;    // "age" is a field of "person"
vec[0] = $vec;      // "vec[0]" is a vector index
$vec = 1;           // "$vec" is a vector length
*ptr = 1;           // "ptr" is a pointer to a variable
a! = 1;             // "a" is of an option type

```

## References

Céu supports *aliases* and *pointers* as references to entities, aka *strong* and *weak* references, respectively.

An alias is an alternate view for an entity: after the entity and alias are bounded, they are indistinguishable.

A pointer is a value that is the address of an entity, providing indirect access to it.

As an analogy with a person's identity, a family nickname referring to a person is an alias; a job position referring to a person is a pointer.

## Aliases

Céu support aliases to all storage entity classes, except external events and pointer types. Céu also supports option variable aliases which are aliases that may be bounded or not.

An alias is declared by suffixing the entity class with the modifier `&` and is acquired by prefixing an entity identifier with the operator `&`.

An alias must have a narrower scope than the entity it refers to. The assignment to the alias is immutable and must occur between its declaration and first access or next yielding statement.

Example:

```
var  int v = 0;
var& int a = &v;          // "a" is an alias to "v"
...
a = 1;                    // "a" and "v" are indistinguishable
_printf("%d\n", v);       // prints 1
```

An option variable alias, declared as `var&?`, serves two purposes:

- Map a native resource to Céu. The alias is acquired by prefixing the associated native call with the operator `&`. Since the allocation may fail, the alias may remain unbounded.
- Hold the result of a `spawn` invocation. Since the allocation may fail, the alias may remain unbounded.

Accesses to option variable aliases must always use option checking or unwrapping.

TODO: or `implicit assert` with `&` declarations

Examples:

```
var&? _FILE f = &_fopen(<...>) finalize with
    _fclose(f);
end;

if f? then
    <...>    // "f" is assigned
else
    <...>    // "f" is not assigned
end

var&? My_Code my_code = spawn My_Code();
```

```

if my_code? then
    <...>    // "spawn" succeeded
else
    <...>    // "spawn" failed
end

```

## Pointers

A pointer is declared by suffixing the type with the modifier `&&` and is acquired by prefixing an entity with the operator `&&`. Applying the operator `*` to a pointer provides indirect access to its referenced entity.

Example:

```

var int    v = 0;
var int&& p = &&v;    // "p" holds a pointer to "v"
...
*p = 1;          // "p" provides indirect access to "v"
_printf("%d\n", v);    // prints 1

```

The following restrictions apply to pointers in Céu:

- No support for pointers to events, vectors, or pools (only variables).
- A pointer is only accessible between its declaration and the next yielding statement.

## Statements

### Statements

A program in Céu is a sequence of statements delimited by an implicit enclosing block:

```

Program ::= Block
Block   ::= {Stmt `;`}

```

*Note: statements terminated with the **end** keyword do not require a terminating semicolon.*

### Nothing

`nothing` is an innocuous statement:

```
Nothing ::= nothing
```

## Blocks

A **Block** delimits a lexical scope for storage entities and abstractions, which are only visible to statements inside the block.

Compound statements (e.g. *do-end*, *if-then-else*, *loops*, etc.) create new blocks and can be nested to an arbitrary level.

### do-end and escape

The **do-end** statement creates an explicit block. The **escape** statement terminates the deepest matching enclosing **do-end**:

```
Do ::= do [``(ID_int|`_`)] [``( [LIST(ID_int)] `)`]
      Block
      end
```

```
Escape ::= escape [``ID_int] [Exp]
```

A **do-end** and **escape** accept an optional identifier following the symbol /. An **escape** only matches a **do-end** with the same identifier. The neutral identifier **\_** in a **do-end** is guaranteed not to match any **escape** statement.

A **do-end** also supports an optional list of identifiers in parenthesis which restricts the visible storage entities inside the block to those matching the list. An empty list hides all storage entities from the enclosing scope.

A **do-end** can be assigned to a variable whose type must be matched by nested **escape** statements. The whole block evaluates to the value of a reached **escape**. If the variable is of option type, the **do-end** is allowed to terminate without an **escape**, otherwise it raises a runtime error.

Programs have an implicit enclosing **do-end** that assigns to a *program status variable* of type **int** whose meaning is platform dependent.

Examples:

```
do
  do/a
    do/_
      escape;      // matches line 1
    end
    escape/a;      // matches line 2
  end
end

var int a;
var int b;
do (a)
  a = 1;
```

```

    b = 2;  // "b" is not visible
end
var int? v =
  do
    if <cnd> then
      escape 10;  // assigns 10 to "v"
    else
      nothing;    // "v" remains unassigned
    end
  end;
escape 0;          // program terminates with a status value of 0

```

### pre-do-end

The pre-do-end statement prepends its statements in the beginning of the program:

```

Pre_Do ::= pre do
          Block
        end

```

All pre-do-end statements are concatenated together in the order they appear and are moved to the beginning of the top-level block, before all other statements.

### Declarations

A declaration introduces a storage entity to the enclosing block. All declarations are subject to lexical scope.

Céu supports variables, vectors, pools, internal events, and external events:

```

Var  ::= var [&|&?'] [ '[' [Exp ['*']] `]' ] ["/dynamic"/"/nohold"] Type ID_int ['=' Sources]
Pool ::= pool [&']  '[' [Exp] `]' Type ID_int ['=' Sources]
Int  ::= event [&'] (Type | `(' LIST(Type) `)') ID_int ['=' Sources]

Ext  ::= input  (Type | `(' LIST(Type) `)') ID_ext
       | output (Type | `(' LIST([&'] Type [ID_int]) `)') ID_ext
       [ do Block end ]

```

```
Sources ::= /* (see "Assignments") */
```

Most declarations support an initialization assignment.

## Variables

A variable declaration has an associated type and can be optionally initialized. Declarations can also be aliases or option aliases.

Examples:

```
var int v = 10;    // "v" is an integer variable initialized to 10
var int a=0, b=3;  // "a" and "b" are integer variables initialized to 0 and 3
var& int z = &v;   // "z" is an alias to "v"
```

## Vectors

A vector declaration specifies a dimension between brackets, an associated type and can be optionally initialized. Declarations can also be aliases. **TODO: ring buffers**

Examples:

```
var int n = 10;
var[10] int vs1 = [];    // "vs1" is a static vector of 10 elements max
var[n] int vs2 = [];     // "vs2" is a dynamic vector of 10 elements max
var[] int vs3 = [];      // "vs3" is an unbounded vector
var&[] int vs4 = &vs1;   // "vs4" is an alias to "vs1"
```

## Pools

A pool declaration specifies a dimension and an associated type. Declarations for pools can also be aliases. Only in this case they can be initialized.

The expression between the brackets specifies the dimension of the pool.

Examples:

```
code/await Play (...) do ... end
pool[10] Play plays;        // "plays" is a static pool of 10 elements max
pool&[] Play a = &plays;    // "a" is an alias to "plays"
```

**TODO: data pools**

## Dimension

Declarations for vectors or pools require an expression between brackets to specify a dimension as follows:

- *constant expression*: Maximum number of elements is fixed and space is statically pre-allocated.
- *variable expression*: Maximum number of elements is fixed but space is dynamically allocated. The expression is evaluated once at declaration time.

- *omitted*: Maximum number of elements is unbounded and space is dynamically allocated. The space for dynamic dimensions grow and shrink automatically.
- **TODO: ring buffers**

## Events

An event declaration specifies a type for the values it carries when occurring. It can be also a list of types if the event communicates multiple values.

## External Events

Examples:

```
input  none A;           // "A" is an input event carrying no values
output int  MY_EVT;      // "MY_EVT" is an output event carrying integer values
input (int,byte&&) BUF;  // "BUF" is an input event carrying an "(int,byte&&)" pair

TODO: output &/impl
```

## Internal Events

Declarations for internal events can also be aliases. Only in this case they can be initialized.

Examples:

```
event  none a;           // "a" is an internal events carrying no values
event& none z = &a;      // "z" is an alias to event "a"
event (int,int) c;       // "c" is a internal event carrying an "(int,int)" pair
```

## Assignments

An assignment associates the statement or expression at the right side of the symbol = with the location(s) at the left side:

**Assignment ::= (Loc | `(` LIST(Loc|`\_`) `)` ) `=` Sources**

```
Sources ::= ( Do
              | Emit_Ext
              | Await
              | Watching
              | Thread
              | Lua_Stmts
              | Code_Await
              | Code_Spawn
              | Vec_Cons
```



```

| Data_Cons
| Exp
| ` _ ' )

```

Céu supports the following constructs as assignment sources:

- `do-end` block
- external emit
- `await`
- watching statement
- thread
- lua statement
- code `await`
- code `spawn`
- vector length & constructor
- data constructor
- expression
- the special identifier `_`

The special identifier `_` makes the assignment innocuous. In the case of assigning to an option type, the `_` unsets it.

TODO: required for uninitialized variables

## Copy Assignment

A *copy assignment* evaluates the statement or expression at the right side and copies the result(s) to the location(s) at the left side.

## Alias Assignment

An *alias assignment*, aka *binding*, makes the location at the left side to be an alias to the expression at the right side.

The right side of a binding must always be prefixed with the operator `&`.

## Event Handling

### Await

The `await` statement halts the running trail until the specified event occurs. The event can be an input event, an internal event, a terminating code abstraction, a timer, a pausing event, or forever (i.e., never awakes):

```

Await ::= await (ID_ext | Loc) [until Exp]      /* events and option aliases */
        | await (WCLOCKK|WCLOCKE)              /* timers */
        | await (pause|resume)                  /* pausing events */
        | await FOREVER                         /* forever */

```

Examples:

```
await A;                // awaits the input event "A"
await a until v==10;    // awaits the internal event "a" until the condition is satisfied

var&? My_Code my = <...>; // acquires a reference to a code abstraction instance
await my;               // awaits it terminate

await 1min10s30ms100us; // awaits the specified time
await (t)ms;            // awaits the current value of the variable "t" in milliseconds

await FOREVER;          // awaits forever
```

An `await` evaluates to zero or more values which can be captured with an optional assignment.

## Event

The `await` statement for events halts the running trail until the specified input event or internal event occurs. The `await` evaluates to a value of the type of the event.

The optional clause `until` tests an awaking condition. The condition can use the returned value from the `await`. It expands to a loop as follows:

```
loop do
  <ret> = await <evt>;
  if <Exp> then // <Exp> can use <ret>
    break;
  end
end
```

Examples:

```
input int E;                // "E" is an input event carrying "int" values
var int v = await E until v>10; // assigns occurring "E" to "v", awaking only when "v>10"

event (bool,int) e;          // "e" is an internal event carrying "(bool,int)" pairs
var bool v1;
var int v2;
(v1,v2) = await e;          // awakes on "e" and assigns its values to "v1" and "v2"
```

## Code Abstraction

The `await` statement for a code abstraction halts the running trail until the specified instance terminates.

The `await` evaluates to the return value of the abstraction.

TODO: option return on kill

Example:

```
var&? My_Code my = spawn My_Code();  
var? int ret = await my;
```

## Timer

The `await` statement for timers halts the running trail until the specified timer expires:

- `WCLOCKK` specifies a constant timer expressed as a sequence of value/unit pairs.
- `WCLOCKE` specifies an integer expression in parenthesis followed by a single unit of time.

The `await` evaluates to a value of type `s32` and is the *residual delta time* ( $dt$ ) measured in microseconds: the difference between the actual elapsed time and the requested time. The residual  $dt$  is always greater than or equal to 0.

If a program awaits timers in sequence (or in a `loop`), the residual  $dt$  from the preceding timer is reduced from the timer in sequence.

Examples:

```
var int t = <...>;  
await (t)ms;           // awakes after "t" milliseconds  
  
var int dt = await 100us; // if 1000us elapses, then dt=900us (1000-100)  
await 100us;           // since dt=900, this timer is also expired, now dt=800us (900-100)  
await 1ms;             // this timer only awaits 200us (1000-800)
```

## Pausing

Pausing events are dicussed in Pausing.

## FOREVER

The `await` statement for `FOREVER` halts the running trail forever. It cannot be used in assignments because it never evaluates to anything.

Example:

```
if v==10 then  
    await FOREVER; // this trail never awakes if condition is true  
end
```

## Emit

The `emit` statement broadcasts an event to the whole program. The event can be an external event, an internal event, or a timer:

```
Emit_Int ::= emit Loc [ `( ` [LIST(Exp)] ` ) ` ]
Emit_Ext ::= emit ID_ext [ `( ` [LIST(Exp)] ` ) ` ]
           | emit (WCLOCKK|WCLOCKE)
```

Examples:

```
emit A;           // emits the output event `A` of type "none"
emit a(1);        // emits the internal event `a` of type "int"

emit 1s;          // emits the specified time
emit (t)ms;       // emits the current value of the variable `t` in milliseconds
```

## Events

The `emit` statement for events expects the arguments to match the event type.

An `emit` to an input or timer event can only occur inside asynchronous blocks.

An `emit` to an output event is also an expression that evaluates to a value of type `s32` and can be captured with an optional assignment (its meaning is platform dependent).

An `emit` to an internal event starts a new internal reaction.

Examples:

```
input int I;
async do
    emit I(10);           // broadcasts "I" to the application itself, passing "10"
end

output none 0;
var int ret = emit 0(); // outputs "0" to the environment and captures the result

event (int,int) e;
emit e(1,2);             // broadcasts "e" passing a pair of "int" values
```

## Timer

The `emit` statement for timers expects a timer expression.

Like input events, time can only be emitted inside asynchronous blocks.

Examples:

```

async do
    emit 1s;    // broadcasts "1s" to the application itself
end

```

## Lock

TODO

## Conditional

The `if-then-else` statement provides conditional execution in Céu:

```

If ::= if Exp then
    Block
    { else/if Exp then
        Block }
    [ else
        Block ]
end

```

Each condition `Exp` is tested in sequence, first for the `if` clause and then for each of the optional `else/if` clauses. On the first condition that evaluates to `true`, the `Block` following it executes. If all conditions fail, the optional `else` clause executes.

All conditions must evaluate to a value of type `bool`.

## Loops

Céu supports simple loops, numeric iterators, event iterators, and pool iterators:

```

Loop ::=
    /* simple loop */
    loop [ ` / `Exp ] do
        Block
    end

    /* numeric iterator */
    | loop [ ` / `Exp ] NumericRange do
        Block
    end

    /* event iterator */
    | every [ (Loc | ` ( LIST(Loc | ` _ `) `) ) in ] (ID_ext | Loc | WCLOCKK | WCLOCKE) do
        Block
    end

```

```

/* pool iterator */
| loop [(`/`Exp] (ID_int|`_`) in Loc do
    Block
end

```

```

Break      ::= break [(`/`ID_int]
Continue ::= continue [(`/`ID_int]

```

```

NumericRange ::= /* (see "Numeric Iterator") */

```

The body of a loop **Block** executes an arbitrary number of times, depending on the conditions imposed by each kind of loop.

Except for the **every** iterator, all loops support an optional constant expression `(`/`Exp` that limits the maximum number of iterations to avoid infinite execution. If the number of iterations reaches the limit, a runtime error occurs.

### **break and continue**

The **break** statement aborts the deepest enclosing loop.

The **continue** statement aborts the body of the deepest enclosing loop and restarts it in the next iteration.

The optional modifier `(`/`ID_int` in both statements only applies to numeric iterators.

### **Simple Loop**

The simple **loop-do-end** statement executes its body forever:

```

SimpleLoop ::= loop [(`/`Exp] do
    Block
end

```

The only way to terminate a simple loop is with the **break** statement.

Examples:

```

// blinks a LED with a frequency of 1s forever
loop do
    emit LED(1);
    await 1s;
    emit LED(0);
    await 1s;
end

loop do
    loop do

```

```

        if <cnd-1> then
            break;          // aborts the loop at line 2 if <cnd-1> is satisfied
        end
    end
    if <cnd-2> then
        continue;          // restarts the loop at line 1 if <cnd-2> is satisfied
    end
end
end

```

### Numeric Iterator

The numeric loop executes its body a fixed number of times based on a numeric range for a control variable:

```

NumericIterator ::= loop [ ` / ` Exp ] NumericRange do
    Block
end

NumericRange ::= ( ` _ ` | ID_int ) in [ ( ` [ ` | ` ] ` )
                                     ( (      Exp `->` ( ` _ ` | Exp ) )
                                       | ( ` _ ` | Exp ) `<-` Exp      ) )
                                     ( ` [ ` | ` ] ` ) [ ` , ` Exp ] ]

```

The control variable assumes the values specified in the interval, one by one, for each iteration of the loop body:

- **control variable:** `ID_int` is a read-only variable of a numeric type. Alternatively, the special anonymous identifier `_` can be used if the body of the loop does not access the variable.
- **interval:** Specifies a direction, endpoints with open or closed modifiers, and a step.
  - **direction:**
    - \* `->`: Starts from the endpoint `Exp` on the left increasing towards `Exp` on the right.
    - \* `<-`: Starts from the endpoint `Exp` on the right decreasing towards `Exp` on the left. Typically, the value on the left is smaller or equal to the value on the right.
  - **endpoints:** `[Exp and Exp]` are closed intervals which include `Exp` as the endpoints; `]Exp and Exp[` are open intervals which exclude `Exp` as the endpoints. Alternatively, the finishing endpoint may be `_` which means that the interval goes towards infinite.
  - **step:** An optional positive number added or subtracted towards the limit. If the step is omitted, it assumes the value 1. If the direction is `->`, the step is added, otherwise it is subtracted.

If the interval is not specified, it assumes the default `[0 -> _[`.

A numeric iterator executes as follows:

- **initialization:** The starting endpoint is assigned to the control variable. If the starting endpoint is open, the control variable accumulates a step immediately.
- **iteration:**
  1. **limit check:** If the control variable crossed the finishing endpoint, the loop terminates.
  2. **body execution:** The loop body executes.
  3. **step** Applies a step to the control variable. Goto step 1.

The **break** and **continue** statements inside numeric iterators accept an optional modifier `‘/’ID_int` to affect the enclosing loop matching the control variable.

Examples:

```
// prints "i=0", "i=1", ...
var int i;
loop i do
  _printf("i=%d\n", i);
end

// awaits 1s and prints "Hello World!" 10 times
loop _ in [0 -> 10[ do
  await 1s;
  _printf("Hello World!\n");
end

var int i;
loop i do
  var int j;
  loop j do
    if <cnd-1> then
      continue/i;           // continues the loop at line 1
    else/if <cnd-2> then
      break/j;              // breaks the loop at line 4
    end
  end
end
```

*Note : the runtime asserts that the step is a positive number and that the control variable does not overflow.*

## Event Iterator

The **every** statement iterates over an event continuously, executing its body whenever the event occurs:

```
EventIterator ::= every [(Loc | `(` LIST(Loc|`_`) `)` in] (ID_ext|Loc|WCLOCKK|WCLOCKE) do
  Block
```



end

The event can be an external or internal event or a timer.

The optional assignment to a variable (or list of variables) stores the carrying value(s) of the event.

An **every** expands to a **loop** as illustrated below:

```
every <vars> in <event> do
  <body>
end
```

is equivalent to

```
loop do
  <vars> = await <event>;
  <body>
end
```

However, the body of an **every** cannot contain synchronous control statements, ensuring that no occurrences of the specified event are ever missed.

TODO: reject break inside every

Examples:

```
every 1s do
  _printf("Hello World!\n");      // prints the "Hello World!" message on every second
end

event (bool,int) e;
var bool cnd;
var int v;
every (cnd,v) in e do
  if not cnd then
    break;                        // terminates when the received "cnd" is false
  else
    _printf("v = %d\n", v);       // prints the received "v" otherwise
  end
end
```

### Pool Iterator

The pool iterator visits all alive abstraction instances residing in a given pool:

```
PoolIterator ::= loop [ ` / `Exp ] (ID_int | ` _ `) in Loc do
  Block
end
```

On each iteration, the optional control variable becomes a reference to an instance, starting from the oldest created to the newest.

The control variable must be an alias to the same type of the pool with the same rules that apply to **spawn**.

Examples:

```
pool[] My_Code my_codes;

<...>

var&? My_Code my_code;
loop my_code in mycodes do
  <...>
end
```

### Parallel Compositions

```
Pars ::= (par | par/and | par/or) do
  Block
  with
  Block
  { with
  Block }
end

Spawn ::= spawn [ `( ` [LIST(ID_int)] ` ) ` ] do
  Block
end
```

```
Watching ::= watching LIST(ID_ext|Loc|WCLOCKK|WCLOCKE|Abs_Cons) do
  Block
end
```

The parallel statements **par/and**, **par/or**, and **par** fork the running trail in multiple others. They differ only on how trails rejoin and terminate the composition.

The **spawn** statement starts to execute a block in parallel with the enclosing block.

The **watching** statement executes a block and terminates when one of its specified events occur.

See also Parallel Compositions and Abortion.

### **par**

The **par** statement never rejoins.

Examples:

```

// reacts continuously to "1s" and "KEY_PRESSED" and never terminates
input none KEY_PRESSED;
par do
  every 1s do
    <...>          // does something every "1s"
  end
with
  every KEY_PRESSED do
    <...>          // does something every "KEY_PRESSED"
  end
end
end

```

### par/and

The **par/and** statement stands for *parallel-and* and rejoins when all nested trails terminate.

Examples:

```

// reacts once to "1s" and "KEY_PRESSED" and terminates
input none KEY_PRESSED;
par/and do
  await 1s;
  <...>          // does something after "1s"
with
  await KEY_PRESSED;
  <...>          // does something after "KEY_PRESSED"
end
end

```

### par/or

The **par/or** statement stands for *parallel-or* and rejoins when any of the trails terminate, aborting all other trails.

Examples:

```

// reacts once to `1s` or `KEY_PRESSED` and terminates
input none KEY_PRESSED;
par/or do
  await 1s;
  <...>          // does something after "1s"
with
  await KEY_PRESSED;
  <...>          // does something after "KEY_PRESSED"
end
end

```

### **spawn**

The **spawn** statement starts to execute a block in parallel with the enclosing block. When the enclosing block terminates, the spawned block is aborted.

Like a **do-end** block, a **spawn** also supports an optional list of identifiers in parenthesis which restricts the visible variables inside the block to those matching the list.

Examples:

```
spawn do
  every 1s do
    <...>          // does something every "1s"...
  end
end

<...>              // ...in parallel with whatever comes next
```

### **watching**

A **watching** expands to a **par/or** with  $n+1$  trails: one to await each of the listed events, and one to execute its body, i.e.:

```
watching <e1>,<e2>,... do
  <body>
end
```

expands to

```
par/or do
  await <e1>;
with
  await <e2>;
with
  ...
with
  <body>
end
```

The **watching** statement accepts a list of events and terminates when any of them occur. The events are the same supported by the **await** statement. It evaluates to what the occurring event value(s), which can be captured with an optional assignment.

If the event is a code abstraction, the nested blocked does not require the unwrap operator **!**.

Examples:

```

// reacts continuously to "KEY_PRESSED" during "1s"
input none KEY_PRESSED;
watching 1s do
  every KEY_PRESSED do
    <...>          // does something every "KEY_PRESSED"
  end
end
end

```

## Pausing

The `pause/if` statement controls if its body should temporarily stop to react to events:

```

Pause_If ::= pause/if (Loc|ID_ext) do
  Block
end

```

```

Pause_Await ::= await (pause|resume)

```

A `pause/if` specifies a pausing event of type `bool` which, when emitted, toggles between pausing (`true`) and resuming (`false`) reactions for its body.

When its body terminates, the whole `pause/if` terminates and proceeds to the statement in sequence.

In transition instants, the body can react to the special `pause` and `resume` events before the corresponding state applies.

TODO: finalize/pause/resume

Examples:

```

event bool e;
pause/if e do          // pauses/resumes the nested body on each "e"
  every 1s do
    <...>              // does something every "1s"
  end
end

event bool e;
pause/if e do          // pauses/resumes the nested body on each "e"
  <...>
  loop do
    await pause;
    <...>              // does something before pausing
    await resume;
    <...>              // does something before resuming
  end
  <...>
end

```

end

## Exceptions

TODO

```
Throw ::= throw Exp
Catch ::= catch LIST(Loc) do
    Block
end
```

## Asynchronous Execution

Asynchronous execution allow programs to departure from the rigorous synchronous model and preform computations under separate scheduling rules.

Céu supports *asynchronous blocks*, *threads*, and *interrupt service routines*:

```
Async  ::= await async [ `(`LIST(Var)` )` ] do
    Block
end

Thread ::= await async/thread [ `(`LIST(Var)` )` ] do
    Block
end

Isr    ::= spawn async/isr `[ `LIST(Exp) ` ]` [ `(`LIST(Var) ` )` ] do
    Block
end

Atomic ::= atomic do
    Block
end
```

Asynchronous execution supports tight loops while keeping the rest of the application, aka the *synchronous side*, reactive to incoming events. However, it does not support any synchronous control statement (e.g., parallel compositions, event handling, pausing, etc.).

By default, asynchronous bodies do not share variables with their enclosing scope, but the optional list of variables makes them visible to the block.

Even though asynchronous blocks execute in separate, they are still managed by the program hierarchy and are also subject to lexical scope and abortion.

## Asynchronous Block

Asynchronous blocks, aka *asyncs*, intercalate execution with the synchronous side as follows:

1. Start/Resume whenever the synchronous side is idle. When multiple *asyncs* are active, they execute in lexical order.
2. Suspend after each `loop` iteration.
3. Suspend on every input `emit` (see Simulation).
4. Execute atomically and to completion unless rules 2 and 3 apply.

This rules imply that *asyncs* never execute with real parallelism with the synchronous side, preserving determinism in the program.

Examples:

```
// calculates the factorial of some "v" if it doesn't take too long
var u64 v = <...>;
var u64 fat = 1;
var bool ok = false;
watching 1s do
    await async (v,fat) do      // keeps "v" and "fat" visible
        loop i in [1 -> v] do  // reads from "v"
            fat = fat * i;      // writes to "fat"
        end
    end
    ok = true;                  // completed within "1s"
end
```

## Simulation

An `async` block can emit input and timer events towards the synchronous side, providing a way to test programs in the language itself. Every time an `async` emits an event, it suspends until the synchronous side reacts to the event (see rule 1 above).

Examples:

```
input int A;

// tests a program with input simulation in parallel
par do

    // original program
    var int v = await A;
    loop i in [0 -> _] do
        await 10ms;
        _printf("v = %d\n", v+i);
    end
end
```

```

with

    // input simulation
    async do
        emit A(0);      // initial value for "v"
        emit 1s35ms;    // the loop in the original program executes 103 times
    end
    escape 0;

end

// The example prints the message `v = <v+i>` exactly 103 times.

```

## Thread

Threads provide real parallelism for applications in Céu. Once started, a thread executes completely detached from the synchronous side. For this reason, thread execution is non deterministic and require explicit atomic blocks on accesses to variables to avoid race conditions.

A thread evaluates to a boolean value which indicates whether it started successfully or not. The value can be captured with an optional assignment.

Examples:

```

// calculates the factorial of some "v" if it doesn't take too long
var u64 v = <...>;
var u64 fat = 1;
var bool ok = false;
watching 1s do
    await async/thread (v,fat) do // keeps "v" and "fat" visible
        loop i in [1 -> v] do // reads from "v"
            fat = fat * i; // writes to "fat"
        end
    end
    ok = true; // completed within "1s"
end

```

## Asynchronous Interrupt Service Routine

TODO

## Atomic Block



Atomic blocks provide mutual exclusion among threads, interrupts, and the synchronous side of application. Once an atomic block starts to execute, no other atomic block in the program starts.

Examples:

// A "race" between two threads: one incrementing, the other decrementing "count".

```
var s64 count = 0;                                // "count" is a shared variable
par do
  every 1s do
    atomic do
      _printf("count = %d\n", count);           // prints current value of "count" every "1s"
    end
  end
with
  await async/thread (count) do
    loop do
      atomic do
        count = count - 1;                      // decrements "count" as fast as possible
      end
    end
  end
with
  await async/thread (count) do
    loop do
      atomic do
        count = count + 1;                      // increments "count" as fast as possible
      end
    end
  end
end
end
```

## C Integration

Céu provides native declarations to import C symbols, native blocks to define new code in C, native statements to inline C statements, native calls to call C functions, and finalization to deal with C pointers safely:

```
Nat_Symbol ::= native [ '/' (pure|const|nohold|plain) ] `(` LIST(ID_nat) `)`
Nat_Block  ::= native `/' (pre|pos) do
                <code definitions in C>
            end
Nat_End    ::= native `/' end

Nat_Stmts  ::= `{` {<code in C> | `@` (`(`Exp`)`|Exp)} `}` /* `@@` escapes to `@` */
```

```

Nat_Call ::= [call] (Loc | `(` Exp `)` ) `(` [ LIST(Exp) ] `)`

Finalization ::= do [Stmt] Finalize
  | var [`&'|`&?`] Type ID_int `=' `&` (Call_Nat | Call_Code) Finalize
Finalize ::= finalize [ `(` LIST(Loc) `)` ] with
  Block
  [ pause with Block ]
  [ resume with Block ]
end

```

Native calls and statements transfer execution to C, losing the guarantees of the synchronous model. For this reason, programs should only resort to C for asynchronous functionality (e.g., non-blocking I/O) or simple **struct** accessors, but never for control purposes.

TODO: Nat\_End

## Native Declaration

In Céu, any identifier prefixed with an underscore is a native symbol defined externally in C. However, all external symbols must be declared before their first use in a program.

Native declarations support four modifiers as follows:

- **const**: declares the listed symbols as constants. Constants can be used as bounded limits in vectors, pools, and numeric loops. Also, constants cannot be assigned.
- **plain**: declares the listed symbols as *plain* types, i.e., types (or composite types) that do not contain pointers. A value of a plain type passed as argument to a function does not require finalization.
- **nohold**: declares the listed symbols as *non-holding* functions, i.e., functions that do not retain received pointers after returning. Pointers passed to non-holding functions do not require finalization.
- **pure**: declares the listed symbols as pure functions. In addition to the **nohold** properties, pure functions never allocate resources that require finalization and have no side effects to take into account for the safety checks.

Examples:

```

// values
native/const _LOW, _HIGH;      // Arduino "LOW" and "HIGH" are constants
native      _errno;           // POSIX "errno" is a global variable

// types
native/plain _char;           // "char" is a "plain" type

```

```

native      _SDL_PixelFormat; // SDL "SDL_PixelFormat" is a type holding a pointer

// functions
native      _uv_read_start;   // Libuv "uv_read_start" retains the received pointer
native/nohold _free;          // POSIX "free" receives a pointer but does not retain it
native/pure  _strlen;         // POSIX "strlen" is a "pure" function

```

## Native Block

A native block allows programs to define new external symbols in C.

The contents of native blocks is copied unchanged to the output in C depending on the modifier specified:

- **pre**: code is placed before the declarations for the Céu program. Symbols defined in **pre** blocks are visible to Céu.
- **pos**: code is placed after the declarations for the Céu program. Symbols implicitly defined by the compiler of Céu are visible to **pos** blocks.

Native blocks are copied in the order they appear in the source code.

Since Céu uses the C preprocessor, hash directives **#** inside native blocks must be quoted as **##** to be considered only in the C compilation phase.

If the code in C contains the terminating **end** keyword of Céu, the **native** block should be delimited with matching comments to avoid confusing the parser:

Symbols defined in native blocks still need to be declared for use in the program.

Examples:

```

native/plain _t;
native/pre do
    typedef int t;                // definition for "t" is placed before Céu declarations
end
var _t x = 10;                   // requires "t" to be already defined
input none A;                   // declaration for "A" is placed before "pos" blocks
native _get_A_id;
native/pos do
    int get_A_id (void) {
        return CEU_INPUT_A;      // requires "A" to be already declared
    }
end

native/nohold _printf;
native/pre do
    ##include <stdio.h>           // include the relevant header for "printf"
end

```

```

native/pos do
    /*****/
    char str = "This `end` confuses the parser";
    /*****/
end

```

## Native Statement

The contents of native statements in between { and } are inlined in the program.

Native statements support interpolation of expressions in Céu which are expanded when preceded by the symbol @.

Examples:

```

var int v_ceu = 10;
{
    int v_c = @v_ceu * 2;           // yields 20
}
v_ceu = { v_c + @v_ceu };         // yields 30
{
    printf("%d\n", @v_ceu);        // prints 30
}

```

## Native Call

Expressions that evaluate to a native type can be called from Céu.

If a call passes or returns pointers, it may require an accompanying finalization statement.

Examples:

// all expressions below evaluate to a native type and can be called

```
_printf("Hello World!\n");
```

```

var _t f = <...>;
f();

```

```

var _s s = <...>;
s.f();

```

## Resources & Finalization

A finalization statement unconditionally executes a series of statements when its associated block terminates or is aborted.

Céu tracks the interaction of native calls with pointers and requires **finalize** clauses to accompany the calls:

- If Céu **passes** a pointer to a native call, the pointer represents a **local resource** that requires finalization. Finalization executes when the block of the local resource goes out of scope.
- If Céu **receives** a pointer from a native call return, the pointer represents an **external resource** that requires finalization. Finalization executes when the block of the receiving pointer goes out of scope.

In both cases, the program does not compile without the **finalize** statement.

A **finalize** cannot contain synchronous control statements.

Examples:

```
// Local resource finalization
watching <...> do
  var _buffer_t msg;
  <...>                                // prepares msg
  do
    _send_request(&&msg);
    finalize with
      _send_cancel(&&msg);
  end
  await SEND_ACK;                      // transmission is complete
end
```

In the example above, the local variable `msg` is an internal resource passed as a pointer to `_send_request`, which is an asynchronous call that transmits the buffer in the background. If the enclosing **watching** aborts before awaking from the `await SEND_ACK`, the local `msg` goes out of scope and the external transmission would hold a *dangling pointer*. The **finalize** ensures that `_send_cancel` also aborts the transmission.

```
// External resource finalization
watching <...> do
  var&? _FILE f = &_fopen(<...>) finalize with
    _fclose(f);
  end;
  _fwrite(<...>, f);
  await A;
  _fwrite(<...>, f);
end
```

In the example above, the call to `_fopen` returns an external file resource as a pointer. If the enclosing **watching** aborts before awaking from the `await A`, the file would remain open as a *memory leak*. The **finalize** ensures that `_fclose` closes the file properly.

To access an external resource from Céu requires an alias assignment to a variable alias. If the external call returns NULL and the variable is an option alias `var&?`, the alias remains unbounded. If the variable is an alias `var&`, the assignment raises a runtime error.

*Note: the compiler only forces the programmer to write finalization clauses, but cannot check if they handle the resource properly.*

Declaration and expression modifiers may suppress the requirement for finalization in calls:

- `nohold` modifiers or `/nohold` typecasts make passing pointers safe.
- `pure` modifiers or `/pure` typecasts make passing pointers and returning pointers safe.
- `/plain` typecasts make return values safe.

Examples:

```
// "_free" does not retain "ptr"
native/nohold _free;
_free(ptr);
// or
(_free as /nohold)(ptr);

// "_strchr" does retain "ptr" or allocates resources
native/pure _strchr;
var _char&& found = _strchr(ptr);
// or
var _char&& found = (_strchr as /pure)(ptr);

// "_f" returns a non-pointer type
var _tp v = _f() as /plain;
```

## Lua Integration

Céu provides Lua states to delimit the effects of inlined Lua statements. Lua statements transfer execution to the Lua runtime, losing the guarantees of the synchronous model:

```
Lua_State ::= lua `[` [Exp] `]` do
    Block
end
Lua_Stmts ::= `[` {`=}` `[`
    { {<code in Lua> | `@` (`(`Exp`)`|Exp)} } /* `@@` escapes to `@` */
`]` {`=}` `]`
```

Programs have an implicit enclosing *global Lua state* which all orphan statements apply.

## Lua State

A Lua state creates an isolated state for inlined Lua statements.

Example:

```
// "v" is not shared between the two statements
par do
  // global Lua state
  [[ v = 0 ]];
  var int v = 0;
  every 1s do
    [[print('Lua 1', v, @v) ]];
    v = v + 1;
    [[ v = v + 1 ]];
  end
with
  // local Lua state
  lua[] do
    [[ v = 0 ]];
    var int v = 0;
    every 1s do
      [[print('Lua 2', v, @v) ]];
      v = v + 1;
      [[ v = v + 1 ]];
    end
  end
end
```

TODO: dynamic scope, assignment/error, [dim]

## Lua Statement

The contents of Lua statements in between [[ and ]] are inlined in the program.

Like native statements, Lua statements support interpolation of expressions in Céu which are expanded when preceded by a @.

Lua statements only affect the Lua state in which they are embedded.

If a Lua statement is used in an assignment, it is evaluated as an expression that either satisfies the destination or generates a runtime error. The list that follows specifies the *Céu destination* and expected *Lua source*:

- a boolean variable expects a **boolean** value
- a numeric variable expects a **number** value
- a pointer variable expects a **lightuserdata** value
- a byte vector expects a **string** value

TODO: lua state captures errors

Examples:

```
var int v_ceu = 10;
[[
    v_lua = @v_ceu * 2          -- yields 20
]]
v_ceu = [[ v_lua + @v_ceu ]];  // yields 30
[[
    print(@v_ceu)              -- prints 30
]]
```

## Abstractions

Céu supports reuse with **data** declarations to define new types, and **code** declarations to define new subprograms.

Declarations are subject to lexical scope.

## Data

A **data** declaration creates a new data type:

```
Data ::= data ID_abs [as (nothing|Exp)] [ with
      (Var|Vec|Pool|Int) `;` { (Var|Vec|Pool|Int) `;` }
end
```

```
Data_Cons ::= (val|new) Abs_Cons
Abs_Cons  ::= [Loc `.`] ID_abs `( LIST(Data_Cons|Vec_Cons|Exp|`_`) `)`
```

A declaration may pack fields with storage declarations which become publicly accessible in the new type. Field declarations may assign default values for uninitialized instances.

Data types can form hierarchies using dots (.) in identifiers:

- An isolated identifier such as **A** makes **A** a base type.
- A dotted identifier such as **A.B** makes **A.B** a subtype of its supertype **A**.

A subtype inherits all fields from its supertype.

The optional modifier **as** expects the keyword **nothing** or a constant expression of type **int**:

- **nothing**: the **data** cannot be instantiated.
- *constant expression*: typecasting a value of the type to **int** evaluates to the specified enumeration expression.

Examples:



```

data Rect with
  var int x;
  var int y;
  var int h;
  var int w;
  var int z = 0;
end
var Rect r = val Rect(10,10, 100,100, _); // "r.z" defaults to 0

data Dir      as nothing; // "Dir" is a base type and cannot be instantiated
data Dir.Right as 1;      // "Dir.Right" is a subtype of "Dir"
data Dir.Left  as -1;     // "Dir.Left" is a subtype of "Dir"
var Dir dir = <...>;      // receives one of "Dir.Right" or "Dir.Left"
escape (dir as int);      // returns 1 or -1

TODO: new, pool, recursive types

```

## Data Constructor

A new data value is created in the contexts that follow:

- Prefixed by the keyword **val** in an assignment to a variable.
- As an argument to a **code** invocation.
- Nested as an argument in a **data** creation (i.e., a **data** that contains another **data**).

In all cases, the arguments are copied to the destination. The destination must be a plain declaration (i.e., not an alias or pointer).

The constructor uses the **data** identifier followed by a list of arguments matching the fields of the type.

Variables of the exact same type can be copied in assignments.

For assignments from a subtype to a supertype, the rules are as follows:

- Copy assignments
  - plain values: only if the subtype contains no extra fields
  - pointers: allowed
- Alias assignment: allowed.

```

data Object with
  var Rect rect;
  var Dir dir;
end
var Object o1 = val Object(Rect(0,0,10,10,_), Dir.Right());
var Object o2 = o1;           // makes a deep copy of all fields from "o1" to "o2"

```

## Code

The `code/tight` and `code/await` declarations specify new subprograms that can be invoked from arbitrary points in programs:

```
// prototype declaration
Code_Tight ::= code/tight Mods ID_abs `(` Params `)` `->` Type
Code_Await ::= code/await Mods ID_abs `(` Params `)`
                                     [ `->` `(` Params `)` ]
                                     `->` (Type | NEVER)
                                     [ throws LIST(ID_abs) ]
Params ::= none | LIST(Var|Vec|Pool|Int)

// full declaration
Code_Impl ::= (Code_Tight | Code_Await) do
    Block
end

// invocation
Code_Call  ::= call  Mods Abs_Cons
Code_Await ::= await Mods Abs_Cons
Code_Spawn ::= spawn Mods Abs_Cons [in Loc]
Code_Kill  ::= kill  Loc [ `(` Exp `)` ]

Mods ::= [ `/dynamic | `/static ] [ `/recursive ]
```

A `code/tight` is a subprogram that cannot contain synchronous control statements and its body runs to completion in the current internal reaction.

A `code/await` is a subprogram with no restrictions (e.g., it can manipulate events and use parallel compositions) and its body execution may outlive multiple reactions.

A *prototype declaration* specifies the interface parameters of the abstraction which invocations must satisfy. A *full declaration* (aka *definition*) also specifies an implementation with a block of code. An *invocation* specifies the name of the code abstraction and arguments matching its declaration.

Declarations can be nested. A nested declaration is not visible outside its enclosing declaration. The body of a nested declaration may access entities from its enclosing declarations with the prefix **outer**.

To support recursive abstractions, a code invocation can appear before the implementation is known, but after the prototype declaration. In this case, the declaration must use the modifier `/recursive`.

Examples:

```
code/tight Absolute (var int v) -> int do    // declares the prototype for "Absolute"
    if v > 0 then                             // implements the behavior
```

```

        escape v;
    else
        escape -v;
    end
end
var int abs = call Absolute(-10);           // invokes "Absolute" (yields 10)
code/await Hello_World (none) -> NEVER do
    every 1s do
        _printf("Hello World!\n"); // prints "Hello World!" every second
    end
end
await Hello_World();                       // never awakes
code/tight/recursive Fat (var int v) -> int; // "Fat" is a recursive code
code/tight/recursive Fat (var int v) -> int do
    if v > 1 then
        escape v * (call/recursive Fat(v-1)); // recursive invocation before full declarat
    else
        escape 1;
    end
end
var int fat = call/recursive Fat(10);       // invokes "Fat" (yields 3628800)
TODO: hold

```

## Code Declaration

Code abstractions specify a list of input parameters in between the symbols ( and ). Each parameter specifies an entity class with modifiers, a type and an identifier. A **none** list specifies that the abstraction has no parameters.

Code abstractions also specify an output return type. A **code/await** may use **NEVER** as output to indicate that it never returns.

A **code/await** may also specify an optional *public field list*, which are local storage entities living in the outermost scope of the abstraction body. These entities are visible to the invoking context, which may access them while the abstraction executes. Likewise, nested code declarations in the outermost scope, known as methods, are also visible to the invoking context.

TODO: throws

## Code Invocation

A **code/tight** is invoked with the keyword **call** followed by the abstraction name and list of arguments. A **code/await** is invoked with the keywords **await** or **spawn** followed by the abstraction name and list of arguments.

The list of arguments must satisfy the list of parameters in the code declaration.

The `call` and `await` invocations suspend the current trail and transfer control to the code abstraction. The invoking point only resumes after the abstraction terminates and evaluates to a value of its return type which can be captured with an optional assignment.

The `spawn` invocation also suspends and transfers control to the code abstraction. However, as soon as the abstraction becomes idle (or terminates), the invoking point resumes. This makes the invocation point and abstraction to execute concurrently.

The `spawn` invocation evaluates to a reference representing the instance and can be captured with an optional assignment. The alias must be an option alias variable of the same type of the code abstraction. If the abstraction never terminates (i.e., return type is `NEVER`), the variable may be a simple alias. If the `spawn` fails (e.g., lack of memory) the option alias variable is unset. In the case of a simple alias, the assignment raises a runtime error.

The `spawn` invocation also accepts an optional pool which provides storage and scope for invoked abstractions. When the pool goes out of scope, all invoked abstractions residing in that pool are aborted. If the `spawn` omits the pool, the invocation always succeed and has the same scope as the invoking point: when the enclosing block terminates, the invoked code is also aborted.

TODO: kill

## Code References

The `spawn` invocation and the control variable of pool iterators evaluate to a reference as an option alias to an abstraction instance. If the instance terminates at any time, the option variable is automatically unset.

A reference provides access to the public fields and methods of the instance.

Examples:

```
code/await My_Code (var int x) -> (var int y) -> NEVER do
    y = x;                                // "y" is a public field

    code/tight Get_X (none) -> int do    // "Get_X" is a public method
        escape outer.x;
    end

    await FOREVER;
end

var& My_Code c = spawn My_Code(10);
_printf("y=%d, x=%d\n", c.y, c.Get_X()); // prints "y=10, x=10"
```

## Dynamic Dispatching

Céu supports dynamic code dispatching based on multiple parameters.

The modifier `/dynamic` in a declaration specifies that the code is dynamically dispatched. A dynamic code must have at least one **dynamic** parameter. Also, all dynamic parameters must be pointers or aliases to a data type in some hierarchy.

A dynamic declaration requires other compatible dynamic declarations with the same name, modifiers, parameters, and return type. The exceptions are the **dynamic** parameters, which must be in the same hierarchy of their corresponding parameters in other declarations.

To determine which declaration to execute during runtime, the actual argument runtime type is checked against the first formal **dynamic** parameter of each declaration. The declaration with the most specific type matching the argument wins. In the case of a tie, the next dynamic parameter is checked.

A *catchall* declaration with the most general dynamic types must always be provided.

If the argument is explicitly typecast to a supertype, then dispatching considers that type instead.

Example:

```
data Media as nothing;
data Media.Audio      with <...> end
data Media.Video      with <...> end
data Media.Video.Avi  with <...> end

code/await/dynamic Play (dynamic var& Media media) -> none do
    _assert(0);                // never dispatched
end
code/await/dynamic Play (dynamic var& Media.Audio media) -> none do
    <...>                      // plays an audio
end
code/await/dynamic Play (dynamic var& Media.Video media) -> none do
    <...>                      // plays a video
end
code/await/dynamic Play (dynamic var& Media.Video.Avi media) -> none do
    <...>                      // prepare the avi video
    await/dynamic Play(&m as Media.Video); // dispatches the supertype
end

var& Media m = <...>;          // receives one of "Media.Audio" or "Media.Video"
await/dynamic Play(&m);         // dispatches the appropriate subprogram to play the media
```

## Synchronous Control Statements

The *synchronous control statements* which follow cannot appear in event iterators, pool iterators, asynchronous execution, finalization, and tight code abstractions: `await`, `spawn`, `emit` (internal events), `every`, `finalize`, `pause/if`, `par`, `par/and`, `par/or`, and `watching`.

As exceptions, an `every` can `emit` internal events, and a `code/tight` can contain empty `finalize` statements.

## Locations & Expressions

### Locations & Expressions

Céu specifies locations and expressions as follows:

```
Exp ::= NUM | STR | null | true | false | on | off | yes | no
      | `(` Exp `)`
      | Exp <binop> Exp
      | <unop> Exp
      | Exp `:`|`.` (ID_int|ID_nat)
      | Exp `?`|`!`
      | Exp `[` Exp `]`
      | Exp `(` [ LIST(Exp) ] `)`
      | Exp is Type
      | Exp as Type
      | Exp as `/(nohold|plain|pure)
      | sizeof `(` (Type|Exp) `)`
      | Nat_Call | Code_Call
      | ID_int
      | ID_nat
      | outer
```

/\* Locations \*/

```
Loc ::= Loc [as (Type | `/(nohold|plain|pure)) `)`
      | `[*`|`$`] Loc
      | Loc { `[Exp`] | `:`|`.` (ID_int|ID_nat) | `!` }
      | ID_int
      | ID_nat
      | outer
      | `{` <code in C> `}`
      | `(` Loc `)`
```

/\* Operator Precedence \*/

```

/* lowest priority */

// locations
*      $
:      .      !      []
as

// expressions
is      as                                // binops
or
and
!=      ==      <=      >=      <      >
|
^
&
<<      >>
+      -
*      /      %
not      +      -      ~      $$      $      *      &&      &      // unops
:      .      !      ?      (      []

/* highest priority */

```

## Primary

TODO

## Outer

TODO

## Arithmetic

Céu supports the arithmetic expressions *addition*, *subtraction*, *modulo (remainder)*, *multiplication*, *division*, *unary-plus*, and *unary-minus* through the operators that follow:

```

+      -      %      *      /      +      -

```

## Bitwise

Céu supports the bitwise expressions *not*, *and*, *or*, *xor*, *left-shift*, and *right-shift* through the operators that follow:

~      &      |      ^      <<      >>

## Relational

Céu supports the relational expressions *equal-to*, *not-equal-to*, *greater-than*, *less-than*, *greater-than-or-equal-to*, and *less-than-or-equal-to* through the operators that follow:

==      !=      >      <      >=      <=

Relational expressions evaluate to *true* or *false*.

## Logical

Céu supports the logical expressions *not*, *and*, and *or* through the operators that follow:

not      and      or

Logical expressions evaluate to *true* or *false*.

## Types

Céu supports type checks and casts:

Check ::= Exp is Type

Cast ::= Exp as Type

### Type Check

A type check evaluates to *true* or *false* depending on whether the runtime type of the expression is a subtype of the checked type or not.

The static type of the expression must be a supertype of the checked type.

Example:

```
data Aa;
data Aa.Bb;
var Aa a = <...>;      // "a" is of static type "Aa"
<...>
if a is Aa.Bb then      // is the runtime type of "a" a subtype of "Aa.Bb"?
  <...>
end
```



## Type Cast

A type cast converts the type of an expression into a new type as follows:

1. The expression type is a data type:
  1. The new type is `int`: Evaluates to the type enumeration for the expression type.
  2. The new type is a subtype of the expression static type:
    1. The expression runtime type is a subtype of the new type: Evaluates to the new type.
    2. Evaluates to error.
  3. The new type is a supertype of the expression static type: Always succeeds and evaluates to the new type. See also Dynamic Dispatching.
  4. Evaluates to error.
2. Evaluates to the new type (i.e., a *weak typecast*, as in C).

Examples:

```
var Direction dir = <...>;
_printf("dir = %d\n", dir as int);

var Aa a = <...>;
_printf("a.v = %d\n", (a as Aa.Bb).v);

var Media.Video vid = <...>;
await/dynamic Play(&m as Media);

var bool b = <...>;
_printf("b= %d\n", b as int);
```

## Modifiers

Expressions that evaluate to native types can be modified as follows:

Mod ::= Exp as `/(nohold|plain|pure)

Modifiers may suppress the requirement for resource finalization.

## References

Céu supports *aliases* and *pointers* as references.

### Aliases

An alias is acquired by prefixing a native call or a location with the operator `&`:

Alias ::= `&` (Nat\_Call | Loc)

See also the unwrap operator `!` for option variable aliases.

## Pointers

The operator `&&` returns the address of a location, while the operator `*` dereferences a pointer:

```
Addr  ::= `&&` Loc
Deref ::= `*`  Loc
```

## Option

The operator `?` checks if the location of an option type is set, while the operator `!` unwraps the location, raising an error if it is unset:

```
Check  ::= Loc `?`
Unwrap ::= Loc `!`
```

## Sizeof

A `sizeof` expression returns the size of a type or expression, in bytes:

```
Sizeof ::= sizeof `( (Type|Exp) `)`
```

## Calls

See Native Call and Code Invocation.

## Vectors

### Index

Céu uses square brackets to index vectors:

```
Vec_Idx ::= Loc `[` Exp `]`
```

The index expression must be of type `usize`.

Vectors start at index zero. Céu generates an error for out-of-bounds vector accesses.

## Length

The operator `$` returns the current length of a vector, while the operator `$$` returns the max length:

```
Vec_Len ::= ` $ ` Loc
Vec_Max ::= ` $$ ` Loc
```

TODO: max

The vector length can also be assigned:

```
var[] int vec = [ 1, 2, 3 ];
$vec = 1;
```

The new length must be smaller or equal to the current length, otherwise the assignment raises a runtime error. The space for dynamic vectors shrinks automatically.

## Constructor

Vector constructors are only valid in assignments:

```
Vec_Cons  ::= (Loc | Exp) Vec_Concat { Vec_Concat }
           | ` [ ` [LIST(Exp)] ` ] ` { Vec_Concat }
Vec_Concat ::= ` .. ` (Exp | Lua_Stmts | ` [ ` [LIST(Exp)] ` ] `)
```

Examples:

```
var[3] int v;           // declare an empty vector of length 3    (v = [])
v = v .. [8];           // append value '8' to the empty vector   (v = [8])
v = v .. [1] .. [5];    // append values '1' and '5' to the vector (v = [8, 1, 5])
```

## Fields

The operators `.` and `:` access public fields of data abstractions, code abstractions, and native structs:

```
Dot    ::= Loc ` . ` (ID_int|ID_nat)
Colon  ::= Loc ` : ` (ID_int|ID_nat)
```


The expression `e:f` is a sugar for `(*e).f`.

TODO: ID\_nat to avoid clashing with Céu keywords.

# Compilation

## Compilation

The compiler converts an input program in Céu to an output in C, which is further embedded in an environment satisfying a C API, which is finally compiled to an executable:



## Command Line

The single command `ceu` is used for all compilation phases:

Usage: `ceu [<options>] <file>...`

Options:

<code>--help</code>	display this help, then exit
<code>--version</code>	display version information, then exit
<code>--pre</code>	Preprocessor phase: preprocess Céu into Céu
<code>--pre-exe=FILE</code>	preprocessor executable
<code>--pre-args=ARGS</code>	preprocessor arguments
<code>--pre-input=FILE</code>	input file to compile (Céu source)
<code>--pre-output=FILE</code>	output file to generate (Céu source)
<code>--ceu</code>	Céu phase: compiles Céu into C
<code>--ceu-input=FILE</code>	input file to compile (Céu source)
<code>--ceu-output=FILE</code>	output source file to generate (C source)

<code>--ceu-line-directives=BOOL</code>	insert <code>`#line`</code> directives in the C output (default <code>`false`</code> )
<code>--ceu-features-trace=BOOL</code>	enable trace support (default <code>`false`</code> )
<code>--ceu-features-exception=BOOL</code>	enable exceptions support (default <code>`false`</code> )
<code>--ceu-features-dynamic=BOOL</code>	enable dynamic allocation support (default <code>`false`</code> )
<code>--ceu-features-pool=BOOL</code>	enable pool support (default <code>`false`</code> )
<code>--ceu-features-lua=BOOL</code>	enable <code>`lua`</code> support (default <code>`false`</code> )
<code>--ceu-features-thread=BOOL</code>	enable <code>`async/thread`</code> support (default <code>`false`</code> )
<code>--ceu-features-isr=BOOL</code>	enable <code>`async/isr`</code> support (default <code>`false`</code> )
<code>--ceu-features-pause=BOOL</code>	enable <code>`pause/if`</code> support (default <code>`false`</code> )
<code>--ceu-err-unused=OPT</code>	effect for unused identifier: error warning pass
<code>--ceu-err-unused-native=OPT</code>	unused native identifier
<code>--ceu-err-unused-code=OPT</code>	unused code identifier
<code>--ceu-err-uninitialized=OPT</code>	effect for uninitialized variable: error warning pass
<code>--ceu-err-uncaught-exception=OPT</code>	effect for uncaught exception: error warning pass
<code>--ceu-err-uncaught-exception-main=OPT</code>	... at the main block (outside <code>`code`</code> abstraction)
<code>--ceu-err-uncaught-exception-lua=OPT</code>	... from Lua code
<code>--env</code>	Environment phase: packs all C files together
<code>--env-types=FILE</code>	header file with type declarations (C source)
<code>--env-threads=FILE</code>	header file with thread declarations (C source)
<code>--env-ceu=FILE</code>	output file from Céu phase (C source)
<code>--env-main=FILE</code>	source file with main function (C source)
<code>--env-output=FILE</code>	output file to generate (C source)
<code>--cc</code>	C phase: compiles C into binary
<code>--cc-exe=FILE</code>	C compiler executable
<code>--cc-args=ARGS</code>	compiler arguments
<code>--cc-input=FILE</code>	input file to compile (C source)
<code>--cc-output=FILE</code>	output file to generate (binary)

All phases are optional. To enable a phase, the associated prefix must be enabled. If two consecutive phases are enabled, the output of the preceding and the input of the succeeding phases can be omitted.

Examples:

```
## Preprocess "user.ceu", and converts the output to "user.c"
$ ceu --pre --pre-input="user.ceu" --ceu --ceu-output="user.c"

## Packs "user.c", "types.h", and "main.c", compiling them to "app.out"
$ ceu --env --env-ceu=user.c --env-types=types.h --env-main=main.c \
    --cc --cc-output=app.out
```

## C API

The environment phase of the compiler packs the converted Céu program and additional files in the order as follows:

1. type declarations (option `--env-types`)
2. thread declarations (option `--env-threads`, optional)
3. a callback prototype (fixed, see below)
4. Céu program (option `--env-ceu`, auto generated)
5. main program (option `--env-main`)

The Céu program uses standardized types and calls, which must be previously mapped from the host environment in steps 1-3.

The main program depends on declarations from the Céu program.

### Types

The type declarations must map the types of the host environment to all primitive types of Céu.

Example:

```
##include <stdint.h>
##include <sys/types.h>
```

```
typedef unsigned char bool;
typedef unsigned char byte;
typedef unsigned int  uint;
```

```
typedef ssize_t  ssize;
typedef size_t   usize;
```

```
typedef int8_t   s8;
typedef int16_t  s16;
typedef int32_t  s32;
typedef int64_t  s64;
```

```
typedef uint8_t   u8;
typedef uint16_t  u16;
typedef uint32_t  u32;
typedef uint64_t  u64;
```

```
typedef float     real;
typedef float     r32;
typedef double    r64;
```

## Threads

If the user program uses threads and the option `--ceu-features-thread` is set, the host environment must provide declarations for types and functions expected by Céu.

Example:

```
##include <pthread.h>
##include <unistd.h>
##define CEU_THREADS_T          pthread_t
##define CEU_THREADS_MUTEX_T    pthread_mutex_t
##define CEU_THREADS_CREATE(t,f,p) pthread_create(t,NULL,f,p)
##define CEU_THREADS_CANCEL(t)  ceu_dbg_assert(pthread_cancel(t)==0)
##define CEU_THREADS_JOIN_TRY(t) 0
##define CEU_THREADS_JOIN(t)      ceu_dbg_assert(pthread_join(t,NULL)==0)
##define CEU_THREADS_MUTEX_LOCK(m) ceu_dbg_assert(pthread_mutex_lock(m)==0)
##define CEU_THREADS_MUTEX_UNLOCK(m) ceu_dbg_assert(pthread_mutex_unlock(m)==0)
##define CEU_THREADS_SLEEP(us)    usleep(us)
##define CEU_THREADS_PROTOTYPE(f,p) void* f (p)
##define CEU_THREADS_RETURN(v)    return v
```

TODO: describe them

## Céu

The converted program generates types and constants required by the main program.

## External Events

For each external input and output event `<ID>` defined in Céu, the compiler generates corresponding declarations as follows:

1. An enumeration item `CEU_INPUT_<ID>` that univocally identifies the event.
2. A `define` macro `_CEU_INPUT_<ID>_`.
3. A struct type `tceu_input_<ID>` with fields corresponding to the types in of the event payload.

Example:

Céu program:

```
input (int,u8&&) MY_EVT;
```

Converted program:

```
enum {
    ...
    CEU_INPUT_MY_EVT,
```

```

    ...
};

#define _CEU_INPUT_MY_EVT_

typedef struct tceu_input_MY_EVT {
    int _1;
    u8* _2;
} tceu_input_MY_EVT;

```

## Data

The global `CEU_APP` of type `tceu_app` holds all program memory and runtime information:

```

typedef struct tceu_app {
    bool end_ok;           /* if the program terminated */
    int  end_val;          /* final value of the program */
    bool async_pending;    /* if there is a pending "async" to execute */
    ...
    tceu_code_mem_ROOT root; /* all Céu program memory */
} tceu_app;

static tceu_app CEU_APP;

```

The struct `tceu_code_mem_ROOT` holds the whole memory of the Céu program. The identifiers for global variables are preserved, making them directly accessible.

Example:

```

var int x = 10;

typedef struct tceu_code_mem_ROOT {
    ...
    int x;
} tceu_code_mem_ROOT;

```

## Main

The main program provides the entry point for the host platform (i.e., the `main` function), implementing the event loop that senses the world and notifies the Céu program about changes.

The main program interfaces with the Céu program in both directions:

- Through direct calls, in the direction `main -> Céu`, typically when new input is available.
- Through callbacks, in the direction `Céu -> main`, typically when new output is available.



## Calls

The functions that follow are called by the main program to command the execution of Céu programs:

- `void ceu_start (tceu_callback* cb, int argc, char* argv[])`  
Initializes and starts the program. Should be called once. Expects a callback to register for further notifications. Also receives the program arguments in `argc` and `argv`.
- `void ceu_stop (void)`  
Finalizes the program. Should be called once.
- `void ceu_input (tceu_nevt id, void* params)`  
Notifies the program about an input `id` with a payload `params`. Should be called whenever the event loop senses a change. The call to `ceu_input(CEU_INPUT__ASYNC, NULL)` makes asynchronous blocks to execute a step.
- `int ceu_loop (tceu_callback* cb, int argc, char* argv[])`  
Implements a simple loop encapsulating `ceu_start`, `ceu_input`, and `ceu_stop`. On each loop iteration, make a `CEU_CALLBACK_STEP` callback and generates a `CEU_INPUT__ASYNC` input. Should be called once. Returns the final value of the program.
- `void ceu_callback_register (tceu_callback* cb)`  
Registers a new callback.

## Callbacks

The Céu program makes callbacks to the main program in specific situations:

```
enum {  
    CEU_CALLBACK_START,           /* once in the beginning of `ceu_start`  
    CEU_CALLBACK_STOP,           /* once in the end of `ceu_stop`  
    CEU_CALLBACK_STEP,           /* on every iteration of `ceu_loop`  
    CEU_CALLBACK_ABORT,          /* whenever an error occurs  
    CEU_CALLBACK_LOG,            /* on error and debugging messages  
    CEU_CALLBACK_TERMINATING,    /* once after executing the last statement  
    CEU_CALLBACK_ASYNC_PENDING,  /* whenever there's a pending "async" block  
    CEU_CALLBACK_THREAD_TERMINATING, /* whenever a thread terminates  
    CEU_CALLBACK_ISR_ENABLE,     /* whenever interrupts should be enabled/disabled  
    CEU_CALLBACK_ISR_ATTACH,     /* whenever an "async/isr" starts  
    CEU_CALLBACK_ISR_DETACH,     /* whenever an "async/isr" is aborted  
    CEU_CALLBACK_ISR_EMIT,       /* whenever an "async/isr" emits an innput  
    CEU_CALLBACK_WCLOCK_MIN,     /* whenever a next minimum timer is required
```

```

        CEU_CALLBACK_WCLOCK_DT,          /* whenever the elapsed time is requested
        CEU_CALLBACK_OUTPUT,            /* whenever an output is emitted
        CEU_CALLBACK_REALLOC,           /* whenever memory is allocated/deallocated
};

```

TODO: payloads

Céu invokes the registered callbacks in reverse register order, one after the other, stopping when a callback returns that it handled the request.

A callback is composed of a function handler and a pointer to the next callback:

```

typedef struct tceu_callback {
    tceu_callback_f    f;
    struct tceu_callback* nxt;
} tceu_callback;

```

A handler expects a request identifier with two arguments, as well as runtime trace information (e.g., file name and line number of the request):

```

typedef int (*tceu_callback_f) (int, tceu_callback_val, tceu_callback_val, tceu_trace);

```

An argument has one of the following types:

```

typedef union tceu_callback_val {
    void* ptr;
    s32  num;
    usize size;
} tceu_callback_val;

```

A handler returns whether it handled the request or not (return type `int`).

Depending on the request, the handler must also assign a return value to the global `ceu_callback_ret`:

```

static tceu_callback_val ceu_callback_ret;

```

## Example

Suppose the environment supports the events that follow:

```

input  int I;
output int O;

```

The `main.c` implements an event loop to sense occurrences of `I` and a callback to handle occurrences of `O`:

```

#include "types.h"          // as illustrated above in "Types"

int ceu_is_running;        // detects program termination

int ceu_callback_main (int cmd, tceu_callback_val p1, tceu_callback_val p2, tceu_trace trace)

```

```

{
    int is_handled = 0;
    switch (cmd) {
        case CEU_CALLBACK_TERMINATING:
            ceu_is_running = 0;
            is_handled = 1;
            break;
        case CEU_CALLBACK_OUTPUT:
            if (p1.num == CEU_OUTPUT_0) {
                printf("output 0 has been emitted with %d\n", p2.num);
                is_handled = 1;
            }
            break;
    }
    return ret;
}

int main (int argc, char* argv[])
{
    ceu_is_running = 1;
    tceu_callback cb = { &ceu_callback_main, NULL };
    ceu_start(&cb, argc, argv);

    while (ceu_is_running) {
        if (<call-to-detect-if-A-occurred>()) {
            int v = <argument-to-A>;
            ceu_input(CEU_INPUT_A, &v);
        }
        ceu_input(CEU_INPUT__ASYNC, NULL);
    }

    ceu_stop();
}

```

## Syntax

### Syntax

Follows the complete syntax of Céu in a BNF-like syntax:

- **A** : non terminal (starting in uppercase)
- **a** : terminal (in bold and lowercase)
- **'** : terminal (non-alphanumeric characters)
- **A ::= ...** : defines A as ...

- $x\ y$  :  $x$  in sequence with  $y$
- $x|y$  :  $x$  or  $y$
- $\{x\}$  : zero or more  $x$ s
- $[x]$  : optional  $x$
- $LIST(x)$  : expands to  $x\ {'\ '}\ x\ {'\ '}$
- $(\dots)$  : groups  $\dots$
- $\langle \dots \rangle$  : special informal rule

Program ::= Block

Block ::= {Stmt `;`}

Stmt ::= nothing

/\* Blocks \*/

// Do ::=

| do [(`/`ID\_int|`\_`)] [(`/` LIST(ID\_int)) `)`]  
Block

end

| escape [(`/`ID\_int] [Exp]

/\* pre (top level) execution \*/

| pre do

Block

end

/\* Storage Entities / Declarations \*/

// Dcls ::=

| var [(`/`|`&?`)] [(`/` [Exp [(`/`]] `)` [(`/`dynamic|`/`nohold`] Type ID\_int [(`/` Sources]  
| pool [(`/`&`] [(`/` [Exp] `)` Type ID\_int [(`/` Sources]  
| event [(`/`&`] (Type | [(`/` LIST(Type) `)`]) ID\_int [(`/` Sources]

| input (Type | [(`/` LIST(Type) `)`]) ID\_ext

| output (Type | [(`/` LIST([(`/`&`] Type [ID\_int]) `)`]) ID\_ext  
[ do Block end ]

/\* Event Handling \*/

// Await ::=

| await (ID\_ext | Loc) [until Exp]

| await (WCLOCKK|WCLOCKE)

//

| await (FOREVER | pause | resume)

// Emit\_Ext ::=

```

| emit ID_ext [ `( ` [LIST(Exp|`_`) ] ` ) ` ]
| emit (WCLOCKK|WCLOCKE)
//
| emit Loc [ `( ` [LIST(Exp|`_`) ] ` ) ` ]

| lock Loc do
    Block
end

/* Conditional */

| if Exp then
    Block
{ else/if Exp then
    Block }
[ else
    Block ]
end

/* Loops */

/* simple */
| loop [ `/ `Exp ] do
    Block
end

/* numeric iterator */
| loop [ `/ `Exp ] (ID_int|`_`) in [Range] do
    Block
end
// where
Range ::= ( `[ ` | ` ] ` )
          ( ( Exp `->` (Exp|`_`) )
            | ((Exp|`_`) `<-` Exp ) )
          ( `[ ` | ` ] ` ) [ `, ` Exp ]

/* pool iterator */
| loop [ `/ `Exp ] (ID_int|`_`) in Loc do
    Block
end

/* event iterator */
| every [(Loc | `( ` [LIST(Loc|`_`) ] ` ) ` ) in] (ID_ext|Loc|WCLOCKK|WCLOCKE) do
    Block
end

```

```

    | break [``ID_int]
    | continue [``ID_int]

/* Parallel Compositions */

/* parallels */
| (par | par/and | par/or) do
    Block
with
    Block
{ with
    Block }
end

/* watching */
// Watching ::=
| watching LIST(ID_ext|Loc|WCLOCKK|WCLOCKE|Abs_Cons) do
    Block
end

/* block spawn */
| spawn [`` [LIST(ID_int)] ``] do
    Block
end

/* Exceptions */

| throw Exp
| catch LIST(Loc) do
    Block
end

/* Pause */

| pause/if (Loc|ID_ext) do
    Block
end

/* Asynchronous Execution */

| await async [ `` [LIST(Var) ``] ] do
    Block
end

// Thread ::=
| await async/thread [ `` [LIST(Var) ``] ] do

```

```

        Block
    end

| spawn async/isr `[ LIST(Exp) `] [ `( LIST(Var) `) ` ] do
    Block
end

/* synchronization */
| atomic do
    Block
end

/* C integration */

| native [/(pure|const|nohold|plain)] `( LIST(ID_nat) `) `
| native [/(pre|pos) do
    <code definitions in C>
end
| native `/ end
| `{ {<code in C> | `@` ( `(Exp)` |Exp) } `} ` /* `@@` escapes to `@` */

// Nat_Call ::=
| [call] Exp

/* finalization */
| do [Stmt] Finalize
| var [ `&` | `&?` ] Type ID_int `= `&` (Nat_Call | Code_Call) Finalize
// where
    Finalize ::= finalize [ `( LIST(Loc) `) ` ] with
        Block
        [ pause with Block ]
        [ resume with Block ]
    end

/* Lua integration */

// Lua_State ::=
| lua `[ [Exp] `] ` do
    Block
end

// Lua_Stmts ::=
| `[ {`= `} `[
    { {<code in Lua> | `@` ( `(Exp)` |Exp) } } /* `@@` escapes to `@` */
    `] ` {`= `} `] `

/* Abstractions */

```

```

/* Data */

| data ID_abs [as (nothing|Exp)] [ with
    Dcls `;` { Dcls `;` }
end ]

/* Code */

// Code_Tight ::=
| code/tight Mods ID_abs `( Params `)` `->` Type

// Code_Await ::=
| code/await Mods ID_abs `( Params `)`
    [ `->` `( Params `)` ]
    `->` (Type | NEVER)
    [ throws LIST(ID_abs) ]

// where
    Params ::= none | LIST(Dcls)

/* code implementation */
| (Code_Tight | Code_Await) do
    Block
end

/* code invocation */

// Code_Call ::=
| call Mods Abs_Cons

// Code_Await ::=
| await Mods Abs_Cons

// Code_Spawn ::=
| spawn Mods Abs_Cons [in Loc]
| kill Loc [ `( Exp `)` ]

// where
    Mods ::= [ `/`dynamic | `/static ] [ `/recursive ]
    Abs_Cons ::= [ Loc `.` ] ID_abs `( LIST(Data_Cons|Vec_Cons|Exp|`_`) `)`

/* Assignments */

| (Loc | `( LIST(Loc|`_`) `)) `=` Sources
// where
    Sources ::= ( Do

```



```

        | Emit_Ext
        | Await
        | Watching
        | Thread
        | Lua_Stmts
        | Code_Await
        | Code_Spawn
        | Vec_Cons
        | Data_Cons
        | Exp
        | `.` `)`
Vec_Cons ::= (Loc | Exp) Vec_Concat { Vec_Concat }
        | `[` [LIST(Exp)] `]` { Vec_Concat }
        // where
        Vec_Concat ::= `..` (Exp | Lua_Stmts | `[` [LIST(Exp)] `]`)
Data_Cons ::= (val|new) Abs_Cons

/* Identifiers */

ID      ::= [a-zA-Z0-9_]+
ID_int  ::= ID           // ID beginning with lowercase
ID_ext  ::= ID           // ID all in uppercase, not beginning with digit
ID_abs  ::= ID {`.` ID}  // IDs beginning with uppercase, containing at least one lower
ID_field ::= ID          // ID not beginning with digit
ID_nat  ::= ID           // ID beginning with underscore
ID_type ::= ( ID_nat | ID_abs
        | none
        | bool | on/off | yes/no
        | byte
        | r32 | r64 | real
        | s8 | s16 | s32 | s64
        | u8 | u16 | u32 | u64
        | int | uint | integer
        | ssize | usize )

/* Types */

Type ::= ID_type { `&&` } [ `?` ]

/* Wall-clock values */

WCLOCKK ::= [NUM h] [NUM min] [NUM s] [NUM ms] [NUM us]
WCLOCKE ::= `(` Exp `)` (h|min|s|ms|us)

/* Literals */

```

```

NUM ::= [0-9] ([0-9] | [xX] | [A-F] | [a-f] | \.)* // regex
STR ::= " [^\n]* " // regex

/* Expressions */

Exp ::= NUM | STR | null | true | false | on | off | yes | no
      | `(` Exp `)`
      | Exp <binop> Exp
      | <unop> Exp
      | Exp `:` | `.` (ID_int|ID_nat)
      | Exp `(?!)`
      | Exp `[` Exp `]`
      | Exp `(` [ LIST(Exp) ] `)`
      | Exp is Type
      | Exp as Type
      | Exp as `/(nohold|plain|pure)`
      | sizeof `( (Type|Exp) )`
      | Nat_Call | Code_Call
      | ID_int
      | ID_nat
      | outer

/* Locations */

Loc ::= Loc [as (Type | `/(nohold|plain|pure))`] `)`
      | `[*|`$`] Loc
      | Loc { `[Exp`] | `:` | `.` (ID_int|ID_nat) | `!` }
      | ID_int
      | ID_nat
      | outer
      | `{` <code in C> `}`
      | `( Loc )`

/* Operator Precedence */

/* lowest priority */

// locations
*      $
:      .      !      []
as

// expressions
is      as // binops
or
and

```

```

!=      ==      <=      >=      <      >
|
^
&
<<      >>
+      -
*      /      %
not      +      -      ~      $$      $      *      &&      &      // unops
:      .      !      ?      (      []

/* highest priority */

/* Other */

// single-line comment

/** nested
    /* multi-line */
    comments */

# preprocessor directive

TODO: statements that do not require ;

```

## License

### License

Céu is distributed under the MIT license reproduced below:

Copyright (C) 2012-2017 Francisco Sant'Anna

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE

AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.