

**I DON'T ALWAYS CODE IN  
PYTHON**

**BUT WHEN I DO, MY  
DOCSTRINGS ARE  
GLORIOUS**

# Python Computing for Scientific Research:

## Monday 2-5pm (65 Evans; AY 250; 06082)

### Schedule

Date	Content	Leader
Aug 27	Advanced Python Language Concepts (geared towards Boot Camp graduates)	Josh
Sep 3	holiday	
Sep 10	(matplotlib) Advanced plotting and data vizualization, mayavi	Fernando
Sep 17	Advanced versioning, application building (optparse), debugging & testing	Isaac
Sep 24	scipy, numpy, stats	Josh/Joey
Oct 1	scikits: image, learn	Joey/Berian
Oct 8	interacting with the world (xml-rpc, urllib, sending and receiving email, serial)	Isaac
Oct 15	database interaction, large datasets (HDF5)	Josh/Erik
Oct 22	GUI (Tkinter, GTK, Traits)	Josh
Oct 29	parallelization (ipython), cuda	Fernando/Paul
Nov 5	web-frameworks (CGI), Flask/Bottle	Josh
Nov 12	holiday	
Nov 19	Symbolic, mathematical and Bayesian programming: simpy, sage, R, rpy2, pyMC/emc	Berian/Joey
Nov 26	cython; wrapper around legacy code – FORTRAN, C, etc	Erik
Onward	final project work	

preliminary schedule

8:15 - 8:45 homework review (optional)

8:45 - 9:45 Advanced Strings & File IO

- string methods + formatting
- regex
- read/write (writelines)
- subprocess
- StringIO

9:45-10:10 breakout

10:10 - 10:55 Advanced Stuff

- lambda functions
- filter, map, reduce, zip
- try/except/finally
- exec, eval

10:55 - 11:20 breakout

11:20 - 12:20

Object oriented programming

- classes
- methods
- instances

12:20 - 1:05 pm lunch/breakout

1:05 -2:00 OOP (II)

- special methods (init, del, str, ...)
- with
- exception classes
- sub-classing and inheritance
- yield

2-2:40 breakout

2:40 - 3:40 Development w/ git

3:40 - 4:10 breakout

4:10 - start homework

# Advanced Strings & File I/O



# Strings can do operations on themselves:

`.lower(), .upper(), .capitalize()`

```
>>> "funKY tOwn".capitalize()
'Funky town'
>>> "funky tOwn".lower()
'funky town'
```

`.split([sep [,maxsplit]])`

```
>>> "funKY tOwn".split()
['funKY', 'tOwn']
>>> "funKY tOwn".capitalize().split()
['Funky', 'town']
>>> [x.capitalize() for x in "funKY tOwn".split()]
['Funky', 'Town']
>>> "I want to take you to, funKY tOwn".split("u")
['I want to take yo', ' to, f', 'nKY tOwn']
>>> "I want to take you to, funKY tOwn".split("you")
['I want to take ', ' to, funKY tOwn']
```

# **.strip(), .join(), .replace()**

```
>>> csv_string = 'Dog,Cat,Spam,Defenestrate,1, 3.1415 \n\t'
>>> csv_string.strip()
'Dog,Cat,Spam,Defenestrate,1, 3.1415'
>>> clean_list = [x.strip() for x in csv_string.split(",")]
>>> clean_list
['Dog', 'Cat', 'Spam', 'Defenestrate', '1', '3.1415']
```

**.join()** allows you to glue a list of strings together with a certain string

```
>>> print ",".join(clean_list)
'Dog,Cat,Spam,Defenestrate,1,3.1415'
>>> print "\t".join(clean_list)
Dog Cat SpamDefenestrate 1 3.1415
```

**.replace()** strings in strings

```
>>> csv_string = 'Dog,Cat,Spam,Defenestrate,1, 3.1415 \n\t'
>>> alt_csv = csv_string.strip().replace(' ','')
>>> alt_csv
'Dog,Cat,Spam,Defenestrate,1,3.1415'
>>> print csv_string.strip().replace(' ','').replace(',','\t')
Dog Cat SpamDefenestrate 1 3.1415
```



# `.find()`

*incredibly useful searching,  
returning the index of the search*

```
>>> s = 'My Funny Valentine'
>>> s.find("y")
1
>>> s.find("y",2)
7
>>> s[s.find("Funny"):]
'Funny Valentine'
>>> s.find("z")
-1
>>> ss = [s,"Argentine","American","Quarentine"]
>>> for thestring in ss:
    if thestring.find("tine") != -1:
        print "'" + str(thestring) + "' contains 'tine'."

'My Funny Valentine' contains 'tine'.
'Argentine' contains 'tine'.
'Quarentine' contains 'tine'.
>>>
```

# string module

*exposes useful variables and functions*

```
>>> import string
>>> string.swapcase("fUNKY tOWN")
'Funky Town'
>>> string.ascii_letters
'abcdefghijklmnopqrstuvwxyzABCDEFGHIJKLMNOPQRSTUVWXYZ '
>>> string.digits
'0123456789'
```

## file: checkemail.py

```
import string
## let's only allow .com, .edu, and .org email domains
allowed_domains = ["com","edu","org"]
## let's nix all the possible bad characters
disallowed = string.punctuation.replace(".", "")
while True:
    res = raw_input("Enter your full email address: ")
    res = res.strip()    # get rid of extra spaces from a key-happy user
    if res.count("@") != 1:
        print "missing @ sign or too many @ signs"
        continue
    username, domain = res.split("@")

    ## let's look at the domain
    if domain.find(".") == -1:
        print "invalid domain name"
        continue
    if domain.split(".")[-1] not in allowed_domains:
        ## does this end as it should?
        print "invalid top-level domain...must be in " + ",".join(allowed_domains)
        continue
    goodtogo = True
    for s in domain:
        if s in disallowed:
            print "invalid character " + s
            ## cannot use continue here because then we only continue the for loop, not the while loop
            goodtogo = False

    ## if we're here then we're good on domain. Make sure that
    for s in username:
        if s in disallowed:
            print "invalid character " + s
            goodtogo = False

    if goodtogo:
        print "valid email. Thank you."
        break
```



## *example: check email address*

```
BootCamp> python checkemail.py
Enter your full email address: josh.python.org
missing @ sign or too many @ signs
Enter your full email address: josh@pythonorg
invalid domain name
Enter your full email address: joshrocks!@python,.org
invalid character ,
invalid character !
Enter your full email address: joshrocks@python.org
valid email. Thank you.
BootCamp>
```

# String Formatting

casting using `str()` is very limited  
Python gives access to C-like string formatting

usage: “%(format)” % (variable)

```
>>> print "My favorite integer is %i and my favorite float is %f,\n" \
      " which to three decimal places is %.3f and in exponential form is %e" \
      % (3,math.pi,math.pi,math.pi)
My favorite integer is 3 and my favorite float is 3.141593,
which to three decimal places is 3.142 and in exponential form is 3.141593e+00
```

common formats:

f (float), i (integer), s (string), g (nicely formatting floats)

<http://docs.python.org/release/2.7.2/library/stdtypes.html#string-formatting-operations>

# String Formatting

`%` escapes “%”

```
>>> print "I promise to give 100%% effort whenever asked of %s." % ("me")
I promise to give 100% effort whenever asked of me.
```

`+` and zero-padding

```
>>> print "%f\n%f\n%f\n%010f\n%10s" %
(math.pi,math.pi,-1.0*math.pi,math.pi,"pi")
3.141593
+3.141593
-3.141593
003.141593
      pi
```

# String Formatting

the (new) preferred way  
is *string*.format(value0,value1,...)

```
>>> 'on {0}, I feel {1}'.format("saturday","groovy")
'on saturday, I feel groovy'
>>> 'on {}, I feel {}'.format("saturday","groovy")
'on saturday, I feel groovy'
>>> 'on {0}, I feel {1}'.format(["saturday","groovy"])
IndexError: tuple index out of range
>>> 'on {0}, I feel {0}'.format(["saturday","groovy"])
'on ['saturday', 'groovy'], I feel ['saturday', 'groovy']"
>>> 'on {0}, I feel {0}'.format("saturday","groovy")
'on saturday, I feel saturday'
```

## you can assign by argument position

```
>>> '{desire} to {place}'.format(desire='Fly me',place='The Moon')
'Fly me to The Moon'
>>> '{desire} to {place} or else I wont visit {place}.'.format(desire='Fly
me',place='The Moon')
'Fly me to The Moon or else I wont visit The Moon.'
>>> f = {"desire": "I want to take you", "place": "funky town"}
>>> '{desire} to {place}'.format(**f)
'I want to take you to funky town'
```

## or by name

# Formatting comes after a colon (:

```
>>> ("%03.2f" % 3.14159) == "{:03.2f}".format(3.14159)
True
>>> "{0:03.2f}".format(3.14159,42)
'3.14'
>>> "{1:03.2f}".format(3.14159,42)
'42.00'
>>> # format also supports binary numbers
>>> "int: {0:d}; hex: {0:x}; oct: {0:o}; bin: {0:b}".format(42)
'int: 42; hex: 2a; oct: 52; bin: 101010'
```

<b>format_spec</b>	::=	[ [ <u>fill</u> ] <u>align</u> ] [ <u>sign</u> ] [ # ] [ 0 ] [ <u>width</u> ] [ , ] [ . <u>precision</u> ] [ <u>type</u> ]
<b>fill</b>	::=	<a character other than '}'>
<b>align</b>	::=	"<"   ">"   "="   "^"
<b>sign</b>	::=	"+"   "-"   " "
<b>width</b>	::=	<u>integer</u>
<b>precision</b>	::=	<u>integer</u>
<b>type</b>	::=	"b"   "c"   "d"   "e"   "E"   "f"   "F"   "g"   "G"   "n"   "o"   "s"   "x"   "X"

```
>>> "{:*^11}".format(" meh ")
'*** meh ***'
>>> "{:*<11}".format(" meh ")
' meh ***'
>>> "{:*>11}".format(" meh ")
'***** meh '
>>> "{:>11.2}".format(3.1415)
'          3.1'
```

# Regular Expressions

complex string that defines search

`import re`

```
>>> import re
>>> emailsearch = re.compile(r"[a-z0-9!#$%&'*/+=?^_`{|}~-]+(?:\.[a-z0-9!#$%&'*/+=?^_`{|}~-]+)*@(?:[a-z0-9](?:[a-z0-9-]*[a-z0-9])?\.)+[a-z0-9](?:[a-z0-9-]*[a-z0-9])?")
>>> emailsearch.findall("jbloom@python.org")
['jbloom@python.org']
>>> emailsearch.findall("jbloom@python!org")
```

FYI...

```
>>> visacard = re.compile("4\d{3}[\s-]?\d{4}[\s-]?\d{4}[\s-]?\d{4}")
>>> mastercard= re.compile("5[1-5]\d{2}[\s-]?\d{4}[\s-]?\d{4}[\s-]?\d{4}")
```

[http://diveintopython.org/regular\\_expressions](http://diveintopython.org/regular_expressions)



# File I/O (read/write)

`.open()` and `.close()` are builtin functions

```
>> file_stream = open("mydata.dat","r")
>> <type 'file'>
>> file_stream.close()
```

open modes: “*r*” (read), “*w*” (write), “*r+*” (read + update),  
“*rb*” (read as a binary stream, ...)

Writing data: `.write()` or `.writelines()`

```
>>> f= open("test.dat","w")
>>> f.write("This is my first file I/O. Zing!")
>>> f.close()
>>> import os ; os.system("cat %s" % "test.dat")
This is my first file I/O. Zing!0
```

```
>>> f= open("test.dat","w")
>>> f.writelines(["This is my first file I/O.\n","Take that Dr. Zing!\n"])
>>> f.close() ; os.system("cat %s" % "test.dat")
This is my first file I/O.
Take that Dr. Zing!
0
```

Likewise, there is `.readlines()` and `.read()`

```
>>> f= open("test.dat","r")
>>> data = f.readlines()
>>> f.close() ; print data
This is my first file I/O.
Take that Dr. Zing!
>>>
```

## file: tabbify\_my\_csv.py

```
"""
small copy program that turns a csv file into a tabbed file
"""

import os

def tabbify(infilename,outfilename,ignore_comments=True,comment_chars="#;/"):
    """
    INPUT: infilename
    OUTPUT: creates a file called outfilename
    """
    if not os.path.exists(infilename):
        return # do nothing if the file isn't there
    f = open(infilename,"r")
    o = open(outfilename,"w")
    inlines = f.readlines() ; f.close()
    outlines = []
    for l in inlines:
        if ignore_comments and (l[0] in comment_chars):
            outlines.append(l)
        else:
            outlines.append(l.replace(",","\t"))
    o.writelines(outlines) ; o.close()
```

```
BootCamp> cat google_share_price.csv
# Date,Open,High,Low,Close,Volume,Adj Close
2008-10-14,393.53,394.50,357.00,362.71,7784800,362.71
...
BootCamp> cat google_share_price.tab
# Date,Open,High,Low,Close,Volume,Adj Close
2008-10-14      393.53   394.50   357.00   362.71   7784800 362.71
....
```

# File I/O (read/write)

`shutil` module is preferred for copying, archiving & removing files/directories

<http://docs.python.org/library/shutil.html#module-shutil>

`tempfile` module is used for the creation of temporary directories and files

```
>>> import tempfile
>>> tmp = tempfile.TemporaryFile() ; type(tmp)
<type 'file'>
>>> tmp = tempfile.NamedTemporaryFile(suffix=".csv",\
                                     prefix="boot",dir="/tmp",delete=False)

>>> tmp.name
'/tmp/bootG2zoE8.csv'
>>> tmp.write("# stock phrases of today's youth\nWassup?!,OMG,LOL,BRB,Python\n")
>>> tmp.close() ; import os ; os.system("cat %s" % tmp.name)
# stock phrases of today's youth
Wassup?!,OMG,LOL,BRB,Python
0
```

<http://www.doughellmann.com/PyMOTW/tempfile/>

# StringIO module

handy for making file-like objects out of strings

```
>>> import StringIO
>>> myfile = StringIO.StringIO( \
    "# stock phrases of today's youth\nWassup?!,OMG,LOL,BRB,Python\n")
>>> myfile.getvalue() ## get what we just wrote
"# stock phrases of today's youth\nWassup?!,OMG,LOL,BRB,Python\n"
>>> myfile.seek(0)      ## go back to the beginning
>>> myfile.readlines()
["# stock phrases of today's youth\n", 'Wassup?!,OMG,LOL,BRB,Python\n']
>>> myfile.close()
>>> myfile.write("not gonna happen")
ValueError: I/O operation on closed file
>>> myfile = StringIO.StringIO("# stock phrases of today's youth
\nWassup?!,OMG,LOL,BRB,Python\n")
>>> myfile.seek(2) ; myfile.write("silly") ; myfile.seek(0)
>>> myfile.readlines()
["# silly phrases of today's youth\n", 'Wassup?!,OMG,LOL,BRB,Python\n']
```

(**cStringIO** is actually faster but doesn't work on some platforms)

# subprocess module

subprocess is the preferred way to interact with other programs, as you might do on the command line

```
>>> from subprocess import *
>>> p = Popen("ls", shell=True, stdout=PIPE) # list the directory
>>> p.pid # get the process ID of the new subprocess
12121
>>> print p.stdout.readlines()
['Archive.zip\n', 'Day1BreakoutSolutions\n', 'Day1Files\n', 'LecturePDFs\n',
'Object_Oriented_I.key\n',...]
>>> p = Popen("spamalot", shell=True, stdout=PIPE,stderr=PIPE)
>>> print p.stderr.readlines()
['/bin/sh: spamalot: command not found\n']
```

it's often advisable to wait until the subprocess has finished

```
>>> # this returns immediately
>>> p = Popen("find .. -name '*.py'", shell=True, stdout=PIPE,stderr=PIPE)
>>> os.waitpid(p.pid, 0) ## this will block until the search is done
['../py4science/examples/pyrex/trailstats/setup.py\n',
'../py4science/examples/qsort.py\n',
'../py4science/examples/quad_newton.py\n']
```

<http://docs.python.org/library/subprocess.html>



# Breakout Work

build a command-line utility file which copies the input file to another file and:

1. reverses the ending of the file name  
e.g. *josh.dat* is copied to *josh.tad*
2. deletes every other line
3. changes every occurrence of the words:  
love → hate, not → is, is → not
4. sets every number to half its original value  
e.g. *I like 3.14 and you like 2*  
→ *I like 1.57 and you like 1*
5. count the number of words "astrology" and "physics"  
try it on the file *elie.info*