Scan Report

January 26, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone "Coordinated Universal Time", which is abbreviated "UTC". The task was " hgdfdghgdgd". The scan started at Mon Jan 26 01:47:47 2026 UTC and ended at Mon Jan 26 14:04:13 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1 Result Overview **2**

2 Results per Host **2**

2.1 172.30.2.2 2

2.1.1 High 22/tcp 2

2.1.2 Medium 22/tcp 8

2.1.3 Medium 21/tcp 23

2.1.4 Medium 80/tcp 25

2.1.5 Low 22/tcp 33

2.1.6 Low general/tcp 37

2.1.7 Low 80/tcp 38

2.1.8 Low general/icmp 40

2.1.9 Log general/CPE-T 41

2.1.10 Log 22/tcp 41

2.1.11 Log general/tcp 46

2.1.12 Log 21/tcp 50

2.1.13 Log 80/tcp 52

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
172.30.2.2 proftpd-vuln.trabalho_vulnnet	0	3	16	6	23	0
Total: 1	0	3	16	6	23	0

Vendor security updates are not trusted.
Overrides are off. Even when a result has an override, this report uses the actual threat of the result.
Information on overrides is included in the report.
Notes are included in the report.
This report might not show details of all issues that were found.
Issues with the threat level "Critical" are not shown.
Issues with the threat level "Debug" are not shown.

This report contains all 48 results selected by the filtering described above. Before filtering there were 5586 results.

2 Results per Host

2.1 172.30.2.2

Host scan start	Mon Jan 26 07:19:16 2026 UTC
Host scan end	Mon Jan 26 09:14:27 2026 UTC

Service (Port)	Threat Level
22/tcp	High
22/tcp	Medium
21/tcp	Medium
80/tcp	Medium
22/tcp	Low
general/tcp	Low
80/tcp	Low
general/icmp	Low
general/CPE-T	Log
22/tcp	Log
general/tcp	Log
21/tcp	Log
80/tcp	Log

2.1.1 High 22/tcp

High (CVSS: 7.5)
NVT: Diffie-Hellman Ephemeral Key Exchange DoS Vulnerability (SSH, D(HE)ater)

Product detection result

```
cpe:/a:ietf:secure_shell_protocol
Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565
↪)
```

Summary

The remote SSH server is supporting Diffie-Hellman ephemeral (DHE) Key Exchange (KEX) algorithms and thus could be prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
The remote SSH server supports the following DHE KEX algorithm(s):
diffie-hellman-group14-sha256
diffie-hellman-group16-sha512
diffie-hellman-group18-sha512
diffie-hellman-group-exchange-sha256
```

Impact

This vulnerability allows remote attackers (from the client side) to send arbitrary numbers that are actually not public keys, and trigger expensive server-side DHE modular-exponentiation calculations, also known as a D(HE)ater attack.
There could be an increase in CPU usage in the affected component. For OpenSSH, users may observe issues such as a slowdown in SSH connections.

Solution:
Solution type: Mitigation
- DHE key exchange should be disabled if no other mitigation mechanism can be used and either elliptic-curve variant of Diffie-Hellman (ECDHE) or RSA key exchange is supported by the clients. The fact that RSA key exchange is not forward secret should be considered.
- Limit the maximum number of concurrent connections in e.g. the configuration of the remote server. For OpenSSH this limit can be configured via the 'MaxStartups' option, for other products please refer to the manual of the product in question on configuration possibilities.

Vulnerability Insight

- CVE-2002-20001: The Diffie-Hellman Key Agreement Protocol allows remote attackers (from the client side) to send arbitrary numbers that are actually not public keys, and trigger expensive server-side DHE modular-exponentiation calculations, aka a D(HE)ater attack. The client needs very little CPU resources and network bandwidth. The attack may be more disruptive in cases where a client can require a server to select its largest supported key size. The basic attack scenario is that the client must claim that it can only communicate with DHE, and the server must be configured to allow DHE.

. . . continues on next page . . .

. . . continued from previous page . . .

- CVE-2022-40735: The Diffie-Hellman Key Agreement Protocol allows use of long exponents that arguably make certain calculations unnecessarily expensive, because the 1996 van Oorschot and Wiener paper found that '(appropriately) short exponents' can be used when there are adequate subgroup constraints, and these short exponents can lead to less expensive calculations than for long exponents. This issue is different from CVE-2002-20001 because it is based on an observation about exponent size, rather than an observation about numbers that are not public keys. The specific situations in which calculation expense would constitute a server-side vulnerability depend on the protocol (e.g., TLS, SSH, or IKE) and the DHE implementation details. In general, there might be an availability concern because of server-side resource consumption from DHE modular-exponentiation calculations. Finally, it is possible for an attacker to exploit this vulnerability and CVE-2002-20001 together.
- CVE-2024-41996: Validating the order of the public keys in the Diffie-Hellman Key Agreement Protocol, when an approved safe prime is used, allows remote attackers (from the client side) to trigger unnecessarily expensive server-side DHE modular-exponentiation calculations. The client may cause asymmetric resource consumption. The basic attack scenario is that the client must claim that it can only communicate with DHE, and the server must be configured to allow DHE and validate the order of the public key.

Vulnerability Detection Method
Checks the supported KEX algorithms of the remote SSH server.
Details: `Diffie-Hellman Ephemeral Key Exchange DoS Vulnerability (SSH, D(HE)ater)`
OID:1.3.6.1.4.1.25623.1.0.117839
Version used: `2024-10-03T05:05:33Z`

Product Detection Result
Product: `cpe:/a:ietf:secure_shell_protocol`
Method: `SSH Protocol Algorithms Supported`
OID: 1.3.6.1.4.1.25623.1.0.105565)

References
`cve: CVE-2002-20001`
`cve: CVE-2022-40735`
`cve: CVE-2024-41996`
`url: https://dheatattack.gitlab.io/`
`url: https://dheatattack.gitlab.io/details/`
`url: https://www.researchgate.net/profile/Anton-Stiglic-2/publication/2401745_Se`
`↪curity_Issues_in_the_Diffie-Hellman_Key_Agreement_Protocol`
`url: https://github.com/Balasys/dheater`
`url: https://github.com/c0r0n3r/dheater`
`cert-bund: WID-SEC-2024-3056`
`cert-bund: WID-SEC-2023-1886`
`cert-bund: WID-SEC-2023-1352`
`cert-bund: WID-SEC-2022-2251`
`cert-bund: WID-SEC-2022-2000`
`cert-bund: CB-K22/0224`
`cert-bund: CB-K21/1276`

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2025-3324
dfn-cert: DFN-CERT-2024-2847
dfn-cert: DFN-CERT-2024-2578
dfn-cert: DFN-CERT-2024-1671
dfn-cert: DFN-CERT-2023-1697
dfn-cert: DFN-CERT-2023-1332
dfn-cert: DFN-CERT-2022-2147
dfn-cert: DFN-CERT-2022-0437
dfn-cert: DFN-CERT-2021-2622
```

High (CVSS: 7.4)
NVT: OpenBSD OpenSSH <= 8.6 Command Injection Vulnerability

Product detection result

```
cpe:/a:openbsd:openssh:8.4p1
Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)
```

Summary

OpenBSD OpenSSH is prone to a command injection vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 8.4p1
Fixed version:     None
Installation
path / port:       22/tcp
```

Impact

Successful exploitation would allow an attacker to execute arbitrary code on the target machine.

Solution:

Solution type: WillNotFix

No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.

Affected Software/OS

OpenBSD OpenSSH through version 8.6 (initially reported for 8.3p1).

Vulnerability Insight

scp of OpenSSH allows command injection in spc.c via backtick characters in the destination argument.

. . . continues on next page . . .

. . . continued from previous page . . .

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `OpenBSD OpenSSH <= 8.6 Command Injection Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.113736
Version used: `2025-07-29T05:44:59Z`

Product Detection Result
Product: `cpe:/a:openbsd:openssh:8.4p1`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

References
```
cve: CVE-2020-15778
url: https://github.com/cpandya2909/CVE-2020-15778/
cert-bund: WID-SEC-2024-1082
cert-bund: WID-SEC-2023-1599
cert-bund: WID-SEC-2022-2413
cert-bund: WID-SEC-2022-1308
cert-bund: CB-K21/1268
dfn-cert: DFN-CERT-2024-1260
dfn-cert: DFN-CERT-2020-1691
```

High (CVSS: 7.0)
NVT: OpenSSH 6.2 <= 8.7 Privilege Escalation Vulnerability

Product detection result
```
cpe:/a:openbsd:openssh:8.4p1
Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)
```

Summary
OpenSSH is prone to a privilege scalation vulnerability in certain configurations.

Quality of Detection (QoD): 30%

Vulnerability Detection Result
```
Installed version: 8.4p1
Fixed version:     8.8
Installation
path / port:       22/tcp
```

Solution:
Solution type: VendorFix
Update to version 8.8 or later.

. . . continues on next page . . .

. . . continued from previous page . . .

Affected Software/OS
OpenSSH versions 6.2 through 8.7.

Vulnerability Insight
sshd failed to correctly initialise supplemental groups when executing an AuthorizedKeysCommand or AuthorizedPrincipalsCommand, where a AuthorizedKeysCommandUser or AuthorizedPrincipalsCommandUser directive has been set to run the command as a different user. Instead these commands would inherit the groups that sshd was started with.
Depending on system configuration, inherited groups may allow AuthorizedKeysCommand/AuthorizedPrincipalsCommand helper programs to gain unintended privilege.
Neither AuthorizedKeysCommand nor AuthorizedPrincipalsCommand are enabled by default in sshd_config.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `OpenSSH 6.2 <= 8.7 Privilege Escalation Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.117696
Version used: `2021-10-11T08:01:31Z`

Product Detection Result
Product: `cpe:/a:openbsd:openssh:8.4p1`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

References
`cve: CVE-2021-41617`
`url: https://www.openssh.com/txt/release-8.8`
`cert-bund: WID-SEC-2024-1082`
`cert-bund: WID-SEC-2023-1969`
`cert-bund: WID-SEC-2023-0426`
`cert-bund: WID-SEC-2022-1308`
`cert-bund: WID-SEC-2022-0676`
`cert-bund: WID-SEC-2022-0534`
`cert-bund: CB-K22/0310`
`cert-bund: CB-K22/0011`
`cert-bund: CB-K21/1268`
`cert-bund: CB-K21/1017`
`dfn-cert: DFN-CERT-2024-1260`
`dfn-cert: DFN-CERT-2024-0022`
`dfn-cert: DFN-CERT-2023-3218`
`dfn-cert: DFN-CERT-2023-3210`
`dfn-cert: DFN-CERT-2022-1571`
`dfn-cert: DFN-CERT-2022-0579`
`dfn-cert: DFN-CERT-2021-2586`
`dfn-cert: DFN-CERT-2021-2017`

. . . continues on next page . . .

. . . continued from previous page . . .

dfn-cert: DFN-CERT-2021-2015

[return to 172.30.2.2]

2.1.2 Medium 22/tcp

Medium (CVSS: 6.8)
NVT: OpenBSD OpenSSH 6.8p1 - 9.9p1 MitM Vulnerability

Product detection result
cpe:/a:openbsd:openssh:8.4p1
Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)

Summary
OpenBSD OpenSSH is prone to a man-in-the-middle (MitM) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 8.4p1
Fixed version:     9.9p2
Installation
path / port:       22/tcp
```

Solution:
Solution type: VendorFix
Update to version 9.9p2 or later.

Affected Software/OS
OpenBSD OpenSSH versions 6.8p1 through 9.9p1.

Vulnerability Insight
ssh(1) in OpenSSH contained a logic error that allowed an on-path attacker (a.k.a MITM) to impersonate any server when the VerifyHostKeyDNS option is enabled. This option is off by default.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: OpenBSD OpenSSH 6.8p1 - 9.9p1 MitM Vulnerability
OID:1.3.6.1.4.1.25623.1.0.114946
Version used: 2025-02-20T08:47:14Z

Product Detection Result

. . . continues on next page . . .

. . . continued from previous page . . .

Product: cpe:/a:openbsd:openssh:8.4p1
Method: OpenSSH Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.108577)

References

```
cve: CVE-2025-26465
url: https://www.openssh.com/txt/release-9.9p2
url: https://www.openssh.com/security.html
url: https://www.qualys.com/2025/02/18/openssh-mitm-dos.txt
url: https://blog.qualys.com/vulnerabilities-threat-research/2025/02/18/qualys-t
↪ru-discovers-two-vulnerabilities-in-openssh-cve-2025-26465-cve-2025-26466
url: https://www.openwall.com/lists/oss-security/2025/02/18/1
url: https://www.openwall.com/lists/oss-security/2025/02/18/4
cert-bund: WID-SEC-2025-1439
cert-bund: WID-SEC-2025-1007
cert-bund: WID-SEC-2025-0394
dfn-cert: DFN-CERT-2026-0097
dfn-cert: DFN-CERT-2025-1201
dfn-cert: DFN-CERT-2025-1200
dfn-cert: DFN-CERT-2025-0993
dfn-cert: DFN-CERT-2025-0819
dfn-cert: DFN-CERT-2025-0470
dfn-cert: DFN-CERT-2025-0428
```

Medium (CVSS: 4.0)
NVT: OpenBSD OpenSSH < 9.1 Multiple Vulnerabilities

Product detection result

```
cpe:/a:openbsd:openssh:8.4p1
Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)
```

Summary

OpenBSD OpenSSH is prone to multiple vulnerabilities.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 8.4p1
Fixed version:     9.1
Installation
path / port:       22/tcp
```

Solution:

Solution type: VendorFix

. . . continues on next page . . .

. . . continued from previous page . . .

Update to version 9.1 or later.

Affected Software/OS
OpenBSD OpenSSH prior to version 9.1.

Vulnerability Insight
The following vulnerabilities exist:
- A one-byte overflow in SSH- banner processing in ssh-keyscan.
- A double free() in error path of file hashing step in signing/verify code in ssh-keygen.
- A double-free in error path in ssh-keysign.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `OpenBSD OpenSSH < 9.1 Multiple Vulnerabilities`
OID:1.3.6.1.4.1.25623.1.0.127244
Version used: `2025-01-21T05:37:33Z`

Product Detection Result
Product: `cpe:/a:openbsd:openssh:8.4p1`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

References
`url: https://www.openssh.com/releasenotes.html#9.1`

Medium (CVSS: 5.0)
NVT: OpenBSD OpenSSH < 9.2 Unspecified Vulnerability

Product detection result
`cpe:/a:openbsd:openssh:8.4p1`
`Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)`

Summary
OpenBSD OpenSSH is prone to an unspecified vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result
```
Installed version: 8.4p1
Fixed version:     9.2
Installation
path / port:       22/tcp
```

. . . continues on next page . . .

. . . continued from previous page . . .

Solution:
Solution type: VendorFix
Update to version 9.2 or later.

Affected Software/OS
OpenBSD OpenSSH prior to version 9.2.

Vulnerability Insight
If the CanonicalizeHostname and CanonicalizePermittedCNAMEs options were enabled, and the system/libc resolver did not check that names in DNS responses were valid, then use of these options could allow an attacker with control of DNS to include invalid characters (possibly including wildcards) in names added to known_hosts files when they were updated. These names would still have to match the CanonicalizePermittedCNAMEs allow-list, so practical exploitation appears unlikely.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `OpenBSD OpenSSH < 9.2 Unspecified Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.104512
Version used: `2025-01-21T05:37:33Z`

Product Detection Result
Product: `cpe:/a:openbsd:openssh:8.4p1`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

References
`url: https://www.openssh.com/releasenotes.html#9.2`
`url: https://www.openwall.com/lists/oss-security/2023/02/02/3`

Medium (CVSS: 5.0)
NVT: OpenBSD OpenSSH < 9.3 Unspecified Vulnerability

Product detection result
`cpe:/a:openbsd:openssh:8.4p1`
`Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)`

Summary
OpenBSD OpenSSH is prone to an unspecified vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

. . . continues on next page . . .

. . . continued from previous page . . .

```
Installed version: 8.4p1
Fixed version:     9.3
Installation
path / port:       22/tcp
```

Solution:
Solution type: VendorFix
Update to version 9.3 or later.

Affected Software/OS
OpenBSD OpenSSH prior to version 9.3.

Vulnerability Insight
ssh(1): Portable OpenSSH provides an implementation of the getrrsetbyname(3) function if the standard library does not provide it, for use by the VerifyHostKeyDNS feature. A specifically crafted DNS response could cause this function to perform an out-of-bounds read of adjacent stack data, but this condition does not appear to be exploitable beyond denial-of-service to the ssh(1) client.
The getrrsetbyname(3) replacement is only included if the system's standard library lacks this function and portable OpenSSH was not compiled with the ldns library (–with-ldns). getrrsetbyname(3) is only invoked if using VerifyHostKeyDNS to fetch SSHFP records.This problem was found by the Coverity static analyzer.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `OpenBSD OpenSSH < 9.3 Unspecified Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.104635
Version used: `2025-01-21T05:37:33Z`

Product Detection Result
Product: `cpe:/a:openbsd:openssh:8.4p1`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

References
`url: https://www.openssh.com/releasenotes.html#9.3`
`url: https://www.openwall.com/lists/oss-security/2023/03/15/8`

Medium (CVSS: 6.5)
NVT: OpenBSD OpenSSH < 9.6 Multiple Vulnerabilities (Terrapin Attack)

Product detection result
`cpe:/a:openbsd:openssh:8.4p1`
`Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)`

. . . continues on next page . . .

. . . continued from previous page . . .

Summary
OpenBSD OpenSSH is prone to multiple vulnerabilities.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 8.4p1
Fixed version:     9.6
Installation
path / port:       22/tcp
```

Solution:
Solution type: VendorFix
Update to version 9.6 or later.
Note: Client and Server implementations need to run a fixed version to mitigate the Terrapin flaw.

Affected Software/OS
OpenBSD OpenSSH prior to version 9.6.

Vulnerability Insight
The following vulnerabilities exist:
- CVE-2023-48795: The SSH transport protocol with certain OpenSSH extensions allows remote attackers to bypass integrity checks such that some packets are omitted (from the extension negotiation message), and a client and server may consequently end up with a connection for which some security features have been downgraded or disabled, aka a 'Terrapin attack'.
- CVE-2023-51384: In ssh-agent certain destination constraints can be incompletely applied. When destination constraints are specified during addition of PKCS#11-hosted private keys, these constraints are only applied to the first key, even if a PKCS#11 token returns multiple keys.
- CVE-2023-51385: OS command injection might occur if a user name or host name has shell metacharacters, and this name is referenced by an expansion token in certain situations. For example, an untrusted Git repository can have a submodule with shell metacharacters in a user name or host name.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `OpenBSD OpenSSH < 9.6 Multiple Vulnerabilities (Terrapin Attack)`
OID:1.3.6.1.4.1.25623.1.0.118572
Version used: `2025-10-08T05:38:55Z`

Product Detection Result
Product: `cpe:/a:openbsd:openssh:8.4p1`
Method: `OpenSSH Detection Consolidation`

. . . continues on next page . . .

. . . continued from previous page . . .

OID: 1.3.6.1.4.1.25623.1.0.108577)

References

```
cve: CVE-2023-48795
cve: CVE-2023-51384
cve: CVE-2023-51385
url: https://www.openssh.com/txt/release-9.6
url: https://terrapin-attack.com
url: https://vin01.github.io/piptagole/ssh/security/openssh/libssh/remote-code-e
↪xecution/2023/12/20/openssh-proxycommand-libssh-rce.html
url: https://github.com/vin01/poc-proxycommand-vulnerable
cert-bund: WID-SEC-2025-0810
cert-bund: WID-SEC-2025-0168
cert-bund: WID-SEC-2025-0144
cert-bund: WID-SEC-2025-0139
cert-bund: WID-SEC-2024-3377
cert-bund: WID-SEC-2024-3320
cert-bund: WID-SEC-2024-3198
cert-bund: WID-SEC-2024-3195
cert-bund: WID-SEC-2024-3140
cert-bund: WID-SEC-2024-1913
cert-bund: WID-SEC-2024-1781
cert-bund: WID-SEC-2024-1701
cert-bund: WID-SEC-2024-1656
cert-bund: WID-SEC-2024-1655
cert-bund: WID-SEC-2024-1643
cert-bund: WID-SEC-2024-1642
cert-bund: WID-SEC-2024-1639
cert-bund: WID-SEC-2024-1637
cert-bund: WID-SEC-2024-1630
cert-bund: WID-SEC-2024-1474
cert-bund: WID-SEC-2024-1248
cert-bund: WID-SEC-2024-1228
cert-bund: WID-SEC-2024-1186
cert-bund: WID-SEC-2024-1082
cert-bund: WID-SEC-2024-0899
cert-bund: WID-SEC-2024-0892
cert-bund: WID-SEC-2024-0889
cert-bund: WID-SEC-2024-0885
cert-bund: WID-SEC-2024-0874
cert-bund: WID-SEC-2024-0869
cert-bund: WID-SEC-2024-0578
cert-bund: WID-SEC-2024-0564
cert-bund: WID-SEC-2024-0523
cert-bund: WID-SEC-2023-3182
cert-bund: WID-SEC-2023-3174
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2026-0097
dfn-cert: DFN-CERT-2025-3629
dfn-cert: DFN-CERT-2025-3272
dfn-cert: DFN-CERT-2025-2058
dfn-cert: DFN-CERT-2025-2037
dfn-cert: DFN-CERT-2025-1447
dfn-cert: DFN-CERT-2025-1177
dfn-cert: DFN-CERT-2025-1025
dfn-cert: DFN-CERT-2025-0660
dfn-cert: DFN-CERT-2025-0502
dfn-cert: DFN-CERT-2025-0294
dfn-cert: DFN-CERT-2025-0173
dfn-cert: DFN-CERT-2025-0165
dfn-cert: DFN-CERT-2025-0024
dfn-cert: DFN-CERT-2024-3171
dfn-cert: DFN-CERT-2024-2818
dfn-cert: DFN-CERT-2024-2759
dfn-cert: DFN-CERT-2024-2741
dfn-cert: DFN-CERT-2024-2682
dfn-cert: DFN-CERT-2024-2602
dfn-cert: DFN-CERT-2024-2573
dfn-cert: DFN-CERT-2024-2392
dfn-cert: DFN-CERT-2024-2210
dfn-cert: DFN-CERT-2024-2209
dfn-cert: DFN-CERT-2024-2194
dfn-cert: DFN-CERT-2024-2169
dfn-cert: DFN-CERT-2024-2048
dfn-cert: DFN-CERT-2024-2030
dfn-cert: DFN-CERT-2024-2028
dfn-cert: DFN-CERT-2024-1930
dfn-cert: DFN-CERT-2024-1895
dfn-cert: DFN-CERT-2024-1869
dfn-cert: DFN-CERT-2024-1868
dfn-cert: DFN-CERT-2024-1865
dfn-cert: DFN-CERT-2024-1862
dfn-cert: DFN-CERT-2024-1854
dfn-cert: DFN-CERT-2024-1846
dfn-cert: DFN-CERT-2024-1817
dfn-cert: DFN-CERT-2024-1794
dfn-cert: DFN-CERT-2024-1715
dfn-cert: DFN-CERT-2024-1698
dfn-cert: DFN-CERT-2024-1688
dfn-cert: DFN-CERT-2024-1655
dfn-cert: DFN-CERT-2024-1600
dfn-cert: DFN-CERT-2024-1443
dfn-cert: DFN-CERT-2024-1442
dfn-cert: DFN-CERT-2024-1413
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2024-1382
dfn-cert: DFN-CERT-2024-1380
dfn-cert: DFN-CERT-2024-1373
dfn-cert: DFN-CERT-2024-1260
dfn-cert: DFN-CERT-2024-1259
dfn-cert: DFN-CERT-2024-1108
dfn-cert: DFN-CERT-2024-1061
dfn-cert: DFN-CERT-2024-1029
dfn-cert: DFN-CERT-2024-1003
dfn-cert: DFN-CERT-2024-1000
dfn-cert: DFN-CERT-2024-0896
dfn-cert: DFN-CERT-2024-0779
dfn-cert: DFN-CERT-2024-0762
dfn-cert: DFN-CERT-2024-0744
dfn-cert: DFN-CERT-2024-0698
dfn-cert: DFN-CERT-2024-0633
dfn-cert: DFN-CERT-2024-0619
dfn-cert: DFN-CERT-2024-0618
dfn-cert: DFN-CERT-2024-0616
dfn-cert: DFN-CERT-2024-0597
dfn-cert: DFN-CERT-2024-0545
dfn-cert: DFN-CERT-2024-0526
dfn-cert: DFN-CERT-2024-0491
dfn-cert: DFN-CERT-2024-0480
dfn-cert: DFN-CERT-2024-0451
dfn-cert: DFN-CERT-2024-0440
dfn-cert: DFN-CERT-2024-0420
dfn-cert: DFN-CERT-2024-0388
dfn-cert: DFN-CERT-2024-0343
dfn-cert: DFN-CERT-2024-0306
dfn-cert: DFN-CERT-2024-0299
dfn-cert: DFN-CERT-2024-0285
dfn-cert: DFN-CERT-2024-0267
dfn-cert: DFN-CERT-2024-0251
dfn-cert: DFN-CERT-2024-0215
dfn-cert: DFN-CERT-2024-0211
dfn-cert: DFN-CERT-2024-0164
dfn-cert: DFN-CERT-2024-0154
dfn-cert: DFN-CERT-2024-0101
dfn-cert: DFN-CERT-2024-0092
dfn-cert: DFN-CERT-2024-0088
dfn-cert: DFN-CERT-2024-0067
dfn-cert: DFN-CERT-2024-0063
dfn-cert: DFN-CERT-2024-0062
dfn-cert: DFN-CERT-2024-0024
dfn-cert: DFN-CERT-2024-0022
dfn-cert: DFN-CERT-2024-0013
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2023-3219
dfn-cert: DFN-CERT-2023-3218
dfn-cert: DFN-CERT-2023-3210
dfn-cert: DFN-CERT-2023-3201
dfn-cert: DFN-CERT-2023-3200
dfn-cert: DFN-CERT-2023-3195
dfn-cert: DFN-CERT-2023-3193
dfn-cert: DFN-CERT-2023-3191
dfn-cert: DFN-CERT-2023-3185
dfn-cert: DFN-CERT-2023-3184
dfn-cert: DFN-CERT-2023-3183
dfn-cert: DFN-CERT-2023-3182
dfn-cert: DFN-CERT-2023-3175
```

Medium (CVSS: 5.3)
NVT: OpenSSH Information Disclosure Vulnerability (CVE-2016-20012)

Product detection result

```
cpe:/a:openbsd:openssh:8.4p1
Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)
```

Summary

OpenBSD OpenSSH is prone to an information disclosure vulnerability.

Quality of Detection (QoD): 50%

Vulnerability Detection Result

```
Installed version: 8.4p1
Fixed version:     None
Installation
path / port:       22/tcp
```

Solution:

Solution type: WillNotFix

No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.

Affected Software/OS

All currently OpenSSH versions are known to be affected.

Vulnerability Insight

. . . continues on next page . . .

. . . continued from previous page . . .

OpenSSH allows remote attackers, who have a suspicion that a certain combination of username and public key is known to an SSH server, to test whether this suspicion is correct. This occurs because a challenge is sent only when that combination could be valid for a login session.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `OpenSSH Information Disclosure Vulnerability (CVE-2016-20012)`
OID:1.3.6.1.4.1.25623.1.0.117777
Version used: `2022-11-24T10:18:54Z`

Product Detection Result
Product: `cpe:/a:openbsd:openssh:8.4p1`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

References
```
cve: CVE-2016-20012
url: https://github.com/openssh/openssh-portable/pull/270
url: https://rushter.com/blog/public-ssh-keys/
url: https://utcc.utoronto.ca/~cks/space/blog/tech/SSHKeysAreInfoLeak
cert-bund: WID-SEC-2024-1082
cert-bund: WID-SEC-2024-0229
cert-bund: CB-K21/0979
dfn-cert: DFN-CERT-2024-1260
```

Medium (CVSS: 5.9)
NVT: Prefix Truncation Attacks in SSH Specification (Terrapin Attack)

Product detection result
```
cpe:/a:ietf:secure_shell_protocol
Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565
↪)
```

Summary
The remote SSH server is supporting an specific encryption algorithm or MAC. Parts of their SSH specification are vulnerable to a novel prefix truncation attack (a.k.a. Terrapin attack).

Quality of Detection (QoD): 30%

Vulnerability Detection Result
```
The remote SSH server supports the following possible affected client-to-server
↪encryption algorithm(s):
chacha20-poly1305@openssh.com
The remote SSH server supports the following possible affected server-to-client
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
↪encryption algorithm(s):
chacha20-poly1305@openssh.com
The remote SSH server supports the following "strict kex" algorithm as a possibl
↪e mitigation:
kex-strict-s-v00@openssh.com
```

Solution:
Solution type: VendorFix
- Update OpenSSH to version 9.6 or later
- Update Apache MINA SSHD to version 2.12.0 or later
- For other products please contact the vendor for possible fixes / updates
Mitigation:
- To mitigate this protocol vulnerability, OpenSSH suggested a so-called 'strict kex' which alters the SSH handshake to ensure a Man-in-the-Middle attacker cannot introduce unauthenticated messages as well as convey sequence number manipulation across handshakes. Support for strict key exchange has been added to a variety of SSH implementations, including OpenSSH itself, PuTTY, libssh, and more.
Warning: To take effect, both the client and server must support this countermeasure.
As a stop-gap measure, peers may also (temporarily) disable the affected algorithms and use unaffected alternatives like AES-GCM instead until patches are available.

Affected Software/OS
Systems supporting the following encryption algorithm and/or MACs:
- ChaCha20-Poly1305 (chacha20-poly1305@openssh.com) encryption algorithm
- CBC encryption algorithm and Encrypt-then-MAC (*-etm@openssh.com) MAC

Vulnerability Insight
Parts of the SSH specification are vulnerable to a novel prefix truncation attack (a.k.a. Terrapin attack), which allows a man-in-the-middle attacker to strip an arbitrary number of messages right after the initial key exchange, breaking SSH extension negotiation (RFC8308) in the process and thus downgrading connection security.

Vulnerability Detection Method
Checks the supported algorithms and MACs of the remote SSH server.
Note: This VT has a low QoD because mitigation is possible / available via software updates.
Details: `Prefix Truncation Attacks in SSH Specification (Terrapin Attack)`
OID:1.3.6.1.4.1.25623.1.0.114238
Version used: `2025-04-23T05:39:47Z`

Product Detection Result
Product: `cpe:/a:ietf:secure_shell_protocol`
Method: `SSH Protocol Algorithms Supported`
OID: 1.3.6.1.4.1.25623.1.0.105565)

References

. . . continues on next page . . .

. . . continued from previous page . . .

```
cve: CVE-2023-48795
cve: CVE-2024-41909
url: https://terrapin-attack.com
url: https://www.openssh.com/txt/release-9.6
url: https://lists.apache.org/thread/vwf1ot8wx1njyy8n19j5j2tcnjnozt3b
url: https://github.com/apache/mina-sshd/issues/445
url: https://github.com/apache/mina-sshd/pull/449
cert-bund: WID-SEC-2025-2359
cert-bund: WID-SEC-2025-0810
cert-bund: WID-SEC-2025-0168
cert-bund: WID-SEC-2025-0144
cert-bund: WID-SEC-2025-0139
cert-bund: WID-SEC-2024-3377
cert-bund: WID-SEC-2024-3320
cert-bund: WID-SEC-2024-3221
cert-bund: WID-SEC-2024-3198
cert-bund: WID-SEC-2024-3195
cert-bund: WID-SEC-2024-1913
cert-bund: WID-SEC-2024-1781
cert-bund: WID-SEC-2024-1701
cert-bund: WID-SEC-2024-1656
cert-bund: WID-SEC-2024-1655
cert-bund: WID-SEC-2024-1643
cert-bund: WID-SEC-2024-1642
cert-bund: WID-SEC-2024-1639
cert-bund: WID-SEC-2024-1637
cert-bund: WID-SEC-2024-1630
cert-bund: WID-SEC-2024-1474
cert-bund: WID-SEC-2024-1248
cert-bund: WID-SEC-2024-1228
cert-bund: WID-SEC-2024-1186
cert-bund: WID-SEC-2024-1082
cert-bund: WID-SEC-2024-0899
cert-bund: WID-SEC-2024-0892
cert-bund: WID-SEC-2024-0889
cert-bund: WID-SEC-2024-0885
cert-bund: WID-SEC-2024-0874
cert-bund: WID-SEC-2024-0869
cert-bund: WID-SEC-2024-0578
cert-bund: WID-SEC-2024-0564
cert-bund: WID-SEC-2024-0523
cert-bund: WID-SEC-2023-3174
dfn-cert: DFN-CERT-2026-0097
dfn-cert: DFN-CERT-2025-3629
dfn-cert: DFN-CERT-2025-3272
dfn-cert: DFN-CERT-2025-2941
dfn-cert: DFN-CERT-2025-2058
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2025-2037
dfn-cert: DFN-CERT-2025-1447
dfn-cert: DFN-CERT-2025-1177
dfn-cert: DFN-CERT-2025-1025
dfn-cert: DFN-CERT-2025-0660
dfn-cert: DFN-CERT-2025-0502
dfn-cert: DFN-CERT-2025-0294
dfn-cert: DFN-CERT-2025-0173
dfn-cert: DFN-CERT-2025-0165
dfn-cert: DFN-CERT-2025-0024
dfn-cert: DFN-CERT-2024-3171
dfn-cert: DFN-CERT-2024-2818
dfn-cert: DFN-CERT-2024-2759
dfn-cert: DFN-CERT-2024-2741
dfn-cert: DFN-CERT-2024-2602
dfn-cert: DFN-CERT-2024-2573
dfn-cert: DFN-CERT-2024-2392
dfn-cert: DFN-CERT-2024-2210
dfn-cert: DFN-CERT-2024-2209
dfn-cert: DFN-CERT-2024-2194
dfn-cert: DFN-CERT-2024-2169
dfn-cert: DFN-CERT-2024-2048
dfn-cert: DFN-CERT-2024-2030
dfn-cert: DFN-CERT-2024-2028
dfn-cert: DFN-CERT-2024-1930
dfn-cert: DFN-CERT-2024-1895
dfn-cert: DFN-CERT-2024-1869
dfn-cert: DFN-CERT-2024-1868
dfn-cert: DFN-CERT-2024-1865
dfn-cert: DFN-CERT-2024-1862
dfn-cert: DFN-CERT-2024-1854
dfn-cert: DFN-CERT-2024-1846
dfn-cert: DFN-CERT-2024-1817
dfn-cert: DFN-CERT-2024-1715
dfn-cert: DFN-CERT-2024-1698
dfn-cert: DFN-CERT-2024-1688
dfn-cert: DFN-CERT-2024-1655
dfn-cert: DFN-CERT-2024-1600
dfn-cert: DFN-CERT-2024-1443
dfn-cert: DFN-CERT-2024-1442
dfn-cert: DFN-CERT-2024-1413
dfn-cert: DFN-CERT-2024-1382
dfn-cert: DFN-CERT-2024-1380
dfn-cert: DFN-CERT-2024-1373
dfn-cert: DFN-CERT-2024-1260
dfn-cert: DFN-CERT-2024-1259
dfn-cert: DFN-CERT-2024-1108
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2024-1061
dfn-cert: DFN-CERT-2024-1029
dfn-cert: DFN-CERT-2024-1003
dfn-cert: DFN-CERT-2024-1000
dfn-cert: DFN-CERT-2024-0896
dfn-cert: DFN-CERT-2024-0779
dfn-cert: DFN-CERT-2024-0762
dfn-cert: DFN-CERT-2024-0744
dfn-cert: DFN-CERT-2024-0698
dfn-cert: DFN-CERT-2024-0633
dfn-cert: DFN-CERT-2024-0619
dfn-cert: DFN-CERT-2024-0618
dfn-cert: DFN-CERT-2024-0616
dfn-cert: DFN-CERT-2024-0597
dfn-cert: DFN-CERT-2024-0545
dfn-cert: DFN-CERT-2024-0526
dfn-cert: DFN-CERT-2024-0491
dfn-cert: DFN-CERT-2024-0451
dfn-cert: DFN-CERT-2024-0440
dfn-cert: DFN-CERT-2024-0420
dfn-cert: DFN-CERT-2024-0388
dfn-cert: DFN-CERT-2024-0343
dfn-cert: DFN-CERT-2024-0306
dfn-cert: DFN-CERT-2024-0299
dfn-cert: DFN-CERT-2024-0285
dfn-cert: DFN-CERT-2024-0267
dfn-cert: DFN-CERT-2024-0251
dfn-cert: DFN-CERT-2024-0215
dfn-cert: DFN-CERT-2024-0211
dfn-cert: DFN-CERT-2024-0164
dfn-cert: DFN-CERT-2024-0154
dfn-cert: DFN-CERT-2024-0101
dfn-cert: DFN-CERT-2024-0092
dfn-cert: DFN-CERT-2024-0088
dfn-cert: DFN-CERT-2024-0067
dfn-cert: DFN-CERT-2024-0063
dfn-cert: DFN-CERT-2024-0062
dfn-cert: DFN-CERT-2024-0024
dfn-cert: DFN-CERT-2024-0013
dfn-cert: DFN-CERT-2023-3219
dfn-cert: DFN-CERT-2023-3218
dfn-cert: DFN-CERT-2023-3210
dfn-cert: DFN-CERT-2023-3201
dfn-cert: DFN-CERT-2023-3200
dfn-cert: DFN-CERT-2023-3195
dfn-cert: DFN-CERT-2023-3193
dfn-cert: DFN-CERT-2023-3191
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2023-3185
dfn-cert: DFN-CERT-2023-3184
dfn-cert: DFN-CERT-2023-3183
dfn-cert: DFN-CERT-2023-3182
dfn-cert: DFN-CERT-2023-3175
```

[return to 172.30.2.2]

2.1.3 Medium 21/tcp

Medium (CVSS: 6.4)
NVT: Anonymous FTP Login Reporting

Summary
Reports if the remote FTP Server allows anonymous logins.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
It was possible to login to the remote FTP service with the following anonymous
↪account(s):
anonymous:anonymous@example.com
ftp:anonymous@example.com
Here are the contents of the remote FTP directory listing:
Account "anonymous":
-rw-r--r--    1 0        0            1864 May 04  2024 welcome-letter.txt
Account "ftp":
-rw-r--r--    1 0        0            1864 May 04  2024 welcome-letter.txt
```

Impact
Based on the files accessible via this anonymous FTP login and the permissions of this account an attacker might be able to:
- gain access to sensitive files
- upload or delete files.

Solution:
Solution type: Mitigation
If you do not want to share files, you should disable anonymous logins.

Vulnerability Insight
A host that provides an FTP service may additionally provide Anonymous FTP access as well. Under this arrangement, users do not strictly need an account on the host. Instead the user typically enters 'anonymous' or 'ftp' when prompted for username. Although users are commonly asked to send their email address as their password, little to no verification is actually performed on the supplied data.

. . . continues on next page . . .

. . . continued from previous page . . .

Remark: NIST don't see 'configuration issues' as software flaws so the referenced CVE has a severity of 0.0. The severity of this VT has been raised by Greenbone to still report a configuration issue on the target.

Vulnerability Detection Method
Details: `Anonymous FTP Login Reporting`
OID:1.3.6.1.4.1.25623.1.0.900600
Version used: `2021-10-20T09:03:29Z`

References
`cve: CVE-1999-0497`

Medium (CVSS: 4.8)
NVT: FTP Unencrypted Cleartext Login

Summary
The remote host is running a FTP service that allows cleartext logins over unencrypted connections.

Quality of Detection (QoD): 70%

Vulnerability Detection Result

```
The remote FTP service accepts logins without a previous sent 'AUTH TLS' command
↪. Response(s):
Non-anonymous sessions: 331 Please specify the password.
Anonymous sessions:     331 Please specify the password.
```

Impact
An attacker can uncover login names and passwords by sniffing traffic to the FTP service.

Solution:
Solution type: Mitigation
Enable FTPS or enforce the connection via the 'AUTH TLS' command. Please see the manual of the FTP service for more information.

Vulnerability Detection Method
Tries to login to a non FTPS enabled FTP service without sending a 'AUTH TLS' command first and checks if the service is accepting the login without enforcing the use of the 'AUTH TLS' command.
Details: `FTP Unencrypted Cleartext Login`
OID:1.3.6.1.4.1.25623.1.0.108528
Version used: `2023-12-20T05:05:58Z`

[return to 172.30.2.2]

2.1.4 Medium 80/tcp

Medium (CVSS: 5.0)
NVT: Apache HTTP Server 2.4.17 < 2.4.64 DoS Vulnerability - Linux

Product detection result
`cpe:/a:apache:http_server:2.4.59`
`Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1`
`↪.0.117232)`

Summary
Apache HTTP Server is prone to a denial of service (DoS) vulnerability via HTTP/2.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 2.4.59
Fixed version:     2.4.64
Installation
path / port:       80/tcp
```

Solution:
Solution type: VendorFix
Update to version 2.4.64 or later.

Affected Software/OS
Apache HTTP Server version 2.4.17 through 2.4.63.

Vulnerability Insight
Late release of memory after effective lifetime vulnerability in Apache HTTP Server.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Apache HTTP Server 2.4.17 < 2.4.64 DoS Vulnerability - Linux`
OID:1.3.6.1.4.1.25623.1.0.154915
Version used: `2025-07-11T15:43:14Z`

Product Detection Result
Product: `cpe:/a:apache:http_server:2.4.59`
Method: `Apache HTTP Server Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.117232)

References
`cve: CVE-2025-53020`

. . . continues on next page . . .

. . . continued from previous page . . .

```
url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.64
cert-bund: WID-SEC-2025-1850
cert-bund: WID-SEC-2025-1529
dfn-cert: DFN-CERT-2025-2182
dfn-cert: DFN-CERT-2025-1860
```

Medium (CVSS: 5.0)
NVT: Apache HTTP Server 2.4.26 < 2.4.64 DoS Vulnerability - Linux

Product detection result

```
cpe:/a:apache:http_server:2.4.59
Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1
↪.0.117232)
```

Summary

Apache HTTP Server is prone to a denial of service (DoS) vulnerability in mod_proxy_http2.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 2.4.59
Fixed version:     2.4.64
Installation
path / port:       80/tcp
```

Solution:

Solution type: VendorFix

Update to version 2.4.64 or later.

Affected Software/OS

Apache HTTP Server version 2.4.26 through 2.4.63.

Vulnerability Insight

In certain proxy configurations, a denial of service attack against Apache HTTP Server can be triggered by untrusted clients causing an assertion in mod_proxy_http2.
Configurations affected are a reverse proxy is configured for an HTTP/2 backend, with ProxyPreserveHost set to 'on'.

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.
Details: `Apache HTTP Server 2.4.26 < 2.4.64 DoS Vulnerability - Linux`
OID:1.3.6.1.4.1.25623.1.0.154913
Version used: `2025-07-11T15:43:14Z`

. . . continues on next page . . .

. . . continued from previous page . . .

Product Detection Result
Product: cpe:/a:apache:http_server:2.4.59
Method: Apache HTTP Server Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.117232)

References
cve: CVE-2025-49630
url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.64
cert-bund: WID-SEC-2025-1850
cert-bund: WID-SEC-2025-1529
dfn-cert: DFN-CERT-2025-2421
dfn-cert: DFN-CERT-2025-2345
dfn-cert: DFN-CERT-2025-2231
dfn-cert: DFN-CERT-2025-2182
dfn-cert: DFN-CERT-2025-1860

Medium (CVSS: 5.0)
NVT: Apache HTTP Server 2.4.35 < 2.4.64 Access Control Bypass Vulnerability - Linux

Product detection result
cpe:/a:apache:http_server:2.4.59
Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1
↪.0.117232)

Summary
Apache HTTP Server is prone to an access control bypass vulnerability in mod_ssl.

Quality of Detection (QoD): 30%

Vulnerability Detection Result
Installed version: 2.4.59
Fixed version: 2.4.64
Installation
path / port: 80/tcp

Solution:
Solution type: VendorFix
Update to version 2.4.64 or later.

Affected Software/OS
Apache HTTP Server version 2.4.35 through 2.4.63.

Vulnerability Insight

. . . continues on next page . . .

. . . continued from previous page . . .

In some mod_ssl configurations an access control bypass by trusted clients is possible using TLS 1.3 session resumption.
Configurations are affected when mod_ssl is configured for multiple virtual hosts, with each restricted to a different set of trusted client certificates (for example with a different SSLCACertificateFile/Path setting). In such a case, a client trusted to access one virtual host may be able to access another virtual host, if SSLStrictSNIVHostCheck is not enabled in either virtual host.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Apache HTTP Server 2.4.35 < 2.4.64 Access Control Bypass Vulnerability - Linux`
OID:1.3.6.1.4.1.25623.1.0.154911
Version used: `2025-07-11T15:43:14Z`

Product Detection Result
Product: `cpe:/a:apache:http_server:2.4.59`
Method: `Apache HTTP Server Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.117232)

References
```
cve: CVE-2025-23048
url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.64
cert-bund: WID-SEC-2026-0162
cert-bund: WID-SEC-2025-1850
cert-bund: WID-SEC-2025-1529
dfn-cert: DFN-CERT-2026-0205
dfn-cert: DFN-CERT-2025-2421
dfn-cert: DFN-CERT-2025-2373
dfn-cert: DFN-CERT-2025-2231
dfn-cert: DFN-CERT-2025-2182
dfn-cert: DFN-CERT-2025-1860
```

Medium (CVSS: 5.8)
NVT: Apache HTTP Server 2.4.7 - 2.4.65 Authentication Bypass Vulnerability - Linux

Product detection result
```
cpe:/a:apache:http_server:2.4.59
Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1
↪.0.117232)
```

Summary
Apache HTTP Server is prone to an authentication bypass vulnerability.

Quality of Detection (QoD): 30%

. . . continues on next page . . .

. . . continued from previous page . . .

Vulnerability Detection Result

```
Installed version: 2.4.59
Fixed version:     2.4.66
Installation
path / port:       80/tcp
```

Solution:
Solution type: VendorFix
Update to version 2.4.66 or later.

Affected Software/OS
Apache HTTP Server version 2.4.7 through 2.4.65.

Vulnerability Insight
mod_userdir+suexec bypass via AllowOverride FileInfo vulnerability in Apache HTTP Server. Users with access to use the RequestHeader directive in htaccess can cause some CGI scripts to run under an unexpected userid.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Apache HTTP Server 2.4.7 - 2.4.65 Authentication Bypass Vulnerability - Linux`
OID:1.3.6.1.4.1.25623.1.0.125567
Version used: `2025-12-05T05:44:55Z`

Product Detection Result
Product: `cpe:/a:apache:http_server:2.4.59`
Method: `Apache HTTP Server Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.117232)

References

```
cve: CVE-2025-66200
url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.66
url: https://www.openwall.com/lists/oss-security/2025/12/04/8
cert-bund: WID-SEC-2025-2750
dfn-cert: DFN-CERT-2025-3602
dfn-cert: DFN-CERT-2025-3581
dfn-cert: DFN-CERT-2025-3512
dfn-cert: DFN-CERT-2025-3405
```

Medium (CVSS: 4.3)
NVT: Apache HTTP Server 2.4.x < 2.4.66 Improper Neutralization Vulnerability - Linux

Product detection result
`cpe:/a:apache:http_server:2.4.59`

. . . continues on next page . . .

. . . continued from previous page . . .

Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1
↪.0.117232)

Summary
Apache HTTP Server is prone to an improper neutralization vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 2.4.59
Fixed version:     2.4.66
Installation
path / port:       80/tcp
```

Solution:
Solution type: VendorFix
Update to version 2.4.66 or later.

Affected Software/OS
Apache HTTP Server version 2.4.x prior to 2.4.66.

Vulnerability Insight
Improper neutralization of escape, meta, or control sequences vulnerability in Apache HTTP Server through environment variables set via the Apache configuration unexpectedly superseding variables calculated by the server for CGI programs.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: Apache HTTP Server 2.4.x < 2.4.66 Improper Neutralization Vulnerability - Linux
OID:1.3.6.1.4.1.25623.1.0.125566
Version used: 2025-12-05T05:44:55Z

Product Detection Result
Product: cpe:/a:apache:http_server:2.4.59
Method: Apache HTTP Server Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.117232)

References

```
cve: CVE-2025-65082
url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.66
url: https://www.openwall.com/lists/oss-security/2025/12/04/7
cert-bund: WID-SEC-2026-0155
cert-bund: WID-SEC-2025-2750
dfn-cert: DFN-CERT-2026-0214
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2025-3602
dfn-cert: DFN-CERT-2025-3581
dfn-cert: DFN-CERT-2025-3512
dfn-cert: DFN-CERT-2025-3405
```

Medium (CVSS: 5.0)
NVT: Apache HTTP Server < 2.4.64 Multiple Vulnerabilities - Linux

Product detection result

```
cpe:/a:apache:http_server:2.4.59
Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1
↪.0.117232)
```

Summary

Apache HTTP Server is prone to multiple vulnerabilities.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 2.4.59
Fixed version:     2.4.64
Installation
path / port:       80/tcp
```

Solution:

Solution type: VendorFix

Update to version 2.4.64 or later.

Affected Software/OS

Apache HTTP Server version 2.4.63 and prior.

Vulnerability Insight

The following flaws exist:

- CVE-2024-42516: HTTP response splitting
- CVE-2024-43204: SSRF with mod_headers setting Content-Type header
- CVE-2024-47252: mod_ssl error log variable escaping
- CVE-2025-49812: mod_ssl TLS upgrade attack

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.

Details: `Apache HTTP Server < 2.4.64 Multiple Vulnerabilities - Linux`

OID:1.3.6.1.4.1.25623.1.0.154909

Version used: `2025-07-11T15:43:14Z`

. . . continues on next page . . .

. . . continued from previous page . . .

Product Detection Result
Product: cpe:/a:apache:http_server:2.4.59
Method: Apache HTTP Server Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.117232)

References
cve: CVE-2024-42516
cve: CVE-2024-43204
cve: CVE-2024-47252
cve: CVE-2025-49812
url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.64
cert-bund: WID-SEC-2026-0162
cert-bund: WID-SEC-2025-1850
cert-bund: WID-SEC-2025-1529
dfn-cert: DFN-CERT-2026-0205
dfn-cert: DFN-CERT-2025-2421
dfn-cert: DFN-CERT-2025-2403
dfn-cert: DFN-CERT-2025-2402
dfn-cert: DFN-CERT-2025-2373
dfn-cert: DFN-CERT-2025-2231
dfn-cert: DFN-CERT-2025-2182
dfn-cert: DFN-CERT-2025-1917
dfn-cert: DFN-CERT-2025-1860

Medium (CVSS: 4.3)
NVT: Apache HTTP Server < 2.4.66 SSI Vulnerability - Linux

Product detection result
cpe:/a:apache:http_server:2.4.59
Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1
↪.0.117232)

Summary
Apache HTTP Server is prone to a Server Side Includes (SSI) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result
Installed version: 2.4.59
Fixed version: 2.4.66
Installation
path / port: 80/tcp

Solution:

. . . continues on next page . . .

. . . continued from previous page . . .

Solution type: VendorFix
Update to version 2.4.66 or later.

Affected Software/OS
Apache HTTP Server prior to version 2.4.66.

Vulnerability Insight
Apache HTTP Server with SSI enabled and mod_cgid (but not mod_cgi) passes the shell-escaped query string to #exec cmd='...' directives.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Apache HTTP Server < 2.4.66 SSI Vulnerability - Linux`
OID:1.3.6.1.4.1.25623.1.0.125564
Version used: `2025-12-05T05:44:55Z`

Product Detection Result
Product: `cpe:/a:apache:http_server:2.4.59`
Method: `Apache HTTP Server Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.117232)

References
```
cve: CVE-2025-58098
url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.66
url: https://www.openwall.com/lists/oss-security/2025/12/04/5
cert-bund: WID-SEC-2026-0153
cert-bund: WID-SEC-2025-2750
dfn-cert: DFN-CERT-2026-0027
dfn-cert: DFN-CERT-2026-0012
dfn-cert: DFN-CERT-2025-3602
dfn-cert: DFN-CERT-2025-3581
dfn-cert: DFN-CERT-2025-3512
dfn-cert: DFN-CERT-2025-3405
```

[return to 172.30.2.2]

2.1.5 Low 22/tcp

Low (CVSS: 3.8)
NVT: OpenBSD OpenSSH 7.4 - 9.9 Unspecified Vulnerability

Product detection result
```
cpe:/a:openbsd:openssh:8.4p1
Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)
```

. . . continues on next page . . .

. . . continued from previous page . . .

Summary
OpenBSD OpenSSH is prone to an unspecified vulnerability due to a logic error.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 8.4p1
Fixed version:     10.0
Installation
path / port:       22/tcp
```

Solution:
Solution type: VendorFix
Update to version 10.0 or later.

Affected Software/OS
OpenBSD OpenSSH versions 7.4 through 9.9.

Vulnerability Insight
A logic error in sshd(8) caused the DisableForwarding option to not disable X11 or agent forwarding as documented. Note that X11 forwarding is disabled by default in sshd(8) and agent forwarding is not requested by default by ssh(1).

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `OpenBSD OpenSSH 7.4 - 9.9 Unspecified Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.105000
Version used: `2025-05-23T05:40:17Z`

Product Detection Result
Product: `cpe:/a:openbsd:openssh:8.4p1`
Method: `OpenSSH Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.108577)

References

```
cve: CVE-2025-32728
url: https://www.openssh.com/txt/release-10.0
url: https://www.openssh.com/security.html
url: https://www.openwall.com/lists/oss-security/2025/04/09/1
url: https://bugzilla.redhat.com/show_bug.cgi?id=2358767
cert-bund: WID-SEC-2025-2361
cert-bund: WID-SEC-2025-1439
cert-bund: WID-SEC-2025-0775
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2025-1562
dfn-cert: DFN-CERT-2025-0918
```

Low (CVSS: 2.4)
NVT: OpenBSD OpenSSH < 10.1 Multiple Vulnerabilities

Product detection result

```
cpe:/a:openbsd:openssh:8.4p1
Detected by OpenSSH Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.108577)
```

Summary

OpenBSD OpenSSH is prone to multiple vulnerabilities.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 8.4p1
Fixed version:     10.1
Installation
path / port:       22/tcp
```

Solution:

Solution type: VendorFix

Update to version 10.1 or later.

Affected Software/OS

OpenBSD OpenSSH versions prior to 10.1.

Vulnerability Insight

The following flaws exist:

- CVE-2025-61984: 'ssh' allows control characters in usernames that originate from certain possibly untrusted sources, potentially leading to code execution when a ProxyCommand is used. The untrusted sources are the command line and %-sequence expansion of a configuration file. (A configuration file that provides a complete literal username is not categorized as an untrusted source.)

- CVE-2025-61985: 'ssh' allows the '\0' character in an ssh:// URI, potentially leading to code execution when a ProxyCommand is used.

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.

Details: `OpenBSD OpenSSH < 10.1 Multiple Vulnerabilities`

OID:1.3.6.1.4.1.25623.1.0.119134

Version used: `2025-10-08T05:38:55Z`

. . . continues on next page . . .

. . . continued from previous page . . .

Product Detection Result
Product: cpe:/a:openbsd:openssh:8.4p1
Method: OpenSSH Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.108577)

References
cve: CVE-2025-61984
cve: CVE-2025-61985
url: https://www.openssh.com/txt/release-10.1
url: https://www.openssh.com/security.html
url: https://www.openwall.com/lists/oss-security/2025/10/06/1
url: https://dgl.cx/2025/10/bash-a-newline-ssh-proxycommand-cve-2025-61984#_
cert-bund: WID-SEC-2025-2212
dfn-cert: DFN-CERT-2026-0218
dfn-cert: DFN-CERT-2025-3384
dfn-cert: DFN-CERT-2025-2768

Low (CVSS: 2.6)
NVT: Weak MAC Algorithm(s) Supported (SSH)

Product detection result
cpe:/a:ietf:secure_shell_protocol
Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565
↪)

Summary
The remote SSH server is configured to allow / support weak MAC algorithm(s).

Quality of Detection (QoD): 80%

Vulnerability Detection Result
The remote SSH server supports the following weak client-to-server MAC algorithm
↪(s):
umac-64-etm@openssh.com
umac-64@openssh.com
The remote SSH server supports the following weak server-to-client MAC algorithm
↪(s):
umac-64-etm@openssh.com
umac-64@openssh.com

Solution:
Solution type: Mitigation
Disable the reported weak MAC algorithm(s).

. . . continues on next page . . .

. . . continued from previous page . . .

Vulnerability Detection Method
Checks the supported MAC algorithms (client-to-server and server-to-client) of the remote SSH server.
Currently weak MAC algorithms are defined as the following:
- MD5 based algorithms
- 96-bit based algorithms
- 64-bit based algorithms
- 'none' algorithm
Details: `Weak MAC Algorithm(s) Supported (SSH)`
OID:1.3.6.1.4.1.25623.1.0.105610
Version used: `2024-06-14T05:05:48Z`

Product Detection Result
Product: `cpe:/a:ietf:secure_shell_protocol`
Method: `SSH Protocol Algorithms Supported`
OID: 1.3.6.1.4.1.25623.1.0.105565)

References
`url: https://www.rfc-editor.org/rfc/rfc6668`
`url: https://www.rfc-editor.org/rfc/rfc4253#section-6.4`

[return to 172.30.2.2]

2.1.6 Low general/tcp

Low (CVSS: 2.6)
NVT: TCP Timestamps Information Disclosure

Summary
The remote host implements TCP timestamps and therefore allows to compute the uptime.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
It was detected that the host implements RFC1323/RFC7323.
The following timestamps were retrieved with a delay of 1 seconds in-between:
Packet 1: 999486459
Packet 2: 999487559
```

Impact
A side effect of this feature is that the uptime of the remote host can sometimes be computed.

Solution:
Solution type: Mitigation

. . . continues on next page . . .

. . . continued from previous page . . .

To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.
To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled. The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.
See the references for more information.

Affected Software/OS
TCP implementations that implement RFC1323/RFC7323.

Vulnerability Insight
The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.

Vulnerability Detection Method
Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.
Details: `TCP Timestamps Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.80091
Version used: `2023-12-15T16:10:08Z`

References
`url: https://datatracker.ietf.org/doc/html/rfc1323`
`url: https://datatracker.ietf.org/doc/html/rfc7323`
`url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/d`
`↪ownload/details.aspx?id=9152`
`url: https://www.fortiguard.com/psirt/FG-IR-16-090`

[return to 172.30.2.2]

2.1.7 Low 80/tcp

Low (CVSS: 2.6)
NVT: Apache HTTP Server 2.4.30 - 2.4.65 Integer Overflow Vulnerability - Linux

Product detection result
`cpe:/a:apache:http_server:2.4.59`
`Detected by Apache HTTP Server Detection Consolidation (OID: 1.3.6.1.4.1.25623.1`
`↪.0.117232)`

Summary
Apache HTTP Server is prone to an integer overflow vulnerability.

. . . continues on next page . . .

. . . continued from previous page . . .

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 2.4.59
Fixed version:     2.4.66
Installation
path / port:       80/tcp
```

Solution:
Solution type: VendorFix
Update to version 2.4.66 or later.

Affected Software/OS
Apache HTTP Server version 2.4.30 through 2.4.65.

Vulnerability Insight
An integer overflow in the case of failed ACME certificate renewal leads, after a number of failures (30 days in default configurations), to the backoff timer becoming 0. Attempts to renew the certificate then are repeated without delays until it succeeds.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Apache HTTP Server 2.4.30 - 2.4.65 Integer Overflow Vulnerability - Linux`
OID:1.3.6.1.4.1.25623.1.0.125565
Version used: `2025-12-05T05:44:55Z`

Product Detection Result
Product: `cpe:/a:apache:http_server:2.4.59`
Method: `Apache HTTP Server Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.117232)

References

```
cve: CVE-2025-55753
url: https://httpd.apache.org/security/vulnerabilities_24.html#2.4.66
url: https://www.openwall.com/lists/oss-security/2025/12/04/4
cert-bund: WID-SEC-2025-2750
dfn-cert: DFN-CERT-2026-0218
dfn-cert: DFN-CERT-2026-0012
dfn-cert: DFN-CERT-2025-3581
dfn-cert: DFN-CERT-2025-3415
dfn-cert: DFN-CERT-2025-3405
```

[return to 172.30.2.2]

2.1.8 Low general/icmp

Low (CVSS: 2.1)
NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
The following response / ICMP packet has been received:
- ICMP Type: 14
- ICMP Code: 0
```

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:
- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: `ICMP Timestamp Reply Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: `2025-01-21T05:37:33Z`

References

```
cve: CVE-1999-0524
url: https://datatracker.ietf.org/doc/html/rfc792
url: https://datatracker.ietf.org/doc/html/rfc2780
cert-bund: CB-K15/1514
cert-bund: CB-K14/0632
dfn-cert: DFN-CERT-2014-0658
```

[return to 172.30.2.2]

2.1.9 Log general/CPE-T

Log (CVSS: 0.0)
NVT: CPE Inventory

Summary
This routine uses information collected by other routines about CPE identities of operating systems, services and applications detected during the scan.
Note: Some CPEs for specific products might show up twice or more in the output. Background: After a product got renamed or a specific vendor was acquired by another one it might happen that a product gets a new CPE within the NVD CPE Dictionary but older entries are kept with the older CPE.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
172.30.2.2|cpe:/a:apache:http_server:2.4.59
172.30.2.2|cpe:/a:beasts:vsftpd:3.0.3
172.30.2.2|cpe:/a:ietf:secure_shell_protocol:2.0
172.30.2.2|cpe:/a:openbsd:openssh:8.4p1
172.30.2.2|cpe:/o:debian:debian_linux:11
```

Solution:

Log Method
Details: `CPE Inventory`
OID:1.3.6.1.4.1.25623.1.0.810002
Version used: `2022-07-27T10:11:28Z`

References
`url: https://nvd.nist.gov/products/cpe`

[return to 172.30.2.2]

2.1.10 Log 22/tcp

Log (CVSS: 0.0)
NVT: PQC Key Exchange (KEX) Algorithm(s) Missing (SSH)

Product detection result
```
cpe:/a:ietf:secure_shell_protocol
Detected by SSH Protocol Algorithms Supported (OID: 1.3.6.1.4.1.25623.1.0.105565
↪)
```

. . . continues on next page . . .

. . . continued from previous page . . .

Summary
The remote SSH server is configured to NOT allow / support at least ONE Post-Quantum Cryptography (PQC) key exchange (KEX) algorithm(s).

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`The remote SSH server is NOT supporting at least ONE PQC KEX algorithm.`

Impact
The connection may be vulnerable to 'store now, decrypt later' attacks.

Solution:
Solution type: Mitigation
Update the remote SSH server to a version supporting PQC KEX algorithms (e.g. OpenSSH 8.9 or later) and enable relevant PQC KEX algorithms accordingly.
Please see the references/manual of the remote SSH server and/or contact the vendor of it for more support.

Log Method
Checks the (previously collected) supported KEX algorithms of the remote SSH server.
Currently the following PQC KEX algorithms are defined / getting used for this check:
- sntrup761x25519-sha512@openssh.com
- sntrup761x25519-sha512
- mlkem768x25519-sha256
- sntrup4591761x25519-sha512@tinyssh.org
- ecdh-nistp256-kyber-512r3-sha256-d00@openquantumsafe.org
- ecdh-nistp384-kyber-768r3-sha384-d00@openquantumsafe.org
- ecdh-nistp521-kyber-1024r3-sha512-d00@openquantumsafe.org
- x25519-kyber-512r3-sha256-d00@amazon.com
- mlkem1024nistp384-sha384
- mlkem768nistp256-sha256
- curve25519-frodokem1344-sha512@ssh.com
- ecdh-nistp521-kyber1024-sha512@ssh.com

Details: `PQC Key Exchange (KEX) Algorithm(s) Missing (SSH)`
OID:1.3.6.1.4.1.25623.1.0.119214
Version used: `2025-10-31T05:40:56Z`

Product Detection Result
Product: `cpe:/a:ietf:secure_shell_protocol`
Method: `SSH Protocol Algorithms Supported`
OID: 1.3.6.1.4.1.25623.1.0.105565)

References

. . . continues on next page . . .

. . . continued from previous page . . .

```
url: https://openssh.com/pq.html
url: https://quantumcomputingreport.com/openssh-10-0-introduces-default-post-qua
↪ntum-key-exchange-algorithm/
url: https://www.nist.gov/news-events/news/2024/08/nist-releases-first-3-finaliz
↪ed-post-quantum-encryption-standards
url: https://csrc.nist.gov/News/2024/postquantum-cryptography-fips-approved
url: https://www.forescout.com/blog/post-quantum-cryptography-the-real-risks-of-
↪not-adopting-it/
```

Log (CVSS: 0.0)
NVT: Services

Summary
This plugin performs service detection.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`An ssh server is running on this port`

Solution:

Vulnerability Insight
This plugin attempts to guess which service is running on the remote port(s). For instance, it searches for a web server which could listen on another port than 80 or 443 and makes this information available for other check routines.

Log Method
Details: `Services`
OID:1.3.6.1.4.1.25623.1.0.10330
Version used: `2025-03-05T05:38:53Z`

Log (CVSS: 0.0)
NVT: SSH Protocol Algorithms Supported

Summary
This script detects which algorithms are supported by the remote SSH service.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
The following options are supported by the remote SSH service:
kex_algorithms:
curve25519-sha256,curve25519-sha256@libssh.org,ecdh-sha2-nistp256,ecdh-sha2-nist
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
↪p384,ecdh-sha2-nistp521,diffie-hellman-group-exchange-sha256,diffie-hellman-gr
↪oup16-sha512,diffie-hellman-group18-sha512,diffie-hellman-group14-sha256,kex-s
↪trict-s-v00@openssh.com
server_host_key_algorithms:
rsa-sha2-512,rsa-sha2-256,ssh-rsa,ecdsa-sha2-nistp256,ssh-ed25519
encryption_algorithms_client_to_server:
chacha20-poly1305@openssh.com,aes128-ctr,aes192-ctr,aes256-ctr,aes128-gcm@openss
↪h.com,aes256-gcm@openssh.com
encryption_algorithms_server_to_client:
chacha20-poly1305@openssh.com,aes128-ctr,aes192-ctr,aes256-ctr,aes128-gcm@openss
↪h.com,aes256-gcm@openssh.com
mac_algorithms_client_to_server:
umac-64-etm@openssh.com,umac-128-etm@openssh.com,hmac-sha2-256-etm@openssh.com,h
↪mac-sha2-512-etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64@openssh.com,uma
↪c-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-sha1
mac_algorithms_server_to_client:
umac-64-etm@openssh.com,umac-128-etm@openssh.com,hmac-sha2-256-etm@openssh.com,h
↪mac-sha2-512-etm@openssh.com,hmac-sha1-etm@openssh.com,umac-64@openssh.com,uma
↪c-128@openssh.com,hmac-sha2-256,hmac-sha2-512,hmac-sha1
compression_algorithms_client_to_server:
none,zlib@openssh.com
compression_algorithms_server_to_client:
none,zlib@openssh.com
```

Solution:

Log Method
Details: `SSH Protocol Algorithms Supported`
OID:1.3.6.1.4.1.25623.1.0.105565
Version used: `2026-01-21T05:50:46Z`

Log (CVSS: 0.0)
NVT: SSH Protocol Versions Supported

Summary
Identification of SSH protocol versions supported by the remote SSH Server. Also reads the corresponding fingerprints from the service.

Quality of Detection (QoD): 95%

Vulnerability Detection Result

```
The remote SSH Server supports the following SSH Protocol Versions:
1.99
2.0
SSHv2 Fingerprint(s):
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
ecdsa-sha2-nistp256: 83:85:58:4d:6a:f9:a0:76:a6:a5:7c:e7:b5:8d:cf:d4
ssh-ed25519: 43:b6:80:87:d9:1f:80:f9:30:20:d4:56:50:fd:48:3c
ssh-rsa: a2:06:61:48:82:e8:b1:3d:df:f7:d0:85:e5:14:0f:36
```

Solution:

Log Method
The following versions are tried: 1.33, 1.5, 1.99 and 2.0.
Details: `SSH Protocol Versions Supported`
OID:1.3.6.1.4.1.25623.1.0.100259
Version used: `2024-06-17T08:31:37Z`

Log (CVSS: 0.0)
NVT: SSH Server type and version

Summary
This detects the SSH Server's type and version by connecting to the server and processing the buffer received.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Remote SSH server banner: SSH-2.0-OpenSSH_8.4p1 Debian-5+deb11u3
Remote SSH supported authentication: password,publickey
Remote SSH text/login banner: (not available)
This is probably (a):
- OpenSSH
Concluded from remote connection attempt with credentials:
Login:    OpenVASVT
Password: OpenVASVT
```

Solution:

Vulnerability Insight
This information gives potential attackers additional information about the system they are attacking. Versions and Types should be omitted where possible.

Log Method
Details: `SSH Server type and version`
OID:1.3.6.1.4.1.25623.1.0.10267
Version used: `2025-11-13T05:40:19Z`

[return to 172.30.2.2]

2.1.11 Log general/tcp

Log (CVSS: 0.0)
NVT: Apache HTTP Server Detection Consolidation

Summary
Consolidation of Apache HTTP Server detections.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Detected Apache HTTP Server
Version:       2.4.59
Location:      80/tcp
CPE:           cpe:/a:apache:http_server:2.4.59
Concluded from version/product identification result:
Server: Apache/2.4.59 (Debian)
```

Solution:

Log Method
Details: `Apache HTTP Server Detection Consolidation`
OID:1.3.6.1.4.1.25623.1.0.117232
Version used: `2024-03-08T15:37:10Z`

References
`url: https://httpd.apache.org`

Log (CVSS: 0.0)
NVT: Hostname Determination Reporting

Summary
The script reports information on how the hostname of the target was determined.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Hostname determination for IP 172.30.2.2:
Hostname|Source
proftpd-vuln.trabalho_vulnnet|Reverse-DNS
```

Solution:

Log Method

. . . continues on next page . . .

. . . continued from previous page . . .

Details: `Hostname Determination Reporting`
OID:1.3.6.1.4.1.25623.1.0.108449
Version used: `2022-07-27T10:11:28Z`

Log (CVSS: 0.0)
NVT: IP Forwarding Enabled - Active Check

Summary
Checks if the remote host has IP forwarding enabled.

Quality of Detection (QoD): 70%

Vulnerability Detection Result

```
It was possible to route a TCP packet through the target host and received an an
↪swer which means IP forwarding is enabled.
```

Solution:

Log Method
Sends a crafted Local Link Layer (LLL) frame and checks the response.
Details: `IP Forwarding Enabled - Active Check`
OID:1.3.6.1.4.1.25623.1.0.147205
Version used: `2021-12-03T08:27:06Z`

References
`cve: CVE-1999-0511`

Log (CVSS: 0.0)
NVT: OpenSSH Detection Consolidation

Summary
Consolidation of OpenSSH detections.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Detected OpenSSH Server
Version:       8.4p1
Location:      22/tcp
CPE:           cpe:/a:openbsd:openssh:8.4p1
Concluded from version/product identification result:
SSH-2.0-OpenSSH_8.4p1 Debian-5+deb11u3
```

Solution:

. . . continues on next page . . .

. . . continued from previous page . . .

Log Method
Details: OpenSSH Detection Consolidation
OID:1.3.6.1.4.1.25623.1.0.108577
Version used: 2024-12-13T05:05:32Z

References
url: https://www.openssh.com/

Log (CVSS: 0.0)
NVT: OS Detection Consolidation and Reporting

Summary
This script consolidates the OS information detected by several VTs and tries to find the best matching OS.
Furthermore it reports all previously collected information leading to this best matching OS. It also reports possible additional information which might help to improve the OS detection.
If any of this information is wrong or could be improved please consider to report these to the referenced community forum.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Best matching OS:
OS:           Debian GNU/Linux 11
Version:      11
CPE:          cpe:/o:debian:debian_linux:11
Found by VT:  1.3.6.1.4.1.25623.1.0.105586 (Operating System (OS) Detection (SSH
↪ Banner))
Concluded from SSH banner on port 22/tcp: SSH-2.0-OpenSSH_8.4p1 Debian-5+deb11u3
Setting key "Host/runs_unixoide" based on this information
Other OS detections (in order of reliability):
OS:           Linux/Unix
CPE:          cpe:/o:linux:kernel
Found by VT:  1.3.6.1.4.1.25623.1.0.105355 (Operating System (OS) Detection (FTP
↪))
Concluded from FTP banner on port 21/tcp: 220 (vsFTPd 3.0.3)
OS:           Debian GNU/Linux 12
Version:      12
CPE:          cpe:/o:debian:debian_linux:12
Found by VT:  1.3.6.1.4.1.25623.1.0.111067 (Operating System (OS) Detection (HTT
↪P))
Concluded from HTTP Server banner on port 80/tcp: Server: Apache/2.4.59 (Debian)
OS:           Debian GNU/Linux 11
Version:      11
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
CPE:          cpe:/o:debian:debian_linux:11
Found by VT:  1.3.6.1.4.1.25623.1.0.111067 (Operating System (OS) Detection (HTT
↪P))
Concluded from HTTP Server banner on port 80/tcp: Server: Apache/2.4.59 (Debian)
OS:           Debian GNU/Linux 10
Version:      10
CPE:          cpe:/o:debian:debian_linux:10
Found by VT:  1.3.6.1.4.1.25623.1.0.111067 (Operating System (OS) Detection (HTT
↪P))
Concluded from HTTP Server banner on port 80/tcp: Server: Apache/2.4.59 (Debian)
OS:           Debian GNU/Linux
CPE:          cpe:/o:debian:debian_linux
Found by VT:  1.3.6.1.4.1.25623.1.0.111067 (Operating System (OS) Detection (HTT
↪P))
Concluded from HTTP Server default page on port 80/tcp: <title>Apache2 Debian De
↪fault Page
```

Solution:

Log Method
Details: OS Detection Consolidation and Reporting
OID:1.3.6.1.4.1.25623.1.0.105937
Version used: 2026-01-21T05:50:46Z

References
url: https://forum.greenbone.net/c/vulnerability-tests/7

Log (CVSS: 0.0)
NVT: Traceroute

Summary
Collect information about the network route and network distance between the scanner host and the target host.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Network route from scanner (172.30.0.2) to target (172.30.2.2):
172.30.0.2
172.30.2.2
Network distance between scanner and target: 2
```

Solution:

. . . continues on next page . . .

. . . continued from previous page . . .

Vulnerability Insight
For internal networks, the distances are usually small, often less than 4 hosts between scanner and target. For public targets the distance is greater and might be 10 hosts or more.

Log Method
A combination of the protocols ICMP and TCP is used to determine the route. This method is applicable for IPv4 only and it is also known as 'traceroute'.
Details: `Traceroute`
OID:1.3.6.1.4.1.25623.1.0.51662
Version used: `2022-10-17T11:13:19Z`

[return to 172.30.2.2]

2.1.12 Log 21/tcp

Log (CVSS: 0.0)
NVT: FTP Banner Detection

Summary
This script detects and reports a FTP Server Banner.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Remote FTP server banner:
220 (vsFTPd 3.0.3)
This is probably (a):
- vsFTPd
Server operating system information collected via "SYST" command:
215 UNIX Type: L8
Server status information collected via "STAT" command:
211-FTP server status:
     Connected to ::ffff:172.30.0.2
     Logged in as ftp
     TYPE: ASCII
     No session bandwidth limit
     Session timeout in seconds is 300
     Control connection is plain text
     Data connections will be plain text
     At session startup, client count was 1
     vsFTPd 3.0.3 - secure, fast, stable
211 End of status
```

Solution:

. . . continues on next page . . .

. . . continued from previous page . . .

Log Method
Details: `FTP Banner Detection`
OID:1.3.6.1.4.1.25623.1.0.10092
Version used: `2025-04-16T05:39:43Z`

Log (CVSS: 0.0)
NVT: Services

Summary
This plugin performs service detection.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
An FTP server is running on this port.
Here is its banner :
220 (vsFTPd 3.0.3)
```

Solution:

Vulnerability Insight
This plugin attempts to guess which service is running on the remote port(s). For instance, it searches for a web server which could listen on another port than 80 or 443 and makes this information available for other check routines.

Log Method
Details: `Services`
OID:1.3.6.1.4.1.25623.1.0.10330
Version used: `2025-03-05T05:38:53Z`

Log (CVSS: 0.0)
NVT: SSL/TLS: FTP Missing Support For AUTH TLS

Summary
The remote FTP server does not support the 'AUTH TLS' command.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
The remote FTP server does not support the 'AUTH TLS' command.
```

Solution:

. . . continues on next page . . .

. . . continued from previous page . . .

Log Method
Details: `SSL/TLS: FTP Missing Support For AUTH TLS`
OID:1.3.6.1.4.1.25623.1.0.108553
Version used: `2021-03-19T08:13:38Z`

Log (CVSS: 0.0)
NVT: vsFTPd FTP Server Detection

Summary
The script is grabbing the banner of a FTP server and attempts to identify a vsFTPd FTP Server and its version from the reply.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Detected vsFTPd
Version:       3.0.3
Location:      21/tcp
CPE:           cpe:/a:beasts:vsftpd:3.0.3
Concluded from version/product identification result:
220 (vsFTPd 3.0.3)
```

Solution:

Log Method
Details: `vsFTPd FTP Server Detection`
OID:1.3.6.1.4.1.25623.1.0.111050
Version used: `2023-07-26T05:05:09Z`

[return to 172.30.2.2]

2.1.13 Log 80/tcp

Log (CVSS: 0.0)
NVT: Allowed HTTP Methods Enumeration

Summary
Enumerates which HTTP methods are allowed.

Quality of Detection (QoD): 70%

Vulnerability Detection Result

. . . continues on next page . . .

. . . continued from previous page . . .

```
The following list contains the URLs and corresponding supported HTTP methods.
URL                                  | HTTP Methods
--------------------------------------------------------------------------------
↪----------------
http://proftpd-vuln.trabalho_vulnnet/ | OPTIONS,HEAD,GET,POST (obtained via HTTP
↪ OPTIONS method)
```

Solution:

Vulnerability Insight
- Basic HTTP methods: GET, HEAD, POST, PUT, DELETE, CONNECT, OPTIONS, TRACE
- Extended HTTP methods: ACL, BASELINE-CONTROL, BIND, CHECKIN, CHECKOUT, COPY, LABEL, LINK, LOCK, MERGE, MKACTIVITY, MKCALENDAR, MKCOL, MKREDIRECTREF, MKWORKSPACE, MOVE, ORDERPATCH, PATCH, PRI, PROPFIND, PROPPATCH, REBIND, REPORT, SEARCH, UNBIND, UNCHECKOUT, UNLINK, UNLOCK, UPDATE, UPDATEREDIRECTREF, VERSION-CONTROL

Log Method
Sends multiple HTTP requests and checks the responses.
Disclaimer:
- This enumeration script is provided 'as is' (means no support is given) and only providing rudimentary information about the possible enabled methods
- This script doesn't guarantee completeness or full reliability
For more reliable determination of the enabled HTTP methods please inspect the configuration of the web server manually and directly on the target host.
Details: `Allowed HTTP Methods Enumeration`
OID:1.3.6.1.4.1.25623.1.0.153974
Version used: `2025-02-28T05:38:49Z`

Log (CVSS: 0.0)
NVT: HTTP Security Headers Detection

Summary
All known security headers are being checked on the remote web server.
On completion a report will hand back whether a specific security header has been implemented (including its value and if it is deprecated) or is missing on the target.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Missing Headers                   | More Information
--------------------------------------------------------------------------------
↪--------------------------------------------------------------------------------
↪-----------------------------------------------
Content-Security-Policy           | https://owasp.org/www-project-secure-headers
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
↪/#content-security-policy
Cross-Origin-Embedder-Policy      | https://scotthelme.co.uk/coop-and-coep/, Not
↪e: This is an upcoming header
Cross-Origin-Opener-Policy        | https://scotthelme.co.uk/coop-and-coep/, Not
↪e: This is an upcoming header
Cross-Origin-Resource-Policy      | https://scotthelme.co.uk/coop-and-coep/, Not
↪e: This is an upcoming header
Document-Policy                   | https://w3c.github.io/webappsec-feature-poli
↪cy/document-policy#document-policy-http-header
Feature-Policy                    | https://owasp.org/www-project-secure-headers
↪/#feature-policy, Note: The Feature Policy header has been renamed to Permissi
↪ons Policy
Permissions-Policy                | https://w3c.github.io/webappsec-feature-poli
↪cy/#permissions-policy-http-header-field
Referrer-Policy                   | https://owasp.org/www-project-secure-headers
↪/#referrer-policy
Sec-Fetch-Dest                    | https://developer.mozilla.org/en-US/docs/Web
↪/HTTP/Headers#fetch_metadata_request_headers, Note: This is a new header suppo
↪rted only in newer browsers like e.g. Firefox 90
Sec-Fetch-Mode                    | https://developer.mozilla.org/en-US/docs/Web
↪/HTTP/Headers#fetch_metadata_request_headers, Note: This is a new header suppo
↪rted only in newer browsers like e.g. Firefox 90
Sec-Fetch-Site                    | https://developer.mozilla.org/en-US/docs/Web
↪/HTTP/Headers#fetch_metadata_request_headers, Note: This is a new header suppo
↪rted only in newer browsers like e.g. Firefox 90
Sec-Fetch-User                    | https://developer.mozilla.org/en-US/docs/Web
↪/HTTP/Headers#fetch_metadata_request_headers, Note: This is a new header suppo
↪rted only in newer browsers like e.g. Firefox 90
X-Content-Type-Options            | https://owasp.org/www-project-secure-headers
↪/#x-content-type-options
X-Frame-Options                   | https://owasp.org/www-project-secure-headers
↪/#x-frame-options
X-Permitted-Cross-Domain-Policies | https://owasp.org/www-project-secure-headers
↪/#x-permitted-cross-domain-policies
X-XSS-Protection                  | https://owasp.org/www-project-secure-headers
↪/#x-xss-protection, Note: Most major browsers have dropped / deprecated suppor
↪t for this header in 2020.
```

Solution:

Log Method

Details: `HTTP Security Headers Detection`
OID:1.3.6.1.4.1.25623.1.0.112081
Version used: `2025-03-21T15:40:43Z`

References

. . . continues on next page . . .

. . . continued from previous page . . .

```
url: https://owasp.org/www-project-secure-headers/
url: https://owasp.org/www-project-secure-headers/#div-headers
url: https://securityheaders.com/
```

Log (CVSS: 0.0)
NVT: HTTP Server Banner Enumeration

Summary
This script tries to detect / enumerate different HTTP server banner (e.g. from a frontend, backend or proxy server) by sending various different HTTP requests (valid and invalid ones).

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
It was possible to enumerate the following HTTP server banner(s):
Server banner                   | Enumeration technique
--------------------------------------------------------------------------------
↪-----------------
Server: Apache/2.4.59 (Debian) | Invalid HTTP 00.5 GET request (non-existent HTT
↪P version) to '/'
```

Solution:

Log Method
Details: HTTP Server Banner Enumeration
OID:1.3.6.1.4.1.25623.1.0.108708
Version used: 2025-01-31T15:39:24Z

Log (CVSS: 0.0)
NVT: HTTP Server type and version

Summary
This script detects and reports the HTTP Server's banner which might provide the type and version of it.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
The remote HTTP Server banner is:
Server: Apache/2.4.59 (Debian)
```

Solution:

. . . continues on next page . . .

. . . continued from previous page . . .

Log Method
Details: `HTTP Server type and version`
OID:1.3.6.1.4.1.25623.1.0.10107
Version used: `2023-08-01T13:29:10Z`

Log (CVSS: 0.0)
NVT: robot.txt / robots.txt exists on the Web Server (HTTP)

Summary
Web Servers can use a file called /robot(s).txt to ask search engines to ignore certain files and directories. By nature this file can not be used to protect private files from public read access.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
The file 'http://proftpd-vuln.trabalho_vulnnet/robots.txt' contains the followin
↪g:
User-agent: *
Disallow: security.html
Disallow: Security-Report.pdf
Disallow: private.html
Disallow: Trusted.html
```

Solution:
Solution type: Mitigation
Review the content of the /robot(s).txt file and consider removing the files from the server or protect them in other ways in case you actually intended non-public availability.

Vulnerability Insight
Any serious web search engine will honor the /robot(s).txt file and not scan the files and directories listed there.
Any entries listed in this file are not even hidden anymore.

Log Method
Details: `robot.txt / robots.txt exists on the Web Server (HTTP)`
OID:1.3.6.1.4.1.25623.1.0.10302
Version used: `2024-02-26T14:36:40Z`

References
`url: https://www.robotstxt.org/`
`url: https://www.robotstxt.org/norobots-rfc.txt`

Log (CVSS: 0.0)
NVT: Services

Summary
This plugin performs service detection.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`A web server is running on this port`

Solution:

Vulnerability Insight
This plugin attempts to guess which service is running on the remote port(s). For instance, it searches for a web server which could listen on another port than 80 or 443 and makes this information available for other check routines.

Log Method
Details: `Services`
OID:1.3.6.1.4.1.25623.1.0.10330
Version used: `2025-03-05T05:38:53Z`

Log (CVSS: 0.0)
NVT: Web Application Scanning Consolidation / Info Reporting

Summary
The script consolidates and reports various information for web application (formerly called 'CGI') scanning.
This information is based on the following scripts / settings:
- HTTP-Version Detection (OID: 1.3.6.1.4.1.25623.1.0.100034)
- No 404 check (OID: 1.3.6.1.4.1.25623.1.0.10386)
- Web mirroring / webmirror.nasl (OID: 1.3.6.1.4.1.25623.1.0.10662)
- Directory Scanner / DDI_Directory_Scanner.nasl (OID: 1.3.6.1.4.1.25623.1.0.11032)
- The configured 'cgi_path' within the 'Scanner Preferences' of the scan config in use
- The configured 'Enable CGI scanning', 'Enable generic web application scanning' and 'Add historic /scripts and /cgi-bin to directories for CGI scanning' within the 'Global variable settings' of the scan config in use
If you think any of this information is wrong please report it to the referenced community forum.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The Hostname/IP "proftpd-vuln.trabalho_vulnnet" was used to access the remote ho
↪st.
Generic web application scanning is disabled for this host via the "Enable gener
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
↪ic web application scanning" option within the "Global variable settings" of t
↪he scan config in use.
Requests to this service are done via HTTP/1.1.
This service seems to be able to host PHP scripts.
This service seems to be able to host ASP scripts.
The User-Agent "Mozilla/5.0 [en] (X11, U; OpenVAS-VT <version replaced>)" was us
↪ed to access the remote host.
Historic /scripts and /cgi-bin are not added to the directories used for web app
↪lication scanning. You can enable this again with the "Add historic /scripts a
↪nd /cgi-bin to directories for CGI scanning" option within the "Global variabl
↪e settings" of the scan config in use.
The following directories were used for web application scanning:
http://proftpd-vuln.trabalho_vulnnet/
While this is not, in and of itself, a bug, you should manually inspect these di
↪rectories to ensure that they are in compliance with company security standard
↪s
The following directories were excluded from web application scanning because th
↪e "Regex pattern to exclude directories from CGI scanning" setting of the VT "
↪Global variable settings" (OID: 1.3.6.1.4.1.25623.1.0.12288) for this scan was
↪: "/(index\.php|image|img|css|js$|js/|javascript|style|theme|icon|jquery|graph
↪ic|grafik|picture|bilder|thumbnail|media/|skins?/)"
http://proftpd-vuln.trabalho_vulnnet/icons
```

Solution:

Log Method

Details: Web Application Scanning Consolidation / Info Reporting
OID:1.3.6.1.4.1.25623.1.0.111038
Version used: 2026-01-13T05:47:36Z

References

url: https://forum.greenbone.net/c/vulnerability-tests/7

[return to 172.30.2.2]