Scan Report

January 26, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone "Coordinated Universal Time", which is abbreviated "UTC". The task was " hgdfdghgdgd". The scan started at Mon Jan 26 01:47:47 2026 UTC and ended at Mon Jan 26 14:04:13 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1 Result Overview **2**

2 Results per Host **2**

2.1 172.31.1.101 . . . 2

2.1.1 High 10000/tcp . . . 2

2.1.2 High 53/udp . . . 9

2.1.3 High 53/tcp . . . 36

2.1.4 Medium 10000/tcp . . . 63

2.1.5 Medium 53/udp . . . 68

2.1.6 Medium 53/tcp . . . 81

2.1.7 Low general/tcp . . . 92

2.1.8 Low general/icmp . . . 93

2.1.9 Log 10000/tcp . . . 94

2.1.10 Log general/tcp . . . 107

2.1.11 Log 53/udp . . . 111

2.1.12 Log general/CPE-T . . . 112

2.1.13 Log 53/tcp . . . 113

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
172.31.1.101 bind.trabalho_vulnnet	0	45	22	2	25	0
Total: 1	0	45	22	2	25	0

Vendor security updates are not trusted.
Overrides are off. Even when a result has an override, this report uses the actual threat of the result.
Information on overrides is included in the report.
Notes are included in the report.
This report might not show details of all issues that were found.
Issues with the threat level "Critical" are not shown.
Issues with the threat level "Debug" are not shown.

This report contains all 94 results selected by the filtering described above. Before filtering there were 5586 results.

2 Results per Host

2.1 172.31.1.101

Host scan start	Mon Jan 26 03:30:46 2026 UTC
Host scan end	Mon Jan 26 05:15:00 2026 UTC

Service (Port)	Threat Level
10000/tcp	High
53/udp	High
53/tcp	High
10000/tcp	Medium
53/udp	Medium
53/tcp	Medium
general/tcp	Low
general/icmp	Low
10000/tcp	Log
general/tcp	Log
53/udp	Log
general/CPE-T	Log
53/tcp	Log

2.1.1 High 10000/tcp

High (CVSS: 8.8)
NVT: Webmin < 1.930 RCE Vulnerability

Summary
Webmin is prone to an authenticated remote code execution (RCE) vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Installed version: 1.920
Fixed version:     1.930
Installation
path / port:       /
```

Impact
Successful exploitation would allow an authenticated attacker to gain control over the target system.

Solution:
Solution type: VendorFix
Update to version 1.930 or later.

Affected Software/OS
Webmin version 1.920 and prior.

Vulnerability Insight
rpc.cgi in Webmin through 1.920 allows authenticated Remote Code Execution via a crafted object name because unserialise_variable makes an eval call.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Webmin < 1.930 RCE Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.142804
Version used: `2024-06-28T05:05:33Z`

References

```
cve: CVE-2019-15642
url: https://www.calypt.com/blog/index.php/authenticated-rce-on-webmin/
url: https://github.com/webmin/webmin/commit/df8a43fb4bdc9c858874f72773bcba597ae
↪9432c
cert-bund: CB-K19/0786
```

High (CVSS: 8.8)
NVT: Webmin <= 1.930 XXE Vulnerability

Summary

. . . continues on next page . . .

. . . continued from previous page . . .

Webmin is prone to an authenticated XXE vulnerability in xmlrpc.cgi.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Installed version: 1.920
Fixed version:     None
Installation
path / port:       /
```

Impact

Successful exploitation would allow an authenticated attacker to gain control over the target system.

Solution:

Solution type: WillNotFix

No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.

Affected Software/OS

Webmin version 1.930 and prior.

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.

Details: `Webmin <= 1.930 XXE Vulnerability`

OID:1.3.6.1.4.1.25623.1.0.142805

Version used: `2021-09-08T08:01:40Z`

References

```
cve: CVE-2019-15642
url: https://www.calypt.com/blog/index.php/authenticated-xxe-on-webmin/
cert-bund: CB-K19/0786
```

High (CVSS: 7.8)

NVT: Webmin <= 1.941 RCE Vulnerability

Summary

Webmin is prone to an authenticated remote code execution (RCE) vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Installed version: 1.920
Fixed version:     None
```

. . . continues on next page . . .

. . . continued from previous page . . .

Solution:
Solution type: WillNotFix
No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.

Affected Software/OS
Webmin through version 1.941. The vendor does not classify this vulnerability as workable exploit, as it requires that the attacker already knows the root password. Hence there is no fix for it in Webmin.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Webmin <= 1.941 RCE Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.141897
Version used: `2024-06-28T15:38:46Z`

References
`cve: CVE-2019-9624`
`url: https://www.exploit-db.com/exploits/46201`
`url: http://www.webmin.com/security.html`

High (CVSS: 8.8)
NVT: Webmin <= 1.941 RCE Vulnerability

Summary
Webmin is prone to a remote code execution (RCE) vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
Installed version: 1.920
Fixed version:     None
Installation
path / port:       /
```

Impact
Successful exploitation would allow an authorized attacker to gain control over the target system.

Solution:
Solution type: WillNotFix
No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.

. . . continues on next page . . .

. . . continued from previous page . . .

Affected Software/OS
Webmin through version 1.941.

Vulnerability Insight
Any user authorized to the 'Package Updates' module can execute arbitrary commands with root privileges via the data parameter to update.cgi.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Webmin <= 1.941 RCE Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.113409
Version used: `2024-06-28T05:05:33Z`

References
`cve: CVE-2019-12840`
`url: https://pentest.com.tr/exploits/Webmin-1910-Package-Updates-Remote-Command-`
`↪Execution.html`
`url: https://www.exploit-db.com/exploits/46984`

High (CVSS: 8.8)
NVT: Webmin <= 1.983 RCE Vulnerability

Summary
Webmin is prone to a remote code execution (RCE) vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
Installed version: 1.920
Fixed version:     None
Installation
path / port:       /
```

Solution:
Solution type: WillNotFix
No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.

Affected Software/OS
Webmin version 1.983 and prior.

Vulnerability Insight

. . . continues on next page . . .

. . . continued from previous page . . .

Arbitrary command execution can occur in Webmin. Any user authorized for the Package Updates module can execute arbitrary commands with root privileges via vectors involving %0A and %0C.
NOTE: this issue exists because of an incomplete fix for CVE-2019-12840.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Webmin <= 1.983 RCE Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.145090
Version used: `2021-12-23T08:45:36Z`

References
`cve: CVE-2020-35606`
`url: https://www.pentest.com.tr/exploits/Webmin-1962-PU-Escape-Bypass-Remote-Com`
`↪mand-Execution.html`

High (CVSS: 8.8)
NVT: Webmin <= 1.984 Multiple Vulnerabilities

Summary
Webmin is prone to multiple vulnerabilities.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
Installed version: 1.920
Fixed version:     1.990
Installation
path / port:       /
```

Solution:
Solution type: VendorFix
Update to version 1.990 or later.

Affected Software/OS
Webmin version 1.984 and prior.

Vulnerability Insight
The following vulnerabilities exist:
- CVE-2022-0824: Improper access control leads to remote code execution (RCE)
- CVE-2022-0829: Improper authorization

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Webmin <= 1.984 Multiple Vulnerabilities`

. . . continues on next page . . .

. . . continued from previous page . . .

OID:1.3.6.1.4.1.25623.1.0.147747
Version used: 2022-04-27T08:53:35Z

References

```
cve: CVE-2022-0824
cve: CVE-2022-0829
url: https://www.webmin.com/security.html
url: https://huntr.dev/bounties/d0049a96-de90-4b1a-9111-94de1044f295/
url: https://huntr.dev/bounties/f2d0389f-d7d1-4f34-9f9d-268b0a0da05e/
url: https://github.com/webmin/webmin/commit/eeeea3c097f5cc473770119f7ac61f1dcfa
↪671b9
url: https://github.com/webmin/webmin/commit/39ea464f0c40b325decd6a5bfb7833fa4a1
↪42e38
cert-bund: CB-K22/0267
```

High (CVSS: 8.8)
NVT: Webmin <= 1.991 Privilege Escalation Vulnerability

Summary
Webmin is prone to a privilege escalation vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Installed version: 1.920
Fixed version:     1.994
Installation
path / port:       /
```

Solution:
Solution type: VendorFix
Update to version 1.994 or later.

Affected Software/OS
Webmin version 1.991 and prior.

Vulnerability Insight
Webmin, when the Authentic theme is used, allows remote code execution when a user has been manually created (i.e., not created in Virtualmin or Cloudmin). This occurs because settings-editor_write.cgi does not properly restrict the file parameter.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Webmin <= 1.991 Privilege Escalation Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.127014

. . . continues on next page . . .

. . . continued from previous page . . .

Version used: 2022-05-26T03:04:21Z

References

```
cve: CVE-2022-30708
url: https://github.com/esp0xdeadbeef/rce_webmin
url: https://github.com/webmin/webmin/issues/1635
url: https://www.webmin.com/security.html
cert-bund: CB-K22/0609
```

[return to 172.31.1.101]

2.1.2 High 53/udp

High (CVSS: 7.5)
NVT: ISC BIND 'deny-answer-aliases' Denial of Service Vulnerability

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

ISC BIND is prone to a denial of service vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.4-P1
Installation
path / port:       53/udp
```

Impact

Successful exploitation will allow remote attackers to cause a denial of service (assertion failure).

Solution:

Solution type: VendorFix

Update to ISC BIND version 9.9.13-P1 or 9.10.8-P1 or 9.11.4-P1 or 9.12.2-P1 or 9.11.3-S3 or later. Please see the references for more information.

Affected Software/OS

ISC BIND versions 9.7.0 through 9.8.8, 9.9.0 through 9.9.13, 9.10.0 through 9.10.8, 9.11.0 through 9.11.4, 9.12.0 through 9.12.2 and 9.13.0 through 9.13.2.

. . . continues on next page . . .

. . . continued from previous page . . .

Vulnerability Insight
The flaw exists due to a defect in the feature 'deny-answer-aliases' which leads to assertion failure in 'name.c'.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND 'deny-answer-aliases' Denial of Service Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.813750
Version used: `2023-07-20T05:05:17Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
```
cve: CVE-2018-5740
url: https://kb.isc.org/docs/aa-01639
cert-bund: WID-SEC-2025-1193
cert-bund: CB-K18/0842
dfn-cert: DFN-CERT-2021-2273
dfn-cert: DFN-CERT-2019-2042
dfn-cert: DFN-CERT-2019-1594
dfn-cert: DFN-CERT-2019-1119
dfn-cert: DFN-CERT-2019-0436
dfn-cert: DFN-CERT-2019-0069
dfn-cert: DFN-CERT-2018-2435
dfn-cert: DFN-CERT-2018-1562
```

High (CVSS: 7.5)
NVT: ISC BIND Access Control Vulnerability (Jun 2018) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary
Some versions of BIND can improperly permit recursive query service to unauthorized clients.

Quality of Detection (QoD): 30%

Vulnerability Detection Result
```
Installed version: 9.11.3
Fixed version:     Workaround
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
Installation
path / port:        53/udp
```

Solution:
Solution type: Workaround
See the vendor advisory for workarounds.

Affected Software/OS
ISC BIND 9.9.12, 9.10.7, 9.11.3, 9.12.0->9.12.1-P2, 9.13.0, 9.9.12-S1, 9.10.7-S1, 9.11.3-S1, and 9.11.3-S2.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND Access Control Vulnerability (Jun 2018) - Linux`
OID:1.3.6.1.4.1.25623.1.0.141179
Version used: `2023-07-20T05:05:17Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
`cve: CVE-2018-5738`
`url: https://kb.isc.org/docs/aa-01616`
`cert-bund: CB-K18/0723`
`dfn-cert: DFN-CERT-2019-0436`
`dfn-cert: DFN-CERT-2018-1134`

High (CVSS: 8.1)
NVT: ISC BIND Buffer Overflow Vulnerability (CVE-2020-8625) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary
ISC BIND is prone to a buffer overflow vulnerability in the GSSAPI security policy negotiation.

Quality of Detection (QoD): 30%

Vulnerability Detection Result
`Installed version: 9.11.3`

. . . continues on next page . . .

. . . continued from previous page . . .

```
Fixed version:     9.11.28
Installation
path / port:       53/udp
```

Impact
The most likely outcome of a successful exploitation of the vulnerability is a crash of the named process. However, remote code execution, while unproven, is theoretically possible.

Solution:
Solution type: VendorFix
Update to version 9.11.28, 9.16.12, 9.11.28-S1, 9.16.12-S1 or later.

Affected Software/OS
BIND 9.5.0 - 9.11.27, 9.12.0 - 9.16.11, 9.11.3-S1 - 9.11.27-S1 and 9.16.8-S1 - 9.16.11-S1.

Vulnerability Insight
GSS-TSIG is an extension to the TSIG protocol which is intended to support the secure exchange of keys for use in verifying the authenticity of communications between parties on a network.
SPNEGO is a negotiation mechanism used by GSSAPI, the application protocol interface for GSS-TSIG.
The SPNEGO implementation used by BIND has been found to be vulnerable to a buffer overflow attack.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND Buffer Overflow Vulnerability (CVE-2020-8625) - Linux`
OID:1.3.6.1.4.1.25623.1.0.145412
Version used: `2021-08-17T14:01:00Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
`cve: CVE-2020-8625`
`url: https://kb.isc.org/docs/cve-2020-8625`
`cert-bund: WID-SEC-2023-0063`
`cert-bund: CB-K21/0190`
`dfn-cert: DFN-CERT-2022-0074`
`dfn-cert: DFN-CERT-2021-0955`
`dfn-cert: DFN-CERT-2021-0556`
`dfn-cert: DFN-CERT-2021-0375`

High (CVSS: 8.6)
NVT: ISC BIND Cache Poisoning Vulnerability (CVE-2025-40778) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary
ISC BIND is prone to cache poisoning attacks with unsolicited RRs.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.18.41
Installation
path / port:       53/udp
```

Impact
Forged records can be injected into cache during a query, which can potentially affect resolution of future queries.

Solution:
Solution type: VendorFix
Update to version 9.18.41, 9.18.41-S1, 9.20.15, 9.20.15-S1, 9.21.14 or later.

Affected Software/OS
ISC BIND versions 9.11.0 through 9.16.50, 9.18.0 through 9.18.39, 9.20.0 through 9.20.13, 9.21.0 through 9.21.12, 9.11.3-S1 through 9.16.50-S1, 9.18.11-S1 through 9.18.39-S1 and 9.20.9-S1 through 9.20.13-S1.
Vendor notes:
- Authoritative services are believed to be unaffected by this vulnerability but it is important to read: [link moved to references]
- Resolvers are affected by this vulnerability.

Vulnerability Insight
Under certain circumstances, BIND is too lenient when accepting records from answers, allowing an attacker to inject forged data into the cache.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND Cache Poisoning Vulnerability (CVE-2025-40778) - Linux`
OID:1.3.6.1.4.1.25623.1.0.119202
Version used: `2025-10-24T05:39:31Z`

Product Detection Result

. . . continues on next page . . .

. . . continued from previous page . . .

Product: cpe:/a:isc:bind:9.11.3
Method: ISC BIND Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.145294)

References

```
cve: CVE-2025-40778
url: https://kb.isc.org/docs/cve-2025-40778
url: https://kb.isc.org/docs/why-does-my-authoritative-server-make-recursive-que
↪ries
cert-bund: WID-SEC-2025-2392
dfn-cert: DFN-CERT-2026-0243
dfn-cert: DFN-CERT-2026-0149
dfn-cert: DFN-CERT-2026-0148
dfn-cert: DFN-CERT-2026-0130
dfn-cert: DFN-CERT-2025-3313
dfn-cert: DFN-CERT-2025-3256
dfn-cert: DFN-CERT-2025-3234
dfn-cert: DFN-CERT-2025-3106
dfn-cert: DFN-CERT-2025-3088
dfn-cert: DFN-CERT-2025-2964
```

High (CVSS: 8.6)
NVT: ISC BIND Cache-Poisoning Vulnerability (CVE-2025-40776, Birthday Attack) - Linux

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

ISC BIND is prone to a cache-poisoning vulnerability (Birthday Attack against Resolvers supporting ECS).

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.20.11
Installation
path / port:       53/udp
```

Impact

. . . continues on next page . . .

. . . continued from previous page . . .

A resolver configured to send ECS options to authoritative servers can be compelled to make queries that slightly increase the odds of guessing the source port and other details necessary to bypass the original birthday cache poisoning attack mitigations. As a result of this weakness, a resolver with ECS enabled is more vulnerable to successful cache poisoning via spoofed query responses than one that does not implement this feature.

Solution:
Solution type: VendorFix
Update to version 9.20.11, 9.18.38-S1, 9.20.11-S1 or later.

Affected Software/OS
ISC BIND version 9.0.0 through 9.20.10, 9.11.3-S1 through 9.16.50-S1, 9.18.11-S1 through 9.18.37-S1 and 9.20.9-S1 through 9.20.10-S1.

Vulnerability Insight
A named caching resolver that is configured to send ECS (EDNS Client Subnet) options may be vulnerable to a cache-poisoning attack.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND Cache-Poisoning Vulnerability (CVE-2025-40776, Birthday Attack) - Linux`
OID:1.3.6.1.4.1.25623.1.0.154963
Version used: `2025-07-18T05:44:10Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
`cve: CVE-2025-40776`
`url: https://kb.isc.org/docs/cve-2025-40776`
`cert-bund: WID-SEC-2025-1585`

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2018-5743) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary

. . . continues on next page . . .

. . . continued from previous page . . .

ISC BIND is prone to a denial of service vulnerability due to ineffective simultaneous TCP client limiting.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.6-P1
Installation
path / port:       53/udp
```

Impact

By exploiting the failure to limit simultaneous TCP connections, an attacker can deliberately exhaust the pool of file descriptors available to named, potentially affecting network connections and the management of files such as log files or zone journal files.
In cases where the named process is not limited by OS-enforced per-process limits, this could additionally potentially lead to exhaustion of all available free file descriptors on that system.

Solution:
Solution type: VendorFix
Update to version 9.11.6-P1, 9.12.4-P1, 9.14.1, 9.11.5-S6, 9.11.6-S1 or later.

Affected Software/OS

BIND 9.9.0 to 9.10.8-P1, 9.11.0 to 9.11.6, 9.12.0 to 9.12.4, 9.14.0. BIND 9 Supported Preview Edition versions 9.9.3-S1 to 9.11.5-S3, and 9.11.5-S5. Versions 9.13.0 to 9.13.7 of the 9.13 development branch.

Vulnerability Insight

By design, BIND is intended to limit the number of TCP clients that can be connected at any given time. The number of allowed connections is a tunable parameter which, if unset, defaults to a conservative value for most servers. Unfortunately, the code which was intended to limit the number of simultaneous connections contains an error which can be exploited to grow the number of simultaneous connections beyond this limit.

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2018-5743) - Linux`
OID:1.3.6.1.4.1.25623.1.0.142320
Version used: `2021-08-30T11:01:18Z`

Product Detection Result

Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

. . . continues on next page . . .

. . . continued from previous page . . .

References

```
cve: CVE-2018-5743
url: https://kb.isc.org/docs/cve-2018-5743
cert-bund: WID-SEC-2025-1196
cert-bund: WID-SEC-2025-1195
cert-bund: CB-K19/0423
cert-bund: CB-K19/0349
dfn-cert: DFN-CERT-2020-0048
dfn-cert: DFN-CERT-2019-2042
dfn-cert: DFN-CERT-2019-1594
dfn-cert: DFN-CERT-2019-1119
dfn-cert: DFN-CERT-2019-0935
dfn-cert: DFN-CERT-2019-0896
dfn-cert: DFN-CERT-2019-0833
```

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2021-25215) - Linux

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.31
Installation
path / port:       53/udp
```

Impact

When a vulnerable version of named receives a query for a record triggering the flaw described above, the named process will terminate due to a failed assertion check.

Solution:

Solution type: VendorFix

Update to version 9.11.31, 9.16.15, 9.17.12, 9.11.31-S1, 9.16.15-S1 or later.

Affected Software/OS

BIND 9.0.0 through 9.11.29, 9.12.0 through 9.16.13, 9.9.3-S1 through 9.11.29-S1, 9.16.8-S1 through 9.16.13-S1 and 9.17.0 through 9.17.11.

. . . continues on next page . . .

. . . continued from previous page . . .

Vulnerability Insight
DNAME records, described in RFC 6672, provide a way to redirect a subtree of the domain name tree in the DNS. A flaw in the way named processes these records may trigger an attempt to add the same RRset to the ANSWER section more than once. This causes an assertion check in BIND to fail.
DNAME records are processed by both authoritative and recursive servers. For authoritative servers, the DNAME record triggering the flaw can be retrieved from a zone database. For servers performing recursion, such a record is processed in the course of a query sent to an authoritative server.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2021-25215) - Linux`
OID:1.3.6.1.4.1.25623.1.0.145865
Version used: `2021-08-17T14:01:00Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
```
cve: CVE-2021-25215
url: https://kb.isc.org/docs/cve-2021-25215
cert-bund: WID-SEC-2025-2027
cert-bund: WID-SEC-2022-0623
cert-bund: CB-K22/0012
cert-bund: CB-K21/0452
dfn-cert: DFN-CERT-2022-0566
dfn-cert: DFN-CERT-2021-1504
dfn-cert: DFN-CERT-2021-0915
dfn-cert: DFN-CERT-2021-0909
dfn-cert: DFN-CERT-2021-0898
```

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2022-38177) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

. . . continues on next page . . .

. . . continued from previous page . . .

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.16.33
Installation
path / port:       53/udp
```

Impact

By spoofing the target resolver with responses that have a malformed ECDSA signature, an attacker can trigger a small memory leak. It is possible to gradually erode available memory to the point where named crashes for lack of resources.

Solution:

Solution type: VendorFix

Update to version 9.16.33, 9.16.33-S1 or later.

Affected Software/OS

ISC BIND versions 9.8.4 through 9.16.32, 9.9.4-S1 through 9.11.37-S1 and 9.16.8-S1 through 9.16.32-S1.

Vulnerability Insight

The DNSSEC verification code for the ECDSA algorithm leaks memory when there is a signature length mismatch.

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.

Details: `ISC BIND DoS Vulnerability (CVE-2022-38177) - Linux`

OID:1.3.6.1.4.1.25623.1.0.124172

Version used: `2023-10-18T05:05:17Z`

Product Detection Result

Product: `cpe:/a:isc:bind:9.11.3`

Method: `ISC BIND Detection Consolidation`

OID: 1.3.6.1.4.1.25623.1.0.145294)

References

```
cve: CVE-2022-38177
url: https://kb.isc.org/docs/cve-2022-38177
cert-bund: WID-SEC-2024-0794
cert-bund: WID-SEC-2022-1492
dfn-cert: DFN-CERT-2023-1162
dfn-cert: DFN-CERT-2022-2664
dfn-cert: DFN-CERT-2022-2354
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2022-2191
dfn-cert: DFN-CERT-2022-2099
```

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2022-38178) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.16.33
Installation
path / port:       53/udp
```

Impact
By spoofing the target resolver with responses that have a malformed EdDSA signature, an attacker can trigger a small memory leak. It is possible to gradually erode available memory to the point where named crashes for lack of resources.

Solution:
Solution type: VendorFix
Update to version 9.16.33, 9.18.7, 9.19.5, 9.16.33-S1 or later.

Affected Software/OS
ISC BIND versions 9.9.12 through 9.9.13, 9.10.7 through 9.10.8, 9.11.4-S1 through 9.11.37-S1, 9.16.8-S1 through 9.16.32-S1, 9.18.0 through 9.18.6 and 9.19.0 through 9.19.4.

Vulnerability Insight
The DNSSEC verification code for the EdDSA algorithm leaks memory when there is a signature length mismatch.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2022-38178) - Linux`
OID:1.3.6.1.4.1.25623.1.0.124174
Version used: `2023-10-18T05:05:17Z`

. . . continues on next page . . .

. . . continued from previous page . . .

Product Detection Result
Product: cpe:/a:isc:bind:9.11.3
Method: ISC BIND Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
cve: CVE-2022-38178
url: https://kb.isc.org/docs/cve-2022-38178
cert-bund: WID-SEC-2024-0794
cert-bund: WID-SEC-2022-1492
dfn-cert: DFN-CERT-2023-1162
dfn-cert: DFN-CERT-2022-2664
dfn-cert: DFN-CERT-2022-2354
dfn-cert: DFN-CERT-2022-2099

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2023-2828) - Linux

Product detection result
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result
Installed version: 9.11.3
Fixed version: 9.16.42
Installation
path / port: 53/udp

Impact
By exploiting this flaw, an attacker can cause the amount of memory used by a named resolver to go well beyond the configured max-cache-size limit. The effectiveness of the attack depends on a number of factors (e.g. query load, query patterns), but since the default value of the max-cache-size statement is 90%, in the worst case the attacker can exhaust all available memory on the host running named, leading to a denial-of-service condition.

Solution:
Solution type: VendorFix
Update to version 9.16.42, 9.18.16, 9.19.14, 9.16.42-S1, 9.18.16-S1 or later.

. . . continues on next page . . .

. . . continued from previous page . . .

Affected Software/OS
ISC BIND versions 9.11.0 through 9.16.41, 9.18.0 through 9.18.15, 9.19.0 through 9.19.13, 9.11.3-S1 through 9.16.41-S1 and 9.18.11-S1 through 9.18.15-S1.

Vulnerability Insight
Every named instance configured to run as a recursive resolver maintains a cache database holding the responses to the queries it has recently sent to authoritative servers. The size limit for that cache database can be configured using the max-cache-size statement in the configuration file, it defaults to 90% of the total amount of memory available on the host. When the size of the cache reaches 7/8 of the configured limit, a cache-cleaning algorithm starts to remove expired and/or least-recently used RRsets from the cache, to keep memory use below the configured limit.
It has been discovered that the effectiveness of the cache-cleaning algorithm used in named can be severely diminished by querying the resolver for specific RRsets in a certain order, effectively allowing the configured max-cache-size limit to be significantly exceeded.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2023-2828) - Linux`
OID:1.3.6.1.4.1.25623.1.0.149838
Version used: `2023-10-13T05:06:10Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
`cve: CVE-2023-2828`
`url: https://kb.isc.org/docs/cve-2023-2828`
`cert-bund: WID-SEC-2024-1591`
`cert-bund: WID-SEC-2024-0794`
`cert-bund: WID-SEC-2024-0064`
`cert-bund: WID-SEC-2023-2917`
`cert-bund: WID-SEC-2023-2625`
`cert-bund: WID-SEC-2023-1533`
`dfn-cert: DFN-CERT-2023-1551`
`dfn-cert: DFN-CERT-2023-1444`
`dfn-cert: DFN-CERT-2023-1434`

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2023-3341) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`

. . . continues on next page . . .

. . . continued from previous page . . .

Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.16.44
Installation
path / port:       53/udp
```

Impact
By sending a specially crafted message over the control channel, an attacker can cause the packet-parsing code to run out of available stack memory, causing named to terminate unexpectedly. However, the attack only works in environments where the stack size available to each process/thread is small enough. The exact threshold depends on multiple factors and is therefore impossible to specify universally.

Solution:
Solution type: VendorFix
Update to version 9.16.44, 9.18.19, 9.19.17, 9.16.44-S1, 9.18.19-S1 or later.

Affected Software/OS
ISC BIND versions 9.2.0 through 9.16.43, 9.18.0 through 9.18.18, 9.19.0 through 9.19.16, 9.9.3-S1 through 9.16.43-S1 and 9.18.0-S1 through 9.18.18-S1.

Vulnerability Insight
The code that processes control channel messages sent to named calls certain functions recursively during packet parsing. Recursion depth is only limited by the maximum accepted packet size. Depending on the environment, this may cause the packet-parsing code to run out of available stack memory, causing named to terminate unexpectedly. Since each incoming control channel message is fully parsed before its contents are authenticated, exploiting this flaw does not require the attacker to hold a valid RNDC key. Only network access to the control channel's configured TCP port is necessary.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: ISC BIND DoS Vulnerability (CVE-2023-3341) - Linux
OID:1.3.6.1.4.1.25623.1.0.104923
Version used: 2023-10-13T05:06:10Z

Product Detection Result
Product: cpe:/a:isc:bind:9.11.3

. . . continues on next page . . .

. . . continued from previous page . . .

Method: ISC BIND Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.145294)

References

```
cve: CVE-2023-3341
url: https://kb.isc.org/docs/cve-2023-3341
cert-bund: WID-SEC-2024-1591
cert-bund: WID-SEC-2024-0064
cert-bund: WID-SEC-2023-2412
dfn-cert: DFN-CERT-2025-0010
dfn-cert: DFN-CERT-2023-3177
dfn-cert: DFN-CERT-2023-2941
dfn-cert: DFN-CERT-2023-2223
```

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2023-4408) - Linux

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.16.48
Installation
path / port:       53/udp
```

Impact

By flooding the target server with queries exploiting this flaw an attacker can significantly impair the server's performance, effectively denying legitimate clients access to the DNS resolution service.

Solution:

Solution type: VendorFix

Update to version 9.16.48, 9.18.24, 9.19.21, 9.16.48-S1, 9.18.24-S1 or later.

Affected Software/OS

. . . continues on next page . . .

. . . continued from previous page . . .

ISC BIND version 9.0.0 through 9.16.45, 9.18.0 through 9.18.21, 9.19.0 through 9.19.19, 9.9.3-S1 through 9.11.37-S1, 9.16.8-S1 through 9.16.45-S1 and 9.18.11-S1 through 9.18.21-S1.

Vulnerability Insight
The DNS message parsing code in named includes a section whose computational complexity is overly high. It does not cause problems for typical DNS traffic, but crafted queries and responses may cause excessive CPU load on the affected named instance by exploiting this flaw. This issue affects both authoritative servers and recursive resolvers.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2023-4408) - Linux`
OID:1.3.6.1.4.1.25623.1.0.151725
Version used: `2024-02-15T14:37:33Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
```
cve: CVE-2023-4408
url: https://kb.isc.org/docs/cve-2023-4408
cert-bund: WID-SEC-2024-1313
cert-bund: WID-SEC-2024-1307
cert-bund: WID-SEC-2024-1248
cert-bund: WID-SEC-2024-1226
cert-bund: WID-SEC-2024-0386
dfn-cert: DFN-CERT-2025-0041
dfn-cert: DFN-CERT-2025-0010
dfn-cert: DFN-CERT-2024-1516
dfn-cert: DFN-CERT-2024-1223
dfn-cert: DFN-CERT-2024-0977
dfn-cert: DFN-CERT-2024-0375
```

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2024-11187) - Linux

Product detection result
```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

. . . continues on next page . . .

. . . continued from previous page . . .

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.18.33
Installation
path / port:       53/udp
```

Impact

A named instance vulnerable to this issue can be compelled to consume excessive CPU resources up to the point where exhaustion of resources effectively prevents the server from responding to other client queries. This issue is most likely to affect resolvers but could also degrade authoritative server performance.
- Authoritative servers are affected by this vulnerability.
- Resolvers are affected by this vulnerability.

Solution:
Solution type: VendorFix
Update to version 9.18.33, 9.20.5, 9.21.4, 9.18.33-S1 or later.

Affected Software/OS

ISC BIND version 9.11.37 and prior, 9.16.0 through 9.16.50, 9.18.0 through 9.18.32, 9.20.0 through 9.20.4, 9.21.0 through 9.21.3, 9.11.3-S1 through 9.11.37-S1, 9.16.8-S1 through 9.16.50-S1 and 9.18.11-S1 through 9.18.32-S1.

Vulnerability Insight

It is possible to construct a zone such that some queries to it will generate responses containing numerous records in the Additional section. An attacker sending many such queries can cause either the authoritative server itself or an independent resolver to use disproportionate resources processing the queries. Zones will usually need to have been deliberately crafted to attack this exposure.

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2024-11187) - Linux`
OID:1.3.6.1.4.1.25623.1.0.153891
Version used: `2025-01-31T05:37:27Z`

Product Detection Result

Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References

. . . continues on next page . . .

. . . continued from previous page . . .

```
cve: CVE-2024-11187
url: https://kb.isc.org/docs/cve-2024-11187
cert-bund: WID-SEC-2025-0217
dfn-cert: DFN-CERT-2025-1410
dfn-cert: DFN-CERT-2025-0994
dfn-cert: DFN-CERT-2025-0993
dfn-cert: DFN-CERT-2025-0720
dfn-cert: DFN-CERT-2025-0664
dfn-cert: DFN-CERT-2025-0662
dfn-cert: DFN-CERT-2025-0575
dfn-cert: DFN-CERT-2025-0574
dfn-cert: DFN-CERT-2025-0300
dfn-cert: DFN-CERT-2025-0269
```

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2024-1737) - Linux

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.18.28
Installation
path / port:       53/udp
```

Solution:

Solution type: VendorFix

Update to version 9.18.28, 9.20.0, 9.18.28-S1 or later.

Affected Software/OS

ISC BIND version 9.11.0 through 9.11.37, 9.16.0 through 9.16.50, 9.18.0 through 9.18.27, 9.19.0 through 9.19.24, 9.11.4-S1 through 9.11.37-S1, 9.16.8-S1 through 9.16.50-S1 and 9.18.11-S1 through 9.18.27-S1.

Vulnerability Insight

. . . continues on next page . . .

. . . continued from previous page . . .

Resolver caches and authoritative zone databases that hold significant numbers of RRs for the same hostname (of any RTYPE) can suffer from degraded performance as content is being added or updated, and also when handling client queries for this name.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2024-1737) - Linux`
OID:1.3.6.1.4.1.25623.1.0.152740
Version used: `2024-07-26T05:05:35Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
```
cve: CVE-2024-1737
url: https://kb.isc.org/docs/cve-2024-1737
url: https://www.cisa.gov/news-events/alerts/2024/07/24/isc-releases-security-ad
↪visories-bind-9
cert-bund: WID-SEC-2025-0794
cert-bund: WID-SEC-2025-0225
cert-bund: WID-SEC-2024-1700
dfn-cert: DFN-CERT-2025-2802
dfn-cert: DFN-CERT-2025-0933
dfn-cert: DFN-CERT-2024-2455
dfn-cert: DFN-CERT-2024-2392
dfn-cert: DFN-CERT-2024-2326
dfn-cert: DFN-CERT-2024-2298
dfn-cert: DFN-CERT-2024-2295
dfn-cert: DFN-CERT-2024-2071
dfn-cert: DFN-CERT-2024-2040
dfn-cert: DFN-CERT-2024-1912
```

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2024-1975) - Linux

Product detection result
```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

. . . continues on next page . . .

. . . continued from previous page . . .

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.18.28
Installation
path / port:       53/udp
```

Solution:
Solution type: VendorFix
Update to version 9.18.28, 9.20.0, 9.18.28-S1 or later.

Affected Software/OS
ISC BIND version 9.0.0 through 9.11.37, 9.16.0 through 9.16.50, 9.18.0 through 9.18.27, 9.19.0 through 9.19.24, 9.9.3-S1 through 9.11.37-S1, 9.16.8-S1 through 9.16.49-S1 and 9.18.11-S1 through 9.18.27-S1.

Vulnerability Insight
If a server hosts a zone containing a 'KEY' Resource Record, or a resolver DNSSEC-validates a 'KEY' Resource Record from a DNSSEC-signed domain in cache, a client can exhaust resolver CPU resources by sending a stream of SIG(0) signed requests.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2024-1975) - Linux`
OID:1.3.6.1.4.1.25623.1.0.152742
Version used: `2024-07-26T05:05:35Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References

```
cve: CVE-2024-1975
url: https://kb.isc.org/docs/cve-2024-1975
url: https://www.cisa.gov/news-events/alerts/2024/07/24/isc-releases-security-ad
↪visories-bind-9
cert-bund: WID-SEC-2025-0794
cert-bund: WID-SEC-2025-0225
cert-bund: WID-SEC-2024-1700
dfn-cert: DFN-CERT-2025-2802
dfn-cert: DFN-CERT-2025-0933
dfn-cert: DFN-CERT-2024-2455
dfn-cert: DFN-CERT-2024-2392
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2024-2326
dfn-cert: DFN-CERT-2024-2298
dfn-cert: DFN-CERT-2024-2295
dfn-cert: DFN-CERT-2024-2071
dfn-cert: DFN-CERT-2024-2040
dfn-cert: DFN-CERT-2024-1912
```

High (CVSS: 8.6)
NVT: ISC BIND Multiple DoS Vulnerabilities (CVE-2020-8616, CVE-2020-8617) - Linux

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

ISC BIND is prone to multiple denial of service vulnerabilities.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.19
Installation
path / port:       53/udp
```

Solution:

Solution type: VendorFix

Update to version 9.11.19, 9.14.12, 9.16.3, 9.11.19-S1 or later.

Affected Software/OS

BIND 9.0.0 - 9.11.18, 9.12.0 - 9.12.4-P2, 9.14.0 - 9.14.11, 9.16.0 - 9.16.2, 9.17.0 -> 9.17.1 and 9.9.3-S1 - 9.11.18-S1. Also affects all releases in the obsolete 9.13 and 9.15 development branches.

Vulnerability Insight

ISC BIND is prone to multiple denial of service vulnerabilities:
- BIND does not sufficiently limit the number of fetches performed when processing referrals (CVE-2020-8616)
- A logic error in code which checks TSIG validity can be used to trigger an assertion failure in tsig.c (CVE-2020-8617)

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.

Details: `ISC BIND Multiple DoS Vulnerabilities (CVE-2020-8616, CVE-2020-8617) - Linux`
OID:1.3.6.1.4.1.25623.1.0.143937

. . . continues on next page . . .

. . . continued from previous page . . .

Version used: 2021-07-07T11:00:41Z

Product Detection Result
Product: cpe:/a:isc:bind:9.11.3
Method: ISC BIND Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
cve: CVE-2020-8616
cve: CVE-2020-8617
url: https://kb.isc.org/docs/cve-2020-8616
url: https://kb.isc.org/docs/cve-2020-8617
cert-bund: WID-SEC-2025-1198
cert-bund: WID-SEC-2024-0978
cert-bund: CB-K20/0484
cert-bund: CB-K20/0474
dfn-cert: DFN-CERT-2021-0955
dfn-cert: DFN-CERT-2021-0097
dfn-cert: DFN-CERT-2021-0095
dfn-cert: DFN-CERT-2020-1729
dfn-cert: DFN-CERT-2020-1698
dfn-cert: DFN-CERT-2020-1328
dfn-cert: DFN-CERT-2020-1297
dfn-cert: DFN-CERT-2020-1289
dfn-cert: DFN-CERT-2020-1166
dfn-cert: DFN-CERT-2020-1079
dfn-cert: DFN-CERT-2020-1066

High (CVSS: 7.5)
NVT: ISC BIND Multiple DoS Vulnerabilities (CVE-2020-8622, CVE-2020-8623) - Linux

Product detection result
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)

Summary
ISC BIND is prone to multiple denial of service vulnerabilities.

Quality of Detection (QoD): 30%

Vulnerability Detection Result
Installed version: 9.11.3
Fixed version: 9.11.22
Installation

. . . continues on next page . . .

. . . continued from previous page . . .

path / port: 53/udp

Solution:
Solution type: VendorFix
Update to version 9.11.22, 9.16.6, 9.17.4, 9.11.22-S1 or later.

Affected Software/OS
BIND 9.10.0 - 9.11.21, 9.12.0 - 9.16.5, 9.17.0 - 9.17.3 and 9.10.5-S1 - 9.11.21-S1.

Vulnerability Insight
The following vulnerabilities exist:
- A truncated TSIG response can lead to an assertion failure (CVE-2020-8622)
- A flaw in native PKCS#11 code can lead to a remotely triggerable assertion failure in pk11.c (CVE-2020-8623)

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: ISC BIND Multiple DoS Vulnerabilities (CVE-2020-8622, CVE-2020-8623) - Linux
OID:1.3.6.1.4.1.25623.1.0.144441
Version used: 2021-07-07T11:00:41Z

Product Detection Result
Product: cpe:/a:isc:bind:9.11.3
Method: ISC BIND Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
cve: CVE-2020-8622
cve: CVE-2020-8623
url: https://kb.isc.org/docs/cve-2020-8622
url: https://kb.isc.org/docs/cve-2020-8623
cert-bund: WID-SEC-2022-0623
cert-bund: CB-K21/0337
cert-bund: CB-K20/1253
cert-bund: CB-K20/1030
cert-bund: CB-K20/0837
dfn-cert: DFN-CERT-2021-0955
dfn-cert: DFN-CERT-2021-0924
dfn-cert: DFN-CERT-2021-0776
dfn-cert: DFN-CERT-2020-2588
dfn-cert: DFN-CERT-2020-2205
dfn-cert: DFN-CERT-2020-2064
dfn-cert: DFN-CERT-2020-1886
dfn-cert: DFN-CERT-2020-1875
dfn-cert: DFN-CERT-2020-1835

High (CVSS: 7.5)
NVT: ISC BIND Multiple DoS Vulnerabilities (CVE-2023-50387, CVE-2023-50868, KeyTrap) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary
ISC BIND is prone to multiple denial of service (DoS) vulnerabilities.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.16.48
Installation
path / port:       53/udp
```

Solution:
Solution type: VendorFix
Update to version 9.16.48, 9.18.24, 9.19.21, 9.16.48-S1, 9.18.24-S1 or later.

Affected Software/OS
ISC BIND version 9.0.0 through 9.16.46, 9.18.0 through 9.18.22, 9.19.0 through 9.19.20, 9.9.3-S1 through 9.16.46-S1 and 9.18.11-S1 through 9.18.22-S1.

Vulnerability Insight
The following vulnerabilities exist:
- CVE-2023-50387: KeyTrap - Extreme CPU consumption in DNSSEC validator
- CVE-2023-50868: Preparing an NSEC3 closest encloser proof can exhaust CPU resources

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND Multiple DoS Vulnerabilities (CVE-2023-50387, CVE-2023-50868, KeyTrap).`
↪`..`
OID:1.3.6.1.4.1.25623.1.0.151715
Version used: `2024-02-21T05:06:27Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References

. . . continues on next page . . .

. . . continued from previous page . . .

```
cve: CVE-2023-50387
cve: CVE-2023-50868
url: https://kb.isc.org/docs/cve-2023-50387
url: https://kb.isc.org/docs/cve-2023-50868
url: https://www.athene-center.de/en/keytrap
cert-bund: WID-SEC-2025-0148
cert-bund: WID-SEC-2024-1347
cert-bund: WID-SEC-2024-1313
cert-bund: WID-SEC-2024-1307
cert-bund: WID-SEC-2024-1248
cert-bund: WID-SEC-2024-1226
cert-bund: WID-SEC-2024-1086
cert-bund: WID-SEC-2024-0387
cert-bund: WID-SEC-2024-0386
dfn-cert: DFN-CERT-2025-1459
dfn-cert: DFN-CERT-2025-0041
dfn-cert: DFN-CERT-2025-0010
dfn-cert: DFN-CERT-2024-2264
dfn-cert: DFN-CERT-2024-1904
dfn-cert: DFN-CERT-2024-1523
dfn-cert: DFN-CERT-2024-1516
dfn-cert: DFN-CERT-2024-1474
dfn-cert: DFN-CERT-2024-1413
dfn-cert: DFN-CERT-2024-1223
dfn-cert: DFN-CERT-2024-1011
dfn-cert: DFN-CERT-2024-0984
dfn-cert: DFN-CERT-2024-0977
dfn-cert: DFN-CERT-2024-0921
dfn-cert: DFN-CERT-2024-0829
dfn-cert: DFN-CERT-2024-0529
dfn-cert: DFN-CERT-2024-0498
dfn-cert: DFN-CERT-2024-0404
dfn-cert: DFN-CERT-2024-0399
dfn-cert: DFN-CERT-2024-0387
dfn-cert: DFN-CERT-2024-0379
dfn-cert: DFN-CERT-2024-0375
```

High (CVSS: 7.5)
NVT: ISC BIND Multiple Vulnerabilities (Feb 2019) - Linux

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

. . . continues on next page . . .

. . . continued from previous page . . .

ISC BIND is prone to multiple vulnerabilities.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.5-P4
Installation
path / port:       53/udp
```

Solution:
Solution type: VendorFix
Update to version 9.11.5-S5, 9.11.5-P4, 9.12.3-P4 or later.

Affected Software/OS
ISC BIND versions 9.9.0-9.10.8-P1, 9.11.0-9.11.5-P2, 9.12.0-9.12.3-P2 and 9.9.3-S1-9.11.5-S3.

Vulnerability Insight
ISC BIND is prone to multiple vulnerabilities:
- A specially crafted packet can cause named to leak memory (CVE-2018-5744)
- An assertion failure can occur if a trust anchor rolls over to an unsupported key algorithm when using managed-keys (CVE-2018-5745)
- Zone transfer controls for writable DLZ zones were not effective (CVE-2019-6465)

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND Multiple Vulnerabilities (Feb 2019) - Linux`
OID:1.3.6.1.4.1.25623.1.0.142033
Version used: `2021-08-30T11:01:18Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References

```
cve: CVE-2018-5744
cve: CVE-2018-5745
cve: CVE-2019-6465
url: https://kb.isc.org/docs/cve-2018-5744
url: https://kb.isc.org/docs/cve-2018-5745
url: https://kb.isc.org/docs/cve-2019-6465
cert-bund: WID-SEC-2025-1194
cert-bund: CB-K19/0161
dfn-cert: DFN-CERT-2020-0672
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2019-2042
dfn-cert: DFN-CERT-2019-1119
dfn-cert: DFN-CERT-2019-0935
dfn-cert: DFN-CERT-2019-0781
dfn-cert: DFN-CERT-2019-0436
dfn-cert: DFN-CERT-2019-0435
dfn-cert: DFN-CERT-2019-0382
```

[return to 172.31.1.101]

2.1.3 High 53/tcp

High (CVSS: 7.5)
NVT: ISC BIND 'deny-answer-aliases' Denial of Service Vulnerability

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

ISC BIND is prone to a denial of service vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.4-P1
Installation
path / port:       53/tcp
```

Impact

Successful exploitation will allow remote attackers to cause a denial of service (assertion failure).

Solution:

Solution type: VendorFix

Update to ISC BIND version 9.9.13-P1 or 9.10.8-P1 or 9.11.4-P1 or 9.12.2-P1 or 9.11.3-S3 or later. Please see the references for more information.

Affected Software/OS

ISC BIND versions 9.7.0 through 9.8.8, 9.9.0 through 9.9.13, 9.10.0 through 9.10.8, 9.11.0 through 9.11.4, 9.12.0 through 9.12.2 and 9.13.0 through 9.13.2.

Vulnerability Insight

. . . continues on next page . . .

. . . continued from previous page . . .

The flaw exists due to a defect in the feature 'deny-answer-aliases' which leads to assertion failure in 'name.c'.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND 'deny-answer-aliases' Denial of Service Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.813750
Version used: `2023-07-20T05:05:17Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
```
cve: CVE-2018-5740
url: https://kb.isc.org/docs/aa-01639
cert-bund: WID-SEC-2025-1193
cert-bund: CB-K18/0842
dfn-cert: DFN-CERT-2021-2273
dfn-cert: DFN-CERT-2019-2042
dfn-cert: DFN-CERT-2019-1594
dfn-cert: DFN-CERT-2019-1119
dfn-cert: DFN-CERT-2019-0436
dfn-cert: DFN-CERT-2019-0069
dfn-cert: DFN-CERT-2018-2435
dfn-cert: DFN-CERT-2018-1562
```

High (CVSS: 7.5)
NVT: ISC BIND Access Control Vulnerability (Jun 2018) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary
Some versions of BIND can improperly permit recursive query service to unauthorized clients.

Quality of Detection (QoD): 30%

Vulnerability Detection Result
```
Installed version: 9.11.3
Fixed version:     Workaround
Installation
```

. . . continues on next page . . .

. . . continued from previous page . . .

path / port: 53/tcp

Solution:
Solution type: Workaround
See the vendor advisory for workarounds.

Affected Software/OS
ISC BIND 9.9.12, 9.10.7, 9.11.3, 9.12.0->9.12.1-P2, 9.13.0, 9.9.12-S1, 9.10.7-S1, 9.11.3-S1, and 9.11.3-S2.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: ISC BIND Access Control Vulnerability (Jun 2018) - Linux
OID:1.3.6.1.4.1.25623.1.0.141179
Version used: 2023-07-20T05:05:17Z

Product Detection Result
Product: cpe:/a:isc:bind:9.11.3
Method: ISC BIND Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
cve: CVE-2018-5738
url: https://kb.isc.org/docs/aa-01616
cert-bund: CB-K18/0723
dfn-cert: DFN-CERT-2019-0436
dfn-cert: DFN-CERT-2018-1134

High (CVSS: 8.1)
NVT: ISC BIND Buffer Overflow Vulnerability (CVE-2020-8625) - Linux

Product detection result
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)

Summary
ISC BIND is prone to a buffer overflow vulnerability in the GSSAPI security policy negotiation.

Quality of Detection (QoD): 30%

Vulnerability Detection Result
Installed version: 9.11.3
Fixed version: 9.11.28

. . . continues on next page . . .

. . . continued from previous page . . .

```
Installation
path / port:        53/tcp
```

Impact
The most likely outcome of a successful exploitation of the vulnerability is a crash of the named process. However, remote code execution, while unproven, is theoretically possible.

Solution:
Solution type: VendorFix
Update to version 9.11.28, 9.16.12, 9.11.28-S1, 9.16.12-S1 or later.

Affected Software/OS
BIND 9.5.0 - 9.11.27, 9.12.0 - 9.16.11, 9.11.3-S1 - 9.11.27-S1 and 9.16.8-S1 - 9.16.11-S1.

Vulnerability Insight
GSS-TSIG is an extension to the TSIG protocol which is intended to support the secure exchange of keys for use in verifying the authenticity of communications between parties on a network.
SPNEGO is a negotiation mechanism used by GSSAPI, the application protocol interface for GSS-TSIG.
The SPNEGO implementation used by BIND has been found to be vulnerable to a buffer overflow attack.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND Buffer Overflow Vulnerability (CVE-2020-8625) - Linux`
OID:1.3.6.1.4.1.25623.1.0.145412
Version used: `2021-08-17T14:01:00Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
```
cve: CVE-2020-8625
url: https://kb.isc.org/docs/cve-2020-8625
cert-bund: WID-SEC-2023-0063
cert-bund: CB-K21/0190
dfn-cert: DFN-CERT-2022-0074
dfn-cert: DFN-CERT-2021-0955
dfn-cert: DFN-CERT-2021-0556
dfn-cert: DFN-CERT-2021-0375
```

High (CVSS: 8.6)
NVT: ISC BIND Cache Poisoning Vulnerability (CVE-2025-40778) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary
ISC BIND is prone to cache poisoning attacks with unsolicited RRs.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.18.41
Installation
path / port:       53/tcp
```

Impact
Forged records can be injected into cache during a query, which can potentially affect resolution of future queries.

Solution:
Solution type: VendorFix
Update to version 9.18.41, 9.18.41-S1, 9.20.15, 9.20.15-S1, 9.21.14 or later.

Affected Software/OS
ISC BIND versions 9.11.0 through 9.16.50, 9.18.0 through 9.18.39, 9.20.0 through 9.20.13, 9.21.0 through 9.21.12, 9.11.3-S1 through 9.16.50-S1, 9.18.11-S1 through 9.18.39-S1 and 9.20.9-S1 through 9.20.13-S1.
Vendor notes:
- Authoritative services are believed to be unaffected by this vulnerability but it is important to read: [link moved to references]
- Resolvers are affected by this vulnerability.

Vulnerability Insight
Under certain circumstances, BIND is too lenient when accepting records from answers, allowing an attacker to inject forged data into the cache.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND Cache Poisoning Vulnerability (CVE-2025-40778) - Linux`
OID:1.3.6.1.4.1.25623.1.0.119202
Version used: `2025-10-24T05:39:31Z`

Product Detection Result

. . . continues on next page . . .

. . . continued from previous page . . .

Product: cpe:/a:isc:bind:9.11.3
Method: ISC BIND Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.145294)

References

```
cve: CVE-2025-40778
url: https://kb.isc.org/docs/cve-2025-40778
url: https://kb.isc.org/docs/why-does-my-authoritative-server-make-recursive-que
↪ries
cert-bund: WID-SEC-2025-2392
dfn-cert: DFN-CERT-2026-0243
dfn-cert: DFN-CERT-2026-0149
dfn-cert: DFN-CERT-2026-0148
dfn-cert: DFN-CERT-2026-0130
dfn-cert: DFN-CERT-2025-3313
dfn-cert: DFN-CERT-2025-3256
dfn-cert: DFN-CERT-2025-3234
dfn-cert: DFN-CERT-2025-3106
dfn-cert: DFN-CERT-2025-3088
dfn-cert: DFN-CERT-2025-2964
```

High (CVSS: 8.6)
NVT: ISC BIND Cache-Poisoning Vulnerability (CVE-2025-40776, Birthday Attack) - Linux

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

ISC BIND is prone to a cache-poisoning vulnerability (Birthday Attack against Resolvers supporting ECS).

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.20.11
Installation
path / port:       53/tcp
```

Impact

. . . continues on next page . . .

. . . continued from previous page . . .

A resolver configured to send ECS options to authoritative servers can be compelled to make queries that slightly increase the odds of guessing the source port and other details necessary to bypass the original birthday cache poisoning attack mitigations. As a result of this weakness, a resolver with ECS enabled is more vulnerable to successful cache poisoning via spoofed query responses than one that does not implement this feature.

Solution:
Solution type: VendorFix
Update to version 9.20.11, 9.18.38-S1, 9.20.11-S1 or later.

Affected Software/OS
ISC BIND version 9.0.0 through 9.20.10, 9.11.3-S1 through 9.16.50-S1, 9.18.11-S1 through 9.18.37-S1 and 9.20.9-S1 through 9.20.10-S1.

Vulnerability Insight
A named caching resolver that is configured to send ECS (EDNS Client Subnet) options may be vulnerable to a cache-poisoning attack.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND Cache-Poisoning Vulnerability (CVE-2025-40776, Birthday Attack) - Linux`
OID:1.3.6.1.4.1.25623.1.0.154963
Version used: `2025-07-18T05:44:10Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
`cve: CVE-2025-40776`
`url: https://kb.isc.org/docs/cve-2025-40776`
`cert-bund: WID-SEC-2025-1585`

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2018-5743) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary

. . . continues on next page . . .

. . . continued from previous page . . .

ISC BIND is prone to a denial of service vulnerability due to ineffective simultaneous TCP client limiting.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.6-P1
Installation
path / port:       53/tcp
```

Impact

By exploiting the failure to limit simultaneous TCP connections, an attacker can deliberately exhaust the pool of file descriptors available to named, potentially affecting network connections and the management of files such as log files or zone journal files.
In cases where the named process is not limited by OS-enforced per-process limits, this could additionally potentially lead to exhaustion of all available free file descriptors on that system.

Solution:
Solution type: VendorFix
Update to version 9.11.6-P1, 9.12.4-P1, 9.14.1, 9.11.5-S6, 9.11.6-S1 or later.

Affected Software/OS

BIND 9.9.0 to 9.10.8-P1, 9.11.0 to 9.11.6, 9.12.0 to 9.12.4, 9.14.0. BIND 9 Supported Preview Edition versions 9.9.3-S1 to 9.11.5-S3, and 9.11.5-S5. Versions 9.13.0 to 9.13.7 of the 9.13 development branch.

Vulnerability Insight

By design, BIND is intended to limit the number of TCP clients that can be connected at any given time. The number of allowed connections is a tunable parameter which, if unset, defaults to a conservative value for most servers. Unfortunately, the code which was intended to limit the number of simultaneous connections contains an error which can be exploited to grow the number of simultaneous connections beyond this limit.

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2018-5743) - Linux`
OID:1.3.6.1.4.1.25623.1.0.142320
Version used: `2021-08-30T11:01:18Z`

Product Detection Result

Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

. . . continues on next page . . .

. . . continued from previous page . . .

References

```
cve: CVE-2018-5743
url: https://kb.isc.org/docs/cve-2018-5743
cert-bund: WID-SEC-2025-1196
cert-bund: WID-SEC-2025-1195
cert-bund: CB-K19/0423
cert-bund: CB-K19/0349
dfn-cert: DFN-CERT-2020-0048
dfn-cert: DFN-CERT-2019-2042
dfn-cert: DFN-CERT-2019-1594
dfn-cert: DFN-CERT-2019-1119
dfn-cert: DFN-CERT-2019-0935
dfn-cert: DFN-CERT-2019-0896
dfn-cert: DFN-CERT-2019-0833
```

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2021-25215) - Linux

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.31
Installation
path / port:       53/tcp
```

Impact

When a vulnerable version of named receives a query for a record triggering the flaw described above, the named process will terminate due to a failed assertion check.

Solution:

Solution type: VendorFix

Update to version 9.11.31, 9.16.15, 9.17.12, 9.11.31-S1, 9.16.15-S1 or later.

Affected Software/OS

BIND 9.0.0 through 9.11.29, 9.12.0 through 9.16.13, 9.9.3-S1 through 9.11.29-S1, 9.16.8-S1 through 9.16.13-S1 and 9.17.0 through 9.17.11.

. . . continues on next page . . .

. . . continued from previous page . . .

Vulnerability Insight
DNAME records, described in RFC 6672, provide a way to redirect a subtree of the domain name tree in the DNS. A flaw in the way named processes these records may trigger an attempt to add the same RRset to the ANSWER section more than once. This causes an assertion check in BIND to fail.
DNAME records are processed by both authoritative and recursive servers. For authoritative servers, the DNAME record triggering the flaw can be retrieved from a zone database. For servers performing recursion, such a record is processed in the course of a query sent to an authoritative server.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2021-25215) - Linux`
OID:1.3.6.1.4.1.25623.1.0.145865
Version used: `2021-08-17T14:01:00Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
```
cve: CVE-2021-25215
url: https://kb.isc.org/docs/cve-2021-25215
cert-bund: WID-SEC-2025-2027
cert-bund: WID-SEC-2022-0623
cert-bund: CB-K22/0012
cert-bund: CB-K21/0452
dfn-cert: DFN-CERT-2022-0566
dfn-cert: DFN-CERT-2021-1504
dfn-cert: DFN-CERT-2021-0915
dfn-cert: DFN-CERT-2021-0909
dfn-cert: DFN-CERT-2021-0898
```

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2022-38177) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

. . . continues on next page . . .

. . . continued from previous page . . .

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.16.33
Installation
path / port:       53/tcp
```

Impact

By spoofing the target resolver with responses that have a malformed ECDSA signature, an attacker can trigger a small memory leak. It is possible to gradually erode available memory to the point where named crashes for lack of resources.

Solution:

Solution type: VendorFix

Update to version 9.16.33, 9.16.33-S1 or later.

Affected Software/OS

ISC BIND versions 9.8.4 through 9.16.32, 9.9.4-S1 through 9.11.37-S1 and 9.16.8-S1 through 9.16.32-S1.

Vulnerability Insight

The DNSSEC verification code for the ECDSA algorithm leaks memory when there is a signature length mismatch.

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.

Details: `ISC BIND DoS Vulnerability (CVE-2022-38177) - Linux`

OID:1.3.6.1.4.1.25623.1.0.124172

Version used: `2023-10-18T05:05:17Z`

Product Detection Result

Product: `cpe:/a:isc:bind:9.11.3`

Method: `ISC BIND Detection Consolidation`

OID: 1.3.6.1.4.1.25623.1.0.145294)

References

```
cve: CVE-2022-38177
url: https://kb.isc.org/docs/cve-2022-38177
cert-bund: WID-SEC-2024-0794
cert-bund: WID-SEC-2022-1492
dfn-cert: DFN-CERT-2023-1162
dfn-cert: DFN-CERT-2022-2664
dfn-cert: DFN-CERT-2022-2354
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2022-2191
dfn-cert: DFN-CERT-2022-2099
```

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2022-38178) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.16.33
Installation
path / port:       53/tcp
```

Impact
By spoofing the target resolver with responses that have a malformed EdDSA signature, an attacker can trigger a small memory leak. It is possible to gradually erode available memory to the point where named crashes for lack of resources.

Solution:
Solution type: VendorFix
Update to version 9.16.33, 9.18.7, 9.19.5, 9.16.33-S1 or later.

Affected Software/OS
ISC BIND versions 9.9.12 through 9.9.13, 9.10.7 through 9.10.8, 9.11.4-S1 through 9.11.37-S1, 9.16.8-S1 through 9.16.32-S1, 9.18.0 through 9.18.6 and 9.19.0 through 9.19.4.

Vulnerability Insight
The DNSSEC verification code for the EdDSA algorithm leaks memory when there is a signature length mismatch.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2022-38178) - Linux`
OID:1.3.6.1.4.1.25623.1.0.124174
Version used: `2023-10-18T05:05:17Z`

. . . continues on next page . . .

. . . continued from previous page . . .

Product Detection Result
Product: cpe:/a:isc:bind:9.11.3
Method: ISC BIND Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
cve: CVE-2022-38178
url: https://kb.isc.org/docs/cve-2022-38178
cert-bund: WID-SEC-2024-0794
cert-bund: WID-SEC-2022-1492
dfn-cert: DFN-CERT-2023-1162
dfn-cert: DFN-CERT-2022-2664
dfn-cert: DFN-CERT-2022-2354
dfn-cert: DFN-CERT-2022-2099

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2023-2828) - Linux

Product detection result
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result
Installed version: 9.11.3
Fixed version: 9.16.42
Installation
path / port: 53/tcp

Impact
By exploiting this flaw, an attacker can cause the amount of memory used by a named resolver to go well beyond the configured max-cache-size limit. The effectiveness of the attack depends on a number of factors (e.g. query load, query patterns), but since the default value of the max-cache-size statement is 90%, in the worst case the attacker can exhaust all available memory on the host running named, leading to a denial-of-service condition.

Solution:
Solution type: VendorFix
Update to version 9.16.42, 9.18.16, 9.19.14, 9.16.42-S1, 9.18.16-S1 or later.

. . . continues on next page . . .

. . . continued from previous page . . .

Affected Software/OS
ISC BIND versions 9.11.0 through 9.16.41, 9.18.0 through 9.18.15, 9.19.0 through 9.19.13, 9.11.3-S1 through 9.16.41-S1 and 9.18.11-S1 through 9.18.15-S1.

Vulnerability Insight
Every named instance configured to run as a recursive resolver maintains a cache database holding the responses to the queries it has recently sent to authoritative servers. The size limit for that cache database can be configured using the max-cache-size statement in the configuration file, it defaults to 90% of the total amount of memory available on the host. When the size of the cache reaches 7/8 of the configured limit, a cache-cleaning algorithm starts to remove expired and/or least-recently used RRsets from the cache, to keep memory use below the configured limit.
It has been discovered that the effectiveness of the cache-cleaning algorithm used in named can be severely diminished by querying the resolver for specific RRsets in a certain order, effectively allowing the configured max-cache-size limit to be significantly exceeded.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2023-2828) - Linux`
OID:1.3.6.1.4.1.25623.1.0.149838
Version used: `2023-10-13T05:06:10Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
`cve: CVE-2023-2828`
`url: https://kb.isc.org/docs/cve-2023-2828`
`cert-bund: WID-SEC-2024-1591`
`cert-bund: WID-SEC-2024-0794`
`cert-bund: WID-SEC-2024-0064`
`cert-bund: WID-SEC-2023-2917`
`cert-bund: WID-SEC-2023-2625`
`cert-bund: WID-SEC-2023-1533`
`dfn-cert: DFN-CERT-2023-1551`
`dfn-cert: DFN-CERT-2023-1444`
`dfn-cert: DFN-CERT-2023-1434`

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2023-3341) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`

. . . continues on next page . . .

. . . continued from previous page . . .

Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.16.44
Installation
path / port:       53/tcp
```

Impact
By sending a specially crafted message over the control channel, an attacker can cause the packet-parsing code to run out of available stack memory, causing named to terminate unexpectedly. However, the attack only works in environments where the stack size available to each process/thread is small enough. The exact threshold depends on multiple factors and is therefore impossible to specify universally.

Solution:
Solution type: VendorFix
Update to version 9.16.44, 9.18.19, 9.19.17, 9.16.44-S1, 9.18.19-S1 or later.

Affected Software/OS
ISC BIND versions 9.2.0 through 9.16.43, 9.18.0 through 9.18.18, 9.19.0 through 9.19.16, 9.9.3-S1 through 9.16.43-S1 and 9.18.0-S1 through 9.18.18-S1.

Vulnerability Insight
The code that processes control channel messages sent to named calls certain functions recursively during packet parsing. Recursion depth is only limited by the maximum accepted packet size. Depending on the environment, this may cause the packet-parsing code to run out of available stack memory, causing named to terminate unexpectedly. Since each incoming control channel message is fully parsed before its contents are authenticated, exploiting this flaw does not require the attacker to hold a valid RNDC key. Only network access to the control channel's configured TCP port is necessary.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: ISC BIND DoS Vulnerability (CVE-2023-3341) - Linux
OID:1.3.6.1.4.1.25623.1.0.104923
Version used: 2023-10-13T05:06:10Z

Product Detection Result
Product: cpe:/a:isc:bind:9.11.3

. . . continues on next page . . .

. . . continued from previous page . . .

Method: ISC BIND Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.145294)

References

```
cve: CVE-2023-3341
url: https://kb.isc.org/docs/cve-2023-3341
cert-bund: WID-SEC-2024-1591
cert-bund: WID-SEC-2024-0064
cert-bund: WID-SEC-2023-2412
dfn-cert: DFN-CERT-2025-0010
dfn-cert: DFN-CERT-2023-3177
dfn-cert: DFN-CERT-2023-2941
dfn-cert: DFN-CERT-2023-2223
```

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2023-4408) - Linux

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.16.48
Installation
path / port:       53/tcp
```

Impact

By flooding the target server with queries exploiting this flaw an attacker can significantly impair the server's performance, effectively denying legitimate clients access to the DNS resolution service.

Solution:

Solution type: VendorFix

Update to version 9.16.48, 9.18.24, 9.19.21, 9.16.48-S1, 9.18.24-S1 or later.

Affected Software/OS

. . . continues on next page . . .

. . . continued from previous page . . .

ISC BIND version 9.0.0 through 9.16.45, 9.18.0 through 9.18.21, 9.19.0 through 9.19.19, 9.9.3-S1 through 9.11.37-S1, 9.16.8-S1 through 9.16.45-S1 and 9.18.11-S1 through 9.18.21-S1.

Vulnerability Insight
The DNS message parsing code in named includes a section whose computational complexity is overly high. It does not cause problems for typical DNS traffic, but crafted queries and responses may cause excessive CPU load on the affected named instance by exploiting this flaw. This issue affects both authoritative servers and recursive resolvers.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2023-4408) - Linux`
OID:1.3.6.1.4.1.25623.1.0.151725
Version used: `2024-02-15T14:37:33Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
```
cve: CVE-2023-4408
url: https://kb.isc.org/docs/cve-2023-4408
cert-bund: WID-SEC-2024-1313
cert-bund: WID-SEC-2024-1307
cert-bund: WID-SEC-2024-1248
cert-bund: WID-SEC-2024-1226
cert-bund: WID-SEC-2024-0386
dfn-cert: DFN-CERT-2025-0041
dfn-cert: DFN-CERT-2025-0010
dfn-cert: DFN-CERT-2024-1516
dfn-cert: DFN-CERT-2024-1223
dfn-cert: DFN-CERT-2024-0977
dfn-cert: DFN-CERT-2024-0375
```

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2024-11187) - Linux

Product detection result
```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

. . . continues on next page . . .

. . . continued from previous page . . .

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.18.33
Installation
path / port:       53/tcp
```

Impact

A named instance vulnerable to this issue can be compelled to consume excessive CPU resources up to the point where exhaustion of resources effectively prevents the server from responding to other client queries. This issue is most likely to affect resolvers but could also degrade authoritative server performance.
- Authoritative servers are affected by this vulnerability.
- Resolvers are affected by this vulnerability.

Solution:
Solution type: VendorFix
Update to version 9.18.33, 9.20.5, 9.21.4, 9.18.33-S1 or later.

Affected Software/OS

ISC BIND version 9.11.37 and prior, 9.16.0 through 9.16.50, 9.18.0 through 9.18.32, 9.20.0 through 9.20.4, 9.21.0 through 9.21.3, 9.11.3-S1 through 9.11.37-S1, 9.16.8-S1 through 9.16.50-S1 and 9.18.11-S1 through 9.18.32-S1.

Vulnerability Insight

It is possible to construct a zone such that some queries to it will generate responses containing numerous records in the Additional section. An attacker sending many such queries can cause either the authoritative server itself or an independent resolver to use disproportionate resources processing the queries. Zones will usually need to have been deliberately crafted to attack this exposure.

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2024-11187) - Linux`
OID:1.3.6.1.4.1.25623.1.0.153891
Version used: `2025-01-31T05:37:27Z`

Product Detection Result

Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References

. . . continues on next page . . .

. . . continued from previous page . . .

```
cve: CVE-2024-11187
url: https://kb.isc.org/docs/cve-2024-11187
cert-bund: WID-SEC-2025-0217
dfn-cert: DFN-CERT-2025-1410
dfn-cert: DFN-CERT-2025-0994
dfn-cert: DFN-CERT-2025-0993
dfn-cert: DFN-CERT-2025-0720
dfn-cert: DFN-CERT-2025-0664
dfn-cert: DFN-CERT-2025-0662
dfn-cert: DFN-CERT-2025-0575
dfn-cert: DFN-CERT-2025-0574
dfn-cert: DFN-CERT-2025-0300
dfn-cert: DFN-CERT-2025-0269
```

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2024-1737) - Linux

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.18.28
Installation
path / port:       53/tcp
```

Solution:

Solution type: VendorFix

Update to version 9.18.28, 9.20.0, 9.18.28-S1 or later.

Affected Software/OS

ISC BIND version 9.11.0 through 9.11.37, 9.16.0 through 9.16.50, 9.18.0 through 9.18.27, 9.19.0 through 9.19.24, 9.11.4-S1 through 9.11.37-S1, 9.16.8-S1 through 9.16.50-S1 and 9.18.11-S1 through 9.18.27-S1.

Vulnerability Insight

. . . continues on next page . . .

. . . continued from previous page . . .

Resolver caches and authoritative zone databases that hold significant numbers of RRs for the same hostname (of any RTYPE) can suffer from degraded performance as content is being added or updated, and also when handling client queries for this name.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2024-1737) - Linux`
OID:1.3.6.1.4.1.25623.1.0.152740
Version used: `2024-07-26T05:05:35Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
```
cve: CVE-2024-1737
url: https://kb.isc.org/docs/cve-2024-1737
url: https://www.cisa.gov/news-events/alerts/2024/07/24/isc-releases-security-ad
↪visories-bind-9
cert-bund: WID-SEC-2025-0794
cert-bund: WID-SEC-2025-0225
cert-bund: WID-SEC-2024-1700
dfn-cert: DFN-CERT-2025-2802
dfn-cert: DFN-CERT-2025-0933
dfn-cert: DFN-CERT-2024-2455
dfn-cert: DFN-CERT-2024-2392
dfn-cert: DFN-CERT-2024-2326
dfn-cert: DFN-CERT-2024-2298
dfn-cert: DFN-CERT-2024-2295
dfn-cert: DFN-CERT-2024-2071
dfn-cert: DFN-CERT-2024-2040
dfn-cert: DFN-CERT-2024-1912
```

High (CVSS: 7.5)
NVT: ISC BIND DoS Vulnerability (CVE-2024-1975) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

. . . continues on next page . . .

. . . continued from previous page . . .

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.18.28
Installation
path / port:       53/tcp
```

Solution:
Solution type: VendorFix
Update to version 9.18.28, 9.20.0, 9.18.28-S1 or later.

Affected Software/OS
ISC BIND version 9.0.0 through 9.11.37, 9.16.0 through 9.16.50, 9.18.0 through 9.18.27, 9.19.0 through 9.19.24, 9.9.3-S1 through 9.11.37-S1, 9.16.8-S1 through 9.16.49-S1 and 9.18.11-S1 through 9.18.27-S1.

Vulnerability Insight
If a server hosts a zone containing a 'KEY' Resource Record, or a resolver DNSSEC-validates a 'KEY' Resource Record from a DNSSEC-signed domain in cache, a client can exhaust resolver CPU resources by sending a stream of SIG(0) signed requests.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2024-1975) - Linux`
OID:1.3.6.1.4.1.25623.1.0.152742
Version used: `2024-07-26T05:05:35Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References

```
cve: CVE-2024-1975
url: https://kb.isc.org/docs/cve-2024-1975
url: https://www.cisa.gov/news-events/alerts/2024/07/24/isc-releases-security-ad
↪visories-bind-9
cert-bund: WID-SEC-2025-0794
cert-bund: WID-SEC-2025-0225
cert-bund: WID-SEC-2024-1700
dfn-cert: DFN-CERT-2025-2802
dfn-cert: DFN-CERT-2025-0933
dfn-cert: DFN-CERT-2024-2455
dfn-cert: DFN-CERT-2024-2392
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2024-2326
dfn-cert: DFN-CERT-2024-2298
dfn-cert: DFN-CERT-2024-2295
dfn-cert: DFN-CERT-2024-2071
dfn-cert: DFN-CERT-2024-2040
dfn-cert: DFN-CERT-2024-1912
```

High (CVSS: 8.6)
NVT: ISC BIND Multiple DoS Vulnerabilities (CVE-2020-8616, CVE-2020-8617) - Linux

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

ISC BIND is prone to multiple denial of service vulnerabilities.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.19
Installation
path / port:       53/tcp
```

Solution:

Solution type: VendorFix

Update to version 9.11.19, 9.14.12, 9.16.3, 9.11.19-S1 or later.

Affected Software/OS

BIND 9.0.0 - 9.11.18, 9.12.0 - 9.12.4-P2, 9.14.0 - 9.14.11, 9.16.0 - 9.16.2, 9.17.0 -> 9.17.1 and 9.9.3-S1 - 9.11.18-S1. Also affects all releases in the obsolete 9.13 and 9.15 development branches.

Vulnerability Insight

ISC BIND is prone to multiple denial of service vulnerabilities:
- BIND does not sufficiently limit the number of fetches performed when processing referrals (CVE-2020-8616)
- A logic error in code which checks TSIG validity can be used to trigger an assertion failure in tsig.c (CVE-2020-8617)

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.

Details: `ISC BIND Multiple DoS Vulnerabilities (CVE-2020-8616, CVE-2020-8617) - Linux`
OID:1.3.6.1.4.1.25623.1.0.143937

. . . continues on next page . . .

. . . continued from previous page . . .

Version used: 2021-07-07T11:00:41Z

Product Detection Result
Product: cpe:/a:isc:bind:9.11.3
Method: ISC BIND Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
cve: CVE-2020-8616
cve: CVE-2020-8617
url: https://kb.isc.org/docs/cve-2020-8616
url: https://kb.isc.org/docs/cve-2020-8617
cert-bund: WID-SEC-2025-1198
cert-bund: WID-SEC-2024-0978
cert-bund: CB-K20/0484
cert-bund: CB-K20/0474
dfn-cert: DFN-CERT-2021-0955
dfn-cert: DFN-CERT-2021-0097
dfn-cert: DFN-CERT-2021-0095
dfn-cert: DFN-CERT-2020-1729
dfn-cert: DFN-CERT-2020-1698
dfn-cert: DFN-CERT-2020-1328
dfn-cert: DFN-CERT-2020-1297
dfn-cert: DFN-CERT-2020-1289
dfn-cert: DFN-CERT-2020-1166
dfn-cert: DFN-CERT-2020-1079
dfn-cert: DFN-CERT-2020-1066

High (CVSS: 7.5)
NVT: ISC BIND Multiple DoS Vulnerabilities (CVE-2020-8622, CVE-2020-8623) - Linux

Product detection result
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)

Summary
ISC BIND is prone to multiple denial of service vulnerabilities.

Quality of Detection (QoD): 30%

Vulnerability Detection Result
Installed version: 9.11.3
Fixed version: 9.11.22
Installation

. . . continues on next page . . .

. . . continued from previous page . . .

path / port: 53/tcp

Solution:
Solution type: VendorFix
Update to version 9.11.22, 9.16.6, 9.17.4, 9.11.22-S1 or later.

Affected Software/OS
BIND 9.10.0 - 9.11.21, 9.12.0 - 9.16.5, 9.17.0 - 9.17.3 and 9.10.5-S1 - 9.11.21-S1.

Vulnerability Insight
The following vulnerabilities exist:
- A truncated TSIG response can lead to an assertion failure (CVE-2020-8622)
- A flaw in native PKCS#11 code can lead to a remotely triggerable assertion failure in pk11.c (CVE-2020-8623)

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: ISC BIND Multiple DoS Vulnerabilities (CVE-2020-8622, CVE-2020-8623) - Linux
OID:1.3.6.1.4.1.25623.1.0.144441
Version used: 2021-07-07T11:00:41Z

Product Detection Result
Product: cpe:/a:isc:bind:9.11.3
Method: ISC BIND Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
cve: CVE-2020-8622
cve: CVE-2020-8623
url: https://kb.isc.org/docs/cve-2020-8622
url: https://kb.isc.org/docs/cve-2020-8623
cert-bund: WID-SEC-2022-0623
cert-bund: CB-K21/0337
cert-bund: CB-K20/1253
cert-bund: CB-K20/1030
cert-bund: CB-K20/0837
dfn-cert: DFN-CERT-2021-0955
dfn-cert: DFN-CERT-2021-0924
dfn-cert: DFN-CERT-2021-0776
dfn-cert: DFN-CERT-2020-2588
dfn-cert: DFN-CERT-2020-2205
dfn-cert: DFN-CERT-2020-2064
dfn-cert: DFN-CERT-2020-1886
dfn-cert: DFN-CERT-2020-1875
dfn-cert: DFN-CERT-2020-1835

High (CVSS: 7.5)
NVT: ISC BIND Multiple DoS Vulnerabilities (CVE-2023-50387, CVE-2023-50868, KeyTrap) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary
ISC BIND is prone to multiple denial of service (DoS) vulnerabilities.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.16.48
Installation
path / port:       53/tcp
```

Solution:
Solution type: VendorFix
Update to version 9.16.48, 9.18.24, 9.19.21, 9.16.48-S1, 9.18.24-S1 or later.

Affected Software/OS
ISC BIND version 9.0.0 through 9.16.46, 9.18.0 through 9.18.22, 9.19.0 through 9.19.20, 9.9.3-S1 through 9.16.46-S1 and 9.18.11-S1 through 9.18.22-S1.

Vulnerability Insight
The following vulnerabilities exist:
- CVE-2023-50387: KeyTrap - Extreme CPU consumption in DNSSEC validator
- CVE-2023-50868: Preparing an NSEC3 closest encloser proof can exhaust CPU resources

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND Multiple DoS Vulnerabilities (CVE-2023-50387, CVE-2023-50868, KeyTrap).`
`↪..`
OID:1.3.6.1.4.1.25623.1.0.151715
Version used: `2024-02-21T05:06:27Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References

. . . continues on next page . . .

. . . continued from previous page . . .

```
cve: CVE-2023-50387
cve: CVE-2023-50868
url: https://kb.isc.org/docs/cve-2023-50387
url: https://kb.isc.org/docs/cve-2023-50868
url: https://www.athene-center.de/en/keytrap
cert-bund: WID-SEC-2025-0148
cert-bund: WID-SEC-2024-1347
cert-bund: WID-SEC-2024-1313
cert-bund: WID-SEC-2024-1307
cert-bund: WID-SEC-2024-1248
cert-bund: WID-SEC-2024-1226
cert-bund: WID-SEC-2024-1086
cert-bund: WID-SEC-2024-0387
cert-bund: WID-SEC-2024-0386
dfn-cert: DFN-CERT-2025-1459
dfn-cert: DFN-CERT-2025-0041
dfn-cert: DFN-CERT-2025-0010
dfn-cert: DFN-CERT-2024-2264
dfn-cert: DFN-CERT-2024-1904
dfn-cert: DFN-CERT-2024-1523
dfn-cert: DFN-CERT-2024-1516
dfn-cert: DFN-CERT-2024-1474
dfn-cert: DFN-CERT-2024-1413
dfn-cert: DFN-CERT-2024-1223
dfn-cert: DFN-CERT-2024-1011
dfn-cert: DFN-CERT-2024-0984
dfn-cert: DFN-CERT-2024-0977
dfn-cert: DFN-CERT-2024-0921
dfn-cert: DFN-CERT-2024-0829
dfn-cert: DFN-CERT-2024-0529
dfn-cert: DFN-CERT-2024-0498
dfn-cert: DFN-CERT-2024-0404
dfn-cert: DFN-CERT-2024-0399
dfn-cert: DFN-CERT-2024-0387
dfn-cert: DFN-CERT-2024-0379
dfn-cert: DFN-CERT-2024-0375
```

High (CVSS: 7.5)
NVT: ISC BIND Multiple Vulnerabilities (Feb 2019) - Linux

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

. . . continues on next page . . .

. . . continued from previous page . . .

ISC BIND is prone to multiple vulnerabilities.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.5-P4
Installation
path / port:       53/tcp
```

Solution:
Solution type: VendorFix
Update to version 9.11.5-S5, 9.11.5-P4, 9.12.3-P4 or later.

Affected Software/OS
ISC BIND versions 9.9.0-9.10.8-P1, 9.11.0-9.11.5-P2, 9.12.0-9.12.3-P2 and 9.9.3-S1-9.11.5-S3.

Vulnerability Insight
ISC BIND is prone to multiple vulnerabilities:
- A specially crafted packet can cause named to leak memory (CVE-2018-5744)
- An assertion failure can occur if a trust anchor rolls over to an unsupported key algorithm when using managed-keys (CVE-2018-5745)
- Zone transfer controls for writable DLZ zones were not effective (CVE-2019-6465)

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND Multiple Vulnerabilities (Feb 2019) - Linux`
OID:1.3.6.1.4.1.25623.1.0.142033
Version used: `2021-08-30T11:01:18Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References

```
cve: CVE-2018-5744
cve: CVE-2018-5745
cve: CVE-2019-6465
url: https://kb.isc.org/docs/cve-2018-5744
url: https://kb.isc.org/docs/cve-2018-5745
url: https://kb.isc.org/docs/cve-2019-6465
cert-bund: WID-SEC-2025-1194
cert-bund: CB-K19/0161
dfn-cert: DFN-CERT-2020-0672
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2019-2042
dfn-cert: DFN-CERT-2019-1119
dfn-cert: DFN-CERT-2019-0935
dfn-cert: DFN-CERT-2019-0781
dfn-cert: DFN-CERT-2019-0436
dfn-cert: DFN-CERT-2019-0435
dfn-cert: DFN-CERT-2019-0382
```

[return to 172.31.1.101]

2.1.4 Medium 10000/tcp

Medium (CVSS: 5.0)
NVT: SSL/TLS: Certificate Expired

Product detection result

```
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Collect and Report Certificate Details (OID: 1.3.6.1.4.1.25
↪623.1.0.103692)
```

Summary

The remote server's SSL/TLS certificate has already expired.

Quality of Detection (QoD): 99%

Vulnerability Detection Result

```
The certificate of the remote service expired on 2024-07-04 04:22:57.
Certificate details:
fingerprint (SHA-1)             | ACFF91A8C84FA54410311C1D828AD20C55F9B78F
fingerprint (SHA-256)           | 2D929DF102BC72C79E8288256E22E8B87B6D99B2E29316
↪865894A163AFB6DFF1
issued by                       | 1.2.840.113549.1.9.1=#726F6F744033626130613666
↪6265613865,CN=*,O=Webmin Webserver on 3ba0a6fbea8e
public key algorithm            | RSA
public key size (bits)          | 2048
serial                          | 67263F8B6EAA1EA9C13899C0F90A8015A7C2C7C0
signature algorithm             | sha256WithRSAEncryption
subject                         | 1.2.840.113549.1.9.1=#726F6F744033626130613666
↪6265613865,CN=*,O=Webmin Webserver on 3ba0a6fbea8e
subject alternative names (SAN) | None
valid from                      | 2019-07-06 04:22:57 UTC
valid until                     | 2024-07-04 04:22:57 UTC
```

Solution:
Solution type: Mitigation

. . . continues on next page . . .

. . . continued from previous page . . .

Replace the SSL/TLS certificate by a new one.

Vulnerability Insight
This script checks expiry dates of certificates associated with SSL/TLS-enabled services on the target and reports whether any have already expired.

Vulnerability Detection Method
Details: `SSL/TLS: Certificate Expired`
OID:1.3.6.1.4.1.25623.1.0.103955
Version used: `2024-06-14T05:05:48Z`

Product Detection Result
Product: `cpe:/a:ietf:transport_layer_security`
Method: `SSL/TLS: Collect and Report Certificate Details`
OID: 1.3.6.1.4.1.25623.1.0.103692)

Medium (CVSS: 5.0)
NVT: SSL/TLS: Renegotiation DoS Vulnerability (CVE-2011-1473, CVE-2011-5094)

Summary
The remote SSL/TLS service is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 70%

Vulnerability Detection Result

```
The following indicates that the remote SSL/TLS service is affected:
Protocol Version | Successful re-done SSL/TLS handshakes (Renegotiation) over an
↪ existing / already established SSL/TLS connection
--------------------------------------------------------------------------------
↪-------------------------------------------------
TLSv1.2          | 10
```

Impact
The flaw might make it easier for remote attackers to cause a DoS (CPU consumption) by performing many renegotiations within a single connection.

Solution:
Solution type: VendorFix
Users should contact their vendors for specific patch information.
A general solution is to remove/disable renegotiation capabilities altogether from/in the affected SSL/TLS service.

Affected Software/OS
Every SSL/TLS service which does not properly restrict client-initiated renegotiation.

. . . continues on next page . . .

. . . continued from previous page . . .

Vulnerability Insight
The flaw exists because the remote SSL/TLS service does not properly restrict client-initiated renegotiation within the SSL and TLS protocols.
Note: The referenced CVEs are affecting OpenSSL and Mozilla Network Security Services (NSS) but both are in a DISPUTED state with the following rationale:
> It can also be argued that it is the responsibility of server deployments, not a security library, to prevent or limit renegotiation when it is inappropriate within a specific environment.
Both CVEs are still kept in this VT as a reference to the origin of this flaw.

Vulnerability Detection Method
Checks if the remote service allows to re-do the same SSL/TLS handshake (Renegotiation) over an existing / already established SSL/TLS connection.
Details: `SSL/TLS: Renegotiation DoS Vulnerability (CVE-2011-1473, CVE-2011-5094)`
OID:1.3.6.1.4.1.25623.1.0.117761
Version used: `2024-09-27T05:05:23Z`

References
```
cve: CVE-2011-1473
cve: CVE-2011-5094
url: https://web.archive.org/web/20211201133213/https://orchilles.com/ssl-renego
↪tiation-dos/
url: https://mailarchive.ietf.org/arch/msg/tls/wdg46VE_jkYBbgJ5yE4P9nQ-8IU/
url: https://vincent.bernat.ch/en/blog/2011-ssl-dos-mitigation
url: https://www.openwall.com/lists/oss-security/2011/07/08/2
cert-bund: WID-SEC-2026-0180
cert-bund: WID-SEC-2024-1591
cert-bund: WID-SEC-2024-0796
cert-bund: WID-SEC-2023-1435
cert-bund: CB-K17/0980
cert-bund: CB-K17/0979
cert-bund: CB-K14/0772
cert-bund: CB-K13/0915
cert-bund: CB-K13/0462
dfn-cert: DFN-CERT-2025-0933
dfn-cert: DFN-CERT-2017-1013
dfn-cert: DFN-CERT-2017-1012
dfn-cert: DFN-CERT-2014-0809
dfn-cert: DFN-CERT-2013-1928
dfn-cert: DFN-CERT-2012-1112
```

Medium (CVSS: 6.1)
NVT: Webmin < 2.003 XSS Vulnerability

Summary
Webmin is prone to a cross-site scripting (XSS) vulnerability.

. . . continues on next page . . .

. . . continued from previous page . . .

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Installed version: 1.920
Fixed version:     2.003
Installation
path / port:       /
```

Solution:
Solution type: VendorFix
Update to version 2.003 or later.
Note: While there is no dedicated mention of the fix in any changelog the relevant code fix/commit as been included in the GitHub tag '2.003'.

Affected Software/OS
Webmin prior to version 2.003.

Vulnerability Insight
An XSS vulnerability exists in an unknown function of the file xterm/index.cgi.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Webmin < 2.003 XSS Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.126206
Version used: `2023-11-10T16:09:31Z`

References

```
cve: CVE-2022-3844
url: https://github.com/webmin/webmin/compare/2.001...2.003
url: https://github.com/webmin/webmin/commit/d3d33af3c0c3fd3a889c84e287a038b7a45
↪7d811
cert-bund: WID-SEC-2022-1957
```

Medium (CVSS: 6.1)
NVT: Webmin <= 1.941 Multiple XSS Vulnerabilities

Summary
Webmin is prone to multiple cross-site scripting vulnerabilities.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Installed version: 1.920
Fixed version:     1.953
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
Installation
path / port:        /
```

Solution:
Solution type: VendorFix
Update to version 1.953 or later.

Affected Software/OS
Webmin version 1.941 and prior.

Vulnerability Insight
The following vulnerabilities exist:
- XSS in the Command Shell module (CVE-2020-8820 and CVE-2020-8821)
- XSS in the Read Mail module (CVE-2020-12670)

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Webmin <= 1.941 Multiple XSS Vulnerabilities`
OID:1.3.6.1.4.1.25623.1.0.144734
Version used: `2021-08-16T12:00:57Z`

References
```
cve: CVE-2020-8820
cve: CVE-2020-8821
cve: CVE-2020-12670
url: https://www.webmin.com/security.html
cert-bund: CB-K20/0973
```

Medium (CVSS: 6.1)
NVT: Webmin <= 1.995 XSS Vulnerability

Summary
Webmin is prone to a cross-site scripting (XSS) vulnerability.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
Installed version: 1.920
Fixed version:     None
Installation
path / port:        /
```

Impact
An HTML email crafted by an attacker could capture browser cookies when opened.

. . . continues on next page . . .

. . . continued from previous page . . .

Solution:
Solution type: WillNotFix
No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.

Affected Software/OS
Webmin version 1.995 and prior.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `Webmin <= 1.995 XSS Vulnerability`
OID:1.3.6.1.4.1.25623.1.0.126099
Version used: `2023-08-03T05:05:16Z`

References
`cve: CVE-2022-36880`
`url: https://www.webmin.com/security.html`
`cert-bund: WID-SEC-2022-0838`

[return to 172.31.1.101]

2.1.5 Medium 53/udp

Medium (CVSS: 5.0)
NVT: DNS Cache Snooping Vulnerability (UDP) - Active Check

Summary
The DNS server is prone to a cache snooping vulnerability.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
```
Received (an) answer(s) for a non-recursive query for "example.com".
Result:
104.18.27.120
```

Impact
Attackers might gain information about cached DNS records which might lead to further attacks.
Note: This finding might be an acceptable risk if you:
- trust all clients which can reach the server
- do not allow recursive queries from outside your trusted client network.

Solution:

. . . continues on next page . . .

. . . continued from previous page . . .

Solution type: Mitigation
There are multiple possible mitigation steps depending on location and functionality needed by the DNS server:
- Disable recursion
- Don't allow public access to DNS Servers doing recursion
- Leave recursion enabled if the DNS Server stays on a corporate network that cannot be reached by untrusted clients
- If the risk is accepted either create an override for this result or configure the 'Private LAN' setting mentioned earlier

Vulnerability Insight
DNS cache snooping is when someone queries a DNS server in order to find out (snoop) if the DNS server has a specific DNS record cached, and thereby deduce if the DNS server's owner (or its users) have recently visited a specific site.
This may reveal information about the DNS server's owner, such as what vendor, bank, service provider, etc. they use. Especially if this is confirmed (snooped) multiple times over a period.
This method could even be used to gather statistical information - for example at what time does the DNS server's owner typically access his net bank etc. The cached DNS record's remaining TTL value can provide very accurate data for this.
DNS cache snooping is possible even if the DNS server is not configured to resolve recursively for 3rd parties, as long as it provides records from the cache also to 3rd parties (a.k.a. 'lame requests').

Vulnerability Detection Method
Sends a crafted DNS query and checks the response.
Notes:
- No scan result is expected if localhost (127.0.0.1) was scanned (self scanning)
- If the scanned network is e.g. a private LAN / private WAN which contains systems not accessible to the public (access restricted) and it is accepted that the service is disclosing information to this network please set the 'Network type' configuration of the following VT to e.g. 'Private LAN' or 'Private WAN':
Global variable settings (OID: 1.3.6.1.4.1.25623.1.0.12288)
Details: `DNS Cache Snooping Vulnerability (UDP) - Active Check`
OID:1.3.6.1.4.1.25623.1.0.146591
Version used: `2025-11-25T05:40:35Z`

References
`url: https://www.cs.unc.edu/~fabian/course_papers/cache_snooping.pdf`
`url: https://docs.microsoft.com/en-us/troubleshoot/windows-server/networking/dns`
`↪-server-cache-snooping-attacks`
`url: https://kb.isc.org/docs/aa-00509`
`url: https://kb.isc.org/docs/aa-00482`

Medium (CVSS: 6.8)
NVT: ISC BIND Cache Poisoning Vulnerability (CVE-2021-25220) - Linux

Product detection result
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)

Summary
ISC BIND is prone to a cache poisoning vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.37
Installation
path / port:       53/udp
```

Impact
The cache could become poisoned with incorrect records leading to queries being made to the wrong servers, which might also result in false information being returned to clients.

Solution:
Solution type: VendorFix
Update to version 9.11.37, 9.16.27, 9.18.1, 9.11.37-S1, 9.16.27-S1 or later.

Affected Software/OS
ISC BIND versions 9.1.0 through 9.11.36, 9.12.0 through 9.16.26, 9.11.4-S1 through 9.11.36-S1, 9.16.8-S1 through 9.16.26-S1 and 9.17.0 through 9.18.0.
Versions of BIND 9 back to 9.1.0, including Supported Preview Editions - are believed to be affected but have not been tested by the vendor as they are EOL.

Vulnerability Insight
When using forwarders, bogus NS records supplied by, or via, those forwarders may be cached and used by named if it needs to recurse for any reason, causing it to obtain and pass on potentially incorrect answers.
Some examples of configurations that will be vulnerable are:
- Resolvers using per zone or global forwarding with forward first (forward first is the default).
- Resolvers not using global forwarding, but with per-zone forwarding with either forward first (the default) or forward only.
- Resolvers configured with global forwarding along with zone statements that disable forwarding for part of the DNS namespace.
Authoritative-only BIND 9 servers are not vulnerable to this flaw.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.

. . . continues on next page . . .

. . . continued from previous page . . .

Details: ISC BIND Cache Poisoning Vulnerability (CVE-2021-25220) - Linux
OID:1.3.6.1.4.1.25623.1.0.113846
Version used: 2022-11-30T10:12:07Z

Product Detection Result
Product: cpe:/a:isc:bind:9.11.3
Method: ISC BIND Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
cve: CVE-2021-25220
url: https://kb.isc.org/docs/cve-2021-25220
cert-bund: WID-SEC-2024-1307
cert-bund: WID-SEC-2024-1226
cert-bund: WID-SEC-2024-0064
cert-bund: WID-SEC-2023-1812
cert-bund: WID-SEC-2023-1737
cert-bund: WID-SEC-2023-0809
cert-bund: WID-SEC-2022-1710
cert-bund: WID-SEC-2022-1335
cert-bund: WID-SEC-2022-1228
cert-bund: WID-SEC-2022-0969
cert-bund: WID-SEC-2022-0857
cert-bund: CB-K22/0324
dfn-cert: DFN-CERT-2025-3256
dfn-cert: DFN-CERT-2025-3234
dfn-cert: DFN-CERT-2024-1223
dfn-cert: DFN-CERT-2023-1592
dfn-cert: DFN-CERT-2023-0179
dfn-cert: DFN-CERT-2022-2266
dfn-cert: DFN-CERT-2022-1764
dfn-cert: DFN-CERT-2022-1143
dfn-cert: DFN-CERT-2022-0639
dfn-cert: DFN-CERT-2022-0630
dfn-cert: DFN-CERT-2022-0614

Medium (CVSS: 5.0)
NVT: ISC BIND DoS Vulnerability (Aug 2021) - Linux

Product detection result
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)

Summary

. . . continues on next page . . .

. . . continued from previous page . . .

ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.35
Installation
path / port:       53/udp
```

Solution:
Solution type: VendorFix
Update to version 9.11.35, 9.16.20, 9.17.17 or later.

Affected Software/OS
BIND version prior to 9.11.35, 9.16.x prior 9.16.20 and 9.17.x prior to 9.17.17.

Vulnerability Insight
named failed to check the opcode of responses when performing zone refreshes, stub zone updates, and UPDATE forwarding. This could lead to an assertion failure under certain conditions and has been addressed by rejecting responses whose opcode does not match the expected value.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (Aug 2021) - Linux`
OID:1.3.6.1.4.1.25623.1.0.117683
Version used: `2021-09-17T10:40:50Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References

```
url: https://downloads.isc.org/isc/bind9/9.17.17/doc/arm/html/notes.html#notes-f
↪or-bind-9-17-17
url: https://downloads.isc.org/isc/bind9/9.16.20/doc/arm/html/notes.html#notes-f
↪or-bind-9-16-20
url: https://downloads.isc.org/isc/bind9/9.11.35/doc/arm/notes.html#relnotes-9.1
↪1.35
```

Medium (CVSS: 5.9)
NVT: ISC BIND DoS Vulnerability (CVE-2019-6471) - Linux

. . . continues on next page . . .

. . . continued from previous page . . .

Product detection result
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)

Summary
ISC BIND is prone to a denial of service vulnerability when discarding malformed packets.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.8
Installation
path / port:       53/udp
```

Impact
An attacker who can cause a resolver to perform queries which will be answered by a server which responds with deliberately malformed answers can cause named to exit, denying service to clients.

Solution:
Solution type: VendorFix
Update to version 9.11.8, 9.12.4-P2, 9.14.3, 9.15.1, 9.11.8-S1 or later.

Affected Software/OS
ISC BIND versions 9.11.0 to 9.11.7, 9.12.0 to 9.12.4-P1, 9.14.0 to 9.14.2, all releases of the BIND 9.13 development branch, 9.15.0 and BIND Supported Preview Edition versions 9.11.3-S1 to 9.11.7-S1.

Vulnerability Insight
A race condition which may occur when discarding malformed packets can result in BIND exiting due to a REQUIRE assertion failure in dispatch.c.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: ISC BIND DoS Vulnerability (CVE-2019-6471) - Linux
OID:1.3.6.1.4.1.25623.1.0.140837
Version used: 2021-08-30T11:01:18Z

Product Detection Result
Product: cpe:/a:isc:bind:9.11.3
Method: ISC BIND Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.145294)

. . . continues on next page . . .

. . . continued from previous page . . .

References
cve: CVE-2019-6471
url: https://kb.isc.org/docs/cve-2019-6471
cert-bund: WID-SEC-2025-1197
cert-bund: CB-K19/0525
dfn-cert: DFN-CERT-2021-0955
dfn-cert: DFN-CERT-2019-2042
dfn-cert: DFN-CERT-2019-1755
dfn-cert: DFN-CERT-2019-1242

Medium (CVSS: 6.5)
NVT: ISC BIND DoS Vulnerability (CVE-2021-25214) - Linux

Product detection result
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result
Installed version: 9.11.3
Fixed version: 9.11.31
Installation
path / port: 53/udp

Impact
When a vulnerable version of named receives a malformed IXFR triggering the flaw described above, the named process will terminate due to a failed assertion the next time the transferred secondary zone is refreshed.

Solution:
Solution type: VendorFix
Update to version 9.11.31, 9.16.15, 9.17.12, 9.11.31-S1, 9.16.15-S1 or later.

Affected Software/OS
BIND 9.8.5 through 9.8.8, 9.9.3 through 9.11.29, 9.12.0 through 9.16.13, 9.9.3-S1 through 9.11.29-S1, 9.16.8-S1 through 9.16.13-S1 and 9.17.0 through 9.17.11.

Vulnerability Insight

. . . continues on next page . . .

. . . continued from previous page . . .

Incremental zone transfers (IXFR) provide a way of transferring changed portion(s) of a zone between servers. An IXFR stream containing SOA records with an owner name other than the transferred zone's apex may cause the receiving named server to inadvertently remove the SOA record for the zone in question from the zone database. This leads to an assertion failure when the next SOA refresh query for that zone is made.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2021-25214) - Linux`
OID:1.3.6.1.4.1.25623.1.0.145863
Version used: `2021-08-17T14:01:00Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
```
cve: CVE-2021-25214
url: https://kb.isc.org/docs/cve-2021-25214
cert-bund: WID-SEC-2025-2027
cert-bund: WID-SEC-2023-0063
cert-bund: CB-K21/0452
dfn-cert: DFN-CERT-2022-0566
dfn-cert: DFN-CERT-2022-0074
dfn-cert: DFN-CERT-2021-2388
dfn-cert: DFN-CERT-2021-0915
dfn-cert: DFN-CERT-2021-0898
```

Medium (CVSS: 5.3)
NVT: ISC BIND DoS Vulnerability (CVE-2021-25219)

Product detection result
```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result
```
Installed version: 9.11.3
Fixed version:     9.11.36
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
Installation
path / port:        53/udp
```

Impact
A successful attack exploiting this flaw causes a named resolver to spend most of its CPU time on managing and checking the lame cache. This results in client queries being responded to with large delays, and increased likelihood of DNS timeouts on client hosts.

Solution:
Solution type: VendorFix
Update to version 9.11.36, 9.16.22, 9.17.19, 9.11.36-S1, 9.16.22-S1 or later.

Affected Software/OS
BIND 9.3.0 through 9.11.35, 9.12.0 through 9.16.21, 9.9.3-S1 through 9.11.35-S1, 9.16.8-S1 through 9.16.21-S1 and 9.17.0 through 9.17.18.
Authoritative-only BIND 9 servers are not vulnerable to this flaw.

Vulnerability Insight
Exploitation of broken authoritative servers using a flaw in response processing can cause degradation in BIND resolver performance. The way the lame cache is currently designed makes it possible for its internal data structures to grow almost infinitely, which may cause significant delays in client query processing.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2021-25219)`
OID:1.3.6.1.4.1.25623.1.0.117759
Version used: `2021-11-05T03:03:34Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
`cve: CVE-2021-25219`
`url: https://kb.isc.org/docs/cve-2021-25219`
`cert-bund: WID-SEC-2022-0030`
`cert-bund: CB-K22/0249`
`cert-bund: CB-K21/1127`
`dfn-cert: DFN-CERT-2022-1764`
`dfn-cert: DFN-CERT-2022-0566`
`dfn-cert: DFN-CERT-2021-2586`
`dfn-cert: DFN-CERT-2021-2273`
`dfn-cert: DFN-CERT-2021-2255`

Medium (CVSS: 5.3)
NVT: ISC BIND DoS Vulnerability (CVE-2022-2795) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.16.33
Installation
path / port:       53/udp
```

Solution:
Solution type: VendorFix
Update to version 9.16.33, 9.18.7, 9.19.5, 9.16.33-S1 or later.

Affected Software/OS
ISC BIND version 9.0.0 through 9.16.32, 9.9.3-S1 through 9.11.37-S1, 9.16.8-S1 through 9.16.32-S1, 9.18.0 through 9.18.6 and 9.19.0 through 9.19.4.

Vulnerability Insight
A flaw in resolver code can cause named to spend excessive amounts of time on processing large delegations

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2022-2795) - Linux`
OID:1.3.6.1.4.1.25623.1.0.124164
Version used: `2023-10-18T05:05:17Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
`cve: CVE-2022-2795`
`url: https://kb.isc.org/docs/cve-2022-2795`
`cert-bund: WID-SEC-2024-1307`

. . . continues on next page . . .

. . . continued from previous page . . .

```
cert-bund: WID-SEC-2024-1226
cert-bund: WID-SEC-2024-0794
cert-bund: WID-SEC-2024-0064
cert-bund: WID-SEC-2023-1737
cert-bund: WID-SEC-2023-1542
cert-bund: WID-SEC-2023-0809
cert-bund: WID-SEC-2022-1492
dfn-cert: DFN-CERT-2024-1223
dfn-cert: DFN-CERT-2024-0963
dfn-cert: DFN-CERT-2023-1592
dfn-cert: DFN-CERT-2023-1285
dfn-cert: DFN-CERT-2023-1123
dfn-cert: DFN-CERT-2023-1057
dfn-cert: DFN-CERT-2023-0179
dfn-cert: DFN-CERT-2022-2354
dfn-cert: DFN-CERT-2022-2191
dfn-cert: DFN-CERT-2022-2099
```

Medium (CVSS: 6.5)
NVT: ISC BIND Policies Vulnerability (CVE-2018-5741) - Linux

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

ISC BIND is prone to an information disclosure vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.5
Installation
path / port:       53/udp
```

Impact

The krb5-subdomain and ms-subdomain update policy rule types permit updates from any client authenticated with a valid Kerberos or Windows machine principal from the REALM specified in the identity field, to modify records in the zone at or below the name specified in the name field. The incorrect documentation, however, indicated that the policy would be restricted to names at or below the machine's name as encoded in the Windows or Kerberos principal.

Solution:

Solution type: VendorFix

. . . continues on next page . . .

. . . continued from previous page . . .

Update to version 9.11.5, 9.12.3 or later.

Affected Software/OS
BIND version 9.x.

Vulnerability Insight
To provide fine-grained controls over the ability to use Dynamic DNS (DDNS) to update records in a zone, BIND 9 provides a feature called update-policy. Various rules can be configured to limit the types of updates that can be performed by a client, depending on the key used when sending the update request. Unfortunately, some rule types were not initially documented, and when documentation for them was added to the Administrator Reference Manual (ARM), the language that was added to the ARM at that time incorrectly described the behavior of two rule types, krb5-subdomain and ms-subdomain. This incorrect documentation could mislead operators into believing that policies they had configured were more restrictive than they actually were.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND Policies Vulnerability (CVE-2018-5741) - Linux`
OID:1.3.6.1.4.1.25623.1.0.146636
Version used: `2021-09-06T14:01:33Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
`cve: CVE-2018-5741`
`url: https://kb.isc.org/docs/cve-2018-5741`
`cert-bund: CB-K18/0932`
`dfn-cert: DFN-CERT-2020-1328`
`dfn-cert: DFN-CERT-2019-1594`
`dfn-cert: DFN-CERT-2019-0781`
`dfn-cert: DFN-CERT-2018-1934`

Medium (CVSS: 4.3)
NVT: ISC BIND update-policy Enforcement Vulnerability (CVE-2020-8624) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary

. . . continues on next page . . .

. . . continued from previous page . . .

ISC BIND is prone to a vulnerability where update-policy rules of type 'subdomain' are enforced incorrectly.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.22
Installation
path / port:       53/udp
```

Impact

An attacker who has been granted privileges to change a specific subset of the zone's content could abuse these unintended additional privileges to update other contents of the zone.

Solution:

Solution type: VendorFix

Update to version 9.11.22, 9.16.6, 9.17.4, 9.11.22-S1 or later.

Affected Software/OS

BIND 9.9.12 - 9.9.13, 9.10.7 - 9.10.8, 9.11.3 - 9.11.21, 9.12.1 - 9.16.5, 9.17.0 - 9.17.3, also affects 9.9.12-S1 - 9.9.13-S1 and 9.11.3-S1 - 9.11.21-S1.

Vulnerability Insight

Change 4885 inadvertently caused 'update-policy' rules of type 'subdomain' to be treated as if they were of type 'zonesub', allowing updates to all parts of the zone along with the intended subdomain.

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.

Details: `ISC BIND update-policy Enforcement Vulnerability (CVE-2020-8624) - Linux`

OID:1.3.6.1.4.1.25623.1.0.144439

Version used: `2021-07-07T11:00:41Z`

Product Detection Result

Product: `cpe:/a:isc:bind:9.11.3`

Method: `ISC BIND Detection Consolidation`

OID: 1.3.6.1.4.1.25623.1.0.145294)

References

```
cve: CVE-2020-8624
url: https://kb.isc.org/docs/cve-2020-8624
cert-bund: CB-K20/0837
dfn-cert: DFN-CERT-2021-0924
dfn-cert: DFN-CERT-2020-2588
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
dfn-cert: DFN-CERT-2020-2064
dfn-cert: DFN-CERT-2020-1875
dfn-cert: DFN-CERT-2020-1835
```

[return to 172.31.1.101]

2.1.6 Medium 53/tcp

Medium (CVSS: 6.8)
NVT: ISC BIND Cache Poisoning Vulnerability (CVE-2021-25220) - Linux

Product detection result
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)

Summary
ISC BIND is prone to a cache poisoning vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.37
Installation
path / port:       53/tcp
```

Impact
The cache could become poisoned with incorrect records leading to queries being made to the wrong servers, which might also result in false information being returned to clients.

Solution:
Solution type: VendorFix
Update to version 9.11.37, 9.16.27, 9.18.1, 9.11.37-S1, 9.16.27-S1 or later.

Affected Software/OS
ISC BIND versions 9.1.0 through 9.11.36, 9.12.0 through 9.16.26, 9.11.4-S1 through 9.11.36-S1, 9.16.8-S1 through 9.16.26-S1 and 9.17.0 through 9.18.0.
Versions of BIND 9 back to 9.1.0, including Supported Preview Editions - are believed to be affected but have not been tested by the vendor as they are EOL.

Vulnerability Insight
When using forwarders, bogus NS records supplied by, or via, those forwarders may be cached and used by named if it needs to recurse for any reason, causing it to obtain and pass on potentially incorrect answers.

. . . continues on next page . . .

. . . continued from previous page . . .

Some examples of configurations that will be vulnerable are:
- Resolvers using per zone or global forwarding with forward first (forward first is the default).
- Resolvers not using global forwarding, but with per-zone forwarding with either forward first (the default) or forward only.
- Resolvers configured with global forwarding along with zone statements that disable forwarding for part of the DNS namespace.
Authoritative-only BIND 9 servers are not vulnerable to this flaw.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND Cache Poisoning Vulnerability (CVE-2021-25220) - Linux`
OID:1.3.6.1.4.1.25623.1.0.113846
Version used: `2022-11-30T10:12:07Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
`cve: CVE-2021-25220`
`url: https://kb.isc.org/docs/cve-2021-25220`
`cert-bund: WID-SEC-2024-1307`
`cert-bund: WID-SEC-2024-1226`
`cert-bund: WID-SEC-2024-0064`
`cert-bund: WID-SEC-2023-1812`
`cert-bund: WID-SEC-2023-1737`
`cert-bund: WID-SEC-2023-0809`
`cert-bund: WID-SEC-2022-1710`
`cert-bund: WID-SEC-2022-1335`
`cert-bund: WID-SEC-2022-1228`
`cert-bund: WID-SEC-2022-0969`
`cert-bund: WID-SEC-2022-0857`
`cert-bund: CB-K22/0324`
`dfn-cert: DFN-CERT-2025-3256`
`dfn-cert: DFN-CERT-2025-3234`
`dfn-cert: DFN-CERT-2024-1223`
`dfn-cert: DFN-CERT-2023-1592`
`dfn-cert: DFN-CERT-2023-0179`
`dfn-cert: DFN-CERT-2022-2266`
`dfn-cert: DFN-CERT-2022-1764`
`dfn-cert: DFN-CERT-2022-1143`
`dfn-cert: DFN-CERT-2022-0639`
`dfn-cert: DFN-CERT-2022-0630`
`dfn-cert: DFN-CERT-2022-0614`

Medium (CVSS: 5.0)
NVT: ISC BIND DoS Vulnerability (Aug 2021) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.35
Installation
path / port:       53/tcp
```

Solution:
Solution type: VendorFix
Update to version 9.11.35, 9.16.20, 9.17.17 or later.

Affected Software/OS
BIND version prior to 9.11.35, 9.16.x prior 9.16.20 and 9.17.x prior to 9.17.17.

Vulnerability Insight
named failed to check the opcode of responses when performing zone refreshes, stub zone updates, and UPDATE forwarding. This could lead to an assertion failure under certain conditions and has been addressed by rejecting responses whose opcode does not match the expected value.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (Aug 2021) - Linux`
OID:1.3.6.1.4.1.25623.1.0.117683
Version used: `2021-09-17T10:40:50Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
`url: https://downloads.isc.org/isc/bind9/9.17.17/doc/arm/html/notes.html#notes-f`
`↪or-bind-9-17-17`
`url: https://downloads.isc.org/isc/bind9/9.16.20/doc/arm/html/notes.html#notes-f`

. . . continues on next page . . .

. . . continued from previous page . . .

```
↪or-bind-9-16-20
url: https://downloads.isc.org/isc/bind9/9.11.35/doc/arm/notes.html#relnotes-9.1
↪1.35
```

Medium (CVSS: 5.9)
NVT: ISC BIND DoS Vulnerability (CVE-2019-6471) - Linux

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

ISC BIND is prone to a denial of service vulnerability when discarding malformed packets.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.8
Installation
path / port:       53/tcp
```

Impact

An attacker who can cause a resolver to perform queries which will be answered by a server which responds with deliberately malformed answers can cause named to exit, denying service to clients.

Solution:

Solution type: VendorFix

Update to version 9.11.8, 9.12.4-P2, 9.14.3, 9.15.1, 9.11.8-S1 or later.

Affected Software/OS

ISC BIND versions 9.11.0 to 9.11.7, 9.12.0 to 9.12.4-P1, 9.14.0 to 9.14.2, all releases of the BIND 9.13 development branch, 9.15.0 and BIND Supported Preview Edition versions 9.11.3-S1 to 9.11.7-S1.

Vulnerability Insight

A race condition which may occur when discarding malformed packets can result in BIND exiting due to a REQUIRE assertion failure in dispatch.c.

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.

Details: `ISC BIND DoS Vulnerability (CVE-2019-6471) - Linux`

OID:1.3.6.1.4.1.25623.1.0.140837

. . . continues on next page . . .

. . . continued from previous page . . .

Version used: 2021-08-30T11:01:18Z

Product Detection Result
Product: cpe:/a:isc:bind:9.11.3
Method: ISC BIND Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
cve: CVE-2019-6471
url: https://kb.isc.org/docs/cve-2019-6471
cert-bund: WID-SEC-2025-1197
cert-bund: CB-K19/0525
dfn-cert: DFN-CERT-2021-0955
dfn-cert: DFN-CERT-2019-2042
dfn-cert: DFN-CERT-2019-1755
dfn-cert: DFN-CERT-2019-1242

Medium (CVSS: 6.5)
NVT: ISC BIND DoS Vulnerability (CVE-2021-25214) - Linux

Product detection result
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result
Installed version: 9.11.3
Fixed version: 9.11.31
Installation
path / port: 53/tcp

Impact
When a vulnerable version of named receives a malformed IXFR triggering the flaw described above, the named process will terminate due to a failed assertion the next time the transferred secondary zone is refreshed.

Solution:
Solution type: VendorFix
Update to version 9.11.31, 9.16.15, 9.17.12, 9.11.31-S1, 9.16.15-S1 or later.

. . . continues on next page . . .

. . . continued from previous page . . .

Affected Software/OS
BIND 9.8.5 through 9.8.8, 9.9.3 through 9.11.29, 9.12.0 through 9.16.13, 9.9.3-S1 through 9.11.29-S1, 9.16.8-S1 through 9.16.13-S1 and 9.17.0 through 9.17.11.

Vulnerability Insight
Incremental zone transfers (IXFR) provide a way of transferring changed portion(s) of a zone between servers. An IXFR stream containing SOA records with an owner name other than the transferred zone's apex may cause the receiving named server to inadvertently remove the SOA record for the zone in question from the zone database. This leads to an assertion failure when the next SOA refresh query for that zone is made.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2021-25214) - Linux`
OID:1.3.6.1.4.1.25623.1.0.145863
Version used: `2021-08-17T14:01:00Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
`cve: CVE-2021-25214`
`url: https://kb.isc.org/docs/cve-2021-25214`
`cert-bund: WID-SEC-2025-2027`
`cert-bund: WID-SEC-2023-0063`
`cert-bund: CB-K21/0452`
`dfn-cert: DFN-CERT-2022-0566`
`dfn-cert: DFN-CERT-2022-0074`
`dfn-cert: DFN-CERT-2021-2388`
`dfn-cert: DFN-CERT-2021-0915`
`dfn-cert: DFN-CERT-2021-0898`

Medium (CVSS: 5.3)
NVT: ISC BIND DoS Vulnerability (CVE-2021-25219)

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary
ISC BIND is prone to a denial of service (DoS) vulnerability.

. . . continues on next page . . .

. . . continued from previous page . . .

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.36
Installation
path / port:       53/tcp
```

Impact

A successful attack exploiting this flaw causes a named resolver to spend most of its CPU time on managing and checking the lame cache. This results in client queries being responded to with large delays, and increased likelihood of DNS timeouts on client hosts.

Solution:

Solution type: VendorFix

Update to version 9.11.36, 9.16.22, 9.17.19, 9.11.36-S1, 9.16.22-S1 or later.

Affected Software/OS

BIND 9.3.0 through 9.11.35, 9.12.0 through 9.16.21, 9.9.3-S1 through 9.11.35-S1, 9.16.8-S1 through 9.16.21-S1 and 9.17.0 through 9.17.18.
Authoritative-only BIND 9 servers are not vulnerable to this flaw.

Vulnerability Insight

Exploitation of broken authoritative servers using a flaw in response processing can cause degradation in BIND resolver performance. The way the lame cache is currently designed makes it possible for its internal data structures to grow almost infinitely, which may cause significant delays in client query processing.

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.
Details: `ISC BIND DoS Vulnerability (CVE-2021-25219)`
OID:1.3.6.1.4.1.25623.1.0.117759
Version used: `2021-11-05T03:03:34Z`

Product Detection Result

Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References

```
cve: CVE-2021-25219
url: https://kb.isc.org/docs/cve-2021-25219
cert-bund: WID-SEC-2022-0030
cert-bund: CB-K22/0249
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
cert-bund: CB-K21/1127
dfn-cert: DFN-CERT-2022-1764
dfn-cert: DFN-CERT-2022-0566
dfn-cert: DFN-CERT-2021-2586
dfn-cert: DFN-CERT-2021-2273
dfn-cert: DFN-CERT-2021-2255
```

Medium (CVSS: 5.3)
NVT: ISC BIND DoS Vulnerability (CVE-2022-2795) - Linux

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

ISC BIND is prone to a denial of service (DoS) vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.16.33
Installation
path / port:       53/tcp
```

Solution:

Solution type: VendorFix

Update to version 9.16.33, 9.18.7, 9.19.5, 9.16.33-S1 or later.

Affected Software/OS

ISC BIND version 9.0.0 through 9.16.32, 9.9.3-S1 through 9.11.37-S1, 9.16.8-S1 through 9.16.32-S1, 9.18.0 through 9.18.6 and 9.19.0 through 9.19.4.

Vulnerability Insight

A flaw in resolver code can cause named to spend excessive amounts of time on processing large delegations

Vulnerability Detection Method

Checks if a vulnerable version is present on the target host.

Details: `ISC BIND DoS Vulnerability (CVE-2022-2795) - Linux`

OID:1.3.6.1.4.1.25623.1.0.124164

Version used: `2023-10-18T05:05:17Z`

Product Detection Result

. . . continues on next page . . .

. . . continued from previous page . . .

Product: cpe:/a:isc:bind:9.11.3
Method: ISC BIND Detection Consolidation
OID: 1.3.6.1.4.1.25623.1.0.145294)

References

```
cve: CVE-2022-2795
url: https://kb.isc.org/docs/cve-2022-2795
cert-bund: WID-SEC-2024-1307
cert-bund: WID-SEC-2024-1226
cert-bund: WID-SEC-2024-0794
cert-bund: WID-SEC-2024-0064
cert-bund: WID-SEC-2023-1737
cert-bund: WID-SEC-2023-1542
cert-bund: WID-SEC-2023-0809
cert-bund: WID-SEC-2022-1492
dfn-cert: DFN-CERT-2024-1223
dfn-cert: DFN-CERT-2024-0963
dfn-cert: DFN-CERT-2023-1592
dfn-cert: DFN-CERT-2023-1285
dfn-cert: DFN-CERT-2023-1123
dfn-cert: DFN-CERT-2023-1057
dfn-cert: DFN-CERT-2023-0179
dfn-cert: DFN-CERT-2022-2354
dfn-cert: DFN-CERT-2022-2191
dfn-cert: DFN-CERT-2022-2099
```

Medium (CVSS: 6.5)
NVT: ISC BIND Policies Vulnerability (CVE-2018-5741) - Linux

Product detection result

```
cpe:/a:isc:bind:9.11.3
Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)
```

Summary

ISC BIND is prone to an information disclosure vulnerability.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.5
Installation
path / port:       53/tcp
```

. . . continues on next page . . .

. . . continued from previous page . . .

Impact
The krb5-subdomain and ms-subdomain update policy rule types permit updates from any client authenticated with a valid Kerberos or Windows machine principal from the REALM specified in the identity field, to modify records in the zone at or below the name specified in the name field. The incorrect documentation, however, indicated that the policy would be restricted to names at or below the machine's name as encoded in the Windows or Kerberos principal.

Solution:
Solution type: VendorFix
Update to version 9.11.5, 9.12.3 or later.

Affected Software/OS
BIND version 9.x.

Vulnerability Insight
To provide fine-grained controls over the ability to use Dynamic DNS (DDNS) to update records in a zone, BIND 9 provides a feature called update-policy. Various rules can be configured to limit the types of updates that can be performed by a client, depending on the key used when sending the update request. Unfortunately, some rule types were not initially documented, and when documentation for them was added to the Administrator Reference Manual (ARM), the language that was added to the ARM at that time incorrectly described the behavior of two rule types, krb5-subdomain and ms-subdomain. This incorrect documentation could mislead operators into believing that policies they had configured were more restrictive than they actually were.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND Policies Vulnerability (CVE-2018-5741) - Linux`
OID:1.3.6.1.4.1.25623.1.0.146636
Version used: `2021-09-06T14:01:33Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`
OID: 1.3.6.1.4.1.25623.1.0.145294)

References
`cve: CVE-2018-5741`
`url: https://kb.isc.org/docs/cve-2018-5741`
`cert-bund: CB-K18/0932`
`dfn-cert: DFN-CERT-2020-1328`
`dfn-cert: DFN-CERT-2019-1594`
`dfn-cert: DFN-CERT-2019-0781`
`dfn-cert: DFN-CERT-2018-1934`

Medium (CVSS: 4.3)
NVT: ISC BIND update-policy Enforcement Vulnerability (CVE-2020-8624) - Linux

Product detection result
`cpe:/a:isc:bind:9.11.3`
`Detected by ISC BIND Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.145294)`

Summary
ISC BIND is prone to a vulnerability where update-policy rules of type 'subdomain' are enforced incorrectly.

Quality of Detection (QoD): 30%

Vulnerability Detection Result

```
Installed version: 9.11.3
Fixed version:     9.11.22
Installation
path / port:       53/tcp
```

Impact
An attacker who has been granted privileges to change a specific subset of the zone's content could abuse these unintended additional privileges to update other contents of the zone.

Solution:
Solution type: VendorFix
Update to version 9.11.22, 9.16.6, 9.17.4, 9.11.22-S1 or later.

Affected Software/OS
BIND 9.9.12 - 9.9.13, 9.10.7 - 9.10.8, 9.11.3 - 9.11.21, 9.12.1 - 9.16.5, 9.17.0 - 9.17.3, also affects 9.9.12-S1 - 9.9.13-S1 and 9.11.3-S1 - 9.11.21-S1.

Vulnerability Insight
Change 4885 inadvertently caused 'update-policy' rules of type 'subdomain' to be treated as if they were of type 'zonesub', allowing updates to all parts of the zone along with the intended subdomain.

Vulnerability Detection Method
Checks if a vulnerable version is present on the target host.
Details: `ISC BIND update-policy Enforcement Vulnerability (CVE-2020-8624) - Linux`
OID:1.3.6.1.4.1.25623.1.0.144439
Version used: `2021-07-07T11:00:41Z`

Product Detection Result
Product: `cpe:/a:isc:bind:9.11.3`
Method: `ISC BIND Detection Consolidation`

. . . continues on next page . . .

. . . continued from previous page . . .

OID: 1.3.6.1.4.1.25623.1.0.145294)

References

```
cve: CVE-2020-8624
url: https://kb.isc.org/docs/cve-2020-8624
cert-bund: CB-K20/0837
dfn-cert: DFN-CERT-2021-0924
dfn-cert: DFN-CERT-2020-2588
dfn-cert: DFN-CERT-2020-2064
dfn-cert: DFN-CERT-2020-1875
dfn-cert: DFN-CERT-2020-1835
```

[return to 172.31.1.101]

2.1.7 Low general/tcp

Low (CVSS: 2.6)
NVT: TCP Timestamps Information Disclosure

Summary
The remote host implements TCP timestamps and therefore allows to compute the uptime.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
It was detected that the host implements RFC1323/RFC7323.
The following timestamps were retrieved with a delay of 1 seconds in-between:
Packet 1: 2646325110
Packet 2: 2646326222
```

Impact
A side effect of this feature is that the uptime of the remote host can sometimes be computed.

Solution:
Solution type: Mitigation
To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.
To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.
The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.
See the references for more information.

. . . continues on next page . . .

. . . continued from previous page . . .

Affected Software/OS
TCP implementations that implement RFC1323/RFC7323.

Vulnerability Insight
The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.

Vulnerability Detection Method
Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.
Details: `TCP Timestamps Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.80091
Version used: `2023-12-15T16:10:08Z`

References
`url: https://datatracker.ietf.org/doc/html/rfc1323`
`url: https://datatracker.ietf.org/doc/html/rfc7323`
`url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/d`
`↪ownload/details.aspx?id=9152`
`url: https://www.fortiguard.com/psirt/FG-IR-16-090`

[return to 172.31.1.101]

2.1.8 Low general/icmp

Low (CVSS: 2.1)
NVT: ICMP Timestamp Reply Information Disclosure

Summary
The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The following response / ICMP packet has been received:
- ICMP Type: 14
- ICMP Code: 0
```

Impact
This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:
Solution type: Mitigation
Various mitigations are possible:

. . . continues on next page . . .

. . . continued from previous page . . .

- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight
The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

Vulnerability Detection Method
Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.
Details: `ICMP Timestamp Reply Information Disclosure`
OID:1.3.6.1.4.1.25623.1.0.103190
Version used: `2025-01-21T05:37:33Z`

References
`cve: CVE-1999-0524`
`url: https://datatracker.ietf.org/doc/html/rfc792`
`url: https://datatracker.ietf.org/doc/html/rfc2780`
`cert-bund: CB-K15/1514`
`cert-bund: CB-K14/0632`
`dfn-cert: DFN-CERT-2014-0658`

[return to 172.31.1.101]

2.1.9 Log 10000/tcp

Log (CVSS: 0.0)
NVT: Response Time / No 404 Error Code Check

Summary
This VT tests if the remote web server does not reply with a 404 error code and checks if it is replying to the scanners requests in a reasonable amount of time.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The 'MiniServ' embedded server was found which is fragile when getting scanned.
↪HTTP scanning will be disabled for this host.
```

Solution:

. . . continues on next page . . .

. . . continued from previous page . . .

Vulnerability Insight
This web server might show the following issues:
- it is [mis]configured in that it does not return '404 Not Found' error codes when a non-existent file is requested, perhaps returning a site map, search page, authentication page or redirect instead.
The Scanner might enabled some counter measures for that, however they might be insufficient. If a great number of security issues are reported for this port, they might not all be accurate.
- it doesn't response in a reasonable amount of time to various HTTP requests sent by this VT. In order to keep the scan total time to a reasonable amount, the remote web server might not be tested. If the remote server should be tested it has to be fixed to have it reply to the scanners requests in a reasonable amount of time.
Alternatively the 'Maximum response time (in seconds)' preference could be raised to a higher value if longer scan times are accepted.

Log Method
Details: `Response Time / No 404 Error Code Check`
OID:1.3.6.1.4.1.25623.1.0.10386
Version used: `2025-04-11T15:45:04Z`

Log (CVSS: 0.0)
NVT: Services

Summary
This plugin performs service detection.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`A web server is running on this port through SSL`

Solution:

Vulnerability Insight
This plugin attempts to guess which service is running on the remote port(s). For instance, it searches for a web server which could listen on another port than 80 or 443 and makes this information available for other check routines.

Log Method
Details: `Services`
OID:1.3.6.1.4.1.25623.1.0.10330
Version used: `2025-03-05T05:38:53Z`

Log (CVSS: 0.0)
NVT: Services

Summary
This plugin performs service detection.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`A TLScustom server answered on this port`

Solution:

Vulnerability Insight
This plugin attempts to guess which service is running on the remote port(s). For instance, it searches for a web server which could listen on another port than 80 or 443 and makes this information available for other check routines.

Log Method
Details: `Services`
OID:1.3.6.1.4.1.25623.1.0.10330
Version used: `2025-03-05T05:38:53Z`

Log (CVSS: 0.0)
NVT: SSL/TLS: Certificate - Self-Signed Certificate Detection

Product detection result
```
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Collect and Report Certificate Details (OID: 1.3.6.1.4.1.25
↪623.1.0.103692)
```

Summary
The SSL/TLS certificate on this port is self-signed.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
```
The certificate of the remote service is self signed.
Certificate details:
fingerprint (SHA-1)             | ACFF91A8C84FA54410311C1D828AD20C55F9B78F
fingerprint (SHA-256)           | 2D929DF102BC72C79E8288256E22E8B87B6D99B2E29316
↪865894A163AFB6DFF1
issued by                       | 1.2.840.113549.1.9.1=#726F6F744033626130613666
↪6265613865,CN=*,O=Webmin Webserver on 3ba0a6fbea8e
public key algorithm            | RSA
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
public key size (bits)          | 2048
serial                          | 67263F8B6EAA1EA9C13899C0F90A8015A7C2C7C0
signature algorithm             | sha256WithRSAEncryption
subject                         | 1.2.840.113549.1.9.1=#726F6F744033626130613666
↪6265613865,CN=*,O=Webmin Webserver on 3ba0a6fbea8e
subject alternative names (SAN) | None
valid from                      | 2019-07-06 04:22:57 UTC
valid until                     | 2024-07-04 04:22:57 UTC
```

Solution:

Log Method
Detects and reports if the issuer's distinguished name of the certificate is exactly the same as the subject's distinguished name.
Details: `SSL/TLS: Certificate - Self-Signed Certificate Detection`
OID:1.3.6.1.4.1.25623.1.0.103140
Version used: `2025-07-15T05:43:27Z`

Product Detection Result
Product: `cpe:/a:ietf:transport_layer_security`
Method: `SSL/TLS: Collect and Report Certificate Details`
OID: 1.3.6.1.4.1.25623.1.0.103692)

References
`url: http://en.wikipedia.org/wiki/Self-signed_certificate`
`url: https://datatracker.ietf.org/doc/html/rfc5280#appendix-C.1`

Log (CVSS: 0.0)
NVT: SSL/TLS: Certificate - Subject Common Name Does Not Match Server FQDN

Product detection result
`cpe:/a:ietf:transport_layer_security`
`Detected by SSL/TLS: Collect and Report Certificate Details (OID: 1.3.6.1.4.1.25`
`↪623.1.0.103692)`

Summary
The SSL/TLS certificate contains a common name (CN) that does not match the hostname.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
`The certificate of the remote service contains a common name (CN) that does not`
`↪match the hostname "bind.trabalho_vulnnet".`

. . . continues on next page . . .

. . . continued from previous page . . .

```
Certificate details:
fingerprint (SHA-1)             | ACFF91A8C84FA54410311C1D828AD20C55F9B78F
fingerprint (SHA-256)           | 2D929DF102BC72C79E8288256E22E8B87B6D99B2E29316
↪865894A163AFB6DFF1
issued by                       | 1.2.840.113549.1.9.1=#726F6F744033626130613666
↪6265613865,CN=*,O=Webmin Webserver on 3ba0a6fbea8e
public key algorithm            | RSA
public key size (bits)          | 2048
serial                          | 67263F8B6EAA1EA9C13899C0F90A8015A7C2C7C0
signature algorithm             | sha256WithRSAEncryption
subject                         | 1.2.840.113549.1.9.1=#726F6F744033626130613666
↪6265613865,CN=*,O=Webmin Webserver on 3ba0a6fbea8e
subject alternative names (SAN) | None
valid from                      | 2019-07-06 04:22:57 UTC
valid until                     | 2024-07-04 04:22:57 UTC
```

Solution:

Log Method
Details: SSL/TLS: Certificate - Subject Common Name Does Not Match Server FQDN
OID:1.3.6.1.4.1.25623.1.0.103141
Version used: 2024-06-14T05:05:48Z

Product Detection Result
Product: cpe:/a:ietf:transport_layer_security
Method: SSL/TLS: Collect and Report Certificate Details
OID: 1.3.6.1.4.1.25623.1.0.103692)

Log (CVSS: 0.0)
NVT: SSL/TLS: Collect and Report Certificate Details

Summary
This script collects and reports the details of all SSL/TLS certificates.
This data will be used by other tests to verify server certificates.

Quality of Detection (QoD): 98%

Vulnerability Detection Result

```
The following certificate details of the remote service were collected.
Certificate details:
fingerprint (SHA-1)             | ACFF91A8C84FA54410311C1D828AD20C55F9B78F
fingerprint (SHA-256)           | 2D929DF102BC72C79E8288256E22E8B87B6D99B2E29316
↪865894A163AFB6DFF1
issued by                       | 1.2.840.113549.1.9.1=#726F6F744033626130613666
↪6265613865,CN=*,O=Webmin Webserver on 3ba0a6fbea8e
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
public key algorithm            | RSA
public key size (bits)          | 2048
serial                          | 67263F8B6EAA1EA9C13899C0F90A8015A7C2C7C0
signature algorithm             | sha256WithRSAEncryption
subject                         | 1.2.840.113549.1.9.1=#726F6F744033626130613666
↪6265613865,CN=*,O=Webmin Webserver on 3ba0a6fbea8e
subject alternative names (SAN) | None
valid from                      | 2019-07-06 04:22:57 UTC
valid until                     | 2024-07-04 04:22:57 UTC
```

Solution:

Log Method
Details: SSL/TLS: Collect and Report Certificate Details
OID:1.3.6.1.4.1.25623.1.0.103692
Version used: 2024-09-27T05:05:23Z

Log (CVSS: 0.0)
NVT: SSL/TLS: Report Medium Cipher Suites

Product detection result
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0.
↪802067)

Summary
This routine reports all Medium SSL/TLS cipher suites accepted by a service.

Quality of Detection (QoD): 98%

Vulnerability Detection Result

```
'Medium' cipher suites accepted by this service via the TLSv1.2 protocol:
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256
TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384
TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA256
TLS_RSA_WITH_AES_128_GCM_SHA256
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_256_CBC_SHA256
TLS_RSA_WITH_AES_256_GCM_SHA384
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
'Medium' cipher suites accepted by this service via the TLSv1.3 protocol:
TLS_AES_128_GCM_SHA256
```

Solution:

Vulnerability Insight
Any cipher suite considered to be secure for only the next 10 years is considered as medium.

Log Method
Details: `SSL/TLS: Report Medium Cipher Suites`
OID:1.3.6.1.4.1.25623.1.0.902816
Version used: `2024-09-27T05:05:23Z`

Product Detection Result
Product: `cpe:/a:ietf:transport_layer_security`
Method: `SSL/TLS: Report Supported Cipher Suites`
OID: 1.3.6.1.4.1.25623.1.0.802067)

Log (CVSS: 0.0)
NVT: SSL/TLS: Report Non Weak Cipher Suites

Product detection result

```
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0.
↪802067)
```

Summary
This routine reports all Non Weak SSL/TLS cipher suites accepted by a service.

Quality of Detection (QoD): 98%

Vulnerability Detection Result

```
'Non Weak' cipher suites accepted by this service via the TLSv1.2 protocol:
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256
TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384
TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305_SHA256
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA256
TLS_RSA_WITH_AES_128_GCM_SHA256
TLS_RSA_WITH_AES_256_CBC_SHA
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
TLS_RSA_WITH_AES_256_CBC_SHA256
TLS_RSA_WITH_AES_256_GCM_SHA384
'Non Weak' cipher suites accepted by this service via the TLSv1.3 protocol:
TLS_AES_128_GCM_SHA256
TLS_AES_256_GCM_SHA384
TLS_CHACHA20_POLY1305_SHA256
```

Solution:

Log Method
Details: `SSL/TLS: Report Non Weak Cipher Suites`
OID:1.3.6.1.4.1.25623.1.0.103441
Version used: `2024-09-27T05:05:23Z`

Product Detection Result
Product: `cpe:/a:ietf:transport_layer_security`
Method: `SSL/TLS: Report Supported Cipher Suites`
OID: 1.3.6.1.4.1.25623.1.0.802067)

Log (CVSS: 0.0)
NVT: SSL/TLS: Report Perfect Forward Secrecy (PFS) Cipher Suites

Product detection result

```
cpe:/a:ietf:transport_layer_security
Detected by SSL/TLS: Report Supported Cipher Suites (OID: 1.3.6.1.4.1.25623.1.0.
↪802067)
```

Summary
This routine reports all SSL/TLS cipher suites accepted by a service which are supporting Perfect Forward Secrecy (PFS).

Quality of Detection (QoD): 98%

Vulnerability Detection Result

```
Cipher suites supporting Perfect Forward Secrecy (PFS) are accepted by this serv
↪ice via the TLSv1.2 protocol:
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256
TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384
TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305_SHA256
Cipher suites supporting Perfect Forward Secrecy (PFS) are accepted by this serv
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
↪ice via the TLSv1.3 protocol:
TLS_AES_128_GCM_SHA256
TLS_AES_256_GCM_SHA384
TLS_CHACHA20_POLY1305_SHA256
```

Solution:

Log Method
Details: SSL/TLS: Report Perfect Forward Secrecy (PFS) Cipher Suites
OID:1.3.6.1.4.1.25623.1.0.105018
Version used: 2024-09-30T08:38:05Z

Product Detection Result
Product: cpe:/a:ietf:transport_layer_security
Method: SSL/TLS: Report Supported Cipher Suites
OID: 1.3.6.1.4.1.25623.1.0.802067)

Log (CVSS: 0.0)
NVT: SSL/TLS: Report Supported Cipher Suites

Summary
This routine reports all SSL/TLS cipher suites accepted by a service.

Quality of Detection (QoD): 98%

Vulnerability Detection Result

```
'Strong' cipher suites accepted by this service via the TLSv1.2 protocol:
TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305_SHA256
'Medium' cipher suites accepted by this service via the TLSv1.2 protocol:
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256
TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384
TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384
TLS_RSA_WITH_AES_128_CBC_SHA
TLS_RSA_WITH_AES_128_CBC_SHA256
TLS_RSA_WITH_AES_128_GCM_SHA256
TLS_RSA_WITH_AES_256_CBC_SHA
TLS_RSA_WITH_AES_256_CBC_SHA256
TLS_RSA_WITH_AES_256_GCM_SHA384
No 'Weak' cipher suites accepted by this service via the TLSv1.2 protocol.
No 'Null' cipher suites accepted by this service via the TLSv1.2 protocol.
No 'Anonymous' cipher suites accepted by this service via the TLSv1.2 protocol.
'Strong' cipher suites accepted by this service via the TLSv1.3 protocol:
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
TLS_AES_256_GCM_SHA384
TLS_CHACHA20_POLY1305_SHA256
'Medium' cipher suites accepted by this service via the TLSv1.3 protocol:
TLS_AES_128_GCM_SHA256
No 'Weak' cipher suites accepted by this service via the TLSv1.3 protocol.
No 'Null' cipher suites accepted by this service via the TLSv1.3 protocol.
No 'Anonymous' cipher suites accepted by this service via the TLSv1.3 protocol.
```

Solution:

Vulnerability Insight
Notes:
- As the VT 'SSL/TLS: Check Supported Cipher Suites' (OID: 1.3.6.1.4.1.25623.1.0.900234) might run into a timeout the actual reporting of all accepted cipher suites takes place in this VT instead.
- SSLv2 ciphers are not getting reported as the protocol itself is deprecated, needs to be considered as weak and is reported separately as deprecated.

Log Method
Details: `SSL/TLS: Report Supported Cipher Suites`
OID:1.3.6.1.4.1.25623.1.0.802067
Version used: `2024-09-27T05:05:23Z`

Log (CVSS: 0.0)
NVT: SSL/TLS: Safe/Secure Renegotiation Support Status

Summary
Checks and reports if a remote SSL/TLS service supports safe/secure renegotiation.

Quality of Detection (QoD): 98%

Vulnerability Detection Result

```
Protocol Version | Safe/Secure Renegotiation Support Status
-------------------------------------------------------------------------------
↪-------------------------------------------------------------------------------
↪-------------------------------------
SSLv3            | Unknown, Reason: Scanner failed to negotiate an SSL/TLS conne
↪ction (Either the scanner or the remote host is probably not supporting / acce
↪pting this SSL/TLS protocol version).
TLSv1.0          | Unknown, Reason: Scanner failed to negotiate an SSL/TLS conne
↪ction (Either the scanner or the remote host is probably not supporting / acce
↪pting this SSL/TLS protocol version).
TLSv1.1          | Unknown, Reason: Scanner failed to negotiate an SSL/TLS conne
↪ction (Either the scanner or the remote host is probably not supporting / acce
↪pting this SSL/TLS protocol version).
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
TLSv1.2          | Enabled, Note: While the remote service announces the support
↪ of safe/secure renegotiation it still might not support / accept renegotiatio
↪n at all.
TLSv1.3          | Disabled (The TLSv1.3 protocol generally doesn't support rene
↪gotiation so this is always reported as 'Disabled')
```

Solution:

Log Method
Details: SSL/TLS: Safe/Secure Renegotiation Support Status
OID:1.3.6.1.4.1.25623.1.0.117757
Version used: 2024-09-27T05:05:23Z

References
url: https://www.gnutls.org/manual/html_node/Safe-renegotiation.html
url: https://wiki.openssl.org/index.php/TLS1.3#Renegotiation
url: https://datatracker.ietf.org/doc/html/rfc5746

Log (CVSS: 0.0)
NVT: SSL/TLS: Untrusted Certificate Detection

Summary
Checks and reports if a remote SSL/TLS service is using a certificate which is untrusted / the verification against the system wide trust store has failed.

Quality of Detection (QoD): 98%

Vulnerability Detection Result

```
The remote SSL/TLS server is using the following certificate(s) which failed the
↪ verification against the system wide trust store (serial:issuer):
67263F8B6EAA1EA9C13899C0F90A8015A7C2C7C0:1.2.840.113549.1.9.1=#726F6F74403362613
↪06136666265613865,CN=*,O=Webmin Webserver on 3ba0a6fbea8e (Server certificate)
```

Solution:

Log Method
Details: SSL/TLS: Untrusted Certificate Detection
OID:1.3.6.1.4.1.25623.1.0.117764
Version used: 2024-09-27T05:05:23Z

Log (CVSS: 0.0)
NVT: SSL/TLS: Version Detection

. . . continues on next page . . .

. . . continued from previous page . . .

Summary
Enumeration and reporting of SSL/TLS protocol versions supported by a remote service.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The remote SSL/TLS service supports the following SSL/TLS protocol version(s):
TLSv1.2
TLSv1.3
```

Solution:

Log Method
Sends multiple connection requests to the remote service and attempts to determine the SSL/TLS protocol versions supported by the service from the replies.
Note: The supported SSL/TLS protocol versions included in the report of this VT are reported independently from the allowed / supported SSL/TLS ciphers.
Details: `SSL/TLS: Version Detection`
OID:1.3.6.1.4.1.25623.1.0.105782
Version used: `2024-09-27T05:05:23Z`

Log (CVSS: 0.0)
NVT: Web Application Scanning Consolidation / Info Reporting

Summary
The script consolidates and reports various information for web application (formerly called 'CGI') scanning.
This information is based on the following scripts / settings:
- HTTP-Version Detection (OID: 1.3.6.1.4.1.25623.1.0.100034)
- No 404 check (OID: 1.3.6.1.4.1.25623.1.0.10386)
- Web mirroring / webmirror.nasl (OID: 1.3.6.1.4.1.25623.1.0.10662)
- Directory Scanner / DDI_Directory_Scanner.nasl (OID: 1.3.6.1.4.1.25623.1.0.11032)
- The configured 'cgi_path' within the 'Scanner Preferences' of the scan config in use
- The configured 'Enable CGI scanning', 'Enable generic web application scanning' and 'Add historic /scripts and /cgi-bin to directories for CGI scanning' within the 'Global variable settings' of the scan config in use
If you think any of this information is wrong please report it to the referenced community forum.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
The Hostname/IP "bind.trabalho_vulnnet" was used to access the remote host.
Generic web application scanning is disabled for this host via the "Enable gener
↪ic web application scanning" option within the "Global variable settings" of t
↪he scan config in use.
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
This service is marked as broken and no web application scanning is launched aga
↪inst it. Reason(s):
-----
 - The 'MiniServ' embedded server was found which is fragile when getting scanne
↪d. HTTP scanning will be disabled for this host.
-----
Requests to this service are done via HTTP/1.0.
This service seems to be NOT able to host PHP scripts.
This service seems to be NOT able to host ASP scripts.
The User-Agent "Mozilla/5.0 [en] (X11, U; OpenVAS-VT <version replaced>)" was us
↪ed to access the remote host.
Historic /scripts and /cgi-bin are not added to the directories used for web app
↪lication scanning. You can enable this again with the "Add historic /scripts a
↪nd /cgi-bin to directories for CGI scanning" option within the "Global variabl
↪e settings" of the scan config in use.
The following directories were used for web application scanning:
https://bind.trabalho_vulnnet:10000/
While this is not, in and of itself, a bug, you should manually inspect these di
↪rectories to ensure that they are in compliance with company security standard
↪s
```

Solution:

Log Method
Details: Web Application Scanning Consolidation / Info Reporting
OID:1.3.6.1.4.1.25623.1.0.111038
Version used: 2026-01-13T05:47:36Z

References
url: https://forum.greenbone.net/c/vulnerability-tests/7

Log (CVSS: 0.0)
NVT: Webmin / Usermin Detection (HTTP)

Summary
HTTP based detection of Webmin / Usermin.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Detected Webmin
Version:       1.920
Location:      /
CPE:           cpe:/a:webmin:webmin:1.920
Concluded from version/product identification result:
```

. . . continues on next page . . .

. . . continued from previous page . . .

```
Server: MiniServ/1.920
<title>Login to Webmin</title>
```

Solution:

Log Method
Details: Webmin / Usermin Detection (HTTP)
OID:1.3.6.1.4.1.25623.1.0.10757
Version used: 2023-08-01T13:29:10Z

[return to 172.31.1.101]

2.1.10 Log general/tcp

Log (CVSS: 0.0)
NVT: Hostname Determination Reporting

Summary
The script reports information on how the hostname of the target was determined.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Hostname determination for IP 172.31.1.101:
Hostname|Source
bind.trabalho_vulnnet|Reverse-DNS
```

Solution:

Log Method
Details: Hostname Determination Reporting
OID:1.3.6.1.4.1.25623.1.0.108449
Version used: 2022-07-27T10:11:28Z

Log (CVSS: 0.0)
NVT: IP Forwarding Enabled - Active Check

Summary
Checks if the remote host has IP forwarding enabled.

Quality of Detection (QoD): 70%

. . . continues on next page . . .

. . . continued from previous page . . .

Vulnerability Detection Result

```
It was possible to route a TCP packet through the target host and received an an
↪swer which means IP forwarding is enabled.
```

Solution:

Log Method

Sends a crafted Local Link Layer (LLL) frame and checks the response.
Details: `IP Forwarding Enabled - Active Check`
OID:1.3.6.1.4.1.25623.1.0.147205
Version used: `2021-12-03T08:27:06Z`

References

`cve: CVE-1999-0511`

Log (CVSS: 0.0)
NVT: ISC BIND Detection Consolidation

Summary

Consolidation of ISC BIND detections.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Detected ISC BIND
Version:       9.11.3
Location:      53/tcp
CPE:           cpe:/a:isc:bind:9.11.3
Concluded from version/product identification result:
9.11.3-1ubuntu1.8-Ubuntu
Detected ISC BIND
Version:       9.11.3
Location:      53/udp
CPE:           cpe:/a:isc:bind:9.11.3
Concluded from version/product identification result:
9.11.3-1ubuntu1.8-Ubuntu
```

Solution:

Log Method

Details: `ISC BIND Detection Consolidation`
OID:1.3.6.1.4.1.25623.1.0.145294
Version used: `2025-10-31T05:40:56Z`

. . . continues on next page . . .

. . . continued from previous page . . .

References
url: https://www.isc.org/bind/

Log (CVSS: 0.0)
NVT: OS Detection Consolidation and Reporting

Summary
This script consolidates the OS information detected by several VTs and tries to find the best matching OS.
Furthermore it reports all previously collected information leading to this best matching OS. It also reports possible additional information which might help to improve the OS detection.
If any of this information is wrong or could be improved please consider to report these to the referenced community forum.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

```
Best matching OS:
OS:           Ubuntu
CPE:          cpe:/o:canonical:ubuntu_linux
Found by VT:  1.3.6.1.4.1.25623.1.0.108014 (Operating System (OS) Detection (DNS
↪))
Concluded from DNS server banner on port 53/tcp: 9.11.3-1ubuntu1.8-Ubuntu
Setting key "Host/runs_unixoide" based on this information
Other OS detections (in order of reliability):
OS:           Ubuntu
CPE:          cpe:/o:canonical:ubuntu_linux
Found by VT:  1.3.6.1.4.1.25623.1.0.108014 (Operating System (OS) Detection (DNS
↪))
Concluded from DNS server banner on port 53/udp: 9.11.3-1ubuntu1.8-Ubuntu
```

Solution:

Log Method
Details: OS Detection Consolidation and Reporting
OID:1.3.6.1.4.1.25623.1.0.105937
Version used: 2026-01-21T05:50:46Z

References
url: https://forum.greenbone.net/c/vulnerability-tests/7

Log (CVSS: 0.0)
NVT: SSL/TLS: Hostname discovery from server certificate

Summary
It was possible to discover an additional hostname of this server from its certificate Common or Subject Alt Name.

Quality of Detection (QoD): 98%

Vulnerability Detection Result
```
The following additional but not resolvable hostnames were detected:
*
```

Solution:

Log Method
Details: `SSL/TLS: Hostname discovery from server certificate`
OID:1.3.6.1.4.1.25623.1.0.111010
Version used: `2021-11-22T15:32:39Z`

Log (CVSS: 0.0)
NVT: Traceroute

Summary
Collect information about the network route and network distance between the scanner host and the target host.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
```
Network route from scanner (172.30.0.2) to target (172.31.1.101):
172.30.0.2
172.31.1.101
Network distance between scanner and target: 2
```

Solution:

Vulnerability Insight
For internal networks, the distances are usually small, often less than 4 hosts between scanner and target. For public targets the distance is greater and might be 10 hosts or more.

Log Method
A combination of the protocols ICMP and TCP is used to determine the route. This method is applicable for IPv4 only and it is also known as 'traceroute'.
Details: `Traceroute`

. . . continues on next page . . .

. . . continued from previous page . . .

OID:1.3.6.1.4.1.25623.1.0.51662
Version used: 2022-10-17T11:13:19Z

[return to 172.31.1.101]

2.1.11 Log 53/udp

Log (CVSS: 0.0)
NVT: DNS Recursion Enabled (UDP) - Active Check

Summary
The DNS server has recursion enabled.

Quality of Detection (QoD): 70%

Vulnerability Detection Result
The DNS server replied to a DNS query to 'example.com' with the recursion flag s
↪et in the response.

Solution:

Vulnerability Insight
Recursion refers to the process of having the DNS server itself to make queries to other DNS servers on behalf of the client who made the original request.

Log Method
Sends a crafted DNS query via UDP and checks the response.
Details: DNS Recursion Enabled (UDP) - Active Check
OID:1.3.6.1.4.1.25623.1.0.147232
Version used: 2022-07-18T10:11:09Z

References
url: https://en.wikipedia.org/wiki/Domain_Name_System#Recursive_and_caching_name
↪_server

Log (CVSS: 0.0)
NVT: DNS Server Detection (UDP)

Summary
UDP based detection of a DNS server.

Quality of Detection (QoD): 80%

. . . continues on next page . . .

. . . continued from previous page . . .

Vulnerability Detection Result
The remote DNS server banner is:
9.11.3-1ubuntu1.8-Ubuntu

Solution:

Log Method
Details: DNS Server Detection (UDP)
OID:1.3.6.1.4.1.25623.1.0.100069
Version used: 2025-11-26T05:40:08Z

[return to 172.31.1.101]

2.1.12 Log general/CPE-T

Log (CVSS: 0.0)
NVT: CPE Inventory

Summary
This routine uses information collected by other routines about CPE identities of operating systems, services and applications detected during the scan.
Note: Some CPEs for specific products might show up twice or more in the output. Background: After a product got renamed or a specific vendor was acquired by another one it might happen that a product gets a new CPE within the NVD CPE Dictionary but older entries are kept with the older CPE.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
172.31.1.101|cpe:/a:ietf:transport_layer_security:1.2
172.31.1.101|cpe:/a:ietf:transport_layer_security:1.3
172.31.1.101|cpe:/a:isc:bind:9.11.3
172.31.1.101|cpe:/a:webmin:webmin:1.920
172.31.1.101|cpe:/o:canonical:ubuntu_linux

Solution:

Log Method
Details: CPE Inventory
OID:1.3.6.1.4.1.25623.1.0.810002
Version used: 2022-07-27T10:11:28Z

. . . continues on next page . . .

. . . continued from previous page . . .

References
`url: https://nvd.nist.gov/products/cpe`

[return to 172.31.1.101]

2.1.13 Log 53/tcp

Log (CVSS: 0.0)
NVT: DNS Server Detection (TCP)

Summary
TCP based detection of a DNS server.

Quality of Detection (QoD): 80%

Vulnerability Detection Result
`The remote DNS server banner is:`
`9.11.3-1ubuntu1.8-Ubuntu`

Solution:

Log Method
Details: `DNS Server Detection (TCP)`
OID:1.3.6.1.4.1.25623.1.0.108018
Version used: `2025-12-12T15:41:28Z`

[return to 172.31.1.101]