Lecture 1 Introduction

CS101 Algorithms and Data Structures

Instructor: Dengji Zhao; Yuyao Zhang; Xin Liu; Hao Geng 2022-09-05

Outline


What will we learn from this course?

How we manage this course?


Definition of Data Structure

- A data structure is a scheme for organizing data in the memory of a computer.
- The way in which the data is organized affects the performance of an algorithm for different tasks.
- 数据结构 (data structure) 是计算机中存储、组织数据的方式。通常情况下,精心选择的数据结构可以带来最优效率的算法 (algorithm)。

How to combat problems via a computer









- The following two operations are essential for efficiently arranging your books:
 - Operation 1: how to insert new books?
 - Operation 2: how to find/access an existing book?

- Method 1: randomly insert new books.
 - Operation 1: how to insert new books?

Insert the book wherever there is an available space. Nice and easy!

Operation 2: how to find/access an existing book?

It depends ...

- Method 2: insert new books according to the alphabets order of the first letter.
 - Operation 1: how to insert new books?

EX: we bought a new book "Algorithm".

Operation 2: how to find/access an existing book?

EX: Binary search!

 Discussion 1: is Method 2 absolutely better/more efficient than Method 1?

Method 1: randomly insert new books.

Method 2: insert new books according to the alphabets order of the first letter.

Discussion 2: how can we further improve Method 2?

- Method 3: cluster books according to different topics (computer science, economics, agriculture, politics...), then insert new books according to the alphabets order of the first letter.
 - Operation 1: how to insert new books?

EX: we bought a new book "Algorithm".

Operation 2: how to find/access an existing book?

EX: Binary search for topic first, then binary search for book title.

Discussion 3: how much space we should preserve for each topic?
 How many topics is an optimism option?

The efficiency of a method/algorithm highly depends on the organization&amount of the data.



Ex2 How to implement a function PrintN?

Implement a function named PrintN, when input a positive integer N,
 print all the positive integer from 1 to N.

```
void PrintN ( int N )
{ int i;
    for ( i=1; i<=N; i++ ) {
        printf( "%d\n" , i);
    }
    return;
}
</pre>
void PrintN ( int N )
{ if (N);
    PrintN( N-1);
    printf( "%d\n" , N);
}
return;
}
```

Loop implementation

Recursive implementation

Let N = 100, 1000, 10000, 100000, ...

Ex2 How to implement a function PrintN?

Implement a function named PrintN, when input a positive integer N,
 print all the positive integer from 1 to N.

```
99977
# include <stdio.h>
                                     99978
                                     99979
void PrintN ( int N );
                                      79980
                                     99981
int main ()
                                     99982
                                     99983
{ int N;
                                     99984
 scanf ("%d", &N);
                                     99985
                                     99986
 PrintN(N);
                                     99987
                                      9988
 return 0;
                                     99989
                                     99990
                                     99993
                                     99996
                                      19998
  Press any key to continue_
                                     Press any key to continue_
```

Loop implementation

The efficiency of a method/algorithm depends on the occupation of RAM.



Ex3 compute the summation for a polynomial at a fixed value x.

```
f(x) = a_0 + a_1 x + a_2 x^2 + \dots + a_{n-1} x^{n-1} + a_n x^n
double fpoly1 (int n, double a[], double x)
{ int i;
    double p = a[0];
    for (i = 1; i <=n; i++)
        p += (a[i] * pow(x, i));
    return p;
}
```

```
f(x) = a_0 + x(a_1 + x(a_2 + \cdots x(a_{n-1} + x(a_n))\cdots))
double fpoly2 (int n, double a[], double x)
{ int i;
    double p = a[n];
    for (i = n; i > 0; i--)
        p = a[i-1] + x* p;
    return p;
}
```

- clock(): capture consumed time for running a function. The unit of the captured time is *clock tick*, which depends on the CPU.
- CLOCKS_PER_SEC is a constant that presents the number of clock ticks per second.

```
#include <stdio.h>
#include <time.h>
clock_t start, stop;
/* Clock_t is the variable returned by function clock(). */
double duration;
/* Record the running time for a function. Time unit is second. */
int main ()
 start = clock (); Start timing. */
 Myfunction();
 stop = clock (); Stop timing. */
 duration = ((double) (stop - start))/CLOCKS_PER_SEC;
 return 0;
```

Ex3 compute the summation for a polynomial $f(x) = \sum_{i=0}^{9} i \cdot x^i$ at a fixed value x = 1.1, f(1.1).

```
double fpoly1 ( int n, double a[ ], double x )
{ int i;
   double p = a[0];
   for (i = 1; i <=0; i++)
        p += (a[i] * pow( x, i) );
   return p;
}</pre>
```

```
double fpoly2 ( int n, double a[ ], double x )
{ int i;
   double p = a[n];
   for (i = n; i > 0; i-- )
        p = a[i-1] + x* p;
   return p;
}
```

```
#include <stdio.h> #include <time.h> #include
                                                            f(x) = \sum_{i=0}^{9} i \cdot x^{i}
<math.h>
clock t start, stop;
double duration:
#define MAXN 10 /*maximum order of the
polynomial */
                                               ticks1 = 0.000000
double fpoly1 (int n, double a[], double x)
                                               duration1 = 0.00e+000
double fpoly2 (int n, double a[], double x)
                                               ticks2 = 0.000000
int main ()
                                               duration2 = 0.00e+000
{ int i;
 double a[MAXN]; /*save the coefficient of the Press any key to continue
polynomial*/
 Star(ti≡0; PANAXN; i++) a[i] = (double) i; fpoly1(MAXN-1, a, 1.1);
 stop = clock ();
 duration = ((double) (stop -
start))/CLOCKS PER SEC;
 prinft ("ticks1 = %f\n",(double) (stop - start));
 prinft ("duration1 = \%6.2e\n", duration));
 start = clock ();
 fpoly2(MAXN-1, a, 1.1);
 stop = clock ();
 duration = ((double) (stop - start))/CLOCKS PER SEC;
 prinft ("ticks1 = %f",(double) (stop - start));
 prinft ("duration1 = \%6.2e\n", duration));
return 0:
```

```
#include <stdio.h>
#include <time.h>
#include <math.h>
#define MAXK 1e7
/*maximum repeat time of the test function */
int main ()
{ .....
 start = clock ();
 for ( i=0; i<MAXK; i++)
      fpoly1(MAXN-1, a, 1.1); /* repeat the test function to get enough clock tidks*/
 stop = clock ();
 duration = ((double) (stop - start))/CLOCKS_PER_SEC/MAXK;
  /* compute running time for single function duration */
 prinft ("ticks1 = \%f\n",(double) (stop - start));
 prinft ("duration1 = \%6.2e\n", duration));
                                         ticks1 = 10093.000000
                                         duration1 = 1.01e-006
                                         ticks2 = 1375.000000
                                         duration2 = 1.38e-007
 return 0;
                                         Press any key to continue
```

The efficiency of a method/algorithm depends on the design of the algorithm.



Definition of Data Structure

- **Data structure**, way in which data are stored for efficient search and retrieval.
- Different data structures are suited for different operations.
- Algorithm is a procedure for solving a mathematical problem in a finite number of steps that frequently involves repetition of an operation.

Abstract Data Type (ADT 抽象数据类型)

- Abstract: The method that we describe the data type, does not depend on the implementations.
 - Not related to the computer that stores the data.
 - Not related to the physical structure that stores the data.
 - Not related to the algorithm and language that implements the operation.
- We only care about "how to design" the objective data sets and related operations, not how to "implement" a data structure.

EX4 Abstract data type of a *matrix*

Array? Structural array? Orthogonal list?

- Data type: Matrix
- Objects: a $M \times N$ matrix $A_{M \times N} = (a_{ij})$ $(i = 1, \dots, M; j = 1, \dots, N)$ is composed by a number of $M \times N$ array of < a, i, j >, where a present the value of the matrix element, i present the no. of row, and j present the no. of column.
- Operations: for an arbitrary matrix A, B, C ∈ Matrix, and integers i, j, M, N
- Matrix create (int M, int N): return an empty matrix of $M \times N$;
- int GetMaxRow (Matrix A): return the number of rows;
- int GetMaxCol(Matrix A): return the number of columns;
- ElementType GetEntry (Matrix A, int i, int j): return the element of matrix A in row i, column j;
- Matrix Add (Matrix A, Matrix B): if the dimension of matrix A and B are the same, return matrix C = A + B, otherwise error;
- Matrix multiply (Matrix A, Matrix B): if the number of columns of matrix A is equals to the number of properties are rectain matrix of matrix AB, otherwise return error; or columns? C,C++,Python,...?

•

Outline

What will we learn from this course?

How we manage this course?

Instructors

- ☐ Yuyao Zhang zhangyy8@shanghaitech.edu.cn SIST 3-420
- □ Dengji Zhao <u>zhaodj@shanghaitech.edu.cn</u> SIST 1A-304E
- ☐ Xin Liu <u>liuxin7@shanghaitech.edu.cn</u> SIST 2-302H
- ☐ Hao Geng genghao@shanghaitech.edu.cn SIST 3-332

- **TAs (**13 TAs)
 - ☐ Piazza organization group: Yucen Peng, Zhongxiao Cong
 - ☐ Quiz and homework group: Yihang Lian, Huizhe Su, Ke Gong
 - □ Program assignment group: Cheng Peng
 - ☐ Video group: Miao Li, Haoxin Liu, Yuhan Cao
 - □Blog group: Jintian Hu, Wenchao Li, Kai He, Ye Tian

Classes

☐ Mon 8:15-9:55; Wed 8:15-9:55

Review/Quizzes/Discussions

☐ Format: 5 groups, about 45 students each (Week 3-16 Weekly)

☐ Length: 60mins each time

□ Location: TBA

☐ Time: TBA

☐ Instructors: all TAs

☐ Contents: quizzes, and homework solutions


- Piazza Course Forum
 - □ piazza.com/shanghaitech.edu.cn/fall2022/cs101


You are encouraged to ask questions and participate in discussions

- ☐ Course schedule, slides, office hour etc. are published on the forum
- ☐ Invitation has been sent to your ShanghaiTech email (haven't received it?)
- Office Hours
 - Location and Time: see course forum
- Homework
 - ☐ Submit to gradescope : see course forum

- Reference Book
 - □ Introduction to Algorithms (3rd ed.). Cormen, Thomas H., Leiserson, Charles E., Rivest, Ronald L., Stein, Clifford. MIT Press. ISBN, 9780262033848.
 - □ Algorithm design. Jon Kleinberg, Éva Tardos. Pearson. ISBN,

978-0321295354.





Course Schedule

Week	Date	Content
1	9/05 Mon	Introduction
	9/07 Wed	Elementary Data Structures: Array and Lists
2	9/12 Mon	Mid-Autumn Festival
	9/14 Wed	Stack and Queue
3	9/19 Mon	Big O/Theta/Omega
	9/21 Wed	Hash Table
4	9/26 Mon	Sorting: Insertion, Bubble
	9/28 Wed	Sorting: Merge
5	10/03 10/05 Mon Wed	National Day
	10/08 Sat	Sorting: Quick
6	10/10 Mon	Divide and Conquer
	10/12 Wed	Trees: Introduction, DFS, BFS
7	10/17 Mon	Binary Trees
	10/19 Wed	Heap and Heap Sort
8	10/24 Mon	Binary Search Trees + Huffman Coding
	10/26 Wed	Balanced Binary Search Trees: AVL

Course Schedule

Week	Date	Content
9	10/31 Mon	Red-Black Tree + Disjoint sets 1
	11/02 Wed	Middle Term Exam
10	11/07 Mon	Disjoint sets 2+ Graphs: Introduction, Traversal
	11/09 Wed	Graphs: Traversal
11	11/14 Mon	Minimum Spanning Trees
	11/16 Wed	Greedy
12	11/21 Mon	Topological Sorts
	11/23 Wed	Shortest Path Algorithm: Dijkstra
13	11/28 Mon	A*
	11/30 Wed	Floyd-Warshall Algorithm
14	12/05 Mon	Dynamic Programming
	12/07 Wed	Knapsack Problem
15	12/12 Mon	Reductions
	12/14 Wed	P+NP
16	12/19 Mon	NPC
	12/21 Wed	Review

Course Policy

- Plagiarism
 - ☐ All assignments must be done individually
 - You cannot copy directly from any other source
 - You cannot share solutions with any other students
 - Plagiarism detection software will be used on all the assignments
 - Ways of collaboration
 - You may discuss together or help another student such as debuging his or her code; however, you cannot dictate or give the exact solutions.

Course Policy

Plagiarism

□ Punishment

- When one student copied from another student, both students are responsible.
- Zero point on the assignment or exam in question.
- Disqualified from receiving any awards recommended by the school and from any competitive studying opportunities (e.g., international exchange).
- Repeated violation will result in a F grade for this course as well as further punishment at the school/university level.

- Alex and Bob were roommates.
- Bob let Alex use his laptop to complete an assignment.
- Alex copied Bob's solution for the assignment.

- Leslie asked if Morgan could send her his code so that she could look at it (promising, of course, not to copy it).
- Morgan sent the code.
- Leslie copied it and handed it in.

- Garry and Harry worked together on a single source file initially and then worked separately to finish off the details.
- The result was still noticeably similar with finger-print-like characteristics which left no doubt that some of the code had a common source.

- Jordan uploaded the projects to GITHUB.com without setting appropriate permissions. Kasey found this site, downloaded the projects and submitted them. Both are guilty.
 - ☐ This applies to any public forum, news group, etc., not just gitub.com...

Real Plagiarism Examples

- Copied a piece of the codes from others or online repositories.
- Copied someone's solution from his/her USB drive.
- Copied a piece of others' codes and change all the variable/function names.
- Unusual solutions appeared in different submissions.

Course Policy

Grading

- ☐ Exams (45%): middle term: 20%; final: 25%
- ☐ Weekly Homework (20%): non-programming questions
- □ Programming Tasks (20%): 4 programming tasks (each lasts 3 weeks)
- ☐ In-Class Quizzes (15%): in lectures and discussions

Take Home Message

 Algorithms and Data Structure is one of the most important course during your undergraduate.

 You will sometimes feel it very tough, but please always keep on going, we are here to help.