




上海科技大学
ShanghaiTech University

CS271 Computer Graphics II

Lecture 6

Mesh Simplification





立志成才 报¹国裕民

Definition

Simplification, aka decimation, approximation, downsampling

- Transform a given polygonal mesh into another mesh with fewer faces, edges, and vertices
- The simplification or approximation procedure is usually controlled by user-defined quality criteria







Curvature-preserved vs. Curvature-removed Criteria



上海科技大学
ShanghaiTech University



立志成才 报效国家




Mesh Simplification Applications




上海科技大学
ShanghaiTech University


- Oversampled 3D scan data



~150k triangles



~80k triangles



立志成才 报效国民





Mesh Simplification Applications



上海科技大学
ShanghaiTech University

- Over-tessellation: e.g., iso-surface extraction



立志成才 报國裕民





Mesh Simplification Applications



上海科技大学
ShanghaiTech University

Multi-resolution hierarchies for

- Efficient geometry processing
- Level-of-detail (LOD) rendering



立志成才 报國裕民




Mesh Simplification Applications



上海科技大学
ShanghaiTech University

- Adaption to hardware capabilities



立志成才 报效国民



Mesh Simplification



上海科技大学
ShanghaiTech University

Adjust the complexity of a geometry data set


- Since many decimation schemes work iteratively, i.e., they decimate a mesh by removing one vertex at a time, they usually can be inverted
- Hierarchical method

Problem Statement

- Given: $M = (V, F)$
- Find: $M' = (V', F')$ such that
- $|V'| = n < |V|$ and $\|M - M'\|$ is minimal, or
- $\|M - M'\| < \varepsilon$ and $|V'|$ is minimal

Respect additional fairness criteria

- Normal deviation, triangle shape, scalar attributes, etc.



立志成才 报國裕民





Mesh Simplification



上海科技大学
ShanghaiTech University

Start with the original fine mesh

- **Simply progressively**
E.g., collapse edges, vertex clustering
- **Aim to keep original appearance**
Normal deviation, triangle shape, scalar attributes
Error control




立志成才 报國裕民



上海科技大学
ShanghaiTech University

Local Operations





立志 成才 报国 裕民



Local Simplification Operator


- Vertex Removal






Local Simplification Operator

- Edge Collapse




- Merge two adjacent vertices
- Simple to implement
- Well-suited for implementing geomorphing



Local Simplification Operator

- Half-edge Collapse



- Collapse edge into one end point

- Special case of vertex removal

- Special case of edge collapse



- After collapse: $n(E) - 3$, $n(V) - 1$, $n(F) - 2$
- According to Euler Formula: unchanged
- Half-edge collapsing would not change the genus of a mesh
- Should determine whether collapse is ok (may introduce non-manifold structure)



Topologically Illegal (half-)edge Collapses



上海科技大学
ShanghaiTech University






Simplification via Edge Collapse

One popular scheme: iteratively collapse edges


Greedy algorithm from a general overview:

- Assign each edge a cost
- Collapse edge with least cost
- Repeat until target number of elements is reached
- Particularly effective cost function: **Quadric Error Metric**







Quadric Error Metric



Quadric Error Metric (QEM)


Approximate distance to a collection of triangles

- Q: Distance to plane w/ normal n passing through point p ?
- A: $\text{dist}(x) = \langle n, x \rangle - \langle n, p \rangle = \langle n, x - p \rangle$
- Quadric error is then sum of squared point-to-plane distances



$$Q(x) := \sum_{i=1}^k \langle n_i, x - p \rangle^2$$

$$Q^e = Q_1^v + Q_2^v$$





Quadric Error – Homogeneous Coordinates

Suppose in coordinates we have


- A query point $\mathbf{x} = (x, y, z)$
- A normal $\mathbf{n} = (a, b, c)$
- An offset $\mathbf{d} := \langle \mathbf{n}, \mathbf{p} \rangle$

In **homogeneous coordinates**, let

- $\mathbf{u} := (x, y, z, 1)$
- $\mathbf{v} := (a, b, c, d)$
- Signed distance to plane is then just $\langle \mathbf{u}, \mathbf{v} \rangle = ax + by + cz + d$
- Squared distance is $\langle \mathbf{u}, \mathbf{v} \rangle^2 = \mathbf{u}^T (\mathbf{v} \mathbf{v}^T) \mathbf{u} =: \mathbf{u}^T \mathbf{K} \mathbf{u}$
- Matrix $\mathbf{K} = \mathbf{v} \mathbf{v}^T$ encodes squared distance to plane

Key idea: sum of matrices \mathbf{K} distance to union of planes

$$\mathbf{u}^T \mathbf{K}_1 \mathbf{u} + \mathbf{u}^T \mathbf{K}_2 \mathbf{u} = \mathbf{u}^T (\mathbf{K}_1 + \mathbf{K}_2) \mathbf{u}$$




$$\mathbf{K} = \begin{bmatrix} a^2 & ab & ac & ad \\ ab & b^2 & bc & bd \\ ac & bc & c^2 & cd \\ ad & bd & cd & d^2 \end{bmatrix}$$



Quadric Error of Edge Collapse

- How much does it cost to collapse an edge e_{12} ?
Idea: compute midpoint m , measure error $Q(m) = m^T(K_1 + K_2)m$
- Error becomes “score” for e_{12} , determining priority



- Better idea: find point x that minimize error!
- But how to minimize quadric error?



Revisit: Minimizing a Quadratic Function






上海科技大学
ShanghaiTech University

Suppose you have a function $f(x) = ax^2 + bx + c$

- Q: What does the graph of this function look like?
- Q: How do we find the minimum?
- A: Find where the function looks “flat” if we zoom in really close
- i.e., find point x where 1st derivative vanishes:

$$\begin{aligned}f'(x) &= 0 \\2ax + b &= 0 \\x &= -b/2a\end{aligned}$$





Minimizing Quadratic Polynomial

Not much harder to minimize a quadratic polynomial in n variables

- Can always write in terms of a symmetric matrix A
- E.g., in 2D: $f(\mathbf{x}, \mathbf{y}) = \mathbf{a}\mathbf{x}^2 + \mathbf{b}\mathbf{x}\mathbf{y} + \mathbf{c}\mathbf{y}^2 + \mathbf{d}\mathbf{x} + \mathbf{e}\mathbf{y} + \mathbf{g}$


$$\mathbf{x} = \begin{bmatrix} x \\ y \end{bmatrix} \quad A = \begin{bmatrix} a & b/2 \\ b/2 & c \end{bmatrix} \quad \mathbf{u} = \begin{bmatrix} d \\ e \end{bmatrix}$$

$$f(\mathbf{x}, \mathbf{y}) = \mathbf{x}^T A \mathbf{x} + \mathbf{u}^T \mathbf{x} + \mathbf{g}$$

(will have the same form for any n)

- Q: How do we find a critical point (min/max/saddle)?
- A: Set derivative to zero!

$$2A\mathbf{x} + \mathbf{u} = 0$$
$$\mathbf{x} = -1/2 A^{-1}\mathbf{u}$$






Positive Definite Quadratic Form

Just like our 1D parabola, critical point is not always a min!


- Q: In 2D, 3D, nD, when do we get a minimum?
- A: When matrix A is positive-definite:

$$\mathbf{X}^T \mathbf{A} \mathbf{X} > 0 \quad \forall \mathbf{X}$$


- **1D:** Must have $xax = ax^2 > 0$, i.e., a is positive!
- **2D:** Graph of function looks like a “bowl”:




positive definite



positive semidefinite



indefinite





Minimizing Quadric Error



Find “best” point for edge collapse by minimizing quadratic form

$$\min_{\mathbf{u} \in \mathbb{R}^4} \mathbf{u}^T \mathbf{K} \mathbf{u}$$

- Already know 4th (homogeneous) coordinate for a point is 1
- So, break up our quadratic function into two pieces:

$$\begin{bmatrix} \mathbf{x}^T & 1 \end{bmatrix} \begin{bmatrix} B & \mathbf{w} \\ \mathbf{w}^T & d^2 \end{bmatrix} \begin{bmatrix} \mathbf{x} \\ 1 \end{bmatrix} \\ = \mathbf{x}^T B \mathbf{x} + 2\mathbf{w}^T \mathbf{x} + d^2$$

- Now we have a quadratic polynomial in the unknown position $\mathbf{x} \in \mathbb{R}^3$
- Can minimize as before:


$$2B\mathbf{x} + 2\mathbf{w} = 0 \quad \Longleftrightarrow \quad \mathbf{x} = -B^{-1}\mathbf{w}$$





QEM Simplification: Final Algorithm


- Input: a mesh
- Output: a simplified mesh
- Initialization:
 - Compute \mathbf{K} for each triangle (squared distance to plane)
 - Set \mathbf{K}_i at each vertex to sum of \mathbf{K} s from incident triangles
 - For each edge \mathbf{e}_{ij} :
 - Set $\mathbf{K}_{ij} = \mathbf{K}_i + \mathbf{K}_j$
 - Find point x minimizing error, set cost to $\mathbf{K}_{ij}(x)$
- Until we reach target number of triangles:
 - Collapse edge \mathbf{e}_{ij} with smallest cost to optimal point x
 - Set quadric at new vertex to \mathbf{K}_{ij}
 - Update cost of edges touching new vertex



Full
Resolution

60,000
triangles


1000
triangles





上海科技大学
ShanghaiTech University

Variational Shape Approximation



立志 成才 报国 裕民




Variational Shape Approximation (VSA)



上海科技大学
ShanghaiTech University

VSA is highly sensitive to features and symmetries and produces anisotropic meshes of high approximation quality





立志成才 报²⁶国裕民



Variational Shape Approximation (VSA)

- The input shape is approximated by a set of proxies
- A plane in space through the point x_i with normal direction n_i





Region Representation

- \mathbf{M} : a triangle mesh
- $\mathbf{R} = \{\mathbf{R}_1, \dots, \mathbf{R}_k\}$: a partition of \mathbf{M} into k regions $R_1 \cup \dots \cup R_k = M$
- Proxies: $\mathbf{P} = \{\mathbf{P}_1, \dots, \mathbf{P}_k\}$, $\mathbf{P}_i = (\mathbf{x}_i, \mathbf{n}_i)$


Distance metrics between \mathbf{R}_i and \mathbf{P}_i

- The squared orthogonal distance of x from the plane \mathbf{P}_i

$$L^2(R_i, P_i) = \int_{x \in R_i} (n_i^T x - n_i x_i)^2 dA$$

- A measure of the normal field:

$$L^{2,1}(R_i, P_i) = \int_{x \in R_i} \|n(x) - n_i\|^2 dA$$





Goal of VSA




上海科技大学
ShanghaiTech University

Given a number k and an error metric $E(L_2 \text{ or } L_{2,1})$, find a set $\mathbf{R} = \{\mathbf{R}_1, \dots, \mathbf{R}_k\}$ of regions and a set $\mathbf{P} = \{\mathbf{P}_1, \dots, \mathbf{P}_k\}$ of proxies such that the global distortion

$$E(R, P) = \sum_{i=1}^k E(R_i, P_i)$$

is minimized




立志成才 报²⁰国裕民



Lloyd's Clustering Algorithm



- The algorithm iteratively alternates between a **geometry partitioning** phase and a **proxy fitting** phase
- **Geometry partitioning phase**
 - A set of regions that best fit a **given** set of proxies
 - Modifies the set R of regions to achieve a lower approximation error while keeping the proxies P fixed
- **Proxy fitting phase**
 - The partitioning is kept **fixed**, and the proxies are adjusted to minimize approximation error
 - L^2 metric: the best proxy is the least-squares fitting plane
 - $L^{2,1}$ metric: the proxy normal n_i is just the area-weighted average of the triangle normals
- **Initialization**
 - Randomly picking k triangles as R
 - The planes of k triangles are used to initialize P





More Paper

- Liu Y J, Xu C X, Fan D, et al. **Efficient construction and simplification of Delaunay meshes**[J]. ACM Transactions on Graphics (TOG), 2015, 34(6): 1-13.
- Yi R, Liu Y J, He Y. **Delaunay mesh simplification with differential evolution**[J]. ACM Transactions on Graphics (TOG), 2018, 37(6): 1-12.
- Liang Y, He F, Zeng X. **3D mesh simplification with feature preservation based on whale optimization algorithm and differential evolution**[J]. Integrated Computer-Aided Engineering, 2020, 27(4): 417-435.

