

Protection design space at 32x oversubscription (16 tenants, pool=512, budget=32, 10 seeds, bound=capacity)
protection timing (rows) x transfer-set selection authority (cols); throughput normalized to PROSE

pre-enqueue protection / host selects

```
REFCNT
(all candidates pinned)
valid thr 0.50x   stale-admit 0.0%
RPE payload 0.0% reclaimable 0.0%

REFCNT_S
(budget subset pinned, no gen check)
valid thr 0.82x   stale-admit 17.5%
RPE payload 17.5% reclaimable 93.8%
retries/desc 0.17

CLIFF and/or STALE
```

pre-enqueue protection / endpoint selects

```
RECLAIM_DEFER
(reclaim-side deferral)
valid thr 0.41x   stale-admit 0.0%
RPE payload 17.5% reclaimable 0.0%

CLIFF and/or STALE
```

commit-time protection / host selects

```
PROSE_HOSTSEL
(host-selected subset, gen checked)
valid thr 1.00x   stale-admit 0.0%
RPE payload 0.0% reclaimable 93.8%

SAFE + NO CLIFF
```

commit-time protection / endpoint selects

```
PROSE
(endpoint-selected, gen checked)
valid thr 1.00x   stale-admit 0.0%
RPE payload 0.0% reclaimable 93.8%

SAFE + NO CLIFF
```