

CPS 188

Computer Programming Fundamentals

Prof. Alex Ufkes

Topic 6: Pointers

Notice!

Obligatory copyright notice in the age of digital delivery and online classrooms:

The copyright to this original work is held by Alex Ufkes. Students registered in course CPS 188 can use this material for the purposes of this course but no other use is permitted, and there can be no sale or transfer or use of the work for any other purpose without explicit permission of Alex Ufkes.

Previously:

Useful Functions

- Function to compute hypotenuse?
- Function to find area of a circle?
- Function to find roots of a quadratic?

hypotenuse()

```
#include <stdio.h>
#include <math.h>

double hypotenuse (double a, double b)
{
    return sqrt(a*a + b*b);
}

int main (void)
{
    double s1=3, s2=4;
    printf("hyp=%.21f", hypotenuse(s1, s2));
    return 0;
}
```

helloworld.c - C:\Users\aufke\Google Drive\Teaching\CPS 188\Code Samples - Geany

File Edit Search View Document Project Build Tools Help

Symbols helloworld.c

Functions
hypotenuse [4]
main [9]

```
1 #include <stdio.h>
2 #include <math.h>
3
4 double hypotenuse (double a, double b)
5 {
6     return sqrt(a*a + b*b);
7 }
8
9 int main (void)
10 {
11     double s1=3, s2=4;
12     printf("hyp=%.2lf", hypotenuse(s1, s2));
13     return 0;
14 }
15
```

gcc -Wall -o "helloworld" "helloworld.c" (in directory: C:\Users\aufke\Google Drive\Teaching\CPS 188\Code Samples - Geany)
Compilation finished successfully.

Status
Compiler

line: 12 / 15 col: 23 sel: 0 INS TAB mode: CRLF encoding: UTF-8 filetype: C scope: main

C:\WINDOWS\SYSTEM32\cmd.exe



```
hyp=5.00
-----
(program exited with code: 0)
Press any key to continue . . .
```

circ_area()

```
#include <stdio.h>
#define PI 3.141592

double circ_area (double r)
{
    return PI*r*r;
}

int main (void)
{
    double r=5.0;
    printf("area=%.2lf", circ_area(r));
    return 0;
}
```




quad()

```
#include <stdio.h>
#include <math.h>

double quad (double a, double b, double c)
{
    double disc = sqrt(b*b - 4*a*c);
    double root1 = (-b + disc)/(2*a);
    double root2 = (-b - disc)/(2*a);
    return root1; // What about root2?
}

int main (void)
{
    double c1=1, c2=2, c3=3;
    double r1 = quad(c1, c2, c3);
    printf("root1 = %.2lf", r1);
    return 0;
}
```


$$x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

“Can we have multiple results?”

NO.

We’re stuck!

- One option? Two separate functions, one for each root.
- Another option? Pointers, which we haven’t learned yet.


Moving On...



POINTERS

Recall: Variables in Memory

<code>char c;</code>	<code>/* 1 byte allocated */</code>
<code>int wholeNum1;</code>	<code>/* 4 bytes allocated */</code>
<code>double realNum2;</code>	<code>/* 8 bytes allocated */</code>



Recall: Use & to get address

The & operator returns the address of a variable

```
int number  
scanf("%d", &number);
```



Pointer Data Types

A **pointer** is a variable that stores the **address** of another variable:

```
char *cptr;    /* stores the address of a char */
int *iptr;     /* stores the address of an int  */
float *fptr;   /* stores the address of a float */
double *dptr  /* stores the address of a double */
```

The ***** is used in the variable declaration to specify a pointer.

```
char *cptr;    /* stores the address of a char */
int *iptr;     /* stores the address of an int  */
float *fptr;   /* stores the address of a float */
double *dptr  /* stores the address of a double */
```

In a 32-bit application, pointers are also 32 bits (4 bytes), regardless of the data type they are pointing to.

char* is 4 bytes, even though it points to a **char**, which is 1 byte.

The value of a pointer is simply a memory location (address)

Declaration Syntax

x is a pointer, **y** and **z** are integers

```
int* x, y, z;
```

Each variable needs a ***** if it's a pointer

```
int* x, * y, * z;
```


```
/* Easiest, most clear */
```

```
int *x, *y, *z;
```



```
char abc = 'A';  
char *xyz = &abc;  
  
printf("Value of abc:   %c\n", abc);  
printf("Address of abc: %d\n", &abc);  
printf("Value of xyz:   %d\n", xyz);  
printf("Address of xyz: %d\n", &xyz);
```

```
D:\Programs\quincy\bin\quincy.exe  
Value of abc:   A  
Address of abc: 6356771  
Value of xyz:   6356771  
Address of xyz: 6356764  
  
Press Enter to return to Quincy...
```



Dereferencing



* Operator

NOT multiplication! - Different in the context of pointers.

Use * to *dereference* a pointer.

Dereferencing is used to access the memory location being “pointed” to.

Primitive data types (int, char, float, double) **CANNOT** be dereferenced

only pointers can be dereferenced

```
char c1 = 'A', c2;
```

```
char *ptr = &c1;
```

```
c2 = *ptr;
```

```
*ptr = 'C';
```

```
// ptr stores the address of c1
```

```
// dereference ptr, store in c2
```

```
// store 'C' at location being
```

```
// pointed to by ptr
```

```
printf("c1 is:  %c\n", c1);
```


```
/* c1 is:  C */
```

```
printf("*ptr is: %c\n", *xyz);
```

```
/* *ptr is: C */
```

```
printf("c2 is:  %c\n", c2);
```

```
/* c2 is:  A */
```



Dereferencing Confusion

```
char abc = 'A';
```

```
char *xyz = &abc;    /* NOT dereferencing! */
```

```
*xyz = '$';          /* THIS is dereferencing! */
```

Context matters!

- 1) In the context of declaration, the ***** indicates we are declaring a pointer.
- 2) Outside of declarations, the ***** indicates we are dereferencing a pointer.
- 3) In the context of a binary operation (two operands), the ***** indicates multiplication.

It Gets Complicated...


```
int i, j, *p, *q;    // pointers and ints together
p = &i;              // value of p is the address of i
q = &j;              // value of q is the address of j
*p = 5;              // store 5 at the address stored in p
*q = *p + i;         // dereference p, add i, store at
                     // address stored in q

printf("i = %d, j = %d\n", i, j);
printf("i = %d, j = %d\n", *p, *q);
```

Output?

i = 5, j = 10

```
int i, j, *p, *q;           // pointers and ints together
p = &i;                     // value of p is the address of i
q = &j;                     // value of q is the address of j
*p = 5;                     // store 5 at the address in p
*q = *p + i;                // dereference p, add i, store at
                             // address in q
printf("i = %d, j = %d\n", i, j);
```



You Need Help!



**More
Pointer
Examples**


```
int x = 57, y = 0;  
int *a = &y, *b = &x;
```

```
*a = 12;           // y = 12  
b = a;             // b and a both point to y  
*b = 15;           // y = 15
```

```
printf("x = %d, y = %d\n", x, y);
```

x = 57, y = 15

```
int x = 57, y = 0;  
int *a, *b = &y;
```

```
*b = 7;           // y = 7  
a = &x;           // a points to x  
x = *a - *b;      // x = x - y
```

```
printf("x = %d, y = %d\n", x, y);
```

x = 50, y = 7

```
int x, y, z, *p1, *p2, *p3, *p4;
```

```
p1 = &x;      // p1 points to x
```

```
p4 = p1;      // p4 points to x
```

```
p2 = p4;      // p2 points to x
```

```
*p4 = 5;      // x = 5
```

```
y = x;        // y = 5
```

```
printf("x = %d, y = %d\n", x, y);
```

x = 5, y = 5

```
char c1, c2, c3, *ptr;
```

```
ptr = &c1;           // value of ptr is the address of c1  
*ptr = 'A';         // dereference ptr, store 'A'
```

```
ptr = &c2;           // value of ptr is the address of c2  
*ptr = 'B';         // dereference ptr, store 'B'
```

```
ptr = &c3;           // value of ptr is the address of c3  
*ptr = 'C';         // dereference ptr, store 'C'
```



Is This OK?


```
int x, *p1;  
p1 = &x;
```

```
printf("Please enter an integer: ");  
scanf("%d", p1); /* Missing & */  
printf("x = %d\n", x);
```

Yes! scanf needs an address, p1 is an address

Multiple results?


(WITHOUT using global variables!)





POINTERS
to the rescue!

Consider the following:



Problem:
can only return one thing!

Pointers as
parameters!

`char`
`*sign`


`double`
`num`

`double`
`*fraction`

`split`

`int`
`whole`

Single return value:
`return whole;`



```
int split (double num, char *sign, double *fraction)
```

```
{
```

Pointers

```
    int whole = abs((int)num);
```

```
    *fraction = fabs(num) - whole;
```

```
    if (num >= 0)
```

```
        *sign = '+';
```

```
    else
```

```
        *sign = '-';
```

```
    return (whole);
```

```
}
```

De-reference pointers
to assign values



```
int split (double num, char *sign, double *fraction)
{ /*split code*/
}

int main (void)
{
    double f, n = 3.1415;
    char s;
    int w = split(n, &s, &f);

    printf("Sign:      %c\n", s);
    printf("Whole:     %d\n", w);
    printf("Fraction: %lf\n", f);

    return (0);
}
```

The diagram illustrates the relationship between variables in the `split` and `main` functions. An orange arrow points from the `int` parameter in the `split` function signature to the `int w` variable in the `main` function. Three green arrows point from the `n`, `&s`, and `&f` arguments in the `split` function call to the `double num`, `char *sign`, and `double *fraction` parameters in the `split` function signature, respectively. The `n`, `&s`, and `&f` arguments are each enclosed in a green circle.

When we de-reference `sign` and `fraction` in `split`, we are accessing `s` and `f` in `main`!


```

int split (double num, double *fr, char *sign)
{
    → int whole = abs((int)num); /* 3 */
    → *fr = fabs(num) - whole; /* 0.14159 */
    {
        if (num >= 0) *sign = '+';
        else *sign = '-';
    }
    → return (whole);
}

int main (void)
{
    → double f; int w; char s;
    → w = split(3.14159, &f, &s);
    printf("%c %d %lf", s, w, f);
    return (0);
}


```

Memory

f	0.14159	800
w	3	808
s	'+'	812
num	3.14159	912
fr	800	920
sign	812	924
whole	3	928


Quadratic Formula

```
void quadForm (double a, double b, double c,  
               double *x1, double *x2)  
{  
    double tmp = sqrt(b*b - 4*a*c);  
  
    *x1 = (-b + tmp)/(2*a);  
    *x2 = (-b - tmp)/(2*a);  
}
```


$$x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

Quadratic Formula

```
void quadForm (double a, double b, double c,  
               double *x1, double *x2);  
  
int main (void)  
{  
    double a = 1.1, b = 7.8, c = 2.5;  
    double root1, root2;  
    quadForm(a, b, c, &root1, &root2);  
    printf("roots: %1f, %1f", root1, root2);  
    return 0;  
}
```



quad_form.c - C:\Users\aufke\Google Drive\Teaching\CPS 188\Code Samples - Geany

File Edit Search View Document Project Build Tools Help

Symbols quad_form.c

Functions
main [11]
quadForm [4]

```
1 #include <stdio.h>
2 #include <math.h>
3
4 void quadForm (double a, double b, double c, double *x1, double *x2)
5 {
6     double tmp = sqrt(b*b - 4*a*c);
7     *x1 = (-b + tmp)/(2*a);
8     *x2 = (-b - tmp)/(2*a);
9 }
10
11 int main (void)
12 {
13     double a = 1.1, b = 7.8, c = 2.0;
14     double root1, root2;
15
16     quadForm(a, b, c, &root1, &root2);
17     printf("roots: %lf, %lf", root1, root2);
18
19     return 0;
20 }
21
```

C:\WINDOWS\SYSTEM32\cmd.exe

```
roots: -0.336480, -6.754430
-----
(program exited with code: 0)
Press any key to continue . . .
```


Questions?

