## **CPS 188**

# Computer Programming Fundamentals Prof. Alex Ufkes



### Notice!


## Obligatory copyright notice in the age of digital delivery and online classrooms:

The copyright to this original work is held by Alex Ufkes. Students registered in course CPS 188 can use this material for the purposes of this course but no other use is permitted, and there can be no sale or transfer or use of the work for any other purpose without explicit permission of Alex Ufkes.


### **Today**

#### **Data Representation:**

- Binary: Bits and bytes
- Integers, two's complement
- Characters
- IEEE-754 Floating point



#### **Data Sources**





### **Data Sources**





#### **Data Sources**

- As far as the physical computer system is concerned, there is no such thing as imagery, audio, text, or even numbers.
- The CPU has no idea what a JPG or MP3 is.
- At the hardware level, we deal exclusively in binary (0, 1)
- Different data types are encoded in different ways.
- A Bitmap image is encoded (in binary) differently than a JPG image, and so on.

(Even 0 and 1 are abstractions over voltage levels – 0V/GND for 0, 1.7/3.3/5.0v for 1, depending on the circuit)

### **Computer Memory**

#### Volatile



A few general-purpose registers (8-16) + Cache (<100Mb)



Main memory (RAM): Rarely higher than 64GB. (1GB = 1 billion bytes)

#### Not volatile


#### **Secondary Storage**



Hard drives, SSDs, multiple Terabyte (1TB = 1 trillion bytes)


Wait... What's a byte?

### **Binary:** Bits & Bytes



Byte (group of 8 bits)

### **Binary:** Words



- A word is a group of bytes, length depends on architecture.
- In a 32-bit system, a word is 32 bits (4 bytes).
- Corresponds to the size of registers on the CPU.


### Addressing

Every byte has an address.

Bits are not addressed individually.

· ·	2052
	2053
	2054
Byte address	2055
	2056
	2057
	2058
	2059
-	

_	
	10100011
	00001000
	11001100
	10001100
	10001101
	11001101
	00101010
	10001100



### **Binary Representation**

- How to represent images or audio in binary are beyond the scope of this course.
- However, it's easy enough to represent numbers and characters.
- These are the two most important data types for this course.

#### Whole numbers (integers):

• 0, 1, 2, 3, -76, 896543233, and so on.

#### **Floating Point numbers:**

• 0.0, 3.141592, -7.6, 1.23e4, and so on.

#### **Characters?** Individual letters and symbols:


• 'A', 'x', 'Q', '4', '+', '=', ', etc.

### **Unsigned Integers**

- All data in memory is represented in binary.
- The simplest type of data to understand is the humble unsigned integer.
- Unsigned? Greater than or equal to zero.
- Understand them the same way we understand positive base-10 numbers.

### **Understanding Binary Integers**

**Decimal:** Base 10 number system we're all used to



$$2 \times 10^{0} = 2$$
 $3 \times 10^{1} = 30$ 

 $10^{5}$   $10^{4}$   $10^{3}$   $10^{2}$   $10^{1}$   $10^{0}$  5 5 1 9 3 2 1

$$2 \times 10^{0} = 2$$
 $3 \times 10^{1} = 30$ 
 $9 \times 10^{2} = 900$ 

$$2 \times 10^{0} = 2$$
 $3 \times 10^{1} = 30$ 
 $9 \times 10^{2} = 900$ 
 $1 \times 10^{3} = 1000$ 

```
2 \times 10^{0} = 2
3 \times 10^{1} = 30
9 \times 10^{2} = 900
1 \times 10^{3} = 1000
```

 $5 \times 10^4 =$ 

© Alex Ufkes, 2023

50000

 $10^{5}$   $10^{4}$   $10^{3}$   $10^{2}$   $10^{1}$   $10^{0}$ 5 5 1 9 3 2  $\frac{1}{10}$ 

2 x 
$$10^{0} =$$
 2  
3 x  $10^{1} =$  30  
9 x  $10^{2} =$  900  
1 x  $10^{3} =$  1000  
5 x  $10^{4} =$  50000  
5 x  $10^{5} =$  500000

© Alex Ufkes, 2023

21

22

$$2 \times 10^{0} = 2$$


$$3 \times 10^{1} = 30$$

$$9 \times 10^{2} = 900$$


$$1 \times 10^{3} = 1000$$

$$5 \times 10^{4} = 50000$$

$$5 \times 10^{5} = 500000$$



Binary-to-decimal



$$1 \times 2^{0} = 1$$
  
 $0 \times 2^{1} = 0$   
 $1 \times 2^{2} = 4$ 

1 
$$\times$$
 2<sup>0</sup> = 1  
0  $\times$  2<sup>1</sup> = 0  
1  $\times$  2<sup>2</sup> = 4  
0  $\times$  2<sup>3</sup> = 0

1 x 
$$2^{0} = 1$$
  
0 x  $2^{1} = 0$   
1 x  $2^{2} = 4$   
0 x  $2^{3} = 0$   
0 x  $2^{4} = 0$ 


1 
$$\times$$
 2<sup>0</sup> = 1  
0  $\times$  2<sup>1</sup> = 0  
1  $\times$  2<sup>2</sup> = 4  
0  $\times$  2<sup>3</sup> = 0  
0  $\times$  2<sup>4</sup> = 0  
1  $\times$  2<sup>5</sup> = 32



### Other Bases: Hexadecimal

#### In computing:

- Hexadecimal is very common (base-16), as is octal (base-8)
- Decimal goes from 0-9, Hexadecimal goes from 0 to F.



### **Hexadecimal <-> Binary**

- 1. Divide the binary number into sets of 4 bits
- 2. Convert each set of bits into a hex digit

 $10F9_{16}$  or 0x10F9


### Octal <-> Binary

- Base-8 (oct = 8, octagon), digits go from 0-7
- Conversion follows same procedure as Hex, with one difference:
- Divide binary number into groups of 3 bits instead of 4 bits.

### Binary: Negative Integers? Characters?

#### We've seen:

- Number systems (decimal, binary, hex, octal)
- unsigned integer (positive, whole numbers)




#### Next we will look at:

- Signed integer (whole number, can be positive or negative)
- Floating point (real numbers, positive or negative)
- Characters ('A', 'b', '=', '#', any single character)

### **Integers**

- In practice, integers are 8, 16, 32, or 64 bits.
- The most common in this course is 32-bit



In base 10, 578 is the same number as 000000578. Same applies in binary.

### **Signed Integers**

#### Two options:

- 1. Sign-and-Magnitude
- 2. Two's Complement

#### Sign and magnitude:

- Use the left-most bit as a sign bit
- 1 for negative, 0 for positive

Major Drawback? Two representations for zero:

+0 = 0000 0000

-0 = 1000 0000

# **Two's Complement**

- 1) Write the positive number in binary. If the number is positive, stop here.
- 2) If the number is negative, Invert the bits (1s becomes 0s, 0s become 1s)
- 3) Add 1 (add 1 to the **VALUE** of the number, do **NOT** append 1)

### Write -9 in two's complement format.

+9: 0 0 0 0 1 0 0 1

invert: 1 1 1 1 0 1 1 0

-9: 1 1 1 0 1 1 1

# Two's Complement

To convert a two's complement binary number back to decimal, simply perform the process again in the same order:

1111 0111

Negative!

0000 1000 Invert:

**Add 1:** 0000 0001


0000 1001

first bit is 1

At this point, convert to decimal using previously described method. But remember! The final number is negative because the first bit was 1.

**Example:** Convert -138 into binary


- Number is negative, so we need to perform two's comp operation.
- First though, we just convert 138 to binary.
- 1. Find the highest power of two less than or equal to 138
  - It's 128, or 2<sup>7</sup>. Thus, the bit in position 7 is 1



39


**Example:** Convert -138 into binary

- 1. Find the highest power of two less than or equal to 138
  - It's 128, or 2<sup>7</sup>. Thus, the bit in position 7 is 1
- 2. Subtract 128 from 138, 10 remains. Repeat 1.
  - Highest power of two less than or equal to 10 is 8, or 2<sup>3</sup>
  - The bit in position 3 is 1, positions >3 are zero.




**Example:** Convert -138 into binary

- 1. Find the highest power of two less than or equal to 138
  - It's 128, or 2<sup>7</sup>. Thus, the bit in position 7 is 1
- 2. Subtract highest power of 2 from remainder. Repeat 1.
  - Keep repeating until nothing remains.
- 3. Since the original number was negative, we apply 2s-comp



**Example:** Convert -138 into binary


3. Since the original number was negative, we apply 2s-comp



**Example:** Convert -138 into binary

$$-138_{10} = 1101110110_2$$


To extend this to 32 (or 64) bits, we add leading 1s



## Two's Complement: Another Way

Write -148<sub>10</sub> in two's comp format:

Write the positive number in binary using repeated division by 2:



$$9/2 = 4.5$$
 Rem

$$74/2 = 37$$

$$4/2 = 2$$


$$2/2 = 1$$

1 goes on the left

## Two's Complement: Another Way

Write  $-148_{10}$  in two's comp format:

Write the positive number in binary using repeated division by 2:




Invert, add 1:

1101101100


# Floating-Point (Real) Numbers

Real numbers are represented using a sign bit, a mantissa, and an exponent.



#### **IEEE-754**

Most widely used standard for floating point computation



### **Decimal to IEEE-754**

Learn by example: Convert  $-9_{10}$  to 32-bit floating point format.

1) Convert the <u>absolute</u> value of the number to binary

$$9_{10} = 1001.0_2$$
 (Note the added .0)

2) Append exponent indicator:

$$9 = 1001.0 \times 2^{0}$$

3) Normalize (increment exponent):

Mantissa

#### **Decimal to IEEE-754**

4) Add bias to exponent:

5) Convert exponent to binary:

$$130_{10} = 10000010_2$$

6) Set sign bit (negative), place mantissa and exponent:



### **Another Decimal to IEEE-754**


Convert 18.75<sub>10</sub> to 32-bit floating point format.

Notice the right side of the decimal! Recall:

2-4) Exponent: 
$$10010.11_2 \times 2^0 = 1.001011_2 \times 2^4$$
,  $4 + 127 = 131$ 

5) 
$$131_{10} = 1000 \ 0011_2$$


6) Place components



#### Yet Another Decimal to IEEE-754

Write 9.625<sub>10</sub> in 32-bit floating point format.

Step 1) Convert absolute value to binary (both sides of decimal!)



### Yet Another Decimal to IEEE-754

Write 9.625<sub>10</sub> in 32-bit floating point format.

Step 2) Append exponent indicator:

 $1001.101 \times 2^{0}$ 

Step 3) Normalize (increment exponent):

$$1001.101 \times 2^0 = 1.001101 \times 2^3$$

Step 4) Add bias to exponent:

$$3 + 127 = 130$$


#### Yet Another Decimal to IEEE-754

Write 9.625<sub>10</sub> in 32-bit floating point format.

Step 5) Convert exponent to binary:

$$130_{10} = 1000\ 0010_2$$

Step 6) Set sign bit, place mantissa and exponent:



### Convert Back? IEEE-754 to Decimal

#### 0 10000010 0011010000000000000000

#### **Reverse everything:**

Convert exponent to decimal, subtract bias

Add leading 1 to mantissa

Apply exponent.

Convert both sides back to decimal

$$1000\ 0010_2 = 130_{10}$$

$$130 - 127 = 3$$

$$(1.001101 \times 2^3)$$

$$(1001.101 \times 2^{0})$$

$$1001_2 = 9_{10}$$
  
 $0.101_2 = 0.625_{10}$ 

#### Characters

### Expressed using the ASCII table

American Standard Code for Information Interchange

## **ASCII Table**

NUL	SOH	STX	ETX	EOT	ENQ	ACK	BEL	BS	TAB	LF	VT	FF	CR	SO	SI
^@	^A	^B	^C	^D	^E	^F	^G	^H	^I	^j	^K	^L	^M	^N	^o
0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
DLE ^P	DC1 ^Q	DC2 ^R	DC3 ^5	DC4 ^T	NAK ^U	SYN ^V	ETB ^W	CAN ^X	EM ^Y	SUB ^Z	ESC ^[	FS ^\	GS ^]	RS ^^	US ^?
16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
	!	П	#	\$	%	&	ı	(	)	*	+	,	-		/
32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47
0	1	2	3	4	5	6	7	8	9	:	;	<	=	>	?
48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63
@	A	В	С	D	E	F	G	Н	I	J	K	L	M	N	О
64	65	66	67	68	69	70	71	72	73	74	75	76	77	78	79
P	Q	R	S	T	U	V	W	X	Y	Z	[	\	]	^	_
80	81	82	83	84	85	86	87	88	89	90	91	92	93	94	95
`	a	b	с	d	e	f	g	h	i	j	k	1	m	n	О
96	97	98	99	100	101	102	103	104	105	106	107	108	109	110	111
р	q	r	s	t	u	v	W	x	y	z	{		}	~	DEL
112	113	114	115	116	117	118	119	120	121	122	123	124	125	126	127

#### Characters are 1 byte (8 bits) each

**Notice:** The character '1' does not have the ASCII value of 1. Rather, its value is 49. The difference between the integer 1 and the character '1' is **VERY** important!

	NUL ^@	SOH ^A	STX ^B	ETX ^C	EOT ^D	ENQ ^E	ACK ^F	E
Ш	0	1	2	3	4	5	6	
l	DLE ^P	DC1 ^Q	DC2 ^R	DC3 ^5	DC4 ^T	NAK ^U	SYN ^V	E
Ш	16	17	18	19	20	21	22	
		!	П	#	\$	%	&	
Ш	32	33	34	35	36	37	38	
H	U	1	2	3	4	5	6	
	48	49	50	51	52	53	54	١.
	@	Α	В	С	D	E	F	
Ш	64	65	66	67	68	69	70	
N	Р	Q	R	S	T	U	V	1
Ш	80	81	82	83	84	85	86	
	,	a	b	с	d	e	f	
Ш	96	97	98	99	100	101	102	1
	р	q	r	s	t	u	v	,
	112	113	114	115	116	117	118	1

# **Questions?**

