graph_osv

```
1
 2 --node vul:
 3 DROP TABLE IF EXISTS test.t_tmp_node_vul_osv;
 4 ALTER SEQUENCE cve_graph_seq RESTART START WITH 1;
 5 CREATE TABLE test.t_tmp_node_vul_osv AS
 6 WITH wt_severity AS
 8 SELECT tmp.ecosys || '_' || tmp.osv_id AS id , jsonb_agg(tmp.severity_val) AS severity
 9 FROM (
   SELECT
10
11 --
               CASE severity.value ->> 'type' WHEN 'CVSS_V3'AS severity_type,
12 --
              severity.value ->> 'type' AS severity_type,
             jsonb_build_object(
13
14
                                 CASE split_part(severity.value ->> 'score', '/',1)
15
                                    WHEN 'CVSS:3.1' THEN 'cvssV3_1'
                                    WHEN 'CVSS:3.0' THEN 'cvssV3_0'
16
17
                                    WHEN 'CVSS:4.0' THEN 'cvssV4_0'
                                    ELSE 'cvssV2_0' END , jsonb_build_object('vectorString', severity.value ->> 'sc
18
19
                                                                              'version', split_part( split_part(sev
20
                                                                              'baseScore', NULL,
                                                                              'attackVector', NULL,
21
22
                                                                              'baseSeverity', NULL,
23
                                                                              'confidentialityImpact', NULL,
24
                                                                              'integrityImpact', NULL,
25
                                                                              'availabilityImpact', NULL,
26
                                                                              'userInteraction', NULL,
27
                                                                              'attackComplexity', NULL,
28
                                                                              'privilegesRequired', NULL,
29
                                                                              'scope', null
30
                                                                             ) ) AS severity_val,
31
             oos.osv_id ,
32
             oos.ecosys
33
       FROM warehouse.ods_osv_source_df oos,
34
        jsonb_array_elements(oos.osv_msg -> 'severity') severity )tmp
35 GROUP BY tmp.ecosys || '_' || tmp.osv_id
36
   ) ,
37
    wt_osv_credit AS
38 (
39
       SELECT cre_ot.id, jsonb_build_object('identifier', array_agg( cre_ot.source_msg), 'discovery', null) AS sou
       FROM
40
41
42
           SELECT
              DISTINCT credit->>'name' AS source_msg, t.ecosys || '_' || t.osv_id AS id --, credit -> 'contact'
43
44
45
                warehouse.ods_osv_source_df t,
46
               jsonb_array_elements(t.osv_msg->'credits') AS credit
47
           WHERE
```

```
48
                credit->>'type' = 'FINDER' OR
49
                NOT credit ? 'type'
50
        )cre ot
51
        GROUP BY cre_ot.id
52
53 SELECT nextval('cve_graph_seq') AS seq, tmp.*, ws.severity, COALESCE (oc.source_msg_agg,'{}') AS source
55 (
        SELECT oos.ecosys || '_' || oos.osv_id AS id,
56
               COALESCE(oos.osv_msg ->> 'aliases','') AS aliases,
57
58
               jsonb_build_object('title', COALESCE(oos.osv_msg ->> 'summary',''), 'details', oos.osv_msg ->> 'det
59
               jsonb_build_object('type', NULL, 'cweId', coalesce(COALESCE(oos.osv_msg -> 'database_specific' ->> '
               jsonb_build_object( 'published', oos.osv_msg ->> 'published',
60
61
                                   'lastModified', oos.osv_msg ->> 'modified', 'datePublic', null) AS time_info,
62 --
               oos.ecosys AS ecosys,
63 --
               oos.osv_msg ->> 'schema_version' AS schema_version,
               COALESCE (oos.osv_msg ->> 'database_specific','{}') AS database_specific ,
64 --
65 --
               osv_msg AS msg
66
              ('{"impact_info":{"impacts":null, "impactScore":null},
                "solution_info":[],
                "exploit_info":{"exploitable":null, "exploits":null, "exploit_url":null, "exploitabilityScore":null
68
69
                "PoC_info":{"PoC_available":null, "PoC":null, "PoC_url":null},
70
                "patch_info":{"patch_available":null, "patch_url":null},
71
                "report_status":' || CASE WHEN (oos.osv_msg -> 'database_specific' ->> 'github_reviewed') = 'true'
72
        FROM warehouse.ods_osv_source_df oos
73 )tmp
74 LEFT JOIN wt_severity ws
75
          ON ws.id = tmp.id
76 LEFT JOIN wt_osv_credit oc
77
          ON oc.id = tmp.id;
78
79 DELETE FROM test.dws_graph_node_vul WHERE vul_source = 'OSV';
80 ALTER SEQUENCE cve_graph_seq RESTART START WITH 1;
81 INSERT INTO test.dws_graph_node_vul
82 SELECT nextval('cve_graph_seq') AS seq, tmp.*
83 FROM
84 (
85 SELECT DISTINCT id , aliases , source, description ,weakness, severity, time_info, vul_status, 'OSV' AS vul
86 )tmp;
87
88
89
90
91 --
92 ----node:: SecurityNotice create
93 --SELECT oos.osv_msg ->> 'id' AS osv_id, related.value ->> 0 AS related
94 --FROM warehouse.ods_osv_source_df oos,
95 -- jsonb_array_elements(oos.osv_msg -> 'related') related
96
97 -- node CWE merge
98 DROP TABLE IF EXISTS test.t_tmp_node_cwe;
99 CREATE TABLE test.t_tmp_node_cwe AS
100 SELECT oos.ecosys || '_' || oos.osv_id AS id , cwe_ids.value ->> 0 AS cwe_id
101 FROM warehouse.ods_osv_source_df oos,
102
        jsonb_array_elements(oos.osv_msg -> 'database_specific' -> 'cwe_ids') cwe_ids;
103
104
105 DELETE FROM test.dws_graph_cwe_node WHERE vul_source = 'OSV';
```

```
106 ALTER SEQUENCE cve_graph_seq RESTART START WITH 1;
107 INSERT INTO test.dws_graph_cwe_node
108 SELECT nextval('cve_graph_seq') AS seq, tmp.*
109 FROM
110 (
111 SELECT DISTINCT cwe_id , 'OSV' FROM test.t_tmp_node_cwe
112 )tmp;
113
114 \copy (SELECT DISTINCT cwe_id FROM test.t_tmp_node_cwe) to 'node_cwe_osv.csv' with (delimiter ',', FORCE_QUOTE
115
116
117
118
119 DELETE FROM test.dws_graph_Relationships_cwe WHERE vul_source = 'OSV';
120 ALTER SEQUENCE cve_graph_seq RESTART START WITH 1;
121 INSERT INTO test.dws_graph_Relationships_cwe
122 SELECT nextval('cve_graph_seq') AS seq, tmp.*
123 FROM
124 (
125 SELECT DISTINCT t.id AS vul_id, t.cwe_id , '' AS cwe_type, '' AS cwe_desc, 'OSV' AS vul_source FROM test.t_tm
126 )tmp ;
127
128 SELECT *FROM test.dws_graph_Relationships_cwe LIMIT 100
129
130 SELECT * FROM test.dws_graph_Relationships_cwe
131
132
133
134
135 LOAD CSV WITH HEADERS FROM 'file:///relationships_cwe_${vul_source}_${num}.csv' AS row
136
                MATCH (cve:Vuln_OSV {id: row.vul_id})
137
                 MATCH (cwe:CWE {id: row.cwe_id})
138
                 MERGE (cve)-[:HAS_CWE{cweId: row.cwe_id, type: row.cwe_type, description: row.cwe_desc}]->(cwe);
139
140 -- node Reference merge
141
142 DROP TABLE IF EXISTS test.t_tmp_node_ref;
143 CREATE TABLE test.t_tmp_node_ref AS
144 SELECT oos.ecosys || '_' || oos.osv_id AS id, refs.value ->> 'type' AS ref_type, refs.value ->> 'url' AS ref_ur
145 FROM warehouse.ods_osv_source_df oos,
        jsonb_array_elements(oos.osv_msg -> 'references') refs ;
146
147
148
149
150
151 [{"repo": "https://github.com/kanboard/kanboard", "type": "GIT", "events": [{"introduced": "0"}, {"fixed": "074
152
153 DELETE FROM test.dws_graph_cwe_node WHERE vul_source = 'OSV';
154 ALTER SEQUENCE cve_graph_seq RESTART START WITH 1;
155 INSERT INTO test.dws_graph_refs_node
156 SELECT nextval('cve_graph_seq') AS seq, tmp.*
157 FROM
158 (
159 SELECT DISTINCT ref_url , 'OSV' FROM test.t_tmp_node_ref
160 )tmp;
161
162 SELECT * FROM test.dws_graph_refs_node LIMIT 10
163
```

```
164 LOAD CSV WITH HEADERS FROM 'file:///node_.csv' AS row
165 MERGE (ref:references {url: row.url});
166
167 DELETE FROM test.dws_graph_relationships_refs WHERE vul_source = 'OSV';
168 ALTER SEQUENCE cve_graph_seq RESTART START WITH 1;
169 INSERT INTO test.dws_graph_relationships_refs
170 SELECT nextval('cve_graph_seq') AS seq, tmp.*
171 FROM
172 (
173 SELECT DISTINCT id AS vul_id , ref_url AS url, ref_type AS tag, '' AS description, 'OSV' AS vul_source FROM t
174 )tmp :
175
176 SELECT *FROM test.dws_graph_relationships_refs LIMIT 10
177
178
179 LOAD CSV WITH HEADERS FROM 'file:///ref 10w 9.csv' AS row
                 MATCH (cve:Vuln_NVD {id: row.r_start})
181
                 MATCH (ref:references {url: row.r_end})
182
                 MERGE (cve)-[:HAS_REFERENCE{description: row.ref_source,tags: COALESCE(row.ref_tags, '')}]->(ref);
183
184
185 -- node component:
186
        --if COALESCE(package_ecosys, package_name)
187
DROP TABLE IF EXISTS test.t_tmp_grahp_node_component_osv;
189 CREATE TABLE test.t_tmp_grahp_node_component_osv AS
190 WITH wt_osv_tmp as
191 (
192 SELECT oos.ecosys || '_' || oos.osv_id AS id,
193
               affecteds.value -> 'package' ->> 'ecosystem' AS package_ecosys, --vendor: *
194
               split_part(affecteds.value -> 'package' ->> 'ecosystem', ':', 1) AS package_ecosys_group,
               affecteds.value -> 'package' ->> 'name' AS module_package, --AS component_name
195
196
               affecteds.value -> 'package' ->> 'purl' AS repo_purl,
197
               affecteds ->> 'ranges' AS affected_ranges,
               affecteds ->> 'versions' AS affected_versions, --,
198
199
               affecteds_ranges ->> 'type' AS affected_range_type,
               affecteds_ranges ->> 'repo' AS affected_range_repo,
200
201
               affecteds_ranges.value ->> 'database_specific' AS affected_range_database_specific,
202
               affecteds_ranges ->> 'events' AS affected_range_events,
203
               oos.ecosys
204
        FROM warehouse.ods_osv_source_df oos,
205
            jsonb_array_elements(oos.osv_msg -> 'affected') affecteds ,
            jsonb_array_elements(affecteds.value -> 'ranges') affecteds_ranges
206
         WHERE oos.ecosys || '_' || oos.osv_id = 'GIT_CVE-2020-36138'
207 --
208 )
209 ,wt_osv_tmp1 AS
210 (
211
       SELECT wot.id, wot.package_ecosys_group AS package_ecosys,
212
              CASE WHEN wot.package_ecosys_group = 'Maven' THEN split_part(wot.module_package, ':', 1)
213
                   WHEN wot.package_ecosys_group = 'Packagist' THEN split_part(wot.module_package, '/', 1)
214
                   WHEN wot.package_ecosys_group = 'SwiftURL' THEN split_part(wot.module_package, '/', 2)
                   ELSE '-'
215
216
              END AS vendor,
217
              '-' AS component,
218
              CASE WHEN wot.package_ecosys_group = 'Maven' THEN split_part(wot.module_package, ':', 2)
                   WHEN wot.package_ecosys_group = 'Packagist' THEN split_part(wot.module_package, '/', 2)
219
220
                   WHEN wot.package_ecosys_group = 'SwiftURL' THEN split_part(wot.module_package, '/', 3)
221
                    --GO 语言的 module_package 对应的是 go 官网的id ,可以通过id获取到package 的名称
```

```
222
                                    ELSE wot.module_package
223
                           END AS package,
224
                           wot.module_package,
225
                           wot.ecosys,
226
                          wot.repo_purl, wot.affected_ranges, wot.affected_versions, wot.affected_range_type,
227
                          wot.affected_range_repo,
228
                           split_part(wot.affected\_range\_repo, '/', 3) \sim '^git\\ \\ ([a-zA-Z0-9\_-]+\\ \\ (argt-vorg+1) + (a
229
                          wot.affected_range_events
230
              FROM wt_osv_tmp wot
231 )
232 SELECT tmp.*, COALESCE(em.target_name, tmp.ecosystem_tmp) AS ecosystem
233 FROM
234 (
235 SELECT ot.id, coalesce(ot.package_ecosys, '*') AS ecosystem_tmp, --AS platform
236
                       ot.affected_range_type,
                       ot.vendor AS vendor,
237
238
                       ot.component,
239
                     ot.package,
240
                     ot.repo_purl AS repo_url,
241
                     '' AS defaultstatus, '' AS collectionURL, jsonb_build_object('version_range', ot.affected_range_events,
242
                     jsonb_build_object('version_range', '[]', 'version_list', '[]') AS unaffected_versions
243 FROM wt_osv_tmp1 ot
244 WHERE ot.affected_range_type <> 'GIT'
245 UNTON ALL
246 SELECT ot.id, 'GIT' AS ecosystem_tmp, --AS platform
247
                       ot.affected_range_type,
                     CASE WHEN ot.qit_xxx_org_flag = TRUE THEN substring( split_part(ot.affected_range_repo, '/', 3) FROM '^
248
249
                              WHEN regexp_replace(split_part(ot.affected_range_repo,'/',5), '\.git$','') = '' THEN '-'
                              ELSE split_part(ot.affected_range_repo,'/',4) END AS vendor,
250
251
                     ot.component,
252
                     CASE WHEN ot.git_xxx_org_flag = TRUE THEN regexp_replace( split_part(ot.affected_range_repo, '/', 4) ,
                              WHEN regexp_replace(split_part(ot.affected_range_repo,'/',5), '\.git$','') = '' THEN ot.module_pa
253
                              ELSE regexp_replace(split_part(ot.affected_range_repo,'/',5), '\.git$','') END AS package,
254
255
                     ot.affected_range_repo AS repo_url,
                      '' AS defaultstatus, '' AS collectionURL, jsonb_build_object('version_range', ot.affected_range_events,
256
                     jsonb_build_object('version_range', '[]', 'version_list', '[]') AS unaffected_versions
257
258 FROM wt_osv_tmp1 ot
259 WHERE ot.affected_range_type = 'GIT'
260 )tmp
261 LEFT JOIN test.dim_vul_ecosystem_map em
262
                     ON em.vul_source = 'OSV'
263
                     AND em.source_name = tmp.ecosystem_tmp;
264
266 UPDATE test.t_tmp_grahp_node_component_osv t
267 SET ecosystem = 'GIT', package = 'curl', vendor = 'curl', repo_url = 'https://github.com/curl/curl.git'
268 WHERE split_part(id, '_', 1) <> ecosystem
269 AND t.ecosystem = '*';
270
271
272
273
274
275
276
277
278 SELECT *FROM test.t_tmp_grahp_node_component_osv t WHERE t.package = ''
279
```

```
280 SELECT DISTINCT ecosystem FROM test.t_tmp_grahp_node_component_osv t LIMIT 100
281
282 DELETE FROM test.dws_graph_node_affected_component WHERE vul_source = 'OSV';
283 ALTER SEQUENCE cve_graph_seq RESTART START WITH 1;
284 INSERT INTO test.dws_graph_node_affected_component
285 SELECT nextval('cve_graph_seq') AS seq, tmp.*
286 FROM
287 (
288 SELECT DISTINCT component , vendor, package , ecosystem, 'OSV' AS vul_source FROM test.t_tmp_grahp_node_comp
289 )tmp ;
290
291 SELECT * FROM test.dws_graph_node_affected_component WHERE vul_source = 'OSV' AND package_name IS NULL LIMIT
292
293
294
295 DELETE FROM test.dws_graph_relationships_affected_components WHERE vul_source = 'OSV';
296 ALTER SEQUENCE cve_graph_seq RESTART START WITH 1;
297 INSERT INTO test.dws_graph_relationships_affected_components
298 SELECT nextval('cve_graph_seq') AS seq, tmp.*
299 FROM
300 (
301 SELECT DISTINCT id AS vul_id, component , vendor, package , ecosystem, repo_url AS repo_url,
            '' AS platform, COALESCE(collectionurl,'') AS collectionUrl, COALESCE(defaultstatus,'') AS defaultstatu
302
303
          'OSV' AS vul_source FROM test.t_tmp_grahp_node_component_osv
304 )tmp;
305
306
307
308 bash gen_graph_data.sh "OSV" "node" "affected_component"
309 bash neo4j_affected_component_node_load.sh "OSV" "0"
310
311 bash gen_graph_data.sh "OSV" "relationships" "affected_components"
312 bash neo4j_relationships_affected_components.sh "OSV" "2"
313
314 SELECT *FROM test.t_tmp_grahp_node_component_osv LIMIT 10
315
316
317 (seq int , vul_id varchar, component varchar, vendor varchar, package_name varchar, ecosystem varchar, repo_url
318 INSERT INTO test.dws_graph_relationships_affected_components
319
320 SELECT *FROM test.dws_graph_relationships_affected_components WHERE defaultstatus IS NULL
321
322 Alpine_CVE-2006-20001
323 id: Alpine_CVE-2006-20001
324
325 SELECT *FROM test.dws_graph_relationships_affected_components t
326 WHERE t.vul_id = 'Alpine_CVE-2006-20001'
327
328
329 SELECT *FROM test.dws_graph_relationships_affected_components WHERE vul_id = 'Alpine_CVE-2006-20001'
330
331
332 SELECT *FROM test.dws_graph_node_vul dgvn WHERE dgvn.id = 'Alpine_CVE-2006-20001'
333
334
335
```