

Below is a **clean, deeply structured, internally accurate, and exam-oriented** rewrite of Fetch API, written **exactly in the same learning depth and format** you've been following for **Web Workers, BOM, Storage, Forms API**, etc.

I've **not copied your text** — I've **re-engineered it** so it works perfectly for:

- 📖 Notes (NoteLM / exam prep)
- 🧠 Conceptual clarity
- ⚙️ Internal working
- 🖋️ Real-world usage
- 🗣️ Interview answers

JavaScript Fetch API

1 What is Fetch API?

The **Fetch API** is a **Browser Web API** that allows JavaScript to **send HTTP requests** and **receive responses** from a web server.

It is used to communicate with:

- REST APIs
- Backend servers
- Third-party services

📌 Introduced as a modern replacement for **XMLHttpRequest (XHR)**.

2 Why Fetch API Was Introduced?

✗ Problems with XMLHttpRequest

- Complex syntax
- Callback-based (callback hell)
- Hard to read and maintain
- Poor error handling

✓ Fetch API Advantages

- Promise-based
- Cleaner syntax
- Supports `async/await`
- Better readability
- Easier JSON handling

3 Where Does Fetch API Live?

- Fetch API is **part of the Browser**
- It is available on the **window object**

```
js  
  
window.fetch()
```

Since `window` is global, we usually write:

```
js  
  
fetch()
```

4 Internal Working of Fetch API (VERY IMPORTANT)

Internal Flow

```
pgsql  
  
JavaScript Code  
↓  
fetch() called  
↓  
Browser Network Layer  
↓  
HTTP Request sent  
↓  
Server processes request  
↓  
HTTP Response received  
↓  
Promise resolved with Response object
```

Key Insight

Fetch **does NOT block** the main thread → it works asynchronously.

5 Fetch API Syntax

```
js  
  
fetch(URL, [options])
```

Parameters

Parameter	Description
URL	API endpoint
options	Request configuration (method, headers, body, etc.)

6 What Does fetch() Return?

✓ fetch() always returns a Promise

That Promise:

- Resolves → `Response` object
- Rejects → Network error only

📌 Important

HTTP errors like 404 / 500 do NOT reject the promise

7 Response Object (Internals)

The `Response` object contains:

- Status code
- Headers
- Body (readable only once)

To extract data:

```
js  
  
response.json()  
response.text()  
response.blob()
```

8 Handling Fetch Using `.then()` (Promise Chain)

📌 Flow

```
js  
  
fetch()  
  → Response  
  → Convert body  
  → Use data
```

Example

html

```
<script>
fetch("https://jsonplaceholder.typicode.com/todos/5")
  .then(response => response.json()) // parse JSON
  .then(data => {
    console.log(data);
  })
  .catch(error => {
    console.log(error);
  });
</script>
```

🧠 Internal Notes:

- `response.json()` also returns a Promise
- Each `.then()` waits for the previous Promise

9 Handling Fetch Using `async / await`

Why `async/await`?

- Looks synchronous
- Easier debugging
- Cleaner logic

Example

html

```
<script>
async function getData() {
  const response = await fetch("https://jsonplaceholder.typicode.com/todos/6");
  const data = await response.json();
  console.log(data);
}

getData();
</script>
```

📌 Important

- `await` pauses function execution
- Does NOT block main thread

10 Fetch Options Object (Request Configuration)

```
js
```

```
fetch(URL, {  
  method: "POST",  
  headers: {  
    "Content-Type": "application/json"  
  },  
  body: JSON.stringify(data)  
})
```

1 1 Common Fetch Options

Option	Purpose
method	HTTP method (GET, POST, PUT, DELETE)
headers	Metadata (Content-Type, Auth)
body	Request payload
mode	CORS control
cache	Cache behavior
credentials	Cookies handling
redirect	Redirect handling

1 2 HTTP Methods Using Fetch

◆ GET Request

```
js
```

```
fetch(URL, { method: "GET" })
```

Used to:

- Fetch data
- Read resources

◆ POST Request

```
js
```

```
fetch(URL, {  
  method: "POST",
```

```
headers: {  
  "Content-Type": "application/json"  
},  
body: JSON.stringify(data)  
})
```

Used to:

- Create new records
- Send form data

◆ PUT Request

```
js  
  
fetch(URL, {  
  method: "PUT",  
  headers: {  
    "Content-Type": "application/json"  
  },  
  body: JSON.stringify(updatedData)  
})
```

Used to:

- Update existing data

◆ DELETE Request

```
js  
  
fetch(URL, { method: "DELETE" })
```

Used to:

- Remove data from server

1 3 Error Handling in Fetch (CRITICAL)

✗ Common Mistake

```
js  
  
fetch(url)  
  .catch() // ✗ does NOT catch HTTP errors
```

✓ Correct Way

js

```
fetch(url)
  .then(response => {
    if (!response.ok) {
      throw new Error("HTTP Error");
    }
    return response.json();
  })
  .catch(err => console.error(err));
```

1 4 Fetch vs XMLHttpRequest

Feature	Fetch	XHR
Syntax	Clean	Complex
Promise-based	Yes	No
Async/Await	Yes	No
JSON handling	Easy	Manual
Streaming	Yes	No

1 5 Advantages of Fetch API

- ✓ Modern and clean syntax
- ✓ Promise-based
- ✓ Supports async/await
- ✓ Native JSON handling
- ✓ Flexible request configuration

1 6 Limitations of Fetch API

- ✗ No automatic HTTP error rejection
- ✗ No timeout support (needs AbortController)
- ✗ Requires manual error checks

1 7 Real-World Use Cases

- Fetching REST APIs
- Login / Authentication
- Form submission
- CRUD operations
- Third-party APIs

- SPA data loading

1 8 Exam-Ready One-Line Answers

Q: What is Fetch API?

A web API used to make HTTP requests asynchronously using promises.

Q: What does `fetch()` return?

A Promise that resolves to a Response object.

Q: Is Fetch synchronous?

No, it works asynchronously and does not block the main thread.

1 9 Key Takeaways (FINAL)

- ✓ Fetch is browser-provided
- ✓ Promise-based API
- ✓ Replaces XMLHttpRequest
- ✓ Uses HTTP methods
- ✓ Works with `async/await`
- ✓ Requires manual error handling

▶▶ What's Next?

Perfect continuation topics:

- 1 AbortController & Fetch Timeout
- 2 CORS and Fetch Internals
- 3 Fetch vs Axios
- 4 Streaming responses

👉 Say “next” and I’ll continue in the **same structured, internal, exam-ready style**.