

JavaScript learning path

Perfect 🚀 Let's go deep into `var` — its history, internals, quirks, optimizations, and interview brain-benders.

`var` in JavaScript (Deep Dive)

1. Background

- `var` is the **original way** to declare variables in JavaScript (since 1995).
- Still works, but **modern JS prefers `let` and `const`** because `var` has **quirks** that cause bugs.
- In interviews, you'll often be asked about `var` vs `let` / `const`.

2. Core Properties of `var`

✓ a) Function-scoped (not block-scoped)

```
js

function test() {
  if (true) {
    var x = 10;
  }
  console.log(x); // ✓ 10 (var escapes block!)
}
test();
```

- Unlike `let` and `const`, which are **block-scoped**, `var` ignores `{ }` blocks except function blocks.

✓ b) Hoisting

- Variables declared with `var` are **hoisted** to the **top of their scope** (function or global).
- But **only the declaration is hoisted, not the initialization**.

js

```
console.log(a); // undefined (hoisted but not assigned)
var a = 5;
console.log(a); // 5
```

🔍 Internally, JS engine transforms code like this:

js

```
var a;      // declaration hoisted
console.log(a); // undefined
a = 5;      // assignment happens here
console.log(a); // 5
```

✅ c) Can be re-declared

js

```
var x = 1;
var x = 2; // ✅ No error
console.log(x); // 2
```

- Unlike `let` / `const` which throw errors on redeclaration.

✅ d) Attached to `window` (in browsers)

js

```
var name = "Anoop";
console.log(window.name); // "Anoop" ✅
```

- `var` creates **properties on the global object** (`window` in browsers, `global` in Node).
- `let` and `const` do not.

✅ e) Default value is `undefined`

js

```
var y;  
console.log(y); // undefined
```

3. ⚡ Common Pitfalls (Interview Traps)

❌ a) Block leakage

```
js  
  
for (var i = 0; i < 3; i++) {  
  setTimeout(() => console.log(i), 1000);  
}  
// Output: 3, 3, 3 (not 0, 1, 2!)
```

Why?

- `var` is function-scoped, so the same `i` is shared across all loop iterations.

👉 Fix with `let` :

```
js  
  
for (let i = 0; i < 3; i++) {  
  setTimeout(() => console.log(i), 1000);  
}  
// Output: 0, 1, 2
```

❌ b) Redeclaration bugs

```
js  
  
var score = 50;  
if (true) {  
  var score = 100; // same variable!  
}  
console.log(score); // 100 (oops, overwritten)
```

❌ c) Hoisting confusion

js

```
console.log(msg); // undefined, not error  
var msg = "Hello";
```

👉 Developers expect an error, but `var` silently returns `undefined`.

4. 🧠 Interview Brain-Benders (with Solutions)

Q1:

js

```
var a = 1;  
function test() {  
  console.log(a);  
  var a = 2;  
}  
test();
```

Answer: `undefined`

- Inside `test()`, `var a` is **hoisted** → local `a` shadows global `a`.
 - Declaration hoisted but not initialized, so first `console.log(a)` is `undefined`.
-

Q2:

js

```
var x = 5;  
(function() {  
  console.log(x); // ?  
  var x = 10;  
})();
```

Answer: `undefined`

- Same reasoning: hoisting creates local `x`.
-

Q3:

```
js

if (true) {
  var foo = "bar";
}

console.log(foo); // ?
```

Answer: "bar" ✓

- `var` ignores block scope.

5. 🔧 Real-World Optimizations & Best Practices

- Avoid `var` in modern code; use `let` / `const`.
- If you must use `var` (e.g., legacy projects):
 1. Always declare at the **top of the function** (to avoid hoisting confusion).
 2. Use **IIFE** (Immediately Invoked Function Expressions) to simulate block scope:

```
js

(function() {
  var temp = "isolated";
  console.log(temp); // isolated
})();
console.log(temp); // ReferenceError
```

6. ⚙️ Hidden Internals

- `var` variables live in the **Variable Environment Record** of the Execution Context.
- On compilation phase:
 - JS engine scans and hoists all `var` declarations.
 - Assignments happen in runtime.

This is why **Temporal Dead Zone (TDZ)** does NOT exist for `var`, but exists for `let` / `const`.

✓ That's the **complete deep dive** of `var`.

Shall I now give you a **side-by-side comparison** of `var`, `let`, and `const` with **internals + performance trade-offs**, before we move to `let` individually?