

Perfect. Continuing **systematically**, NotebookLM-ready, with **NOTES** and **CODE** strictly separated.

## **TOPIC: Event Loop & Concurrency Model**

(Call Stack • Web APIs • Callback Queue • Microtasks • Macrotasks)

### **NOTE 1: Why the Event Loop exists**

- JavaScript is **single-threaded**
- Only **one call stack**
- Async operations must not block execution
- Event Loop coordinates **when async callbacks run**

👉 Event Loop is part of the **runtime**, not the JS language.

### **NOTE 2: Core components (mental map)**

JavaScript concurrency involves **5 major parts**:

1. Call Stack
2. Web APIs (Browser) / Libuv (Node)
3. Callback (Task) Queue
4. Microtask Queue
5. Event Loop (scheduler)

### **CODE 1: Simple async example**

```
js

console.log("Start");

setTimeout(() => {
  console.log("Timeout");
}, 0);

console.log("End");
```

### **Output**

```
powershell

Start
End
Timeout
```

### **NOTE 3: Call Stack (execution engine)**

- Stack follows **LIFO** (Last In, First Out)

- JS executes only what's on the stack
- Stack must be **empty** before async callbacks run

## CODE 2: Call stack example

```
js

function a() {
  b();
}

function b() {
  console.log("Inside b");
}

a();
```

## NOTE 4: Web APIs / Host APIs

- Provided by browser / Node
- Handle async work:
  - Timers
  - DOM events
  - Fetch / HTTP
- JS engine **delegates** async work here

## CODE 3: Delegation to Web API

```
js

setTimeout(() => {
  console.log("Done");
}, 1000);
```

## NOTE 5: Callback (Macrotask) Queue

- Stores callbacks after async task completes
- Examples:
  - `setTimeout`
  - `setInterval`
  - DOM events
- Executed **only when call stack is empty**

## NOTE 6: Event Loop (scheduler logic)

Event Loop continuously checks:

1. Is Call Stack empty?
2. Are Microtasks pending?
3. Execute all Microtasks
4. Take ONE task from Callback Queue
5. Push it to Call Stack
6. Repeat forever

#### CODE 4: Visual order example

```
js

console.log("A");

setTimeout(() => console.log("B"), 0);

Promise.resolve().then(() => console.log("C"));

console.log("D");
```

#### Output

```
css

A
D
C
B
```

#### NOTE 7: Microtask Queue (HIGH PRIORITY)

- Executed **before** macrotasks
- Examples:
  - `Promise.then`
  - `catch`
  - `finally`
  - `queueMicrotask`
- Can starve macrotasks if abused

#### CODE 5: Microtask dominance

```
js

setTimeout(() => console.log("Timeout"), 0);
```

```
Promise.resolve().then(() => console.log("Promise"));
```

## Output

javascript

Promise

Timeout

## NOTE 8: Macrotasks (lower priority)

Examples:

- `setTimeout`
- `setInterval`
- UI events
- `MessageChannel`

## CODE 6: Macrotask queue

js

```
setTimeout(() => console.log("Task 1"), 0);  
setTimeout(() => console.log("Task 2"), 0);
```

## NOTE 9: Infinite microtask trap (INTERVIEW)

- Microtasks run until queue is empty
- Recursive microtasks block rendering & timers

## CODE 7: Microtask starvation

js

```
function loop() {  
  Promise.resolve().then(loop);  
}  
  
loop();  
// setTimeout callbacks never run
```

## NOTE 10: `queueMicrotask`

- Explicitly schedules microtask
- Same priority as Promise callbacks

## CODE 8: `queueMicrotask` example

js

```
queueMicrotask(() => console.log("Microtask"));
console.log("Sync");
```

## Output

rust

Sync

Microtask

### NOTE 11: Rendering & Event Loop (Browser)

- Browser renders **between** macrotasks
- Long JS blocks rendering
- Microtasks delay painting

### CODE 9: Rendering block example

js

```
Promise.resolve().then(() => {
  while (true) {}
});
```

### NOTE 12: Node.js Event Loop (difference hint)

- Uses libuv
- Phases:
  - timers
  - I/O callbacks
  - idle
  - poll
  - check
  - close callbacks
- Microtasks still have priority

### NOTE 13: Common interview traps

- Promises run before `setTimeout`
- Event Loop runs only when stack is empty
- Microtasks can block macrotasks
- `setTimeout(fn, 0) ≠ immediate execution`
- Event Loop ≠ Call Stack

### FINAL MENTAL MODEL

- JS runs on one thread
- Async work is delegated
- Call Stack executes JS
- Microtasks run first
- Macrotasks run later
- Event Loop schedules everything

 **STOP HERE**

Next **recommended continuation**:

**1** Browser vs Node.js Runtime (deep differences)

**2** Fetch API + async flow

**3** Error Handling (sync vs async)

Reply with **next** or the **number** you want to continue.