

JavaScript learning path

Great 👍 — let's now go one step deeper into real-world use cases + more tricky pitfalls/interview-style problems for the loops we already covered (`while`, `do...`, `while`, `for`, `break`, `continue`, `labels`).

Loops – Real-World Usage + Interview Pitfalls

✓ Real-World Use Cases

1. `while` loop

- **Best for unknown iteration counts** (runs until condition met).

Example: keep asking user input until valid number:

```
js

let value;
while (true) {
  value = prompt("Enter a number greater than 10:");
  if (value > 10) break;
}
console.log("You entered:", value);
```

2. `do...while` loop

- **Guaranteed execution at least once.**

Example: menu-driven program.

```
js

let choice;
do {
  choice = prompt("1. Add 2. Exit");
  if (choice == 1) console.log("Adding...");
} while (choice != 2);
```

3. `for` loop

- Best for known iteration counts.

Example: printing multiplication table.

```
js

for (let i = 1; i <= 10; i++) {
  console.log(`5 x ${i} = ${5 * i}`);
}
```

4. `break` in real use

- Early termination when condition met.

```
js

let arr = [3, 6, -2, 7, 9];
for (let i = 0; i < arr.length; i++) {
  if (arr[i] < 0) {
    console.log("Found negative:", arr[i]);
    break;
  }
}
```

5. `continue` in real use

- Skip processing certain cases.

```
js

for (let i = 1; i <= 10; i++) {
  if (i % 2 === 0) continue; // skip even
  console.log("Odd:", i);
}
```

6. Labels in real use

- Breaking out of nested loops (rare, but sometimes needed).
-

js

```
outer: for (let i = 0; i < 5; i++) {  
  for (let j = 0; j < 5; j++) {  
    if (i * j > 6) break outer;  
    console.log(i, j);  
  }  
}
```

⚠ Common Pitfalls + Interview Brain-Venders

? Q1. What's the output?

js

```
let i = 0;  
while (i++ < 5) {  
  console.log(i);  
}
```

👉 Output: 1 2 3 4 5

Reason: `i++` compares first, then increments.

? Q2. Guess the result

js

```
for (let i = 0; i < 3; i++) {  
  setTimeout(() => console.log(i), 100);  
}
```

👉 Output: 0 1 2

Because `let` makes `i` block-scoped (new variable each iteration).

⚡ Tricky twist: if it was `var i`, output = 3 3 3.

? Q3. Can this loop end?

js

```
for (let i = 0; i != 10; i += 0.2) {}
```

👉 **No guarantee!** Floating-point numbers may skip 10 (e.g., $9.8 \rightarrow 10.0$ may never be exact).

? Q4. Nested break confusion

js

```
for (let i = 0; i < 2; i++) {  
  for (let j = 0; j < 2; j++) {  
    if (j === 1) break;  
    console.log(i, j);  
  }  
}
```

👉 **Output:**

```
0 0  
1 0
```

Because `break` only exits inner loop.

? Q5. Infinite loop subtlety

js

```
let x = 0.1;  
while (x !== 1.0) {  
  x += 0.1;  
}
```

👉 This is **infinite**.

Because floating-point addition may never produce exactly `1.0`.

? Q6. Scope trap

js

```
for (var i = 0; i < 3; i++) {}  
console.log(i); // ?
```

👉 Prints `3` (because `var` is function-scoped).

With `let`, would be `ReferenceError`.

🧠 Interviewer Tricks

- “Why is `do...while` rarely used in production?”
👉 Because we usually want condition checked before execution. It’s useful in rare cases like menu-driven apps.
- “How to safely terminate a loop that depends on floating-point comparison?”
👉 Use tolerance:

js

```
while (Math.abs(x - 1.0) > 1e-9) { ... }
```

- “Why is `for(;;)` dangerous?”
👉 It’s an **infinite loop** unless controlled with `break`. Used in event loops, but risky for beginners.
-

✅ That’s the **extended deep dive with real-world cases + pitfalls + brain-venders**.

Do you want me to next cover “**loop optimizations (performance tricks, micro-optimizations, interview hacks)**” or should we go ahead to **special loops** (`for...in`, `for...of`)?