

Perfect. Continuing systematically, NotebookLM-ready, with NOTES and CODE strictly separated.

■ TOPIC: Nullish Coalescing Operator (??)

(vs Logical OR || • Edge Cases • Real-World Patterns)

■ NOTE 1: Why ?? was introduced

- || treats all falsy values as “missing”
- This causes bugs when valid falsy values exist (0, "", false)
- ?? fixes this by checking only:
 - null
 - undefined

■ CODE 1: The core problem with ||

```
js

let count = 0;
let result = count || 10;

result; // 10 ❌ (0 is valid but ignored)
```

■ NOTE 2: Definition of ??

- a ?? b returns:
 - b only if a is null or undefined
 - otherwise returns a
- No other falsy values are considered “missing”

■ CODE 2: Basic ?? usage

```
js

let count = 0;
let result = count ?? 10;

result; // 0 ✅
```

■ NOTE 3: Exact comparison logic (internal rule)

Internally, this is how JS treats ?? :

```
js

a !== null && a !== undefined ? a : b
```

No boolean coercion involved.

CODE 3: Internal equivalence

```
js

let value = undefined;
let output = value ?? "default";

// Equivalent to:
let output2 =
  value !== null && value !== undefined
    ? value
    : "default";
```

NOTE 4: ?? vs || — side-by-side behavior

Value	value "X"	value ?? "X"
0	"X" ❌	0 ✅
""	"X" ❌	"" ✅
false	"X" ❌	false ✅
null	"X" ✅	"X" ✅
undefined	"X" ✅	"X" ✅

CODE 4: Side-by-side examples

```
js

0 || 100;    // 100
0 ?? 100;    // 0

"" || "text"; // "text"
"" ?? "text"; // ""

false || true; // true
false ?? true; // false
```

NOTE 5: Common real-world use cases

- Default values from APIs
- Configuration values
- User input handling
- Optional fields

CODE 5: API data example

```
js

let user = {
  name: "Anoop",
  age: 0
};

let age = user.age ?? 18;
age; // 0 (correct)
```

NOTE 6: ?? with function return values

- Safe when a function may return `null` or `undefined`
- Avoids overwriting valid falsy returns

CODE 6: Function defaulting

```
js

function getScore() {
  return 0;
}

let score = getScore() ?? 50;
score; // 0
```

NOTE 7: Short-circuit behavior

- `??` is short-circuiting
- Right side executes **only** if needed

CODE 7: Short-circuit example

```
js

let value = null;

value ?? console.log("Runs"); // console.log runs
```

```
js

let value2 = 10;

value2 ?? console.log("Does not run");
```

NOTE 8: Operator precedence (IMPORTANT)

- `??` has lower precedence than `||` and `&&`
- Mixing without parentheses is **not allowed**

CODE 8: Syntax error example

```
js

// ❌ SyntaxError
// let x = null || 10 ?? 20;
```

NOTE 9: Correct way to mix operators

- Always use parentheses
- Be explicit

CODE 9: Correct mixing

```
js

let x = (null || 10) ?? 20;
x; // 10

let y = null ?? (false || 50);
y; // 50
```

NOTE 10: `??` vs ternary `(?:)`

- `??` is **more readable** for null checks
- Ternary is more flexible but verbose

CODE 10: Comparison

```
js

let value = undefined;

let a = value ?? "default";

let b =
  value === null || value === undefined
    ? "default"
    : value;
```

NOTE 11: When NOT to use `??`

- When any **falsy value** should trigger fallback
- Example: authentication, boolean flags

CODE 11: Wrong usage example

js

```
let isLoggedIn = false;
```

// ❌ wrong

```
let status = isLoggedIn ?? true;
```

// ✅ correct

```
let status2 = isLoggedIn || true;
```

NOTE 12: Interview traps

- `??` checks only `null` and `undefined`
- `||` checks **all falsy values**
- Cannot mix `??` with `&&` / `||` without parentheses
- `??` is short-circuiting

FINAL MENTAL MODEL

- `||` → fallback on **falsy**
- `??` → fallback on **nullish**
- `??` = safer defaults
- Always use parentheses when mixing
- Prefer `??` for data, `||` for logic

STOP HERE

Next **recommended continuation**:

- 1 **Loops** (`for` , `while` , `do...while` , `for...of` , `for...in`)
- 2 **Functions** (declaration, expression, execution context)
- 3 **Scope & Hoisting** (deep, memory-level)

Reply with **next** or the **number** you want to continue.