

Below is a **clean, simplified, exam-ready, and concept-focused** explanation of the `void` keyword in **JavaScript**, written in the **same depth and structured note style** you've been following (perfect for NoteLM, revision, and exams).

◆ `void` Keyword in JavaScript

The `void` keyword in JavaScript is an operator that **evaluates an expression and always returns `undefined`**.

👉 In simple words:

`void` → run something, but return nothing

📌 Key Meaning of `void`

- `void` means **empty / no value**
- It **discards the return value** of an expression
- It **always returns** `undefined`

📘 Syntax

js

```
void expression;
```

- `expression` can be **any valid JavaScript expression**
- Result is **always** `undefined`

🔄 Return Value

text

undefined

🖋️ Basic Example

html

```
<script>
let result = void 10;
console.log(result);
</script>
```

✅ Output

text

undefined

✓ `10` is evaluated

✓ Return value is discarded

⚠ Operator Precedence of `void`

The `void` operator has **higher precedence** than comparison operators.

Example

js

```
let res1 = void 10 === 20;  
let res2 = void (10 === 20);
```

Evaluation

js

```
res1 → (void 10) === 20 → undefined === 20 → false  
res2 → void (10 === 20) → void false → undefined
```

Output

text

false

undefined

📌 Always use parentheses when combining `void` with other operators.

🔗 What is `javascript:void(0)`?

Let's split it:

1 `javascript:` (Pseudo URL)

- Used inside `href`
- Executes JavaScript instead of navigating

Example

html

```
<a href="javascript:alert('Clicked!')">Click</a>
```

✓ Runs JavaScript

✗ Bad practice today (security & readability)

2 `void(0)`

- `0` is evaluated
- Result is discarded
- Returns `undefined`

js

`void(0)` → `undefined`

🔥 `javascript:void(0)` (Most Common Use)

Used to prevent page reload/navigation when clicking a link.

Example

html

```
<a href="javascript:void(0)">Click me</a>
```

✓ Click does nothing

✓ No page reload

✓ No URL change

🎯 Practical Use Case

Change page content without navigation

html

```
<a href="javascript:void(0)"  
  onclick="document.body.style.backgroundColor='blue'">  
  Change Background  
</a>
```

✓ JavaScript executes

✓ Page does NOT reload

🧠 Modern Alternative (Recommended)

html

```
<a href="#" onclick="event.preventDefault()">Click</a>
```

- ✓ Cleaner
- ✓ Better practice
- ✓ Accessible

void with Functions

Important Rule

When `void` is applied to a function declaration/expression:

- Function is **evaluated**
- Result becomes **undefined**
- Function name becomes unusable

Example (Error Case)


```
html

<script>
  try {
    void function test() {
      console.log("Executed");
    };
    test(); // ❌ Error
  } catch {
    console.log("Function is undefined");
  }
</script>
```

Output

```
text

Function is undefined
```

 `void` treats the function as an expression and discards it.

Correct Use: `void` with IIFE

Immediately Invoked Function Expression (IIFE)

```
html
```

```
<script>
void function () {
  console.log("IIFE executed");
}();
</script>
```

Output

text

IIFE executed

- ✓ Function runs
- ✓ Return value discarded
- ✓ No variable pollution



void with Arrow Function

js

```
void (() => console.log("Arrow executed"))();
```

- ✓ Executes arrow function
- ✓ Returns undefined



Why void Exists?

- To explicitly return undefined
- To avoid unwanted return values
- To prevent page navigation
- To force expression execution only



Summary Table

Usage	Purpose
void 10	Returns undefined
void(expression)	Discards result
javascript:void(0)	Prevent navigation
void IIFE()	Execute without return

Usage	Purpose
<code>void function()</code>	Makes function unusable

✗ When NOT to Use `void`

- Modern apps → use `event.preventDefault()`
- Avoid `javascript:` URLs
- Avoid confusing precedence cases



One-Line Exam Definition

The `void` operator evaluates an expression and always returns `undefined`, discarding any result produced by the expression.

If you want next:

- `delete` vs `void`
- Output-based MCQs
- Interview traps
- Modern best practices
- Comparison with `undefined`

Just say **next** 🚀