

# JavaScript learning path

Perfect 🚀 Let's move on to the next primitive:

## undefined in JavaScript (Deep Dive)

---

### 1. ♦ What is undefined?

- A special **primitive value** that represents:

*"a variable has been declared but not assigned any value yet."*

- It is **not** the same as `null`.
- Type:

```
js

typeof undefined; // "undefined"
```

### 2. ♦ When do you get undefined?

#### (a) Variable declared but not assigned

```
js

let x;
console.log(x); // undefined
```

#### (b) Missing function return

```
js

function test() {}
console.log(test()); // undefined
```

#### (c) Accessing missing object properties

```
js

let obj = {};
```

```
console.log(obj.key); // undefined
```

#### (d) Array element not set

```
js
```

```
let arr = [1, , 3]; // sparse array
console.log(arr[1]); // undefined
```

#### (e) Function parameters not passed

```
js
```

```
function greet(name) {
  console.log(name);
}
greet(); // undefined
```

### 3. ♦ Difference between `undefined` and `null`

Feature	<code>undefined</code>	<code>null</code>
Meaning	Declared but not assigned, missing value	Explicitly no value
Type	"undefined"	"object" (quirk of JS)
Set by	JavaScript engine	Developer (intentionally)
Example	<pre>let a; console.log(a); // undefined</pre>	<pre>let a = null;</pre>

### 4. ♦ Type Coercion with `undefined`

```
js
```

```
Number(undefined); // NaN
String(undefined); // "undefined"
Boolean(undefined); // false
```

## Loose equality traps:

```
js

undefined == null; // true (special case)
undefined === null; // false (different types)
```

## 5. ♦ Edge Cases

### 1. Global variable `undefined` is writable in old JS

```
js

undefined = "oops";
console.log(undefined); // "oops" (in ES3/ES5 non-strict mode)
```

✅ In modern JS (ES5 strict mode + ES6+), `undefined` is read-only.

### 2. Array holes vs `undefined`

```
js

let arr = [1, , 3];
console.log(arr[1]); // undefined
console.log(1 in arr); // false (hole, not assigned `undefined`)
```

### 3. `JSON.stringify` drops `undefined`

```
js

JSON.stringify({a: undefined, b: 2});
// '{"b":2}'
```

## 6. ♦ Best Practices

- ✅ Use `===` when comparing with `undefined`.
- ✅ Prefer `null` when you want to **explicitly clear/reset** a variable.

- ✗ Don't manually assign `undefined`, use `null` instead.

js

```
let user = null; // clear value
```

## 🧩 Quick Exercise (Your Turn 😊)

What will be the output?

js

```
let x;  
console.log(x == null); // ?  
console.log(x === null); // ?  
console.log(x === undefined); // ?
```

👉 Do you want me to **solve this right now step by step**, or first give you a few more **brain-bender corner cases** with `undefined`?

Alright 💡 let's solve the exercise step by step, and then I'll also add some **brain-bender corner cases** around `undefined`.

## 🔍 Exercise Solution

js

```
let x;  
console.log(x == null);    // ?  
console.log(x === null);  // ?  
console.log(x === undefined); // ?
```

**Step 1:** `let x;`

- Variable `x` is declared but not assigned.
  - So `x` → `undefined`.
- 

### Step 2: `x == null`

- Loose equality (`==`) does type coercion.
- Special rule:
  - 👉 `null == undefined` → `true`.
- So:

```
js
console.log(undefined == null); // true
```

✅ Output: `true`

---

### Step 3: `x === null`

- Strict equality (`===`) checks type + value.
- `x` is `undefined`, not `null`.
- Types differ: `"undefined"` vs `"object"`.
- So:

```
js
console.log(undefined === null); // false
```

✅ Output: `false`

---

### Step 4: `x === undefined`

- `x` is literally `undefined`.
- Types and values match.
- So:

```
js
console.log(undefined === undefined); // true
```

✓ Output: `true`

## Final Answer

```
js

true
false
true
```

## Extra Brain-Benders (Interview-Style)

### 1. Undefined in arrays

```
js

let arr = [undefined, ,];
console.log(arr.length); // ?
console.log(arr[0]);    // ?
console.log(arr[1]);    // ?
```

### 2. JSON behavior

```
js

console.log(JSON.stringify({a: undefined, b: null}));
// ?
```

### 3. Global undefined quirk

```
js

var undefined = 123;
console.log(undefined); // ?
```

👉 Do you want me to **solve these 3 undefined brain-benders** step by step right now, or should I move on to the next primitive: `null` ?

Perfect 🙌 let's solve these 3 `undefined` brain-benders step by step.

## 🧩 Brain-Bender 1: Undefined in arrays

js

```
let arr = [undefined, ,];  
console.log(arr.length); // ?  
console.log(arr[0]); // ?  
console.log(arr[1]); // ?
```

### Step 1: Array creation

- `arr = [undefined, ,];` creates an array with 2 slots:
  - `arr[0] = undefined` (explicitly set)
  - `arr[1] = <empty slot>` (called a *hole*)

### Step 2: `console.log(arr.length);`

- Array has 2 indexes → length = 2.

### Step 3: `console.log(arr[0]);`

- Explicitly assigned `undefined`.  
✅ Output → `undefined`

### Step 4: `console.log(arr[1]);`

- This is a **hole**, not even `undefined` explicitly.
- When accessed, JS returns `undefined`, but internally `arr` doesn't store a value there.

✅ Output → `undefined`

👉 Difference:

js

```
console.log(0 in arr); // true (index exists, holds undefined)  
console.log(1 in arr); // false (hole, doesn't exist)
```

## Brain-Bender 2: JSON behavior

js

```
console.log(JSON.stringify({a: undefined, b: null}));
```

### Rule:

- `JSON.stringify` drops properties with `undefined` values.
- `null` is preserved.

So:

js

```
{a: undefined, b: null} → {"b":null}
```

✓ Output → `{"b":null}`

---

## Brain-Bender 3: Global undefined quirk

js

```
var undefined = 123;  
console.log(undefined);
```

### In old JS (ES3, ES5 non-strict):

- `undefined` is just a global variable.
- It can be reassigned.

✓ Output → `123`

### In modern JS (ES5 strict mode / ES6+):

- `undefined` is read-only and non-writable.
- Attempting to overwrite has no effect.

✓ Output → `undefined`

---

## ✓ Final Answers

1. Array trick:



```
javascript
```

```
2
```

```
undefined
```

```
undefined
```

(but note: index `0` exists, index `1` is a hole)

## 2. JSON trick:

```
json
```

```
{"b":null}
```

## 3. Global trick:

```
javascript
```

```
123 // old non-strict
```

```
undefined // modern strict
```

---

### ⚡ Interview Tip:

If asked “Is `undefined` a keyword in JS?” → Answer:

No, it’s a **global property**. It only became effectively read-only from ES5 strict mode onward.

---

👉 Do you want me to **move to the next primitive**: `null` now, or would you like me to show `undefined` **in function parameter defaults and destructuring** first (another hidden pitfall)?