


CHAPTER 11 EXERCISES & EXECUTABLES

11.2.1 Exercises

1. Create one plot on the fuel economy data with customized title, subtitle, caption, x, y, and color labels.




2. Recreate the following plot using the fuel economy data. Note that both the colors and shapes of points vary by type of drive train.




```

358 ggplot(mpg, aes(x = cty, y = hwy, color = drv, shape = drv)) +
359   geom_point() +
360   labs(
361     title = "City vs. Highway MPG by Drive Type",
362     subtitle = "Different shapes and colors represent drive types",
363     x = "City MPG",
364     y = "Highway MPG",
365     color = "Type of Drive Train",
366     shape = "Type of Drive Train",
367     caption = "Data source: fueleconomy.gov"
368   )
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

```




3. Take an exploratory graphic that you've created in the last month, and add informative titles to make it easier for others to understand.



11.3.1 Exercises

1. Use `geom_text()` with infinite positions to place text at the four corners of the plot.



2. Use `annotate()` to add a point geom in the middle of your last plot without having to create a tibble. Customize the shape, size, or color of the point.

```
- ggplot(mpg, aes(x = displ, y = hwy)) +  
-   geom_point() +  
-   annotate("point", x = 4, y = 30, color = "red", size = 4, shape = 17) +  
-   labs(  
-     title = "Fuel Efficiency vs. Engine Size",  
-     subtitle = "Sports cars tend to have higher efficiency despite larger engines",  
-     x = "Engine Displacement (L)",  
-     y = "Highway Fuel Economy (mpg)",  
-     caption = "Data source: fueleconomy.gov"  
-   )
```

3. How do labels with `geom_text()` interact with faceting? How can you add a label to a single facet? How can you put a different label in each facet? (Hint: Think about the dataset that is being passed to `geom_text()`.)

- `geom_text()` works within facets by repeating the same label in each facet when applied to the whole dataset.
- To add a label to a single facet, create a smaller dataset that includes the label and map it only to the relevant facet using `facet_*()` settings.
- To put different labels in each facet, create a data frame with the labels mapped to the facet variable.

4. What arguments to `geom_label()` control the appearance of the background box?

- The following `geom_label()` arguments control the background box appearance:
 - **fill** – Sets the background color of the label.
 - **color** – Sets the border and text color.
 - **size** – Adjusts the text size.
 - **label.size** – Sets the size of the label's border.
 - **label.padding** – Adjusts the padding between text and the border.
 - **label.r** – Sets the label's corner radius for rounded edges.

5. What are the four arguments to `arrow()`? How do they work? Create a series of plots that demonstrate the most important options.

- The four main arguments to `arrow()` are:

1. **angle** – Sets the angle of the arrowhead in degrees.
2. **length** – Defines the length of the arrowhead (using `unit()` for measurement).
3. **ends** – Specifies where the arrowhead appears ("last", "first", or "both").
4. **type** – Sets the type of arrow ("open", "closed", or "both").

- Example plot - `ggplot(mpg, aes(x = displ, y = hwy)) +`
- `geom_point() +`
- `annotate("segment", x = 2, xend = 4, y = 20, yend = 30,`
- `arrow = arrow(angle = 30, length = unit(0.2, "inches"), ends = "last", type =`
`"closed"))`

11.4.6 Exercises

1. Why doesn't the following code override the default scale?

```
df <- tibble(  
  x = rnorm(10000),  
  y = rnorm(10000)  
)
```

```
ggplot(df, aes(x, y)) +  
  geom_hex() +  
  scale_color_gradient(low = "white", high = "red") +  
  coord_fixed()
```


- The code fails because `geom_hex()` uses fill, not color, for the hexagons. The `scale_color_gradient()` function adjusts the color aesthetic, not the fill aesthetic. To fix this, we can use `scale_fill_gradient()` instead.
2. What is the first argument to every scale? How does it compare to `labs()`?
 - The first argument to every `scale_*`() function specifies which **aesthetic** (like color, fill, x, or y) the scale applies to. For example, `scale_color_gradient()` modifies the color aesthetic, while `scale_x_continuous()` modifies the x-axis.
 3. Change the display of the presidential terms by:
 1. Combining the two variants that customize colors and x axis breaks.
 2. Improving the display of the y axis.
 3. Labelling each term with the name of the president.
 4. Adding informative plot labels.
 5. Placing breaks every 4 years (this is trickier than it seems!).
 - To create a plot of presidential terms with improved display and labels, you need to:
 1. **Combine color and x-axis customization** using `scale_color_manual()` and `scale_x_continuous()` for breaks.
 2. **Improve y-axis display** by adjusting limits or labels with `scale_y_continuous()`.
 3. **Label each term** using `geom_text()` or `annotate()`.
 4. **Add informative plot labels** using `labs()`.
 5. **Set breaks every 4 years** by adjusting the breaks argument in `scale_x_continuous()`.
 4. First, create the following plot. Then, modify the code using `override.aes` to make the legend easier to see.

```
ggplot(diamonds, aes(x = carat, y = price)) +  
  geom_point(aes(color = cut), alpha = 1/20)
```


- `ggplot(diamonds, aes(x = carat, y = price)) +`
- `geom_point(aes(color = cut), alpha = 1/20) +`
- `guides(color = guide_legend(override.aes = list(alpha = 1, size = 3)))`

11.5.1 Exercises

1. Pick a theme offered by the `ggthemes` package and apply it to the last plot you made.



2. Make the axis labels of your plot blue and bolded.



11.6.1 Exercises

1. What happens if you omit the parentheses in the following plot layout. Can you explain why this happens?

```
p1 <- ggplot(mpg, aes(x = displ, y = hwy)) +  
  geom_point() +  
  labs(title = "Plot 1")
```

```
p2 <- ggplot(mpg, aes(x = drv, y = hwy)) +  
  geom_boxplot() +  
  labs(title = "Plot 2")
```

```
p3 <- ggplot(mpg, aes(x = cty, y = hwy)) +  
  geom_point() +  
  labs(title = "Plot 3")
```

`(p1 | p2) / p3`

- If you omit the parentheses in `(p1 | p2) / p3`, R will interpret it as `p1 | (p2 / p3)`, which is not a valid combination of plots because `|` and `/` are operators for arranging plots from the **patchwork** package. Parentheses control the order of operations, ensuring that `p1 | p2` is processed first as a row, and then combined vertically with `p3`.

- Using the three plots from the previous exercise, recreate the following patchwork.

Fig. A:




Fig. B:





Fig. C:



- If you omit the parentheses, R processes the plot combination from left to right. The operator `|` has higher precedence than `/`, so `p1 | p2` is combined first into a row layout. The `/` operator then tries to place `p3` below the result. Since `p3` is not aligned with `p1 | p2` in terms of dimensions, it can cause an error or incorrect layout. Adding parentheses ensures that the combination order is correctly defined.

Executables

#Chapter 11 Communication.....

#11.1.1 Prerequisites

```
library(tidyverse)
library(scales)
library(ggrepel)
library(patchwork)
```

#11.2 Labels

```
ggplot(mpg, aes(x = displ, y = hwy)) +
  geom_point(aes(color = class)) +
  geom_smooth(se = FALSE) +
  labs(
    x = "Engine displacement (L)",
    y = "Highway fuel economy (mpg)",
    color = "Car type",
    title = "Fuel efficiency generally decreases with engine size",
    subtitle = "Two seaters (sports cars) are an exception because of their light weight",
    caption = "Data from fueleconomy.gov"
  )
```

```
df <- tibble(
  x = 1:10,
  y = cumsum(x^2)
)
```

```
ggplot(df, aes(x, y)) +
  geom_point() +
  labs(
    x = quote(x[i]),
    y = quote(sum(x[i] ^ 2, i == 1, n))
  )
```

#11.3 Annotations

```
label_info <- mpg |>
  group_by(drv) |>
  arrange(desc(displ)) |>
  slice_head(n = 1) |>
  mutate(
    drive_type = case_when(
```

```

    drv == "f" ~ "front-wheel drive",
    drv == "r" ~ "rear-wheel drive",
    drv == "4" ~ "4-wheel drive"
  )
) |>
select(displ, hwy, drv, drive_type)

```

```

ggplot(mpg, aes(x = displ, y = hwy, color = drv)) +
  geom_point(alpha = 0.3) +
  geom_smooth(se = FALSE) +
  geom_text(
    data = label_info,
    aes(x = displ, y = hwy, label = drive_type),
    fontface = "bold", size = 5, hjust = "right", vjust = "bottom"
  ) +
  theme(legend.position = "none")

```

```

potential_outliers <- mpg |>
  filter(hwy > 40 | (hwy > 20 & displ > 5))

```

```

ggplot(mpg, aes(x = displ, y = hwy)) +
  geom_point() +
  geom_text_repel(data = potential_outliers, aes(label = model)) +
  geom_point(data = potential_outliers, color = "red") +
  geom_point(
    data = potential_outliers,
    color = "red", size = 3, shape = "circle open"
  )

```

```

trend_text <- "Larger engine sizes tend to have lower fuel economy." |>
  str_wrap(width = 30)
trend_text

```

```

ggplot(mpg, aes(x = displ, y = hwy)) +
  geom_point() +
  annotate(
    geom = "label", x = 3.5, y = 38,
    label = trend_text,
    hjust = "left", color = "red"
  ) +

```

```

annotate(
  geom = "segment",
  x = 3, y = 35, xend = 5, yend = 25, color = "red",
  arrow = arrow(type = "closed")
)

```

#11.4 Scales

```

ggplot(mpg, aes(x = displ, y = hwy)) +
  geom_point(aes(color = class))

```

```

ggplot(mpg, aes(x = displ, y = hwy)) +
  geom_point(aes(color = class)) +
  scale_x_continuous() +
  scale_y_continuous() +
  scale_color_discrete()

```

#11.4.2 Axis ticks and legend keys

```

ggplot(mpg, aes(x = displ, y = hwy, color = drv)) +
  geom_point() +
  scale_y_continuous(breaks = seq(15, 40, by = 5))

```

```

ggplot(mpg, aes(x = displ, y = hwy, color = drv)) +
  geom_point() +
  scale_x_continuous(labels = NULL) +
  scale_y_continuous(labels = NULL) +
  scale_color_discrete(labels = c("4" = "4-wheel", "f" = "front", "r" = "rear"))

```

Left

```

ggplot(diamonds, aes(x = price, y = cut)) +
  geom_boxplot(alpha = 0.05) +
  scale_x_continuous(labels = label_dollar())

```

Right

```

ggplot(diamonds, aes(x = price, y = cut)) +
  geom_boxplot(alpha = 0.05) +
  scale_x_continuous(
    labels = label_dollar(scale = 1/1000, suffix = "K"),
    breaks = seq(1000, 19000, by = 6000)
  )

```

)

```
ggplot(diamonds, aes(x = cut, fill = clarity)) +  
  geom_bar(position = "fill") +  
  scale_y_continuous(name = "Percentage", labels = label_percent())
```

```
presidential |>  
  mutate(id = 33 + row_number()) |>  
  ggplot(aes(x = start, y = id)) +  
  geom_point() +  
  geom_segment(aes(xend = end, yend = id)) +  
  scale_x_date(name = NULL, breaks = presidential$start, date_labels = "%y")
```

#11.4.3 Legend layout

```
base <- ggplot(mpg, aes(x = displ, y = hwy)) +  
  geom_point(aes(color = class))  
  
base + theme(legend.position = "right") # the default  
base + theme(legend.position = "left")  
base +  
  theme(legend.position = "top") +  
  guides(color = guide_legend(nrow = 3))  
base +  
  theme(legend.position = "bottom") +  
  guides(color = guide_legend(nrow = 3))
```

```
ggplot(mpg, aes(x = displ, y = hwy)) +  
  geom_point(aes(color = class)) +  
  geom_smooth(se = FALSE) +  
  theme(legend.position = "bottom") +  
  guides(color = guide_legend(nrow = 2, override.aes = list(size = 4)))  
#> `geom_smooth()` using method = 'loess' and formula = 'y ~ x'
```

#11.4.4 Replacing a scale

```
# Left  
ggplot(diamonds, aes(x = carat, y = price)) +  
  geom_bin2d()
```

```

# Right
ggplot(diamonds, aes(x = log10(carat), y = log10(price))) +
  geom_bin2d()

ggplot(diamonds, aes(x = carat, y = price)) +
  geom_bin2d() +
  scale_x_log10() +
  scale_y_log10()

ggplot(mpg, aes(x = displ, y = hwy)) +
  geom_point(aes(color = drv))

ggplot(mpg, aes(x = displ, y = hwy)) +
  geom_point(aes(color = drv)) +
  scale_color_brewer(palette = "Set1")

ggplot(mpg, aes(x = displ, y = hwy)) +
  geom_point(aes(color = drv, shape = drv)) +
  scale_color_brewer(palette = "Set1")

presidential |>
  mutate(id = 33 + row_number()) |>
  ggplot(aes(x = start, y = id, color = party)) +
  geom_point() +
  geom_segment(aes(xend = end, yend = id)) +
  scale_color_manual(values = c(Republican = "#E81B23", Democratic = "#00AEF3"))

df <- tibble(
  x = rnorm(10000),
  y = rnorm(10000)
)

ggplot(df, aes(x, y)) +
  geom_hex() +
  coord_fixed() +
  labs(title = "Default, continuous", x = NULL, y = NULL)

ggplot(df, aes(x, y)) +
  geom_hex() +
  coord_fixed() +

```

```
scale_fill_viridis_c() +  
labs(title = "Viridis, continuous", x = NULL, y = NULL)
```

```
ggplot(df, aes(x, y)) +  
  geom_hex() +  
  coord_fixed() +  
  scale_fill_viridis_b() +  
  labs(title = "Viridis, binned", x = NULL, y = NULL)
```

#11.4.5 Zooming

Left

```
ggplot(mpg, aes(x = displ, y = hwy)) +  
  geom_point(aes(color = drv)) +  
  geom_smooth()
```

Right

```
mpg |>  
  filter(displ >= 5 & displ <= 6 & hwy >= 10 & hwy <= 25) |>  
  ggplot(aes(x = displ, y = hwy)) +  
  geom_point(aes(color = drv)) +  
  geom_smooth()
```

Left

```
ggplot(mpg, aes(x = displ, y = hwy)) +  
  geom_point(aes(color = drv)) +  
  geom_smooth() +  
  scale_x_continuous(limits = c(5, 6)) +  
  scale_y_continuous(limits = c(10, 25))
```

Right

```
ggplot(mpg, aes(x = displ, y = hwy)) +  
  geom_point(aes(color = drv)) +  
  geom_smooth() +  
  coord_cartesian(xlim = c(5, 6), ylim = c(10, 25))
```

```
suv <- mpg |> filter(class == "suv")  
compact <- mpg |> filter(class == "compact")
```

Left

```
ggplot(suv, aes(x = displ, y = hwy, color = drv)) +  
  geom_point()
```

```
# Right
```

```
ggplot(compact, aes(x = displ, y = hwy, color = drv)) +  
  geom_point()
```

```
x_scale <- scale_x_continuous(limits = range(mpg$displ))  
y_scale <- scale_y_continuous(limits = range(mpg$hwy))  
col_scale <- scale_color_discrete(limits = unique(mpg$drv))
```

```
# Left
```

```
ggplot(suv, aes(x = displ, y = hwy, color = drv)) +  
  geom_point() +  
  x_scale +  
  y_scale +  
  col_scale
```

```
# Right
```

```
ggplot(compact, aes(x = displ, y = hwy, color = drv)) +  
  geom_point() +  
  x_scale +  
  y_scale +  
  col_scale
```

```
#11.5 Themes
```

```
ggplot(mpg, aes(x = displ, y = hwy)) +  
  geom_point(aes(color = class)) +  
  geom_smooth(se = FALSE) +  
  theme_bw()
```

```
ggplot(mpg, aes(x = displ, y = hwy, color = drv)) +  
  geom_point() +  
  labs(  
    title = "Larger engine sizes tend to have lower fuel economy",  
    caption = "Source: https://fueleconomy.gov."  
  ) +  
  theme(  
    legend.position = c(0.6, 0.7),
```



```

    legend.direction = "horizontal",
    legend.box.background = element_rect(color = "black"),
    plot.title = element_text(face = "bold"),
    plot.title.position = "plot",
    plot.caption.position = "plot",
    plot.caption = element_text(hjust = 0)
  )
#> Warning: A numeric `legend.position` argument in `theme()` was deprecated in ggplot2
#> 3.5.0.
#> i Please use the `legend.position.inside` argument of `theme()` instead.

```

#11.6 Layout

```

p1 <- ggplot(mpg, aes(x = displ, y = hwy)) +
  geom_point() +
  labs(title = "Plot 1")
p2 <- ggplot(mpg, aes(x = drv, y = hwy)) +
  geom_boxplot() +
  labs(title = "Plot 2")
p1 + p2

p3 <- ggplot(mpg, aes(x = cty, y = hwy)) +
  geom_point() +
  labs(title = "Plot 3")
(p1 | p3) / p2

p1 <- ggplot(mpg, aes(x = drv, y = cty, color = drv)) +
  geom_boxplot(show.legend = FALSE) +
  labs(title = "Plot 1")

p2 <- ggplot(mpg, aes(x = drv, y = hwy, color = drv)) +
  geom_boxplot(show.legend = FALSE) +
  labs(title = "Plot 2")

p3 <- ggplot(mpg, aes(x = cty, color = drv, fill = drv)) +
  geom_density(alpha = 0.5) +
  labs(title = "Plot 3")

p4 <- ggplot(mpg, aes(x = hwy, color = drv, fill = drv)) +

```

```
geom_density(alpha = 0.5) +  
labs(title = "Plot 4")
```

```
p5 <- ggplot(mpg, aes(x = cty, y = hwy, color = drv)) +  
  geom_point(show.legend = FALSE) +  
  facet_wrap(~drv) +  
  labs(title = "Plot 5")
```

```
(guide_area() / (p1 + p2) / (p3 + p4) / p5) +  
  plot_annotation(  
    title = "City and highway mileage for cars with different drive trains",  
    caption = "Source: https://fuelconomy.gov."  
  ) +  
  plot_layout(  
    guides = "collect",  
    heights = c(1, 3, 2, 4)  
  ) &  
  theme(legend.position = "top")
```

```
library(ggplot2)
```

```
ggplot(mpg, aes(x = displ, y = hwy, color = class)) +  
  geom_point() +  
  geom_smooth(se = FALSE) +  
  labs(  
    title = "Fuel Efficiency vs. Engine Size",  
    subtitle = "Sports cars tend to have higher efficiency despite larger engines",  
    x = "Engine Displacement (L)",  
    y = "Highway Fuel Economy (mpg)",  
    color = "Car Type",  
    caption = "Data source: fuelconomy.gov"  
  )
```

```
ggplot(mpg, aes(x = cty, y = hwy, color = drv, shape = drv)) +  
  geom_point() +  
  labs(  
    title = "City vs. Highway MPG by Drive Type",  
    subtitle = "Different shapes and colors represent drive types",
```

```

x = "City MPG",
y = "Highway MPG",
color = "Type of Drive Train",
shape = "Type of Drive Train",
caption = "Data source: fueleconomy.gov"
)

```

```

ggplot(mpg, aes(x = displ, y = hwy)) +
  geom_point() +
  labs(
    title = "Main Title Explaining the Plot's Insight",
    subtitle = "Additional details to give context",
    x = "X-axis Label",
    y = "Y-axis Label",
    caption = "Data source: Your source"
  )

```

```

ggplot(mpg, aes(x = displ, y = hwy)) +
  geom_point() +
  annotate("text", x = 2, y = 45, label = "Top Left", hjust = 0) +
  annotate("text", x = 6, y = 45, label = "Top Right", hjust = 1) +
  annotate("text", x = 2, y = 15, label = "Bottom Left", hjust = 0) +
  annotate("text", x = 6, y = 15, label = "Bottom Right", hjust = 1) +
  labs(
    title = "Fuel Efficiency vs. Engine Size",
    subtitle = "Sports cars tend to have higher efficiency despite larger engines",
    x = "Engine Displacement (L)",
    y = "Highway Fuel Economy (mpg)",
    caption = "Data source: fueleconomy.gov"
  )

```

```

ggplot(diamonds, aes(x = carat, y = price)) +
  geom_point(aes(color = cut), alpha = 1/20) +
  guides(color = guide_legend(override.aes = list(alpha = 1, size = 3))) +
  theme_minimal()

```

```

ggplot(diamonds, aes(x = carat, y = price)) +
  geom_point(aes(color = cut), alpha = 1/20) +
  guides(color = guide_legend(override.aes = list(alpha = 1, size = 3))) +
  theme(

```

```
axis.title.x = element_text(color = "blue", face = "bold"),  
axis.title.y = element_text(color = "blue", face = "bold")  
)
```