

VPrivCal

A Brief Three-Option Preference-Elicitation and Awareness-Confirmation Method for User-Aligned Privacy Reminders in Vision-Language Assistants

Updated full research plan for egocentric VLM scenarios

Decision / research question
Can a brief three-option calibration improve immediate acceptance and privacy-cue awareness for standardized VLM reminders under controlled expert-verified detections?

Method at a glance

Element	Current design
Overall method	One rapid calibration method with two components: VPrivCal-Q10 and VPrivCal-Probe.
Component 1	VPrivCal-Q10 initializes category and reminder-policy defaults.
Component 2	Three egocentric scenes; participants point first, then review every verified category and choose one of three reminder-trigger thresholds.
Output	A transparent user-specific trigger policy with binary reminder output.
Primary evaluation	Generic versus Q10-only versus full VPrivCal on identical expert-verified held-out cues.
Primary outcomes	Immediate acceptance, privacy-cue awareness, binary alignment, false reminders, missed reminders, and burden.

Version 7 | July 2026 | Three-option trigger and controlled-evaluation edition

ID	Research question / hypothesis
RQ4	Does Probe improve trigger alignment beyond Q10 alone across categories and contexts?
H1	Full VPrivCal will produce higher cue-level acceptance than the generic policy.
H2	Full VPrivCal will preserve or improve cue awareness while reducing unwanted reminders.
H3	Trigger alignment will be higher when held-out exposure level matches the participant's selected threshold.

4. VPrivCal-Q10: rapid preference initialization

Q1-Q6 retain the six high-level visual privacy categories used in the project. To reduce repetition and leading wording, the system presents one shared question and response scale, then shows the six categories one by one.

Shared question for Q1-Q6

When this type of information appears, when should the assistant show a privacy reminder?

1 Do not show reminders for this category | 2 Show reminders only when identifying or sensitive details are exposed | 3 Show reminders whenever this verified category is present

Item	Category	Examples	Policy parameter
Q1	Biometric data	Faces, fingerprints, and other distinctive body features that may identify a person.	biometric_data_action
Q2	Children images	Children, school events, playgrounds, and child-related activities.	children_images_action
Q3	Personally identifiable information (PII)	Financial or medical data; names, passports, email addresses, phone numbers, GPS, license plates, and other identifiers.	pii_action
Q4	Legal sensitivity information	Nudity or explicit imagery; violent or unlawful acts; criminal acts; weapons or other high-risk items.	legal_sensitivity_action
Q5	Personal life	Home interiors, personal items, location context, landmarks, routines, relationships, and activities.	personal_life_action
Q6	Background individuals	Passersby, bystanders, coworkers, patients, patrons, and other people incidentally captured.	background_individuals_action

4.1 Cross-cutting reminder-policy questions

Item	Dimension	Direct policy question	Parameter
Q7	Inferred risks	When an expert-verified cue supports a sensitive inference, should the assistant show a reminder?	inference_reminder_level

Scene	Scenario context	Available high-level categories	Representative evidence
1. Private - indoor family party	A first-person view during a family birthday gathering inside a home.	Biometric Data; Children Images; PII; Legal Sensitivity Information; Personal Life.	Family faces, an identifiable child, a school report card, a wall-mounted rifle, family photographs, toys, and home/family context.
2. Public - busy cafe	A first-person view while using a laptop and writing notes in a crowded cafe.	Biometric Data; Children Images; PII; Background Individuals.	Patron faces, a child, visible laptop email, phone contact details, a receipt, and incidental cafe bystanders.
3. Semi-public - hospital waiting area	A first-person view while holding medical documents in a hospital waiting area.	Biometric Data; PII; Background Individuals.	Patient and staff faces, an intake form, prescription label, patient wristband, and waiting-room bystanders.

5.2 Point-first, reveal-second interaction

The image is initially shown without overlays. A participant may click multiple regions. The interface converts each click to normalized image coordinates, matches it against the detection file, selects the smallest valid overlapping region, and proposes the detection's primary category. Participants can change the category, delete a selection, or draw a manual region when no detection matches. Only after the participant submits this first pass does the interface reveal the scene's complete category list and category-linked evidence. This avoids using the VLM detections to prime the initial search while still ensuring that every available category is evaluated.

Phase	Participant view	System behavior	Recorded signal
A. Unprompted pointing	Clean image without boxes or category labels.	Hit-test clicks against normalized detection boxes; propose a category but allow correction.	Clicked coordinates, matched detection IDs, spontaneous category selections, corrections, and unmatched manual regions.
B. Category-complete review	All predefined categories present in the scene, one card at a time.	Highlight all evidence linked to the active category only after the participant opens the card.	Awareness status and preferred three-option trigger for each category-image pair.
C. Policy update	Concise summary of category defaults and contextual corrections.	Combine Q10 and Probe trigger levels; resolve against the expert-confirmed exposure label.	Trigger level and resulting binary reminder decision.
D. Export	Completion summary.	Save a de-identified JSON record for later analysis.	Timing, click mapping, category corrections, awareness, actions, and profile confirmation.

5.3 Two questions per category-image pair

Question A: awareness status

Before the content supporting this category was highlighted, which best describes your experience?

- 1 Already noticed it and considered the privacy implication.
- 2 Noticed it but had not considered the privacy implication.
- 3 Had not noticed it, or did not realize the VLM could detect or infer it.
- 4 I do not consider it a privacy concern in this situation.

Trigger level	Participant label	Deterministic runtime behavior
1	Sensitive-detail exposure only	SHOW_REMINDER only for SENSITIVE_DETAIL_EXPOSED; otherwise NO_REMINDER.
2	Whenever verified present	SHOW_REMINDER for either expert-confirmed exposure level.

Recommended proof-of-concept update rule: initialize each category from VPrivCal-Q10; treat each Probe category-image response as one contextual observation; combine the prior and contextual responses using a transparent weighted median or rounded weighted mean. The Probe response may override the questionnaire for the corresponding category, while retaining the scene type as contextual metadata.

Recommended conservative guardrail: apply any approved safety floor only after the participant trigger is resolved, record every override, and review whether floors erase meaningful three-option personalization.

7. Held-out egocentric video evaluation

Held-out comparison under verified detections

All conditions receive the same locked cue labels and the same reminder presentation.




Figure 3. Policy conditions tested on held-out video cues.

Static calibration and dynamic evaluation remain intentionally different. Held-out clips use locked expert-verified detections and the same reminder presentation in every condition. Include both exposure labels when feasible so the middle trigger can be evaluated.

Design element	Recommendation
Participants	N = 80-120 for the main controlled study; use a smaller N = 12-20 usability pilot first.
Design	Within-subject comparison of generic, Q10-only, and full VPrivCal; clip-policy assignment counterbalanced.
Materials	10-12 short clips with locked expert-verified cues; include both exposure levels where feasible.
Policies	Generic baseline, VPrivCal-Q10 only, and full VPrivCal.
Cue balance	Balance categories and PRESENCE_ONLY versus SENSITIVE_DETAIL_EXPOSED labels; avoid cells too small to interpret.
Controls	Exclude unresolved or disputed detections from the main effectiveness comparison.
Model output	Use one fixed VLM; two experts independently verify category and exposure level before locking the cue JSON.

7.1 Questions participants answer for each held-out cue

Construct	Question	Response
Expert verification gate	Do both experts confirm the cue and category?	Agree / adjudicated / excluded
Exposure label	Does the cue merely show category presence or expose identifying/sensitive details?	PRESENCE_ONLY / SENSITIVE_DETAIL_EXPOSED
Cue awareness	Before the reminder, had you noticed the privacy-relevant content?	Yes / partly / no
Preferred decision	Should the assistant have shown a reminder for this cue?	No reminder / show reminder
Decision acceptance	How acceptable was the assistant's reminder decision?	1 Not at all - 5 Completely

Why detector verification is separate

The controlled study estimates the effect of VPrivCal under a locked verified cue set. The VLM candidate error rate and expert agreement must be reported separately from participant acceptance and awareness.

8. Outcomes and metrics

Metric	Operational definition	Role
Immediate acceptance	Mean cue-level acceptance and proportion rated 4-5.	Primary
Privacy-cue awareness	Unaided or pre-reminder awareness of the verified cue.	Primary
Binary decision alignment	System reminder decision equals the participant's preferred decision.	Primary
False-reminder rate	System reminds when the participant prefers no reminder.	Burden guardrail
Missed-reminder rate	System does not remind when the participant prefers a reminder.	Privacy guardrail
Exposure-stratified effect	Outcomes reported separately for both expert-confirmed exposure levels.	Construct check
Probe awareness profile	Already aware / interpretive gap / perceptual-capability gap / rejected cue.	Descriptive
Reminder frequency	Number and proportion of verified cues that trigger the standard reminder.	Dose measure
Calibration burden	Completion time, skipped items, changes, and perceived effort.	Feasibility
User-friendliness	Relevance, number/timing, interruption, control, and willingness to use.	Secondary

8.1 Post-policy user-friendliness items

- The reminders focused on privacy risks that were relevant to me.

- The number of reminders was appropriate.
- The reminders appeared at appropriate moments.
- The reminders interrupted the main task more than necessary.
- The system made me feel sufficiently protected.
- I felt in control of how the assistant handled privacy risks.
- I would use this reminder configuration in a real egocentric assistant.

Use a 7-point agreement scale for overall policy experience, while retaining the cue-level 1-5 acceptance item. Analyze acceptance, awareness, burden, protection/control, and adoption separately unless psychometric evidence supports a composite.

9. Statistical analysis

- Exact alignment: logistic mixed-effects model with policy condition as a fixed effect and participant, clip, and cue as random intercepts.
- Binary decision alignment: mixed-effects logistic model or participant-level paired comparison, with exposure level included as a prespecified factor.
- Over-reminding and under-protection: mixed-effects logistic models; pre-register full VPrivCal versus generic as the primary contrast.
- Subjective scales: paired or mixed-effects comparisons across policies; report confidence intervals and effect sizes.
- Category transfer: interactions between condition and privacy category, expert-confirmed exposure level, inference status, and temporal dependence.
- Robustness: exclude invalid cues, exclude unsure responses, vary severity threshold, and repeat analyses with weighted under-protection costs.

10. Pilot gates and expert screening criteria

Area	Minimum gate before main study
Q10 comprehension	At least 80% of cognitive-interview participants paraphrase each item consistently.
Q10 timing	Median $\leq$ 3 minutes; fewer than 5% skipped core items.
Probe timing	Median $\leq$ 5 minutes for the complete pointing and category-review phase; median total calibration time $\leq$ 7 minutes. Re-estimate after the usability pilot rather than assuming a three-minute total.
Stimulus distinctiveness	Experts and users distinguish the private, public, and semi-public settings and understand why the same category may appear in multiple scenes.
Category and evidence validity	At least 80% accept each listed category as present in its scene and each linked detection as valid supporting evidence; disputed items are revised or removed.
Pointing and mapping usability	At least 90% of intended selections are matched to a detection or successfully corrected through the manual-region/category controls; detections remain hidden before submission.
Safety	No unresolved critical issue involving bystanders, children, false sensitive inferences, or severe under-protection.

11. Ethics, data management, and limitations

- Use only synthetic or fully consented egocentric stimuli; never expose real identifiers or real sensitive records.
- Do not ask the model to infer actual protected traits about identifiable real people. Use synthetic cues and categorical descriptions.
- Allow participants to skip high-risk content and explain that the calibration cannot guarantee privacy.
- Store only de-identified responses; keep image/video files separate from participant identifiers.
- The three-scene Probe provides retrospective and interaction-based awareness evidence, but it still cannot establish spontaneous awareness during unconstrained natural use.

- The initial results generalize to egocentric assistance, not automatically to uploaded photos, screenshots, or social-media images.

12. Recommended execution sequence

Phase	Participants	Purpose
Expert screen	6-10 experts	Review three-option wording, exposure codebook, cue agreement, safety floors, and study feasibility.
Cognitive interviews	6-10 target users	Check interpretation of Q10, probe responses, and policy labels.
Usability pilot	12-20 users	Measure timing, confusion, scene salience, and workflow failures.
Main evaluation	80-120 users	Compare generic, Q10-only, and full VPrivCal on held-out videos.
External validation	Optional	Repeat on a new video set, user population, or VLM.

13. References

Tsaprazlis, E., Feng, T., Ramakrishna, A., Gupta, R., & Narayanan, S. (2025). Assessing Visual Privacy Risks in Multimodal AI: A Novel Taxonomy-Grounded Evaluation of Vision-Language Models. *arXiv:2509.23827*.

Orekondy, T., Schiele, B., & Fritz, M. (2017). Towards a Visual Privacy Advisor: Understanding and Predicting Privacy Risks in Images. *ICCV*.

Tomekce, B., Vero, M., Staab, R., & Vechev, M. (2025). Private Attribute Inference from Images with Vision-Language Models. *NeurIPS*.

Amershi, S., et al. (2019). Guidelines for Human-AI Interaction. *CHI*.

Terwee, C. B., et al. (2018). COSMIN methodology for evaluating content validity. *Quality of Life Research*, 27, 1159-1170.

Polit, D. F., Beck, C. T., & Owen, S. V. (2007). Is the CVI an acceptable indicator of content validity? *Research in Nursing & Health*, 30(4), 459-467.