Add LPN to Order Configuration

Last updated: 07/26/2024

- Overview
  - Configuration Overview
    - Add LPN to Order Strategy
    - Add LPN to Order Criteria

Overview

This document describes the configuration required to perform the 'Add LPN to Order' transaction. The following UI screens will be explained in the subsequent sections :

1. Add LPN to Order Strategy
2. Add LPN to Order Criteria

Configuration Overview

Add LPN to Order Strategy

The Add LPN to Order strategy defines the business configuration for the Add LPN to Order process. This holds the parameters that are required to be configured at a strategic level and can be linked to one or more Add LPN to Order criteria depending on the rules configured.

Field Name	Description
Add LPN to Order Strategy ID	A unique identifier for the Add LPN to Order Strategy Name.
Description	This field holds the description of the Add LPN to Order strategy.

Add LPN to Order Criteria

The Add LPN to Order Criteria entity defines behavior of the Add LPN to Order transaction through a list of attributes. These parameters determine the process and control the screen flow. Additionally, the user can configure one or more Add LPN to Order criteria which can be distinguished by its rule definition.

Field Name	Description
Add LPN to Order Criteria ID	Unique Identifier of the Add LPN to Order Criteria Name
Do you want to add Pallet to an Order?	When this is set as True, the system allows adding pallet to an order
What should be the Pallet creation mode?	This determines how to create oLPN ID • Use IB Pallet as OB Pallet • User-entered • System-generated
Should the system make use of existing order lines?	• Always create new order lines • Use existing order lines only and not allowing adding iLPN if order line does not exist • Use existing order lines if a match is found and create new lines as needed

Copyright © 2026 Manhattan Associates, Inc.

What should be the oLPN creation mode?	This determines how to create oLPN ID • Use iLPN as oLPN • User-entered • System-generated
How should unique attributes be captured?	This parameter determines if fully tracked unique attributes should be transferred from the iLPN to the oLPN as part of Add LPN to Order updates: • Do not capture • Transfer unique attributes from iLPN to oLPN
What should be the non-unique attribute verification mode?	This parameter determines if fully tracked or outbound tracked non-unique attributes should be captured or calculated during Add LPN to Order: • Do not capture • Capture non-unique attributes • Calculate non-unique attributes
Which Labor Activity should the system associate with this transaction?	This indicates the labor activity to be associated with this transaction. **Note**: This is optional and can be set to NULL if labor messages are not required.
Which Print Criteria should the system use to print Labels/Documents?	Print Criteria to determine which labels/documents to print
Should the system invoke Routing for the oLPNs that are packed?	Route/Re-route the oLPNs
Which Outbound Putaway Transaction should the system use if Location determination and/or Putaway of Outbound containers is necessary?	This is to determine consolidation location for packed oLPNs
Which condition code group should be overridden?	This is a list of condition codes which can be overridden.

Note: When 'Should the system make use of existing order lines?' is set to 'Use existing order lines only and not allowing adding iLPN if the order line does not exist' or 'Use existing order lines if a match is found and create new lines as needed', then use the seeded pipeline SEED Ecom Wave Pipeline OR add the below to the pipeline being used.

Copyright © 2026 Manhattan Associates, Inc.

```
  {
    "FromStatus": "2090",
    "ComponentId": "DCORDER",
    "ServiceId": "CubingPipelineRequestService",
    "IntendedDropStatus": "3000",
    "Sequence": 1,
    "ConditionText": null,
    "DropStatus": "3000"
  },
  {
    "FromStatus": "2090",
    "ComponentId": "DCORDER",
    "ServiceId": "PostPlanningExecutionPipelineService",
    "IntendedDropStatus": "7200",
    "Sequence": 1,
    "ConditionText": null,
    "DropStatus": "7200"
  },
  {
    "FromStatus": "2190",
    "ComponentId": "DCORDER",
    "ServiceId": "PostPlanningExecutionPipelineService",
    "IntendedDropStatus": "7100",
    "Sequence": 1,
    "ConditionText": null,
    "DropStatus": "7100"
  },
```

Only the middle section with From Status as 2090 and Drop Status as 7200

```
{
  "FromStatus": "2090",
  "ComponentId": "DCORDER",
  "ServiceId": "CubingPipelineRequestService"
},
{
  "FromStatus": "2090",
  "ComponentId": "DCORDER",
  "ServiceId": "PostPlanningExecutionPipelineService"
},
{
  "FromStatus": "2190",
  "ComponentId": "DCORDER",
  "ServiceId": "PostPlanningExecutionPipelineService"
},
```

Only the middle section with 2090 - PostPlanning*