

## How to Move/Restore DB to New Host and File System using RMAN (Doc ID 1338193.1)

---

### In this Document

[Goal](#)

[Assumptions](#)

[Solution](#)

### [Solution 1 - Concise Steps Without Example Output](#)

[Step 1.1 - Backup the Production Database](#)

[Online Backup](#)

[Offline backup](#)

[Step 1.2 - Transfer Backuppieces to New Host](#)

[Step 1.3 - Restore Database at New Host](#)

### [Solution 2 - Detailed Steps With Example Output](#)

[Step 2.1 - Backup the production database](#)

[Step 2.2 - Transfer the backuppieces to the new host](#)

[Step 2.2.1 This steps are specific to WINDOWS](#)

[Step 2.3 - Restore the controlfile](#)

[Step 2.4 - Catalog the backuppieces if required](#)

[Step 2.5 - Restore the database](#)

[Step 2.6 - Rename the online redo logs](#)

[Step 2.7 - Rename the database](#)

[Step 2.8 - Confirm your tempfiles](#)

[References](#)

---

### APPLIES TO:

---

Oracle Database - Enterprise Edition - Version 9.2.0.6 and later  
Oracle Database Cloud Schema Service - Version N/A and later  
Gen 1 Exadata Cloud at Customer (Oracle Exadata Database Cloud Machine) - Version N/A and later  
Oracle Cloud Infrastructure - Database Service - Version N/A and later  
Oracle Database Cloud Exadata Service - Version N/A and later  
Information in this document applies to any platform.

### GOAL

---

NOTE: In the images and/or the document content below, the user information and environment data used represents fictitious data from the Oracle sample schema(s), Public Documentation delivered with an Oracle database product or other training material. Any similarity to actual environments, actual persons, living or dead, is purely coincidental and not intended in any manner.

**For the purposes of this document, the following fictitious environment is used as an example to describe the procedure:**

Source Database:  
DB\_NAME: PRIM

Copied Database:  
DB\_NAME: TEST

How to relocate a database to a new server

You may need to restore a database to a new server due to the following reasons:

- 1) confirming your disaster recovery strategy
- 2) moving the database to a new server

**NOTE:** If your intention is to clone the database, you should use the RMAN duplicate command. Do not use a restore/recover database to clone your database.

This note will work for all file systems - ASM, OCFS, raw, cooked etc.

The steps can be summarized as:

- 1) take a backup of the database on the existing host
- 2) on the new host, restore the controlfiles, datafiles and tempfiles to the new location
- 3) on the new host, rename the online redo logs
- 4) use NID to change db\_name and dbid

**Important Note:** During the restore and recovery process, do NOT connect to the production database's recovery catalog, even if you are using one to perform the backup. The production database's recovery catalog will get confused if there are multiple databases with the same DBID.

[http://docs.oracle.com/cd/E11882\\_01/backup.112/e10642/rcmadvre.htm#BRADV908](http://docs.oracle.com/cd/E11882_01/backup.112/e10642/rcmadvre.htm#BRADV908)

## Assumptions

- 1) the existing and new hosts are running on the same operating system and RDBMS patchsets. Restoring to a different platform and/or RDBMS patchset is quite complex and will not be addressed in this note.
- 2) all datafiles and tablespaces are onlined and accessible

## SOLUTION

There are two solutions presented in this note as we wanted to give you the options of having either the concise steps and commands in Unix format,

OR

the Windows commands and full example output.

Feel free to jump to whichever section you are most comfortable with.

## Solution 1 - Concise Steps Without Example Output

For users who are familiar with an RMAN restore but just needed the steps to remind themselves

### Step 1.1 - Backup the Production Database

#### Online Backup

When in ARCHIVELOG mode, you can choose to perform either an offline or online backup. For an online backup, you do not need to shutdown the database. You can just backup the database plus all archivelogs whilst the database is up and running:

```
$ . oraenv
ORACLE_SID = [prim] ? PRIM

$ rman target /

RMAN> backup database format '/tmp/db_%U';
RMAN> backup archivelog all format '/tmp/archs_%U';
RMAN> backup current controlfile format '/tmp/control.bks';
RMAN> backup spfile format '/tmp/spfile.bks';
```

#### Offline backup

If the database is running in NOARCHIVELOG mode then it must be restarted in MOUNT mode to take an offline RMAN backup:

```
$ . oraenv
ORACLE_SID = [prim] ? PRIM

$ rman target /

RMAN> shutdown immediate;
RMAN> startup mount;
RMAN> backup database format '/tmp/db_%U';
RMAN> backup current controlfile format '/tmp/control.bks';
RMAN> backup spfile format '/tmp/spfile.bks';
```

### Step 1.2 - Transfer Backuppieces to New Host

Once the backup is completed, transfer the backuppieces across to the new host in the same location using an operating system utility such as cp, scp, ftp etc.

You can certainly place the backuppieces into another location and use the RMAN CATALOG command to tell RMAN about their new location. In Unix you may also consider using symbolic links to the new location. Or use NFS to mount the backuppieces to the new host.

### Step 1.3 - Restore Database at New Host

Once the backuppieces have been transferred to the new host, restore the database at the new host.

### Perform these steps at the new host...

Step 1.3.1) Set the environment to point to the ORACLE\_SID that you are about to restore:

For example:

```
$ . oraenv
ORACLE_SID = [prim] ? PRIM
```

Step 1.3.2) Restore the spfile from the backuppiece:

```
RMAN> startup nomount force;
RMAN> restore spfile from '/tmp/spfile.bks';
RMAN> restore spfile to pfile '/tmp/initnewdb.ora' from '/tmp/spfile.bks';
```

Step 1.3.3) Check the init.ora parameters, and precreate the directories if required. Note that the AUDIT directory must pre-exist before you can NOMOUNT the restored spfile

```
$ grep audit /tmp/initnewdb.ora
*.audit_file_dest='/<path>/admin/PRIM/adump'

$ mkdir -p /<path>/admin/PRIM/adump

SQL> shutdown immediate;
SQL> startup nomount;
SQL> show parameter control_files
SQL> show parameter dump
SQL> show parameter create
SQL> show parameter recovery
```

Or change the parameters to reflect the new directory path if required:  
How to Modify the Content of an SPFILE Parameter File (Doc ID [137483.1](#))

Step 1.3.4) Restore the controlfile from a known backuppiece and mount the database:

```
RMAN> restore controlfile from '/tmp/control.bks';
RMAN> alter database mount;
RMAN> report schema;
```

If the backuppieces are residing in a new location at the new host you'll need to catalog them:

```
RMAN> catalog start with '/<path for backuppiece location>/';
```

Step 1.3.5) Restore the database, using SET NEWNAME to relocate the datafiles and tempfiles to their new locations if required.

a) preview the restore - this will report the backuppieces required for the restore operation. It will not perform the actual restore.

```
RMAN> restore database preview summary;
```

b) If the preview looks valid, then go ahead and perform the actual restore to the new host:

```
RMAN> run {  
# set newname for all datafiles to be mapped to a new path  
# OR use SET NEWNAME FOR DATABASE if you wish to have all files located in the same directory  
# eg. SET NEWNAME FOR DATABASE to '+DATA/inovadg/datafile/%b'  
set newname for datafile 1 to 'new file path and name';  
...  
set newname for tempfile 1 to 'new file path and name';  
restore database;  
switch datafile all;  
switch tempfile all;  
}
```

Step 1.3.6) Confirm that all datafiles have been restored to the new location:

```
RMAN> report schema;
```

### 1.3.7) Recover the database

a) if recovering from an OFFLINE backup, and you do not have further archivelogs to apply from the original host, use recover with NOREDO:

```
RMAN> recover database noredo;
```

b) if the original database is running in archivelog mode and there are subsequent archivelogs generated after the initial backup, you can back up these archivelogs and transfer them to the new host as well.

At the original host:

```
RMAN> backup archivelog all format '/tmp/rest_of_arc_%U.bks;
```

At the new host, catalog this new backuppiece:

```
RMAN> catalog backuppiece '/tmp/rest_of_arc';
```

Now recover the database:

```
RMAN> run {# change the date and time to suit  
SET UNTIL TIME "to_date('01 SEP 2011 12:04:00','DD MON YYYY hh24:mi:ss')";  
recover database;  
}
```

Step 1.3.8) Relocate all the online redo logs if required:

```
SQL> select * from v$logfile;
SQL> alter database rename file '<old redo log path and name>' to '<new redo log path and name>;'
```

Step 1.3.9) Once all files have been renamed, open the database with resetlogs.

a) if the source database had block change tracking, you will need to either precreate the block change tracking directory, or disable and enable it before opening the database:

```
SQL> alter database disable block change tracking;
SQL> alter database enable block change tracking using '<location>';
```

b) now open with resetlogs:

```
RMAN> alter database open resetlogs;
```

Step 1.3.10) confirm the location of your tempfiles, recreating them at the new location if required:

```
SQL> select * from v$tempfile;
SQL> ALTER TABLESPACE TEMP ADD TEMPFILE 'new tempfile path filename' REUSE;
```

Step 1.3.11) If the old database is going to remain up and running on the old server, use NID to rename the DBNAME and DBID of either the old or new database to avoid confusion.

For example:

```
$ nid target=sys/<password> dbname=TEST
```

For further information about NID, see the following note:

How to Change the DBID, DBNAME Using NID Utility in version 10GgR2 onwards (Doc ID [863800.1](#))

---

## Solution 2 - Detailed Steps With Example Output

### Step 2.1 - Backup the production database

```
$rman target / log=backup.log
RMAN>run {
allocate channel t1 type disk;
```

```

allocate channel t2 type disk;
allocate channel t3 type disk;
allocate channel t4 type disk;
backup format '<give location of backup>/%U' filesperset 4 (database);

sql 'alter system archive log current';
backup format '<give location of backup>/%U' filesperset 8 (archivelog all);
backup format '<give location of backup>/%U' current controlfile;
}

```

## Example

### Script

```

rman target / log=backup.log
RMAN>run {
allocate channel t1 type disk;
allocate channel t2 type disk;
allocate channel t3 type disk;
allocate channel t4 type disk;
backup format 'D:\backup\prim\%U' filesperset 4 (database);
backup format 'D:\backup\prim\%U' filesperset 8 (archivelog all);
backup format 'D:\backup\prim\%U' current controlfile;
}

```

### Backup log

Recovery Manager: Release 11.2.0.1.0 - Production on Tue Jan 17 16:21:15 2012

Copyright (c) 1982, 2009, Oracle and/or its affiliates. All rights reserved.

connected to target database: PRIM (DBID=2610619323)

```

RMAN> 2> 3> 4> 5> 6> 7> 8> 9> 10> 11>
using target database control file instead of recovery catalog
allocated channel: t1
channel t1: SID=192 device type=DISK

```

```

allocated channel: t2
channel t2: SID=10 device type=DISK

```

```

allocated channel: t3
channel t3: SID=68 device type=DISK

```

```

allocated channel: t4
channel t4: SID=134 device type=DISK

```

```

Starting backup at 17-JAN-12
channel t1: starting full datafile backup set
channel t1: specifying datafile(s) in backup set
input datafile file number=00001 name=<path>\PRIM\SYSTEM01.DBF
channel t1: starting piece 1 at 17-JAN-12
channel t2: starting full datafile backup set
channel t2: specifying datafile(s) in backup set
input datafile file number=00002 name=<path>\PRIM\SYSAUX01.DBF
channel t2: starting piece 1 at 17-JAN-12
channel t3: starting full datafile backup set

```

channel t3: specifying datafile(s) in backup set  
input datafile file number=00003 name=<path>\PRIM\UNDOTBS01.DBF  
channel t3: starting piece 1 at 17-JAN-12  
channel t4: starting full datafile backup set  
channel t4: specifying datafile(s) in backup set  
input datafile file number=00004 name=<path>\PRIM\USERS01.DBF  
channel t4: starting piece 1 at 17-JAN-12  
channel t3: finished piece 1 at 17-JAN-12  
piece handle=D:\BACKUP\PRIM\0UN10JGO\_1\_1 tag=TAG20120117T162144 comment=NONE  
channel t3: backup set complete, elapsed time: 00:00:01  
channel t4: finished piece 1 at 17-JAN-12  
piece handle=D:\BACKUP\PRIM\0VN10JGP\_1\_1 tag=TAG20120117T162144 comment=NONE  
channel t4: backup set complete, elapsed time: 00:00:01  
channel t1: finished piece 1 at 17-JAN-12  
piece handle=D:\BACKUP\PRIM\0SN10JGO\_1\_1 tag=TAG20120117T162144 comment=NONE  
channel t1: backup set complete, elapsed time: 00:00:26  
channel t2: finished piece 1 at 17-JAN-12  
piece handle=D:\BACKUP\PRIM\0TN10JGO\_1\_1 tag=TAG20120117T162144 comment=NONE  
channel t2: backup set complete, elapsed time: 00:00:26  
Finished backup at 17-JAN-12

Starting Control File and SPFILE Autobackup at 17-JAN-12  
piece handle=<oracle\_home path>\DATABASE\C-2610619323-20120117-03 comment=NONE  
Finished Control File and SPFILE Autobackup at 17-JAN-12

Starting backup at 17-JAN-12  
current log archived  
channel t1: starting archived log backup set  
channel t1: specifying archived log(s) in backup set  
input archived log thread=1 sequence=15 RECID=14 STAMP=772567403  
input archived log thread=1 sequence=16 RECID=15 STAMP=772617742  
channel t1: starting piece 1 at 17-JAN-12  
channel t2: starting archived log backup set  
channel t2: specifying archived log(s) in backup set  
input archived log thread=1 sequence=17 RECID=16 STAMP=772658562  
input archived log thread=1 sequence=18 RECID=17 STAMP=772704521  
input archived log thread=1 sequence=19 RECID=18 STAMP=772710784  
channel t2: starting piece 1 at 17-JAN-12  
channel t3: starting archived log backup set  
channel t3: specifying archived log(s) in backup set  
input archived log thread=1 sequence=20 RECID=19 STAMP=772738880  
input archived log thread=1 sequence=21 RECID=20 STAMP=772790482  
input archived log thread=1 sequence=22 RECID=21 STAMP=772820536  
channel t3: starting piece 1 at 17-JAN-12  
channel t4: starting archived log backup set  
channel t4: specifying archived log(s) in backup set  
input archived log thread=1 sequence=23 RECID=22 STAMP=772820536  
channel t4: starting piece 1 at 17-JAN-12  
channel t4: finished piece 1 at 17-JAN-12  
piece handle=D:\BACKUP\PRIM\14N10JHQ\_1\_1 tag=TAG20120117T162217 comment=NONE  
channel t4: backup set complete, elapsed time: 00:00:01  
channel t1: finished piece 1 at 17-JAN-12  
piece handle=D:\BACKUP\PRIM\11N10JHQ\_1\_1 tag=TAG20120117T162217 comment=NONE  
channel t1: backup set complete, elapsed time: 00:00:07  
channel t2: finished piece 1 at 17-JAN-12  
piece handle=D:\BACKUP\PRIM\12N10JHQ\_1\_1 tag=TAG20120117T162217 comment=NONE  
channel t2: backup set complete, elapsed time: 00:00:08  
channel t3: finished piece 1 at 17-JAN-12  
piece handle=D:\BACKUP\PRIM\13N10JHQ\_1\_1 tag=TAG20120117T162217 comment=NONE  
channel t3: backup set complete, elapsed time: 00:00:08  
Finished backup at 17-JAN-12



Starting Control File and SPFILE Autobackup at 17-JAN-12  
 piece handle= <oracle\_home path>\DATABASE\C-2610619323-20120117-04 comment=NONE  
 Finished Control File and SPFILE Autobackup at 17-JAN-12

Starting backup at 17-JAN-12  
 channel t1: starting full datafile backup set  
 channel t1: specifying datafile(s) in backup set  
 including current control file in backup set  
 channel t1: starting piece 1 at 17-JAN-12  
 channel t1: finished piece 1 at 17-JAN-12  
 piece handle=D:\BACKUP\PRIM\16N10JI7\_1\_1 tag=TAG20120117T162231 comment=NONE <channel t1:  
 backup set complete, elapsed time: 00:00:01  
 Finished backup at 17-JAN-12

Starting Control File and SPFILE Autobackup at 17-JAN-12  
 piece handle= <oracle\_home path>\DATABASE\C-2610619323-20120117-05 comment=NONE  
 Finished Control File and SPFILE Autobackup at 17-JAN-12  
 released channel: t1  
 released channel: t2  
 released channel: t3  
 released channel: t4

## **Step 2.2 - Transfer the backuppieces to the new host**

Transfer the backup pieces from production to the non-production server. Prior to 10g you must locate them in the same directory path. From 10g and onwards we can catalog backuppieces so this is no longer a requirement.

You will also need to bring across the database parameter file.

Henceforth all steps are performed at the new host...

### **Step 2.2.1 This steps are specific to WINDOWS**

- Create an Oracle Password File ( orapwd )
- Create an Initialization Parameter File / or have it copied and adjusted from source database
- Create the Oracle Services (oradim)

#### **1: Create an Oracle Password File**

For full details on how to create a password file please refer to  
 Oracle Database Administrator's Guide.

[http://docs.oracle.com/cd/E11882\\_01/server.112/e25494/dba.htm#ADMIN001](http://docs.oracle.com/cd/E11882_01/server.112/e25494/dba.htm#ADMIN001)

For example: C:\> ORAPWD file=PWD<ORACLE\_SID>.ora password=<password> entries=10

Note:

ORADIM does create a passwordfile if used like in this example in step 3

```
C:\> ORADIM -new -sid ORACLE_SID -intpwd <password> -maxusers 10 -startmode auto -pfile '<your pfile location>'
```

## 2: Create an Initialization Parameter File

Restore the spfile from the backup, and if you don't have the init.ora you can use an init.ora from another database and make the necessary changes. You need setup the required parameters e.g DB\_NAME, CONTROL\_FILES and directories for bdump, udump,cdump etc...

i.e. of restoring spfile

```
RMAN> restore spfile to pfile '/tmp/init<sidname>.ora' from  
'<backup_location>/<backup_piece_name>';
```

in this case as spfile backup was created at

```
Starting Control File and SPFILE Autobackup at 17-JAN-12  
piece handle=<oracle_home path>\DATABASE\C-2610619323-20120117-04 comment=NONE  
Finished Control File and SPFILE Autobackup at 17-JAN-12
```

The restore command using above backup.

```
RMAN> restore spfile to pfile '/tmp/initTEST.ora' from '<oracle_home path>\DATABASE\C-2610619323-  
20120117-04';
```

Parameter file '<ORACLE\_HOME>\DATABASE\init<ORACLE\_SID>.ORA'

at this point the DB\_NAME still be to set as PRIM (Which is the name on the Source DB), it will be changed on step 2.7

## 3: Create the Oracle services

Create a new NT service for the duplicate database TEST using oradim.  
As Guideline please see  
([Doc ID 114384.1](#)) WIN: Checklist for Resolving CONNECT AS SYSDBA Issues

```
C:\> ORADIM -new -sid ORACLE_SID -intpwd <password> -maxusers 10 -startmode auto -pfile '<your pfile location>'
```

### Step 2.3 - Restore the controlfile

Change the pfile related to controlfile location,dump directories etc

Startup in nomount restore the controlfile:

```
$rman target /
RMAN> restore controlfile from '<backup piece name of controlfile ie last step of backup >';
RMAN> alter database mount;
```

### Example

-----

**Here onward we will see at source we took backup to location at "D:\BACKUP\PRIM\" but we copied backup at "D:\BACKUP\TEST" at new server**

```
RMAN> restore controlfile from 'D:\BACKUP\TEST\16N10JI7_1_1';
```

```
Starting restore at 17-JAN-12
using target database control file instead of recovery catalog
allocated channel: ORA_DISK_1
channel ORA_DISK_1: SID=66 device type=DISK
```

```
channel ORA_DISK_1: restoring control file
channel ORA_DISK_1: restore complete, elapsed time: 00:00:03
output file name=<path>\TEST\CONTROL01.CTL
output file name=<path>\TEST_2\CONTROL02.CTL
Finished restore at 17-JAN-12
```

```
RMAN>
```

### Step 2.4 - Catalog the backuppieces if required

If backup pieces have been copied to a different location than source server then we need to catalog those backuppieces (only applicable to 10g and above)

```
+ RMAN> catalog start with '<new location>' noprompt;
  (this command will add all backup pieces in metadata and now onward we can see 2 copies of
  backup in metadata )

+ RMAN> crosscheck backup tag '<backup tag from backup log>' ;
  (By default oracle picks latest backup tag and the first copy if multiple copies exist,to
  avoid conflict or backup piece not found error (as we kept backup pieces in different location)
  ,run crosscheck command so that original location backup pieces ie first copy will be marked as
  expired )

+ RMAN> delete expired backup;
  (delete first copy of backup piece)
```

### Example

-----

RMAN> catalog start with 'D:\BACKUP\TEST\' noprompt;

searching for all files that match the pattern D:\BACKUP\TEST\

#### List of Files Unknown to the Database

=====

File Name: D:\BACKUP\TEST\0SN10JGO\_1\_1

File Name: D:\BACKUP\TEST\0TN10JGO\_1\_1

File Name: D:\BACKUP\TEST\0UN10JGO\_1\_1

File Name: D:\BACKUP\TEST\0VN10JGP\_1\_1

File Name: D:\BACKUP\TEST\11N10JHQ\_1\_1

File Name: D:\BACKUP\TEST\12N10JHQ\_1\_1

File Name: D:\BACKUP\TEST\13N10JHQ\_1\_1

File Name: D:\BACKUP\TEST\14N10JHQ\_1\_1

File Name: D:\BACKUP\TEST\16N10JI7\_1\_1

cataloging files...

cataloging done

#### List of Cataloged Files

=====

File Name: D:\BACKUP\TEST\0SN10JGO\_1\_1

File Name: D:\BACKUP\TEST\0TN10JGO\_1\_1

File Name: D:\BACKUP\TEST\0UN10JGO\_1\_1

File Name: D:\BACKUP\TEST\0VN10JGP\_1\_1

File Name: D:\BACKUP\TEST\11N10JHQ\_1\_1

File Name: D:\BACKUP\TEST\12N10JHQ\_1\_1

File Name: D:\BACKUP\TEST\13N10JHQ\_1\_1

File Name: D:\BACKUP\TEST\14N10JHQ\_1\_1

File Name: D:\BACKUP\TEST\16N10JI7\_1\_1

RMAN> list backup of datafile 1;

#### List of Backup Sets

=====

#### BS Key Type LV Size

-----

25 Full 585.05M

List of Datafiles in backup set 25

File LV Type Ckp SCN Ckp Time Name

-----

1 Full 1498600 17-JAN-12 <path>\PRIM\SYSTEM01.DBF

Backup Set Copy #1 of backup set 25

Device Type Elapsed Time Completion Time Compressed Tag

-----

DISK 00:00:20 17-JAN-12 NO TAG20120117T162144

#### List of Backup Pieces for backup set 25 **Copy #1**

BP Key Pc# Status Piece Name

-----

25 1 AVAILABLE **D:\BACKUP\PRIM\0SN10JGO\_1\_1**

Backup Set Copy #2 of backup set 25

Device Type Elapsed Time Completion Time Compressed Tag

-----

DISK 00:00:20 17-JAN-12 NO TAG20120117T162144

List of Backup Pieces for backup set 25 **Copy #2**

BP Key Pc# Status Piece Name

-----  
32 1 AVAILABLE D:\BACKUP\TEST\0SN10JGO\_1\_1

RMAN&gt;

RMAN&gt; crosscheck backup;

allocated channel: ORA\_DISK\_1

channel ORA\_DISK\_1: SID=66 device type=DISK

crosschecked backup piece: found to be 'EXPIRED'

backup piece handle=D:\BACKUP\PRIM\0UN10JGO\_1\_1 RECID=22 STAMP=772820505

crosschecked backup piece: found to be 'AVAILABLE'

backup piece handle=D:\BACKUP\TEST\0UN10JGO\_1\_1 RECID=34 STAMP=772821367

crosschecked backup piece: found to be 'EXPIRED'

backup piece handle=D:\BACKUP\PRIM\0VN10JGP\_1\_1 RECID=23 STAMP=772820505

crosschecked backup piece: found to be 'AVAILABLE'

backup piece handle=D:\BACKUP\TEST\0VN10JGP\_1\_1 RECID=35 STAMP=772821367

crosschecked backup piece: found to be 'EXPIRED'

backup piece handle=D:\BACKUP\PRIM\0TN10JGO\_1\_1 RECID=24 STAMP=772820505

crosschecked backup piece: found to be 'AVAILABLE'

backup piece handle=D:\BACKUP\TEST\0TN10JGO\_1\_1 RECID=33 STAMP=772821366

crosschecked backup piece: found to be 'EXPIRED'

backup piece handle=D:\BACKUP\PRIM\0SN10JGO\_1\_1 RECID=25 STAMP=772820504

crosschecked backup piece: found to be 'AVAILABLE'

backup piece handle=D:\BACKUP\TEST\0SN10JGO\_1\_1 RECID=32 STAMP=772821366

crosschecked backup piece: found to be 'AVAILABLE'

backup piece handle=D:\&lt;oracle\_home path&gt;\DATABASE\C-2610619323-20120117-03 RECID=26 STAMP=772820531

crosschecked backup piece: found to be 'EXPIRED'

backup piece handle=D:\BACKUP\PRIM\14N10JHQ\_1\_1 RECID=27 STAMP=772820538

crosschecked backup piece: found to be 'AVAILABLE'

backup piece handle=D:\BACKUP\TEST\14N10JHQ\_1\_1 RECID=39 STAMP=772821368

crosschecked backup piece: found to be 'EXPIRED'

backup piece handle=D:\BACKUP\PRIM\13N10JHQ\_1\_1 RECID=28 STAMP=772820538

crosschecked backup piece: found to be 'AVAILABLE'

backup piece handle=D:\BACKUP\TEST\13N10JHQ\_1\_1 RECID=38 STAMP=772821368

crosschecked backup piece: found to be 'EXPIRED'

backup piece handle=D:\BACKUP\PRIM\12N10JHQ\_1\_1 RECID=29 STAMP=772820538

crosschecked backup piece: found to be 'AVAILABLE'

backup piece handle=D:\BACKUP\TEST\12N10JHQ\_1\_1 RECID=37 STAMP=772821367

crosschecked backup piece: found to be 'EXPIRED'

backup piece handle=D:\BACKUP\PRIM\11N10JHQ\_1\_1 RECID=30 STAMP=772820538

crosschecked backup piece: found to be 'AVAILABLE'

backup piece handle=D:\BACKUP\TEST\11N10JHQ\_1\_1 RECID=36 STAMP=772821367

crosschecked backup piece: found to be 'AVAILABLE'

backup piece handle=&lt;oracle\_home path&gt;\DATABASE\C-2610619323-20120117-04 RECID=31 STAMP=772820547

crosschecked backup piece: found to be 'AVAILABLE'

backup piece handle=D:\BACKUP\TEST\16N10JI7\_1\_1 RECID=40 STAMP=772821368

Crosschecked 40 objects

RMAN&gt; delete expired backup tag 'TAG20120117T162144';

using channel ORA\_DISK\_1

## List of Backup Pieces

BP Key BS Key Pc# Cp# Status Device Type Piece Name

-----  
22 22 1 1 EXPIRED DISK D:\BACKUP\PRIM\0UN10JGO\_1\_1

23 23 1 1 EXPIRED DISK D:\BACKUP\PRIM\0VN10JGP\_1\_1

24 24 1 1 EXPIRED DISK D:\BACKUP\PRIM\0TN10JGO\_1\_1

25 25 1 1 EXPIRED DISK D:\BACKUP\PRIM\0SN10JGO\_1\_1

Do you really want to delete the above objects (enter YES or NO)? yes

deleted backup piece

backup piece handle=D:\BACKUP\PRIM\0UN10JGO\_1\_1 RECID=22 STAMP=772820505

deleted backup piece

backup piece handle=D:\BACKUP\PRIM\0VN10JGP\_1\_1 RECID=23 STAMP=772820505

deleted backup piece

backup piece handle=D:\BACKUP\PRIM\0TN10JGO\_1\_1 RECID=24 STAMP=772820505

deleted backup piece

backup piece handle=D:\BACKUP\PRIM\0SN10JGO\_1\_1 RECID=25 STAMP=772820504

Deleted 4 EXPIRED objects

RMAN> delete expired backup tag 'TAG20120117T162217';

using channel ORA\_DISK\_1

List of Backup Pieces

BP Key BS Key Pc# Cp# Status Device Type Piece Name

-----

27 27 1 1 EXPIRED DISK D:\BACKUP\PRIM\14N10JHQ\_1\_1

28 28 1 1 EXPIRED DISK D:\BACKUP\PRIM\13N10JHQ\_1\_1

29 29 1 1 EXPIRED DISK D:\BACKUP\PRIM\12N10JHQ\_1\_1

30 30 1 1 EXPIRED DISK D:\BACKUP\PRIM\11N10JHQ\_1\_1

Do you really want to delete the above objects (enter YES or NO)? yes

deleted backup piece

backup piece handle=D:\BACKUP\PRIM\14N10JHQ\_1\_1 RECID=27 STAMP=772820538

deleted backup piece

backup piece handle=D:\BACKUP\PRIM\13N10JHQ\_1\_1 RECID=28 STAMP=772820538

deleted backup piece

backup piece handle=D:\BACKUP\PRIM\12N10JHQ\_1\_1 RECID=29 STAMP=772820538

deleted backup piece

backup piece handle=D:\BACKUP\PRIM\11N10JHQ\_1\_1 RECID=30 STAMP=772820538

Deleted 4 EXPIRED objects

RMAN> list backup of datafile 1;

List of Backup Sets

=====

BS Key Type LV Size Device Type Elapsed Time Completion Time

-----

25 Full 585.05M DISK 00:00:20 17-JAN-12

BP Key: 32 Status: AVAILABLE Compressed: NO Tag: TAG20120117T162144

Piece Name: **D:\BACKUP\TEST\0SN10JGO\_1\_1**

List of Datafiles in backup set 25

File LV Type Ckp SCN Ckp Time Name

-----

1 Full 1498600 17-JAN-12 <path>\PRIM\SYSTEM01.DBF

RMAN>

## Step 2.5 - Restore the database

Check the datafile locations:

```
RMAN> report schema;
```

### Example.

```
RMAN> report schema;
```

```
RMAN-06139: WARNING: control file is not current for REPORT SCHEMA
Report of database schema for database with db_unique_name PRIM
```

#### List of Permanent Datafiles

```
=====
File Size(MB) Tablespace RB segs Datafile Name
-----
1 680 SYSTEM *** <path>\PRIM\SYSTEM01.DBF
2 512 SYSAUX *** <path>\PRIM\SYSAUX01.DBF
3 30 UNDOTBS1 *** <path>\PRIM\UNDOTBS01.DBF
4 5 USERS *** <path>\PRIM\USERS01.DBF
```

#### List of Temporary Files

```
=====
File Size(MB) Tablespace Maxsize(MB) Tempfile Name
-----
1 20 TEMP 32767 <path>\PRIM\TEMP01.DBF
```

```
RMAN>
```

If you need to the datafiles to be restored to a new location on the new host, you can use SET NEWNAME:

```
RMAN> set newname for datafile x to '<new location and name>';
```

script will look like this

```
$rman target / log=restore.log
RMAN> run{
  allocate channel t1 type disk;
  allocate channel t2 type disk;
  set newname for datafile 1 to '<path>\TEST\ORADATA\SYSTEM01.DBF';
  set newname for datafile 2 to '<path>\TEST\ORADATA\SYSAUX01.DBF';
  set newname for datafile 3 to '<path>\TEST\ORADATA\UNDOTBS01.DBF';
  set newname for datafile 4 to '<path>\TEST\ORADATA\USERS01.DBF';
  set until sequence 24;
  restore database;
  switch datafile all;
  recover database;
}
```

Note# you can get the max sequence number in 2 ways

- 1) select max(sequence#) from v\$backup\_redolog OR
- 2) refer to your RMAN backup log and see the max sequence number backed up

after completion of above step db will be restored and recovered.

#### Example

-----

```
RMAN> run{
2> allocate channel t1 type disk;
3> allocate channel t2 type disk;
4> set newname for datafile 1 to '<path>\TEST\ORADATA\SYSTEM01.DBF';
5> set newname for datafile 2 to '<path>\TEST\ORADATA\SYSAUX01.DBF';
6> set newname for datafile 3 to '<path>\TEST\ORADATA\UNDOTBS01.DBF';
7> set newname for datafile 4 to '<path>\TEST\ORADATA\USERS01.DBF';
8> set until sequence 24;
9> restore database;
10> switch datafile all;
11> recover database;
12> }
```

released channel: ORA\_DISK\_1  
allocated channel: t1  
channel t1: SID=66 device type=DISK

allocated channel: t2  
channel t2: SID=129 device type=DISK

executing command: SET NEWNAME

executing command: SET NEWNAME

executing command: SET NEWNAME

executing command: SET NEWNAME

executing command: SET until clause

Starting restore at 17-JAN-12

channel t1: starting datafile backup set restore  
channel t1: specifying datafile(s) to restore from backup set  
channel t1: restoring datafile 00003 to <path>\TEST\ORADATA\UNDOTBS01.DBF  
channel t1: reading from backup piece D:\BACKUP\TEST\0UN10JGO\_1\_1  
channel t2: starting datafile backup set restore  
channel t2: specifying datafile(s) to restore from backup set  
channel t2: restoring datafile 00004 to <path>\TEST\ORADATA\USERS01.DBF  
channel t2: reading from backup piece D:\BACKUP\TEST\0VN10JGP\_1\_1  
channel t2: piece handle=D:\BACKUP\TEST\0VN10JGP\_1\_1 tag=TAG20120117T162144  
channel t2: restored backup piece 1  
channel t2: restore complete, elapsed time: 00:00:01  
channel t2: starting datafile backup set restore  
channel t2: specifying datafile(s) to restore from backup set  
channel t2: restoring datafile 00002 to <path>\TEST\ORADATA\SYSAUX01.DBF  
channel t2: reading from backup piece D:\BACKUP\TEST\0TN10JGO\_1\_1  
channel t1: piece handle=D:\BACKUP\TEST\0UN10JGO\_1\_1 tag=TAG20120117T162144  
channel t1: restored backup piece 1  
channel t1: restore complete, elapsed time: 00:00:05  
channel t1: starting datafile backup set restore  
channel t1: specifying datafile(s) to restore from backup set  
channel t1: restoring datafile 00001 to <path>\TEST\ORADATA\SYSTEM01.DBF



```

channel t1: reading from backup piece D:\BACKUP\TEST\0SN10JGO_1_1
channel t1: piece handle=D:\BACKUP\TEST\0SN10JGO_1_1 tag=TAG20120117T162144
channel t1: restored backup piece 1
channel t1: restore complete, elapsed time: 00:00:45
channel t2: piece handle=D:\BACKUP\TEST\0TN10JGO_1_1 tag=TAG20120117T162144
channel t2: restored backup piece 1
channel t2: restore complete, elapsed time: 00:00:48
Finished restore at 17-JAN-12

datafile 1 switched to datafile copy
input datafile copy RECID=6 STAMP=772824921 file name=<path>\TEST\ORADATA\SYSTEM01.DBF
datafile 2 switched to datafile copy
input datafile copy RECID=7 STAMP=772824921 file name=<path>\TEST\ORADATA\SYSAUX01.DBF
datafile 3 switched to datafile copy
input datafile copy RECID=8 STAMP=772824922 file name=<path>\TEST\ORADATA\UNDOTBS01.DBF
datafile 4 switched to datafile copy
input datafile copy RECID=9 STAMP=772824922 file name=<path>\TEST\ORADATA\USERS01.DBF

```

Starting recover at 17-JAN-12

starting media recovery

```

channel t1: starting archived log restore to default destination
channel t1: restoring archived log
archived log thread=1 sequence=22
channel t1: reading from backup piece D:\BACKUP\TEST\13N10JHQ_1_1
channel t2: starting archived log restore to default destination
channel t2: restoring archived log
archived log thread=1 sequence=23
channel t2: reading from backup piece D:\BACKUP\TEST\14N10JHQ_1_1
channel t1: piece handle=D:\BACKUP\TEST\13N10JHQ_1_1 tag=TAG20120117T162217
channel t1: restored backup piece 1
channel t1: restore complete, elapsed time: 00:00:01
archived log file name=<path>\ARC0000000022_0772204606.0001 thread=1 sequence=22
channel t2: piece handle=D:\BACKUP\TEST\14N10JHQ_1_1 tag=TAG20120117T162217
channel t2: restored backup piece 1
channel t2: restore complete, elapsed time: 00:00:01
archived log file name=<path>\ARC0000000023_0772204606.0001 thread=1 sequence=23
media recovery complete, elapsed time: 00:00:01
Finished recover at 17-JAN-12
released channel: t1
released channel: t2

```

RMAN>

## Step 2.6 - Rename the online redo logs

Before opening database please make sure online redo logs are in the appropriate location:

```

SQL> set lines 200
      col member format a60
      select a.thread#,a.group#,b.type,b.member,a.bytes/1048576
      from v$log a,v$logfile b
      where a.group#=b.group# order by a.group#;

```

If you want to rename the location and name:

```
SQL> alter database rename file '<old file location and name>' to '<new location and name>';
```

### Example

```
-----
SQL> set lines 200
SQL> col member format a60
SQL> select a.thread#,a.group#,b.type,b.member,a.bytes/1048576 from v$log a,v$logfile b where a.group#=b.group#
order by a.group#;
```

```
THREAD# GROUP# TYPE MEMBER A.BYTES/1048576
-----
```

```
1 1 ONLINE <path>\PRIM\REDO01.LOG 50
1 2 ONLINE <path>\PRIM\REDO02.LOG 50
1 3 ONLINE <path>\PRIM\REDO03.LOG 50
```

```
SQL> alter database rename file '<path>\PRIM\REDO01.LOG' to '<path>\TEST\ORADATA\REDO01.LOG';
```

Database altered.

```
SQL> alter database rename file '<path>\PRIM\REDO02.LOG' to '<path>\TEST\ORADATA\REDO02.LOG';
```

Database altered.

```
SQL> alter database rename file '<path>\PRIM\REDO03.LOG' to '<path>\TEST\ORADATA\REDO03.LOG';
```

Database altered.

### Now confirm the new location of redo

```
SQL> select a.thread#,a.group#,b.type,b.member,a.bytes/1048576 from v$log a,v$logfile b where a.group#=b.group#
order by a.group#;
```

```
THREAD# GROUP# TYPE MEMBER A.BYTES/1048576
-----
```

```
1 1 ONLINE <path>\TEST\ORADATA\REDO01.LOG 50
1 2 ONLINE <path>\TEST\ORADATA\REDO02.LOG 50
1 3 ONLINE <path>\TEST\ORADATA\REDO03.LOG 50
```

```
SQL>
```

Now open database with resetlogs;

```
SQL> alter database open resetlogs;
```

### Step 2.7 - Rename the database

The newly restored database will have the same DBID and DB\_NAME as the original database so we will need to change them.

You can use NID:

## How to Change the DBID, DBNAME Using NID Utility in version 10gR2 onwards (Document ID [863800.1](#))

Or recreate the controlfile as follows...

Take a controlfile trace:

```
SQL> alter database backup controlfile to trace as '<location and name of trace file>';  
SQL> oradebug setmypid;  
SQL> oradebug tracefile_name;
```

Once the trace file is generated do graceful shutdown:

```
SQL> shutdown immediate;
```

Edit the trace file generated above, and change this line:

CREATE CONTROLFILE REUSE DATABASE "PRIM" NORESETLOGS ARCHIVELOG ====>assuming production database name is PRIM

to

CREATE CONTROLFILE set DATABASE "TEST" RESETLOGS ARCHIVELOG FORCE LOGGING ====>assuming Non-Prod database name is TEST

The script will look similar to this

```
CREATE CONTROLFILE set DATABASE "TEST" RESETLOGS ARCHIVELOG FORCE LOGGING  
MAXLOGFILES 16  
MAXLOGMEMBERS 3  
MAXDATAFILES 100  
MAXINSTANCES 8  
MAXLOGHISTORY 292  
LOGFILE  
GROUP 1 '/<path>/TEST/redo01.log' SIZE 50M,  
GROUP 2 '/<path>/TEST/redo02.log' SIZE 50M,  
GROUP 3 '/<path>/TEST/redo03.log' SIZE 50M  
DATAFILE  
'/<path>/TEST/system01.dbf',  
'/<path>/TEST/sysaux01.dbf',  
'/<path>/TEST/undotbs01.dbf'  
'/<path>/TEST/user01.dbf'  
CHARACTER SET WE8MSWIN1252  
;
```

Now set the sid as per new sid name

```
set ORACLE_SID=TEST
```

(assuming TEST is the new SID name)

+assuming pfile has been created for DB TEST

put the database in nomount stage

```
SQL> startup nomount;
```

==>run the script to re-create controlfile

```
SQL> alter database open resetlogs;
```

### **Step 2.8 - Confirm your tempfiles**

Confirm the location of your tempfiles, recreate them at the new location if required:

```
SQL> select * from v$tempfile;  
SQL> ALTER TABLESPACE TEMP ADD TEMPFILE 'new tempfile path filename' REUSE;
```

## **REFERENCES**

[NOTE:863800.1](#) - How to Change the DBID, DBNAME Using NID Utility

[NOTE:1489027.1](#) - RMAN Restore or Duplicate Performs Implicit Crosschecking and Cataloging

[NOTE:558408.1](#) - RMAN DUPLICATE / RESTORE a database to a higher patchset

[NOTE:369644.1](#) - Frequently Asked Questions about Restoring Or Duplicating Between Different Versions And Platforms

[NOTE:1554636.1](#) - Checklist for an RMAN Restore

[NOTE:137483.1](#) - How to Modify the Content of an SPFILE Parameter File

[NOTE:882555.1](#) - RMAN is Not Restoring OMF Datafiles in Their Original Location

[NOTE:345134.1](#) - How to transfer backups from ASM to filesystem when restoring to a new host

Didn't find what you are looking for?