

Technical drawing of a cabinet showing front and side elevations with dimensions.

Front Elevation Dimensions:

- Top width: $17\frac{1}{2}$ " ACTUAL
- Top width (Right of Offset): $16\frac{1}{4}$ " R.O.
- Top width (Actual): $12\frac{3}{4}$ " ACTUAL
- Bottom width (To Parcel Lock): $41\frac{1}{8}$ "
- Bottom width (To Bottom Shelf): $36\frac{3}{8}$ "

Side Elevation Dimensions:

- Depth: 17" R.O.
- Height (Right of Offset): $11\frac{13}{16}$ " R.O.
- Height (From Finished Floor to Bottom of R.O.): $35\frac{1}{2}$ "

Other Labels:

- FINISHED FLOOR

DESCRIPTION	COMPARTMENT	COMPARTMENT SIZE	QTY.
PARCEL	PL3	10" H x 12" W x 15" D	1

AV FLORENCE
manufacturing company

MODEL	4C03S-1P	REV	B
SCALE	NONE	LAST REV DATE	

- Notes:
 1. This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.
 - a. At least one customer compartment shall be positioned less than 48" above finished floor (AFF).
 - b. No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
 - c. No patron (tenant) lock shall be positioned more than 67" AFF.
 - d. No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
 - e. The USPS Arrow lock shall be positioned 36" - 48" AFF.
 2. This 4C mailbox can also be used for private applications.
 3. The rough opening width for multi-unit 4C installations = (the sum of all actual unit widths) - 1½".