versatile™ 4C Mailbox, 4C04S-02

16¼" ACTUAL

16¼" R.O.

17½" ACTUAL

36⅜"
(TO BOTTOM SHELF)

41⅛"
(TO ACCESS DOOR LOCK)

48⅛"
(TO TENANT LOCK)

FINISHED FLOOR

17" R.O. DEPTH

15⁵⁄₁₆" R.O.

35½"
FROM FINISHED FLOOR TO BOTTOM OF R.O.

Notes:

1. This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.

   a. At least one customer compartment shall be positioned less then 48" above finished floor (AFF).
   b. No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
   c. No patron (tenant) lock shall be positioned more than 67" AFF.
   d. No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
   e. The USPS Arrow lock shall be positioned 36"- 48" AFF.

2. This 4C mailbox can also be used for private applications.

3. The rough opening width for multi-unit 4C installations = (the sum of all actual unit widths) - 1⅛".

COMPARTMENT CHART

DESCRIPTION	COMPARTMENT	COMPARTMENT SIZE
MAILBOX	MB1	3"H x 12"W x 15"D
OUTGOING MAIL	OM2	6-1/2"H x 12"W x 15"D

PRODUCT SERIES: VERSATILE™ 4C FRONT LOAD MAILBOX

AF FLORENCE manufacturing company

MODEL	REV
4C04S-02	B

SCALE	LAST REV DATE
NONE	

DRAWING NUMBER	DRAWN BY
4C04S-02CS	

QTY.
2
1