## ωΝ 1. This module meets the USPS STD-4C requirements for installation defined below when the mailbox is This 4C mailbox can also be used for private applications. The rough opening width for multi-unit 4C installations = (the sum of all actual unit widths) - 1%". installed per the dimensions provided on this drawing. e. The USPS Arrow lock shall be positioned 36"- 48" AFF. No patron (tenant) lock shall be positioned more than 67" AFF. At least one customer compartment shall be positioned less then 48" above finished floor (AFF). No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF. No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF. 30¼" ACTUAL 17½" ACTUAL |--- 16¼" R.O. -• • • versatile™ 4C Mailbox, 4C08S-2P (TO BOTTOM SHELF) FINISHED FLOOR 50½" (TO PARCEL LOCK) PRODUCT SERIES: VERSATILETM 4C FRONT LOAD MAILBOX FIORENCE manufacturing company DEPTH DESCRIPTION COMPARTMENT COMPARTMENT CHART FROM BOTTOM OF R.O. TO FINISHED FLOOR 295/16" R.O. DRAWING NUMBER SCALE MODEL 4C08S-2P 4C08S-2PCS COMPARTMENT SIZE 7" H x 12" W x 15" D NONE REV LAST REV DATE DRAWN BY QTY.