

# Complete Mathematical Formulas in Machine Learning

## Table of Contents

1. Foundational Mathematics
  2. Statistical Measures
  3. Linear Algebra in ML
  4. Calculus in ML
  5. Probability Theory
  6. Information Theory
  7. Loss Functions
  8. Optimization Algorithms
  9. Linear Models Mathematics
  10. Tree-Based Models Mathematics
  11. Support Vector Machines Mathematics
  12. Neural Network Mathematics
  13. Clustering Mathematics
  14. Dimensionality Reduction Mathematics
  15. Evaluation Metrics Mathematics
- 

## Foundational Mathematics

### Basic Notation

- **Scalar**: Single value, denoted as  $x, y, a, b$
- **Vector**: Column of values, denoted as  $\mathbf{x}, \mathbf{y}$  (bold)
- **Matrix**: 2D array, denoted as  $\mathbf{X}, \mathbf{W}$  (bold capital)
- **Tensor**: n-dimensional array

### Summation and Product Notation

#### Summation:

$$\sum_{i=1}^n x_i = x_1 + x_2 + \dots + x_n$$

#### Product:

$$\prod_{i=1}^n x_i = x_1 \times x_2 \times \dots \times x_n$$

---

## Statistical Measures

### Mean (Average)

#### Arithmetic Mean:

$$\mu = \bar{x} = (1/n) \times \sum_{i=1}^n x_i$$

- $\mu$  (mu) or  $\bar{x}$  represents the mean
- $n$  is the number of observations
- $x_i$  is the  $i$ -th observation

### Variance

#### Population Variance:

$$\sigma^2 = (1/n) \times \sum_{i=1}^n (x_i - \mu)^2$$

#### Sample Variance (Bessel's correction):

$$s^2 = (1/(n-1)) \times \sum_{i=1}^n (x_i - \bar{x})^2$$

### Standard Deviation

$$\sigma = \sqrt{\sigma^2} \quad (\text{population})$$

$$s = \sqrt{s^2} \quad (\text{sample})$$

### Covariance

#### Between two variables X and Y:

$$\text{Cov}(X, Y) = (1/n) \times \sum_{i=1}^n (x_i - \mu_x)(y_i - \mu_y)$$

### Correlation Coefficient

#### Pearson Correlation:

$$\rho(X, Y) = \text{Cov}(X, Y) / (\sigma_x \times \sigma_y)$$

- Range:  $[-1, 1]$

- -1: perfect negative correlation
- 0: no linear correlation
- 1: perfect positive correlation

## Standardization (Z-score)

$$z = (x - \mu) / \sigma$$

- Transforms data to have  $\mu = 0$  and  $\sigma = 1$
- 

## Linear Algebra in ML

### Vector Operations

**Dot Product** (Inner Product):

$$a \cdot b = \sum_{i=1}^n a_i b_i = a_1 b_1 + a_2 b_2 + \dots + a_n b_n$$

**Vector Norm** (Length):

- L1 Norm (Manhattan):  $\|x\|_1 = \sum_i |x_i|$
- L2 Norm (Euclidean):  $\|x\|_2 = \sqrt{\sum_i x_i^2}$
- L $\infty$  Norm (Max):  $\|x\|_\infty = \max_i |x_i|$

### Matrix Operations

**Matrix Multiplication:**

$$C = AB \text{ where } C_{ij} = \sum_k A_{ik} B_{kj}$$

**Matrix Transpose:**

$$(A^T)_{ij} = A_{ji}$$

**Matrix Inverse:**

$$AA^{-1} = A^{-1}A = I$$

where  $I$  is the identity matrix

## Eigenvalues and Eigenvectors

For matrix  $A$  and vector  $v$ :

$$Av = \lambda v$$

- $\lambda$  is the eigenvalue
- $v$  is the eigenvector

### Characteristic Equation:

$$\det(A - \lambda I) = 0$$

---

## Calculus in ML

### Derivatives

#### Basic Rules:

- Power Rule:  $d/dx(x^n) = nx^{n-1}$
- Chain Rule:  $d/dx[f(g(x))] = f'(g(x)) \times g'(x)$
- Product Rule:  $d/dx[f(x)g(x)] = f'(x)g(x) + f(x)g'(x)$

### Partial Derivatives

For function  $f(x,y)$ :

$\partial f / \partial x$  = partial derivative with respect to  $x$

$\partial f / \partial y$  = partial derivative with respect to  $y$

### Gradient

For function  $f(x_1, x_2, \dots, x_n)$ :

$$\nabla f = [\partial f / \partial x_1, \partial f / \partial x_2, \dots, \partial f / \partial x_n]^T$$

### Gradient Descent Update Rule

$$\theta_{t+1} = \theta_t - \alpha \nabla f(\theta_t)$$

- $\theta$ : parameters
- $\alpha$ : learning rate
- $\nabla f$ : gradient of loss function

### Hessian Matrix

Second-order partial derivatives:

$$H(f)_{ij} = \partial^2 f / (\partial x_i \partial x_j)$$

---

## Probability Theory

### Basic Probability

$$P(A) \in [0, 1]$$

$$P(\Omega) = 1 \quad (\text{probability of sample space})$$

$$P(\emptyset) = 0 \quad (\text{probability of empty set})$$

### Conditional Probability

$$P(A|B) = P(A \cap B) / P(B)$$

- $P(A|B)$ : probability of A given B

### Bayes' Theorem

$$P(A|B) = [P(B|A) \times P(A)] / P(B)$$

**Extended form:**

$$P(A|B) = [P(B|A) \times P(A)] / [\sum_i P(B|A_i) \times P(A_i)]$$

## Probability Distributions

### Bernoulli Distribution:

$$P(X = x) = p^x (1-p)^{1-x} \quad \text{for } x \in \{0, 1\}$$

### Binomial Distribution:

$$P(X = k) = C(n, k) \times p^k \times (1-p)^{n-k}$$

where  $C(n, k) = n! / (k!(n-k)!)$

### Normal (Gaussian) Distribution:

$$f(x) = (1/\sqrt{2\pi\sigma^2}) \times \exp(-(x-\mu)^2/(2\sigma^2))$$

## Multivariate Normal:

$$f(x) = (1 / ((2\pi)^{(k/2)} |\Sigma|^{(1/2)})) \times \exp(-\frac{1}{2}(x-\mu)^T \Sigma^{-1} (x-\mu))$$

- $\Sigma$ : covariance matrix
- $|\Sigma|$ : determinant of  $\Sigma$

## Expectation and Variance

**Expectation** (Expected Value):

- Discrete:  $E[X] = \sum_x x \times P(X = x)$
- Continuous:  $E[X] = \int x \times f(x) dx$

**Variance:**

$$\text{Var}(X) = E[(X - E[X])^2] = E[X^2] - (E[X])^2$$

---

## Information Theory

### Entropy

**For discrete variable X:**

$$H(X) = -\sum_i P(x_i) \times \log_2(P(x_i))$$

- Measures uncertainty/information content
- Units: bits ( $\log_2$ ) or nats ( $\ln$ )

### Cross-Entropy

**Between distributions P and Q:**

$$H(P, Q) = -\sum_i P(x_i) \times \log(Q(x_i))$$

### Kullback-Leibler (KL) Divergence

$$KL(P || Q) = \sum_i P(x_i) \times \log(P(x_i)/Q(x_i))$$

- Measures difference between distributions
- $KL(P||Q) \neq KL(Q||P)$  (not symmetric)

### Mutual Information

$$I(X;Y) = \sum_x \sum_y P(x,y) \times \log(P(x,y)/(P(x)P(y)))$$


---

## Loss Functions

### Regression Loss Functions

#### Mean Squared Error (MSE):

$$MSE = (1/n) \times \sum_{i=1}^n (y_i - \hat{y}_i)^2$$

#### Mean Absolute Error (MAE):

$$MAE = (1/n) \times \sum_{i=1}^n |y_i - \hat{y}_i|$$

#### Huber Loss (Robust to outliers):

$$L_{\delta}(y, \hat{y}) = \begin{cases} \frac{1}{2}(y - \hat{y})^2 & \text{if } |y - \hat{y}| \leq \delta \\ \delta|y - \hat{y}| - \frac{1}{2}\delta^2 & \text{if } |y - \hat{y}| > \delta \end{cases}$$

### Classification Loss Functions

#### Binary Cross-Entropy (Log Loss):

$$BCE = -(1/n) \times \sum_{i=1}^n [y_i \log(\hat{y}_i) + (1 - y_i) \log(1 - \hat{y}_i)]$$

#### Categorical Cross-Entropy (Multi-class):

$$CCE = -(1/n) \times \sum_{i=1}^n \sum_{j=1}^m y_{ij} \log(\hat{y}_{ij})$$

- m: number of classes
- $y_{ij}$ : 1 if sample i belongs to class j, 0 otherwise

#### Hinge Loss (SVM):

$$L = \max(0, 1 - y \times \hat{y})$$


---

## Optimization Algorithms

### Gradient Descent Variants

## Batch Gradient Descent:

$$\theta = \theta - \alpha \times (1/n) \times \sum_{i=1}^n \nabla \theta L(x_i, y_i, \theta)$$

## Stochastic Gradient Descent (SGD):

$$\theta = \theta - \alpha \times \nabla \theta L(x_i, y_i, \theta)$$

## Mini-batch Gradient Descent:

$$\theta = \theta - \alpha \times (1/m) \times \sum_{i=1}^m \nabla \theta L(x_i, y_i, \theta)$$

## Advanced Optimizers

### Momentum:

$$v_t = \beta v_{t-1} + \alpha \nabla \theta L$$

$$\theta_t = \theta_{t-1} - v_t$$

### RMSprop:

$$s_t = \beta s_{t-1} + (1-\beta)(\nabla \theta L)^2$$

$$\theta_t = \theta_{t-1} - \alpha \times \nabla \theta L / \sqrt{s_t + \epsilon}$$

### Adam (Adaptive Moment Estimation):

$$m_t = \beta_1 m_{t-1} + (1-\beta_1) \nabla \theta L \quad (1st \text{ moment})$$

$$v_t = \beta_2 v_{t-1} + (1-\beta_2) (\nabla \theta L)^2 \quad (2nd \text{ moment})$$

$$\hat{m}_t = m_t / (1-\beta_1^t) \quad (\text{bias correction})$$

$$\hat{v}_t = v_t / (1-\beta_2^t) \quad (\text{bias correction})$$

$$\theta_t = \theta_{t-1} - \alpha \times \hat{m}_t / (\sqrt{\hat{v}_t} + \epsilon)$$

---

## Linear Models Mathematics

### Linear Regression

#### Model:

$$\hat{y} = \beta_0 + \beta_1 x_1 + \beta_2 x_2 + \dots + \beta_n x_n = x^T \beta$$

#### Normal Equation (Closed-form solution):



$$\beta = (X^T X)^{-1} X^T y$$

**Cost Function (MSE):**

$$J(\beta) = (1/2n) \times \sum_{i=1}^n (y_i - x_i^T \beta)^2$$

**Gradient:**

$$\nabla J = -(1/n) \times X^T (y - X\beta)$$

## Ridge Regression (L2 Regularization)

**Cost Function:**

$$J(\beta) = (1/2n) \times \sum_{i=1}^n (y_i - x_i^T \beta)^2 + \lambda ||\beta||_2^2$$

**Solution:**

$$\beta = (X^T X + \lambda I)^{-1} X^T y$$

## Lasso Regression (L1 Regularization)

**Cost Function:**

$$J(\beta) = (1/2n) \times \sum_{i=1}^n (y_i - x_i^T \beta)^2 + \lambda ||\beta||_1$$

- No closed-form solution
- Solved using coordinate descent or proximal gradient

## Logistic Regression

**Sigmoid Function:**

$$\sigma(z) = 1/(1 + e^{-z})$$

**Model:**

$$P(y=1|x) = \sigma(x^T \beta) = 1/(1 + e^{-x^T \beta})$$

**Log-Likelihood:**

$$LL = \sum_{i=1}^n [y_i \log(\sigma(x_i^T \beta)) + (1-y_i) \log(1-\sigma(x_i^T \beta))]$$

**Gradient:**

$$\nabla_{\beta} LL = X^T (y - \sigma(X\beta))$$


---

## Tree-Based Models Mathematics

### Decision Trees

**Gini Impurity:**

$$\text{Gini} = 1 - \sum_{j=1}^c p_j^2$$

- c: number of classes
- $p_j$ : proportion of samples in class j

**Entropy:**

$$\text{Entropy} = -\sum_{j=1}^c p_j \log_2(p_j)$$

**Information Gain:**

$$IG = \text{Entropy}(\text{parent}) - \sum_i (n_i/n) \times \text{Entropy}(\text{child}_i)$$

- $n_i$ : number of samples in child i
- n: total samples in parent

**Variance Reduction** (for regression):

$$VR = \text{Var}(\text{parent}) - \sum_i (n_i/n) \times \text{Var}(\text{child}_i)$$

### Random Forest

**Prediction** (Regression):

$$\hat{y} = (1/B) \times \sum_{\beta=1}^B T_{\beta}(x)$$

- B: number of trees
- $T_{\beta}$ : prediction from tree b

## Prediction (Classification):

$$\hat{y} = \text{mode}\{T_1(x), T_2(x), \dots, T^B(x)\}$$

## Feature Importance:

$$\text{Importance}_j = (1/B) \times \sum_{\beta=1}^B \sum_{t \in \beta} 1(v(t)=j) \times p(t) \Delta_{it}$$

- $v(t)$ : variable used at node  $t$
- $p(t)$ : proportion of samples reaching node  $t$
- $\Delta_{it}$ : impurity decrease at node  $t$

## Gradient Boosting

### Additive Model:

$$F(x) = \sum_{m=1}^M \gamma_m h_m(x)$$

### Update Rule:

$$F_m(x) = F_{m-1}(x) + \gamma_m h_m(x)$$

### Gradient Calculation:

$$r_{im} = -[\partial L(y_i, F(x_i)) / \partial F(x_i)]_{F=F_{m-1}}$$

---

## Support Vector Machines Mathematics

### Hard Margin SVM

#### Objective:

$$\begin{aligned} \text{minimize: } & \frac{1}{2} \|w\|^2 \\ \text{subject to: } & y_i(w^T x_i + b) \geq 1 \text{ for all } i \end{aligned}$$

### Soft Margin SVM

#### Objective:

$$\begin{aligned} \text{minimize: } & \frac{1}{2} \|w\|^2 + C \times \sum_i \xi_i \\ \text{subject to: } & y_i(w^T x_i + b) \geq 1 - \xi_i \\ & \xi_i \geq 0 \end{aligned}$$

- $\xi_i$ : slack variables
- C: regularization parameter

## Kernel Trick

### Kernel Function:

$$K(x, x') = \phi(x)^T \phi(x')$$

### Common Kernels:

- Linear:  $K(x, x') = x^T x'$
- Polynomial:  $K(x, x') = (\gamma x^T x' + r)^d$
- RBF (Gaussian):  $K(x, x') = \exp(-\gamma \|x - x'\|^2)$
- Sigmoid:  $K(x, x') = \tanh(\gamma x^T x' + r)$

### Dual Form Prediction:

$$f(x) = \sum_{i=1}^n \alpha_i y_i K(x_i, x) + b$$


---

## Neural Network Mathematics

### Forward Propagation

#### Linear Transformation:

$$z^{(1)} = W^{(1)} a^{(1-1)} + b^{(1)}$$

#### Activation:

$$a^{(1)} = g^{(1)}(z^{(1)})$$

### Activation Functions

#### ReLU (Rectified Linear Unit):

$$\text{ReLU}(z) = \max(0, z)$$

## Leaky ReLU:

$$\text{LeakyReLU}(z) = \max(\alpha z, z) \quad \text{where } \alpha \approx 0.01$$

## Sigmoid:

$$\sigma(z) = 1/(1 + e^{-z})$$

## Tanh:

$$\tanh(z) = (e^z - e^{-z})/(e^z + e^{-z})$$

## Softmax (Multi-class output):

$$\text{softmax}(z_i) = e^{z_i} / \sum_j e^{z_j}$$

## Backpropagation

### Chain Rule Application:

$$\partial L / \partial w^{(1)} = \partial L / \partial z^{(1)} \times \partial z^{(1)} / \partial w^{(1)}$$

### Error Propagation:

$$\delta^{(1)} = (w^{(1+1)})^T \delta^{(1+1)} \odot g'(z^{(1)})$$

- $\odot$ : element-wise multiplication

### Weight Update:

$$w^{(1)} = w^{(1)} - \alpha \times \delta^{(1)} (a^{(1-1)})^T$$

## Batch Normalization

### Normalization:

$$\hat{x}_i = (x_i - \mu_B) / \sqrt{(\sigma_B^2 + \epsilon)}$$

### Scale and Shift:

$$y_i = \gamma \hat{x}_i + \beta$$

- $\gamma, \beta$ : learnable parameters

## Dropout

### Training:

$$a^{(1)} = a^{(1)} \odot m^{(1)} / p$$

- $m^{(i)}$ : binary mask (Bernoulli(p))
  - $p$ : keep probability
- 

## Clustering Mathematics

### K-Means

#### Objective Function:

$$J = \sum_{i=1}^n \sum_{k=1}^K r_{ik} \|x_i - \mu_k\|^2$$

- $r_{ik}$ : 1 if  $x_i$  belongs to cluster  $k$ , 0 otherwise

#### Update Rules:

$$\begin{aligned} \mu_k &= (\sum_i r_{ik} x_i) / (\sum_i r_{ik}) \quad (\text{centroid update}) \\ r_{ik} &= 1 \text{ if } k = \underset{j}{\operatorname{argmin}} \|x_i - \mu_j\|^2 \quad (\text{assignment}) \end{aligned}$$

### DBSCAN

#### Core Point:

$$|N_\epsilon(p)| \geq \text{minPts}$$

- $N_\epsilon(p) = \{q \in D \mid \text{dist}(p, q) \leq \epsilon\}$

#### Density-Reachable:

- $p$  is reachable from  $q$  if there's a chain of core points

## Gaussian Mixture Models

### Probability Model:

$$p(x) = \sum_{k=1}^K \pi_k \times N(x \mid \mu_k, \Sigma_k)$$

### E-step (Expectation):

$$\gamma_{ik} = (\pi_k \times N(x_i | \mu_k, \Sigma_k)) / (\sum_j \pi_j \times N(x_i | \mu_j, \Sigma_j))$$

**M-step** (Maximization):

$$\pi_k = (1/n) \times \sum_i \gamma_{ik}$$

$$\mu_k = (\sum_i \gamma_{ik} x_i) / (\sum_i \gamma_{ik})$$

$$\Sigma_k = (\sum_i \gamma_{ik} (x_i - \mu_k)(x_i - \mu_k)^T) / (\sum_i \gamma_{ik})$$

---

## Dimensionality Reduction Mathematics

### Principal Component Analysis (PCA)

**Objective:** Find projection that maximizes variance

**Covariance Matrix:**

$$C = (1/n) \times X^T X$$

**Eigendecomposition:**

$$C = V \Lambda V^T$$

- $V$ : eigenvectors (principal components)
- $\Lambda$ : eigenvalues (diagonal matrix)

**Projection:**

$$Z = X V_k$$

- $V_k$ : first  $k$  eigenvectors

**Reconstruction:**

$$\hat{X} = Z V_k^T$$

**Explained Variance Ratio:**

$$EVR = \lambda_i / \sum_j \lambda_j$$

### Linear Discriminant Analysis (LDA)

**Between-class Scatter:**

$$S_B = \sum_k n_k (\mu_k - \mu)(\mu_k - \mu)^T$$

### Within-class Scatter:

$$S_W = \sum_k \sum_{i \in C_k} (x_i - \mu_k)(x_i - \mu_k)^T$$

### Objective:

$$\text{maximize: } (w^T S_B w) / (w^T S_W w)$$

**Solution:** Eigenvectors of  $S_W^{-1} S_B$

## t-SNE

### Joint Probability (High-dimensional):

$$p_{i,j} = (p_{j|i} + p_{i|j}) / (2n)$$

where:

$$p_{j|i} = \exp(-||x_i - x_j||^2 / (2\sigma_i^2)) / \sum_{k \neq i} \exp(-||x_i - x_k||^2 / (2\sigma_i^2))$$

### Joint Probability (Low-dimensional):

$$q_{i,j} = (1 + ||y_i - y_j||^2)^{-1} / \sum_{k \neq i} (1 + ||y_i - y_k||^2)^{-1}$$

### Cost Function (KL divergence):

$$C = KL(P||Q) = \sum_i \sum_j p_{i,j} \log(p_{i,j}/q_{i,j})$$

## Evaluation Metrics Mathematics

### Classification Metrics

#### Confusion Matrix Elements:

- TP: True Positives
- TN: True Negatives
- FP: False Positives
- FN: False Negatives



## Accuracy:

$$\text{Accuracy} = (TP + TN) / (TP + TN + FP + FN)$$

## Precision:

$$\text{Precision} = TP / (TP + FP)$$

## Recall (Sensitivity, True Positive Rate):

$$\text{Recall} = TP / (TP + FN)$$

## Specificity (True Negative Rate):

$$\text{Specificity} = TN / (TN + FP)$$

## F1 Score:

$$F1 = 2 \times (\text{Precision} \times \text{Recall}) / (\text{Precision} + \text{Recall})$$

## F-beta Score:

$$F\beta = (1 + \beta^2) \times (\text{Precision} \times \text{Recall}) / ((\beta^2 \times \text{Precision}) + \text{Recall})$$

## Matthews Correlation Coefficient:

$$MCC = (TP \times TN - FP \times FN) / \sqrt{(TP + FP)(TP + FN)(TN + FP)(TN + FN)}$$

## ROC and AUC

**ROC Curve:** Plot of TPR vs FPR at various thresholds

**AUC** (Area Under ROC Curve):

$$AUC = \int_0^1 TPR(FPR) \, dFPR$$

**Approximation** (Trapezoidal Rule):

$$AUC \approx \sum_i \frac{1}{2} (TPR_i + TPR_{i+1}) (FPR_{i+1} - FPR_i)$$

## Regression Metrics

## **R<sup>2</sup> Score** (Coefficient of Determination):

$$R^2 = 1 - (SS_{\text{res}}/SS_{\text{tot}})$$

where:

$$SS_{\text{res}} = \sum_i (y_i - \hat{y}_i)^2 \quad (\text{residual sum of squares})$$

$$SS_{\text{tot}} = \sum_i (y_i - \bar{y})^2 \quad (\text{total sum of squares})$$

## **Adjusted R<sup>2</sup>:**

$$R^2_{\text{adj}} = 1 - [(1-R^2)(n-1)/(n-p-1)]$$

- p: number of predictors

## **Mean Absolute Percentage Error (MAPE):**

$$\text{MAPE} = (100/n) \times \sum_i |y_i - \hat{y}_i|/|y_i|$$

## **Clustering Metrics**

### **Silhouette Score:**

$$s(i) = (b(i) - a(i))/\max(a(i), b(i))$$

where:

- a(i): average distance to points in same cluster
- b(i): minimum average distance to points in other clusters

### **Davies-Bouldin Index:**

$$DB = (1/k) \times \sum_{i=1}^k \max_{j \neq i} [(\sigma_i + \sigma_j)/d(c_i, c_j)]$$

- $\sigma_i$ : average distance of points in cluster i to centroid
- $d(c_i, c_j)$ : distance between centroids

### **Calinski-Harabasz Index:**

$$CH = [\text{tr}(B_k)/(k-1)] / [\text{tr}(W_k)/(n-k)]$$

- $B_k$ : between-group dispersion matrix

- $W_k$ : within-group dispersion matrix
- 

## Additional Important Formulas

### Regularization

**Elastic Net** ( $L1 + L2$ ):

$$J(\theta) = L(\theta) + \lambda_1 ||\theta||_1 + \lambda_2 ||\theta||_2^2$$

### Distance Metrics

**Euclidean Distance:**

$$d(x, y) = \sqrt{\sum_i (x_i - y_i)^2}$$

**Manhattan Distance:**

$$d(x, y) = \sum_i |x_i - y_i|$$

**Cosine Similarity:**

$$\cos(x, y) = (x \cdot y) / (||x||_2 \times ||y||_2)$$

**Minkowski Distance:**

$$d(x, y) = (\sum_i |x_i - y_i|^p)^{1/p}$$

### Bias-Variance Decomposition

**Total Error:**

$$E[(y - \hat{y})^2] = \text{Bias}^2 + \text{Variance} + \text{Irreducible Error}$$

where:

$$\text{Bias} = E[\hat{y}] - y$$

$$\text{Variance} = E[(\hat{y} - E[\hat{y}])^2]$$

### Cross-Validation Error

**k-Fold CV Error:**

$$CV(k) = (1/k) \times \sum_{i=1}^k L(h_i, D_i)$$

- $h_i$ : model trained on all folds except  $i$
  - $D_i$ : validation data from fold  $i$
- 

## Time Series Analysis

### Autoregressive (AR) Model

$$y_t = c + \sum_{i=1}^p \phi_i y_{t-i} + \varepsilon_t$$

- $\phi_i$ : AR coefficients
- $p$ : order of AR model

### Moving Average (MA) Model

$$y_t = \mu + \varepsilon_t + \sum_{i=1}^q \theta_i \varepsilon_{t-i}$$

- $\theta_i$ : MA coefficients
- $q$ : order of MA model

### ARIMA Model

$$(1 - \sum_{i=1}^p \phi_i L^i)(1-L)^d y_t = (1 + \sum_{i=1}^q \theta_i L^i) \varepsilon_t$$

- $L$ : lag operator
- $d$ : degree of differencing

### Exponential Smoothing

**Simple:**  $\alpha y_t + (1-\alpha)\hat{y}_{t-1}$  **Double:**  $\alpha y_t + (1-\alpha)(\hat{y}_{t-1} + \hat{b}_{t-1})$  **Triple (Holt-Winters):** Includes seasonal component

### Autocorrelation Function (ACF)

$$\rho_k = \text{Cov}(y_t, y_{t-k}) / \text{Var}(y_t)$$

### Partial Autocorrelation Function (PACF)

Correlation between  $y_t$  and  $y_{t-k}$  after removing effects of intermediate lags

---

## Bayesian Methods

## Bayes' Rule (Full Form)

$$P(\theta|D) = P(D|\theta)P(\theta) / P(D)$$

- $P(\theta|D)$ : Posterior
- $P(D|\theta)$ : Likelihood
- $P(\theta)$ : Prior
- $P(D)$ : Evidence

## Maximum A Posteriori (MAP)

$$\theta_{\text{MAP}} = \operatorname{argmax}_{\theta} P(\theta|D) = \operatorname{argmax}_{\theta} P(D|\theta)P(\theta)$$

## Bayesian Linear Regression

**Posterior:**

$$P(w|D) = N(w|\mu_n, \Sigma_n)$$

where:

$$\begin{aligned}\Sigma_n &= (\Sigma_0^{-1} + \beta X^T X)^{-1} \\ \mu_n &= \Sigma_n(\Sigma_0^{-1}\mu_0 + \beta X^T y)\end{aligned}$$

## Variational Inference

**ELBO (Evidence Lower Bound):**

$$L(q) = \mathbb{E}_q[\log P(X,Z)] - \mathbb{E}_q[\log q(Z)]$$

## Markov Chain Monte Carlo (MCMC)

**Metropolis-Hastings Accept Probability:**

$$\alpha = \min(1, P(\theta'|D)Q(\theta|\theta') / P(\theta|D)Q(\theta'|\theta))$$

---

## Convolutional Neural Networks

### Convolution Operation

$$(f * g)[n] = \sum_m f[m] \times g[n-m]$$

## 2D Convolution (Images)

$$S(i, j) = (I * K)(i, j) = \sum_m \sum_n I(m, n) K(i-m, j-n)$$

- I: input image
- K: kernel/filter

## Pooling

### Max Pooling:

$$y = \max(x_1, x_2, \dots, x_n) \text{ in pooling window}$$

### Average Pooling:

$$y = (1/n) \sum_i x_i \text{ in pooling window}$$

## Output Size Calculation

$$\text{Output Size} = \lfloor (W - F + 2P) / S \rfloor + 1$$

- W: input size
- F: filter size
- P: padding
- S: stride

## Number of Parameters

**Conv Layer:**  $(F \times F \times C_{in} + 1) \times C_{out}$  **FC Layer:**  $(N_{in} + 1) \times N_{out}$

---

## Recurrent Neural Networks

### Vanilla RNN

$$h_t = \tanh(W_{hh}h_{t-1} + W_{xh}x_t + b_h)$$

$$y_t = W_{hy}h_t + b_y$$

## LSTM (Long Short-Term Memory)

### Forget Gate:

$$f_t = \sigma(W_f \cdot [h_{t-1}, x_t] + b_f)$$

### Input Gate:

$$i_t = \sigma(W_i \cdot [h_{t-1}, x_t] + b_i)$$

$$\tilde{C}_t = \tanh(W_C \cdot [h_{t-1}, x_t] + b_C)$$

### Cell State Update:

$$C_t = f_t * C_{t-1} + i_t * \tilde{C}_t$$

### Output Gate:

$$o_t = \sigma(W_o \cdot [h_{t-1}, x_t] + b_o)$$

$$h_t = o_t * \tanh(C_t)$$

## GRU (Gated Recurrent Unit)

**Update Gate:**  $z_t = \sigma(W_z \cdot [h_{t-1}, x_t])$  **Reset Gate:**  $r_t = \sigma(W_r \cdot [h_{t-1}, x_t])$  **Hidden State:**  $h_t = (1 - z_t)h_{t-1} + z_t \tilde{h}_t$

---

## Transformer Architecture

### Scaled Dot-Product Attention

$$\text{Attention}(Q, K, V) = \text{softmax}(QK^T / \sqrt{d_k})V$$

- Q: Query matrix
- K: Key matrix
- V: Value matrix
- $d_k$ : dimension of keys

### Multi-Head Attention

$$\text{MultiHead}(Q, K, V) = \text{Concat}(\text{head}_1, \dots, \text{head}_h)W^O$$

where:

$$\text{head}_i = \text{Attention}(QW_i^\psi, KW_i^K, VW_i^V)$$

## Positional Encoding

$$PE(pos, 2i) = \sin(pos/10000^{(2i/d\_model)})$$

$$PE(pos, 2i+1) = \cos(pos/10000^{(2i/d\_model)})$$

## Layer Normalization

$$LN(x) = \gamma \times (x - \mu) / \sqrt{\sigma^2 + \epsilon} + \beta$$


---

## Recommender Systems

### Collaborative Filtering

#### Matrix Factorization:

$$R \approx PQ^T$$

- R: user-item rating matrix
- P: user feature matrix
- Q: item feature matrix

#### Objective Function:

$$\min_{\sum (i,j) \in K} (r_{ij} - p_i^T q_j)^2 + \lambda (||p_i||^2 + ||q_j||^2)$$

### Cosine Similarity

$$\text{sim}(u, v) = (\sum_i r_{ui} r_{vi}) / (\sqrt{\sum_i r_{ui}^2} \times \sqrt{\sum_i r_{vi}^2})$$

### Pearson Correlation

$$\text{sim}(u, v) = \sum_i (r_{ui} - \bar{r}_u)(r_{vi} - \bar{r}_v) / \sqrt{(\sum_i (r_{ui} - \bar{r}_u)^2 \times \sum_i (r_{vi} - \bar{r}_v)^2)}$$


---

## Reinforcement Learning Mathematics

### Bellman Equation

#### For Value Function:

$$V(s) = \max_a [R(s, a) + \gamma \sum_{s'} P(s' | s, a) V(s')]$$

#### For Q-Function:



$$Q(s, a) = R(s, a) + \gamma \sum_{s'} P(s' | s, a) \max_{a'} Q(s', a')$$

## Policy Gradient Theorem

$$\nabla \theta J(\theta) = E[\nabla \theta \log \pi_{\theta}(a|s) \times Q_{\pi}(s, a)]$$

## Temporal Difference Learning

**TD(0):**

$$V(s_t) \leftarrow V(s_t) + \alpha [r_{t+1} + \gamma V(s_{t+1}) - V(s_t)]$$

**TD( $\lambda$ ):**

$$V(s) \leftarrow V(s) + \alpha \delta_t e_t(s)$$

where eligibility trace:

$$e_t(s) = \gamma \lambda e_{t-1}(s) + 1(s=s_t)$$

## Actor-Critic

**Critic Update:** Update value function  $V(s)$  **Actor Update:**  $\nabla \theta J = E[\nabla \theta \log \pi_{\theta}(a|s) \times A(s, a)]$  where advantage  $A(s, a) = Q(s, a) - V(s)$

---

## Statistical Hypothesis Testing

### Z-Test

$$z = (\bar{x} - \mu) / (\sigma/\sqrt{n})$$

### T-Test

**One Sample:**

$$t = (\bar{x} - \mu) / (s/\sqrt{n})$$

**Two Sample (Equal Variance):**

$$t = (\bar{x}_1 - \bar{x}_2) / (s_p \sqrt{1/n_1 + 1/n_2})$$

where pooled variance:

$$s_p^2 = ((n_1-1)s_1^2 + (n_2-1)s_2^2) / (n_1+n_2-2)$$

## Chi-Square Test

$$\chi^2 = \sum_i (O_i - E_i)^2 / E_i$$

- $O_i$ : observed frequency
- $E_i$ : expected frequency

## ANOVA F-Statistic

$$F = MSB / MSW = (SSB/(k-1)) / (SSW/(n-k))$$

- MSB: mean square between groups
- MSW: mean square within groups

## p-value

$$p\text{-value} = P(|\text{Test Statistic}| \geq |\text{Observed Value}| \mid H_0)$$

## Ensemble Methods Mathematics

### Bagging

**Bootstrap Sampling:** Sample  $n$  instances with replacement **Aggregation:**  $\hat{y} = (1/B)\sum_{\beta} f_{\beta}(x)$

### AdaBoost

**Sample Weight Update:**

$$w_i^{(t+1)} = w_i^{(t)} \times \exp(-\alpha_i y_i h_i(x_i))$$

**Classifier Weight:**

$$\alpha_i = \frac{1}{2} \log((1-\epsilon_i)/\epsilon_i)$$

**Final Prediction:**

$$H(x) = \text{sign}(\sum_i \alpha_i h_i(x))$$

## Gradient Boosting Mathematics

Pseudo-Residuals:

$$r_{im} = -[\partial L(y_i, f(x_i))/\partial f(x_i)]_{\{f=f_{m-1}\}}$$

Line Search:

$$\gamma_m = \operatorname{argmin}_{\gamma} \sum_i L(y_i, f_{m-1}(x_i) + \gamma h_m(x_i))$$

XGBoost Objective

$$L = \sum_i l(y_i, \hat{y}_i) + \sum_k \Omega(f_k)$$

where:

$$\Omega(f) = \gamma T + \frac{1}{2} \lambda ||w||^2$$

- T: number of leaves
- w: leaf weights

---

Graph Neural Networks

Graph Convolution

$$H^{(l+1)} = \sigma(\tilde{D}^{-1/2} \tilde{A} \tilde{D}^{-1/2} H^{(l)} W^{(l)})$$

- $\tilde{A} = A + I$  (adjacency matrix with self-loops)
- $\tilde{D}$ : degree matrix of  $\tilde{A}$

Message Passing

$$h_i^{(k+1)} = \sigma(w_{self} f(h_i^{(k)}) + \sum_{j \in N(i)} w_{ne i} g_h(h_j^{(k)}))$$

Graph Attention

$$\alpha_{ij} = \operatorname{softmax}_j(\operatorname{LeakyReLU}(a^T [w h_i || w h_j]))$$

---

Advanced Optimization

Newton's Method

$$\theta_{t+1} = \theta_t - H^{-1} \nabla f(\theta_t)$$

- H: Hessian matrix

## L-BFGS

Approximates inverse Hessian using limited memory

## Conjugate Gradient

$$d_{k+1} = -g_{k+1} + \beta_k d_k$$

where:

$$\beta_k = g_{k+1}^T g_{k+1} / g_k^T g_k \text{ (Fletcher-Reeves)}$$

## Natural Gradient

$$\theta_{t+1} = \theta_t - \alpha F^{-1} \nabla L(\theta_t)$$

- F: Fisher Information Matrix
- 

## Sampling Methods

### Rejection Sampling

Accept x with probability:

$$p(\text{accept}) = f(x) / (M \times g(x))$$

### Importance Sampling

$$E_p[f(x)] = E_q[f(x)p(x)/q(x)]$$

### Gibbs Sampling

Sample each variable conditioned on others:

$$x_i^{(t+1)} \sim P(x_i | x_1^{(t+1)}, \dots, x_{i-1}^{(t+1)}, x_{i+1}^{(t)}, \dots, x_n^{(t)})$$


---

## Online Learning

## Stochastic Gradient Descent

$$\theta_{t+1} = \theta_t - \eta_t \nabla l(x_t, y_t, \theta_t)$$

## Online Gradient Descent Regret Bound

$$\text{Regret} \leq ||\theta^*||^2 / (2\eta) + \eta \sum_t ||g_t||^2 / 2$$

## Exponential Weighted Average

$$w_{t+1, i} = w_{t, i} \times \exp(-\eta l_{t, i}) / Z_t$$

---

## Semi-Supervised Learning

### Self-Training Loss

$$L = \sum_l L(x_l, y_l) + \lambda \sum_u L(x_u, \hat{y}_u)$$

### Graph-Based SSL

#### Label Propagation:

$$f_{t+1} = \alpha W f_t + (1-\alpha)y$$

### Co-Training

Train two classifiers on different views:

$$h_1: X_1 \rightarrow Y$$

$$h_2: X_2 \rightarrow Y$$

---

## Probabilistic Graphical Models

### Hidden Markov Models (HMM)

#### Forward Algorithm:

$$\alpha_t(j) = [\sum_i \alpha_{t-1}(i) a_{ij}] \times b_j(o_t)$$

- $a_{ij}$ : transition probability
- $b_j(o_t)$ : emission probability

### Backward Algorithm:

$$\beta_t(i) = \sum_j a_{ij} b_j(o_{t+1}) \beta_{t+1}(j)$$

### Viterbi Algorithm:

$$\delta_t(j) = \max_i [\delta_{t-1}(i) \times a_{ij}] \times b_j(o_t)$$

### Baum-Welch Update:

$$a_{ij} = \sum_t \xi_t(i, j) / \sum_t \gamma_t(i)$$

## Conditional Random Fields (CRF)

$$P(y|x) = (1/Z(x)) \times \exp(\sum_t \sum_k \lambda_k f_k(y_{t-1}, y_t, x, t))$$

- $Z(x)$ : partition function
- $f_k$ : feature functions
- $\lambda_k$ : weights

## Belief Propagation

### Message Update:

$$m_{i \rightarrow j}(x_j) = \sum_{x_i} \psi_i(x_i) \psi_{ij}(x_i, x_j) \prod_{k \in N(i) \setminus j} m_{k \rightarrow i}(x_i)$$

---

## More Probability Distributions

### Poisson Distribution

$$P(X = k) = (\lambda^k e^{-\lambda}) / k!$$

- Mean = Variance =  $\lambda$

### Exponential Distribution

$$f(x) = \lambda e^{-\lambda x} \text{ for } x \geq 0$$

- Mean =  $1/\lambda$
- Variance =  $1/\lambda^2$

## Gamma Distribution

$$f(x) = (\beta^\alpha / \Gamma(\alpha)) \times x^{\alpha-1} e^{-\beta x}$$

## Beta Distribution

$$f(x) = (x^{\alpha-1} (1-x)^{\beta-1}) / B(\alpha, \beta)$$

where  $B(\alpha, \beta) = \Gamma(\alpha)\Gamma(\beta)/\Gamma(\alpha+\beta)$

## Dirichlet Distribution

$$f(x_1, \dots, x_k) = (1/B(\alpha)) \times \prod_i x_i^{\alpha_i-1}$$

## Student's t-Distribution

$$f(x) = \Gamma((v+1)/2) / (\sqrt{v\pi}) \Gamma(v/2) \times (1 + x^2/v)^{-(v+1)/2}$$

## Laplace Distribution

$$f(x) = (1/2b) \times \exp(-|x-\mu|/b)$$

---

## Anomaly Detection

### Gaussian Anomaly Detection

**Anomaly Score:**

$$f(x) = \exp(-\frac{1}{2}(x-\mu)^T \Sigma^{-1}(x-\mu))$$

Anomaly if  $f(x) < \varepsilon$

### Isolation Forest

**Path Length:**

$$h(x) = E[\text{path length to isolate } x]$$

**Anomaly Score:**

$$s(x, n) = 2^{-E(h(x)) / c(n)}$$

## Local Outlier Factor (LOF)

$$\text{LOF}(x) = (\sum_{y \in N(x)} \text{lrd}(y)) / (|N(x)| \times \text{lrd}(x))$$

- lrd: local reachability density

## One-Class SVM

$$\min (1/2) \|w\|^2 + (1/vn) \sum_i \xi_i - \rho$$

subject to:  $w \cdot \phi(x_i) \geq \rho - \xi_i$

## Mahalanobis Distance

$$D(x) = \sqrt{(x - \mu)^T S^{-1} (x - \mu)}$$

---

## Active Learning

### Uncertainty Sampling

**Least Confident:**

$$x^* = \operatorname{argmax}_x [1 - P(\hat{y}|x)]$$

**Margin Sampling:**

$$x^* = \operatorname{argmin}_x [P(\hat{y}_1|x) - P(\hat{y}_2|x)]$$

**Entropy-Based:**

$$x^* = \operatorname{argmax}_x [-\sum_i P(y_i|x) \log P(y_i|x)]$$

### Query by Committee

**Vote Entropy:**

$$x^* = \operatorname{argmax}_x [-\sum_i (V(y_i)/C) \log(V(y_i)/C)]$$

- $V(y_i)$ : votes for class  $i$
- $C$ : committee size

## Expected Model Change



$$x^* = \operatorname{argmax}_x ||\nabla \theta L(\theta; x, y)||$$


---

## Multi-Task Learning

### Hard Parameter Sharing Loss

$$L = \sum_{i=1}^T \alpha_i L_i(f_i(x; \theta_{\text{shared}}, \theta_i), y^{(t)})$$

### Multi-Task Gaussian Process

$$f \sim \text{GP}(\theta, K \otimes K_t)$$

- $K$ : covariance between inputs
- $K_t$ : covariance between tasks

### Task Uncertainty Weighting

$$L = \sum_i (1/2\sigma_i^2) L_i + \log \sigma_i$$


---

## Meta-Learning

### Model-Agnostic Meta-Learning (MAML)

#### Inner Loop:

$$\theta'_i = \theta - \alpha \nabla_{\theta} L_i(f\theta)$$

#### Outer Loop:

$$\theta = \theta - \beta \nabla_{\theta} \sum_i L_i(f\theta'_i)$$

## Prototypical Networks

#### Prototype:

$$c_k = (1/|S_k|) \times \sum_{(x_i, y_i) \in S_k} f\phi(x_i)$$

#### Prediction:

$$P(y=k|x) = \exp(-d(f\phi(x), c_k)) / \sum_k' \exp(-d(f\phi(x), c_k'))$$

## Reptile Algorithm

$$\theta = \theta + \varepsilon(\tilde{\theta} - \theta)$$

where  $\tilde{\theta}$  is obtained after  $k$  steps of SGD

---

## Federated Learning

### FedAvg Algorithm

**Local Update:**

$$w_k^{t+1} = w_k^t - \eta \nabla F_k(w_k^t)$$

**Global Aggregation:**

$$w^{t+1} = \sum_{k=1}^K (n_k/n) w_k^{t+1}$$

## Differential Privacy in FL

$$\tilde{w} = w + N(0, \sigma^2 S^2 I)$$

- $S$ : sensitivity
  - $\sigma$ : noise scale
- 

## Fairness Metrics

### Demographic Parity

$$P(\hat{Y}=1 | A=0) = P(\hat{Y}=1 | A=1)$$

### Equalized Odds

$$P(\hat{Y}=1 | A=0, Y=y) = P(\hat{Y}=1 | A=1, Y=y) \text{ for } y \in \{0, 1\}$$

### Equal Opportunity

$$P(\hat{Y}=1 | A=0, Y=1) = P(\hat{Y}=1 | A=1, Y=1)$$

### Disparate Impact

$$DI = P(\hat{Y}=1|A=0) / P(\hat{Y}=1|A=1)$$

Fair if  $DI \geq 0.8$

## Individual Fairness

$$d(f(x_1), f(x_2)) \leq Ld(x_1, x_2)$$


---

## Causal Inference

### Average Treatment Effect (ATE)

$$\tau = E[Y(1) - Y(0)]$$

### Propensity Score

$$e(x) = P(T=1|X=x)$$

### Inverse Probability Weighting

$$\tau_{IPW} = (1/n) \sum_i [T_i Y_i / e(X_i) - (1-T_i) Y_i / (1-e(X_i))]$$

### Doubly Robust Estimator

$$\tau_{DR} = (1/n) \sum_i [\mu_1(X_i) - \mu_0(X_i) + T_i(Y_i - \mu_1(X_i)) / e(X_i) - (1-T_i)(Y_i - \mu_0(X_i)) / (1-e(X_i))]$$

### Instrumental Variables

$$\beta_{IV} = \text{Cov}(Y, Z) / \text{Cov}(X, Z)$$


---

## Additional Important Concepts

### Rademacher Complexity

$$\hat{R}_n(F) = E_{\sigma}[\sup_{f \in F} (1/n) \sum_i \sigma_i f(x_i)]$$

- $\sigma_i$ : Rademacher random variables

### VC Dimension

For hypothesis class  $H$ :

- $VCD(H)$  = largest set size that can be shattered

## PAC Learning Bound

$$P(|R(h) - \hat{R}(h)| > \epsilon) \leq 2\exp(-2n\epsilon^2)$$

## Margin Theory (SVM)

**Generalization Bound:**

$$R(f) \leq \hat{R}_\gamma(f) + O(\sqrt{(d/\gamma^2 n)})$$

## Spectral Clustering

**Graph Laplacian:**

$$L = D - W$$

**Normalized Laplacian:**

$$L_{\text{norm}} = I - D^{-1/2} W D^{-1/2}$$

## Gaussian Processes

**Prior:**

$$f(x) \sim GP(m(x), k(x, x'))$$

**Posterior:**

$$f^* | X, y, X^* \sim N(\mu^*, \Sigma^*)$$

where:

$$\mu^* = K^{*T} (K + \sigma^2 I)^{-1} y$$

$$\Sigma^* = K^{**} - K^{*T} (K + \sigma^2 I)^{-1} K^*$$

## Variational Autoencoders (VAE)

**ELBO:**

$$\mathcal{L} = \mathbb{E}_{q(z|x)} [\log p(x|z)] - KL(q(z|x) || p(z))$$

# Generative Adversarial Networks (GAN)

## Objective:

$$\min_G \max_D V(D, G) = \mathbb{E}_{x \sim p_{\text{data}}} [\log D(x)] + \mathbb{E}_{z \sim p_z} [\log(1 - D(G(z)))]$$

## Wasserstein Distance

$$W(P, Q) = \inf_{\gamma \in \Pi(P, Q)} \mathbb{E}_{(x, y) \sim \gamma} [\|x - y\|]$$

---

# Modern Deep Learning Methods

## Diffusion Models

### Forward Process (Adding Noise):

$$q(x_t | x_{t-1}) = N(x_t; \sqrt{1 - \beta_t} x_{t-1}, \beta_t I)$$
$$q(x_t | x_0) = N(x_t; \sqrt{\bar{\alpha}_t} x_0, (1 - \bar{\alpha}_t) I)$$

where  $\bar{\alpha}_t = \prod_{s=1}^t \alpha_s$  and  $\alpha_t = 1 - \beta_t$

### Reverse Process (Denoising):

$$p_\theta(x_{t-1} | x_t) = N(x_{t-1}; \mu_\theta(x_t, t), \Sigma_\theta(x_t, t))$$

### Training Objective (Simplified):

$$L = \mathbb{E}_{t, x_0, \epsilon} [\|\epsilon - \epsilon_\theta(\sqrt{\bar{\alpha}_t} x_0 + \sqrt{1 - \bar{\alpha}_t} \epsilon, t)\|^2]$$

### Score Matching:

$$\mathcal{J}(\theta) = \frac{1}{2} \mathbb{E}_{x, t} [\|s_\theta(x, t) - \nabla_x \log p_t(x)\|^2]$$

### DDPM Sampling:

$$x_{t-1} = 1/\sqrt{\alpha_t} (x_t - (1 - \alpha_t)/\sqrt{1 - \bar{\alpha}_t} \epsilon_\theta(x_t, t)) + \sigma_t z$$

## Normalizing Flows

### Change of Variables:

$$\log p(x) = \log p(z) - \log |\det(\partial f / \partial x)|$$

## Flow Transformation:

$$x = f(z) \text{ where } z \sim p(z)$$

## Planar Flow:

$$f(z) = z + u h(w^T z + b)$$

## Real NVP Coupling Layer:

$$\begin{aligned} y_{1:d} &= x_{1:d} \\ y_{d+1:D} &= x_{d+1:D} \odot \exp(s(x_{1:d})) + t(x_{1:d}) \end{aligned}$$

## Glow Objective:

$$\log p(x) = \log p(z) + \sum_i \log |\det(J_i)|$$

## Contrastive Learning

### InfoNCE Loss:

$$L = -\log[\exp(\text{sim}(z_i, z_j)/\tau) / \sum_{k=1}^{2^N} \mathbb{1}[k \neq i] \exp(\text{sim}(z_i, z_k)/\tau)]$$

- $\text{sim}(u, v) = u^T v / (\|u\| \cdot \|v\|)$
- $\tau$ : temperature parameter

### SimCLR Objective:

$$l(i, j) = -\log[\exp(\text{sim}(z_i, z_j)/\tau) / \sum_{k=1}^{2^N} \mathbb{1}[k \neq i] \exp(\text{sim}(z_i, z_k)/\tau)]$$

### MoCo (Momentum Contrast):

$$\theta_k \leftarrow m\theta_k + (1-m)\theta_q$$

- $m$ : momentum coefficient (e.g., 0.999)

### CLIP Loss:

$$L = -\frac{1}{2} \sum_i N [\log(\exp(\text{sim}(I_i, T_i)/\tau) / \sum_j \exp(\text{sim}(I_i, T_j)/\tau)) + \log(\exp(\text{sim}(I_i, T_i)/\tau) / \sum_j \exp(\text{sim}(I_j, T_i)/\tau))]$$

## Vision Transformers (ViT)

### Patch Embedding:

$$z_o = [x_{class}; x^1 pE; x^2 pE; \dots; x^N pE] + E_{pos}$$

- $x^p$ : flattened patch
- $E$ : embedding projection
- $E_{pos}$ : position embeddings

### Patch Size Calculation:

$$N = HW/P^2 \text{ patches}$$

- $H, W$ : image height, width
- $P$ : patch size

## Neural ODEs

### Continuous Dynamics:

$$dh(t)/dt = f(h(t), t, \theta)$$

### Forward Pass:

$$h(t_1) = h(t_0) + \int_{t_0}^{t_1} f(h(t), t, \theta) dt$$

### Adjoint Sensitivity Method:

$$da(t)/dt = -a(t)^T \partial f / \partial h$$

$$dL/d\theta = -\int_{t_1}^{t_0} a(t)^T \partial f / \partial \theta dt$$

---

## Advanced Reinforcement Learning

### Multi-Armed Bandits

#### Upper Confidence Bound (UCB):

$$A_t = \operatorname{argmax}_a [\hat{Q}_t(a) + c\sqrt{\ln t / N_t(a)}]$$

- $N_t(a)$ : times action  $a$  selected
- $c$ : exploration constant

## Thompson Sampling:

$$\theta_a \sim \text{Beta}(\alpha_a, \beta_a)$$

$$A_t = \operatorname{argmax}_a \theta_a$$

## $\epsilon$ -Greedy:

$$A_t = \begin{cases} \operatorname{argmax}_a \hat{Q}_t(a) & \text{with prob } 1-\epsilon \\ \text{random action} & \text{with prob } \epsilon \end{cases}$$

## Exp3 (Exponential-weight for Exploration):

$$p_t(a) = (1-\gamma)w_t(a)/W_t + \gamma/K$$

## Soft Actor-Critic (SAC)

### Soft Value Function:

$$V(s) = E_{a \sim \pi}[Q(s, a) - \alpha \log \pi(a|s)]$$

### Soft Q-Function:

$$Q(s, a) = r + \gamma E_{s'}[V(s')]$$

### Policy Objective:

$$J(\pi) = E_{s \sim \mathcal{D}, \epsilon \sim \pi}[\alpha \log \pi(f(\epsilon; s)|s) - Q(s, f(\epsilon; s))]$$

### Entropy Temperature Update:

$$\alpha \leftarrow \operatorname{argmin}_\alpha E_{a \sim \pi}[-\alpha \log \pi(a|s) - \alpha H]$$

## Trust Region Policy Optimization (TRPO)

### Surrogate Objective:

$$L(\theta) = E_{s, a}[\pi\theta(a|s)/\pi\theta_{\text{old}}(a|s) \times A^\pi(s, a)]$$

### KL Constraint:



$$E_{s \sim \rho} \pi[\text{KL}(\pi_{\theta_{\text{ola}}}(\cdot | s) || \pi_{\theta}(\cdot | s))] \leq \delta$$

## Natural Policy Gradient:

$$\theta_{k+1} = \theta_k + \sqrt{(2\delta/g^T F g)} \times F^{-1} g$$

- F: Fisher information matrix
- g: policy gradient

## Proximal Policy Optimization (PPO)

### Clipped Objective:

$$L(\theta) = E[\min(r_t(\theta)A_t, \text{clip}(r_t(\theta), 1-\epsilon, 1+\epsilon)A_t)]$$

where  $r_t(\theta) = \pi_{\theta}(a_t|s_t)/\pi_{\theta_{\text{ola}}}(a_t|s_t)$

---

## Specialized Machine Learning Areas

### Survival Analysis

#### Hazard Function:

$$h(t) = \lim_{\Delta t \rightarrow 0} P(t \leq T < t + \Delta t \mid T \geq t) / \Delta t$$

#### Survival Function:

$$S(t) = P(T > t) = \exp(-\int_0^t h(u)du)$$

#### Cox Proportional Hazards:

$$h(t|x) = h_0(t)\exp(\beta^T x)$$

#### Partial Likelihood:

$$L(\beta) = \prod_{i=1}^n [\exp(\beta^T x_i) / \sum_{j \in R(t_i)} \exp(\beta^T x_j)]^{\delta_i}$$

#### Kaplan-Meier Estimator:

$$\hat{S}(t) = \prod_{i:t_i \leq t} [(n_i - d_i)/n_i]$$

## Learning to Rank

### RankNet Loss:

$$L = -\sum_{i,j} \bar{P}_{ij} \log P_{ij} + (1 - \bar{P}_{ij}) \log(1 - P_{ij})$$

where  $P_{ij} = 1/(1 + \exp(-(s_i - s_j)))$

### LambdaRank Gradient:

$$\lambda_{ij} = -\sigma/(1 + \exp(\sigma(s_i - s_j))) \times |\Delta \text{NDCG}_{ij}|$$

### ListNet Loss:

$$L = -\sum_i P(\pi_i | y) \log P(\pi_i | s)$$

### NDCG (Normalized Discounted Cumulative Gain):

$$\text{NDCG}@k = \text{DCG}@k / \text{IDCG}@k$$

$$\text{DCG}@k = \sum_{i=1}^k (2^{\text{rel}_i} - 1) / \log_2(i + 1)$$

## Calibration Methods

### Platt Scaling:

$$P(y=1|f(x)) = 1/(1 + \exp(Af(x) + B))$$

### Temperature Scaling:

$$\hat{q}_i = \text{softmax}(z_i/T)$$

### Isotonic Regression: Fit monotonic function $m: \mathbb{R} \rightarrow [0,1]$

$$\min \sum_i w_i (y_i - m(f_i))^2 \text{ s.t. } m \text{ monotonic}$$

### Expected Calibration Error (ECE):

$$\text{ECE} = \sum_{m=1}^M |B_m|/n |\text{acc}(B_m) - \text{conf}(B_m)|$$

## Domain Adaptation

### Domain Adversarial Loss:

$$L = L_v(\theta_f, \theta_y) - \lambda L_d(\theta_f, \theta_d)$$

- $L_v$ : task loss
- $L_d$ : domain classifier loss

### Maximum Mean Discrepancy (MMD):

$$\text{MMD}^2(X, Y) = ||\mathbb{E}[\phi(x)] - \mathbb{E}[\phi(y)]||^2_{\mathcal{H}}$$

### CORAL Loss:

$$L_{\text{CORAL}} = (1/4d^2) ||C_s - C_t||^2_F$$

- $C_s, C_t$ : source/target covariance matrices

### Wasserstein Distance (for DA):

$$W(P_s, P_t) = \inf_{\gamma \in \Pi} \mathbb{E}(x_s, x_t)_{\sim \gamma} [||x_s - x_t||]$$

## Optimal Transport

### Kantorovich Problem:

$$W(\mu, \nu) = \min_{\pi \in \Pi(\mu, \nu)} \int c(x, y) d\pi(x, y)$$

### Sinkhorn Algorithm:

$$\begin{aligned} u^{i+1} &= a \oslash (Kv^i) \\ v^{i+1} &= b \oslash (K^T u^{i+1}) \end{aligned}$$

where  $K = \exp(-C/\epsilon)$

### Wasserstein Barycenter:

$$\min_{\mu} \sum_k \lambda_k W_2^2(\mu, \mu_k)$$

### Gromov-Wasserstein Distance:

$$\text{GW}(C_1, C_2) = \min_{\pi} \sum_{i,j,k,l} |C_1(i,k) - C_2(j,l)|^2 \pi_{ij} \pi_{kl}$$

---

## Advanced Theoretical Concepts

## Conformal Prediction

### Prediction Set:

$$C(x) = \{y : s(x,y) \geq \hat{q}\}$$

where  $\hat{q}$  is  $(1-\alpha)$  quantile of scores

### Coverage Guarantee:

$$P(Y \in C(X)) \geq 1 - \alpha$$

### Conformity Score:

$$\begin{aligned} s(x,y) &= -|y - f(x)| && (\text{regression}) \\ s(x,y) &= f(x)[y] && (\text{classification}) \end{aligned}$$

## Advanced Differential Privacy

### Gaussian Mechanism:

$$M(x) = f(x) + N(0, \sigma^2 S^2 f)$$

where  $Sf = \max_{x,x'} \|f(x) - f(x')\|_2$

### Exponential Mechanism:

$$P(M(x) = r) \propto \exp(\epsilon u(x,r)/(2\Delta u))$$

### Rényi Differential Privacy:

$$D_\alpha(P||Q) = (1/(\alpha-1)) \log \mathbb{E}_q[(p(X)/q(X))^\alpha]$$

### Moments Accountant:

$$\alpha M(\lambda) = \max_{\text{aux}} \log \mathbb{E}[\exp(\lambda \cdot \text{priv\_loss}(\text{aux}))]$$

## Advanced Kernel Methods

### String Kernel:

$$K(s,t) = \sum_u \sum_{i:u=[i]} \sum_{j:u=[j]} \lambda^{(|i|+|j|)}$$

## Graph Kernel (Random Walk):

$$K(G_1, G_2) = \sum_{i,j} [I - \lambda W \times]^{-1}_{i,j}$$

## Fisher Kernel:

$$K(x, x') = \nabla \theta \log p(x|\theta)^T F^{-1} \nabla \theta \log p(x'|\theta)$$

## Polynomial Kernel with Offset:

$$K(x, x') = (\alpha x^T x' + c)^d$$

## Capsule Networks

### Squashing Function:

$$v_j = ||s_j||^2 / (1 + ||s_j||^2) \times s_j / ||s_j||$$

### Routing Algorithm:

$$c_{i,j} = \exp(b_{i,j}) / \sum_k \exp(b_{i,k})$$
$$s_j = \sum_i c_{i,j} \hat{u}_j|_i$$

### Agreement Update:

$$b_{i,j} \leftarrow b_{i,j} + \hat{u}_j|_i \cdot v_j$$

---

## Self-Supervised Learning

### Masked Autoencoders (MAE)

#### Reconstruction Loss:

$$L = (1/|M|) \sum_{i \in M} ||x_i - \hat{x}_i||^2$$

- M: set of masked patches

**Masking Strategy:** Random masking with ratio  $r$  (typically 75%)

### BERT Objectives

#### Masked Language Model (MLM):

$$L_{\text{MLM}} = -\mathbb{E}[\sum_{i \in M} \log P(x_i | x_{(-M)})]$$

## Next Sentence Prediction (NSP):

$$L_{\text{NSP}} = -\mathbb{E}[\log P(y | [\text{CLS}], A, B)]$$

## BERT Total Loss:

$$L = L_{\text{MLM}} + L_{\text{NSP}}$$

## GPT Objectives

### Causal Language Modeling:

$$L = -\sum_t \log P(x_t | x_1, \dots, x_{t-1})$$

## Momentum Contrast (MoCo)

### Queue Update:

```
enqueue(queue, kq)
dequeue(queue)
```

### Momentum Update:

$$\theta_k \leftarrow m\theta_k + (1-m)\theta_q$$

### InfoNCE Loss with Queue:

$$L = -\log[\exp(q \cdot k_+ / \tau) / (\exp(q \cdot k_+ / \tau) + \sum_{k-} \exp(q \cdot k_- / \tau))]$$

## BYOL (Bootstrap Your Own Latent)

### Loss (No Negatives):

$$L = ||\bar{q} - z'||^2_2$$

where:

- $\bar{q} = q\theta(z\theta)$  (prediction)
- $z' = z\xi$  (target)

## Target Network Update:

$$\xi \leftarrow \tau \xi + (1-\tau)\theta$$

## SwAV (Swapping Assignments between Views)

### Clustering Assignment:

$$Q = \text{Sinkhorn}(Z/\varepsilon)$$

### Swapped Prediction Loss:

$$L = -\sum_i [q_i^{(1)} \log p_i^{(2)} + q_i^{(2)} \log p_i^{(1)}]$$

---

## Additional Modern Architectures

### EfficientNet Scaling

#### Compound Scaling:

$$\begin{aligned} \text{depth: } d &= \alpha^\phi \\ \text{width: } w &= \beta^\phi \\ \text{resolution: } r &= \gamma^\phi \end{aligned}$$

where  $\alpha \cdot \beta^2 \cdot \gamma^2 \approx 2$

### Squeeze-and-Excitation

#### Squeeze:

$$z_c = (1/HW) \sum_i \sum_j u_c(i,j)$$

#### Excitation:

$$s = \sigma(W_2 \delta(W_1 z))$$

#### Scale:

$$\tilde{x}_c = s_c \cdot u_c$$

## Feature Pyramid Networks

### Top-down Pathway:

$$P_i = \text{Conv}(P_{i+1} \uparrow + C_i)$$

## Focal Loss

$$FL(p_t) = -\alpha_t(1-p_t)^\gamma \log(p_t)$$

where:

$$p_t = \begin{cases} p & \text{if } y = 1 \\ 1-p & \text{otherwise} \end{cases}$$

## IoU Loss

**Standard IoU:**

$$IoU = |A \cap B| / |A \cup B|$$

**GIoU** (Generalized):

$$GIoU = IoU - |C \setminus (A \cup B)| / |C|$$

where C is smallest enclosing box

**DIoU** (Distance):

$$DIoU = IoU - \rho^2(b, b^{gt}) / c^2$$

**CIoU** (Complete):

$$CIoU = IoU - (\rho^2(b, b^{gt}) / c^2 + \alpha v)$$

where v measures aspect ratio consistency