

RC-specific components

Part name	Part number (without " _ ")	Part count
HSP wheel axle 1/10	_02033	4
HSP Hub 1/10	_02014	4
HSP Differential	_02051	1
HSP Dogbone 77 mm	_08060	2
Tires 1/10	-	4
Rims HEX12 1/10	-	4
Shock Absorber 50mm	-	4
Transmitter/receiver combo	-	1
ESC	-	1
Motor	-	1
Motor gear	-	1
Differential gear	-	1

Comment
Use the front version. Or use the rear version with an additional longer shaft. It is sold as 77 mm, but the bore-to-bore measurement is about 72 mm. Outer Diameter approx. 70 - 75 mm. Optional, if you dont want to print rims. One with several different springs and oil dampening is recommended. I use Carson Reflex X1. I use Hobbywing 1060. I use Tamiya Torque Tuned. I use 48 dp 21 t. I use 48 dp 43 t. MAX DIAMATER 2 cm.

Screws, Nuts, Inserts

<i>Part name</i>	<i>length [mm]</i>	<i>partCount</i>	<i>comment</i>
M2 Flat Head	8	1	Everything between 8 and 14 mm works.
M2 Brass Insert	-	1	Depth: 3 mm.
M3 Flat Head	6	2	
	8	12	
	12	8	
	14	4	
	16	4	
	20	8	
	22	6	
	25	2	
	30	2	
	45	4	
	60	6	
M3 Socket Head	18	2	
	20	2	
M3 Ultra Thin Head	8	4	Everything between 8 and 10 mm works.
M3 Brass Insert	-	26	Depth: 5.7 mm .
M3 Lock Nut	-	18	
M3 Square Nut		2	
M3 Washer		25	"Best looking" diameter: 6.7 mm.
M4 Socket Head	16	4	
M4 Lock Nut	-	8	
M4 Washer	-	4	Diameter must be smaller than 12 mm.