HelixQL (Text to SQL)

SWE3004 – Software Design and Development Project

Submitted in partial fulfillment of the requirements for the degree of

Master of Technology in Software Engineering

in

Department of Software and Systems Engineering

by

Ansh Vohra
22MIS0499

Under the guidance of

Prof. Sweta Bhattacharya
Associate Professor, SCORE



School of Computer Science Engineering and Information Systems
VIT, Vellore

October, 2026

DECLARATION

I hereby declare that the SWE3004 - Software Design and Development Project entitled “HelixQL (Text to SQL)” submitted by me, for the award of the degree of Master of Technology in Software Engineering in Department of Software and Systems Engineering, School of Computer Science Engineering and Information Systems to VIT is a record of bonafide work carried out by me under the supervision of Prof. Sweta Bhattacharya, Associate Professor, SCORE, VIT, Vellore.

I further declare that the work reported in this project has not been submitted and will not be submitted, either in part or in full, for the award of any other degree or diploma in this institute or any other institute or university.

Place: Vellore

Date: Signature of the Candidate

CERTIFICATE

This is to certify that the SWE3004 - Software Design and Development Project entitled “HelixQL (Text to SQL)” submitted by Ansh Vohra & 22MIS0499, SCORE, VIT, for the award of the degree of Master of Technology in Software Engineering in Department of Software and Systems Engineering, is a record of bonafide work carried out by him under my supervision during the period, 06.07.2026 to 03.11.2026, as per the VIT code of academic and research ethics.

The contents of this report have not been submitted and will not be submitted either in part or in full, for the award of any other degree or diploma in this institute or any other institute or university. The project fulfills the requirements and regulations of the University and in my opinion meets the necessary standards for submission.

Place: Vellore

Date:

Signature of the VIT-SCORE - Guide

Internal Examiner External Examiner

Head of the Department

Department of Software and Systems Engineering

ACKNOWLEDGEMENT

It is my pleasure to express with a deep sense of gratitude to my Project guide Prof. Sweta Bhattacharya, Associate Professor, School of Computer Science Engineering and Information Systems, Vellore Institute of Technology, Vellore for her constant guidance, continual encouragement, in my endeavor. My association with her is not confined to academics only, but it is a great opportunity on my part to work with an intellectual and an expert in the field of AI and Natural Language Processing.

I would like to express my heartfelt gratitude to Honorable Chancellor Dr. G Viswanathan; respected Vice Presidents Dr. Sankar Viswanathan, Dr. Sekar Viswanathan, Vice Chancellor Dr. V. S. Kanchana Bhaaskaran; Pro-Vice Chancellor Dr. Partha Sharathi Mallick; and Registrar Dr. Jayabarathi T.

My whole-hearted thanks to Dean Dr. Daphne Lopez, School of Computer Science Engineering and Information Systems, Head, Department of Software and Systems Engineering Dr. Thanapal P, MTech - Software Engineering Project Coordinators Dr. Thilagavathi M and Dr. Brijendra Singh, SCORE School Project Coordinator Dr. Karthikeyan P, all faculty, staff and members working as limbs of our university for their continuous guidance throughout my course of study in unlimited ways.

It is indeed a pleasure to thank my parents and friends who persuaded and encouraged me to take up and complete my project successfully. Last, but not least, I express my gratitude and appreciation to all those who have helped me directly or indirectly towards the successful completion of the project.

Place: Vellore Ansh Vohra

Date:

EXECUTIVE SUMMARY

HelixQL is a secure Text-to-SQL system that lets business users query relational databases in plain English without exposing confidential records to a cloud language model. Its three tiers, a native Electron desktop client, a FastAPI translation gateway and a Next.js control plane, split the pipeline into two isolated zones. The desktop client connects to MySQL or PostgreSQL inside the organisation's firewall, extracts the schema locally and sends the gateway only the question and empty CREATE TABLE blueprints for the few relevant tables. Generated SQL is parsed by SQLGlot into an Abstract Syntax Tree and accepted only if it is a single read-only SELECT. It is then verified with EXPLAIN, and runtime errors trigger a bounded self-correction loop of at most three attempts. A Beta mode adds confirmed insert, update and delete through structured write plans. The platform passes 349 automated tests, and AST validation averages about 0.5 ms per query.

CONTENTS

Acknowledgement ..... **iv**
Executive Summary ..... **v**
Table of Contents ..... **vi**
List of Figures ..... **ix**
List of Tables ..... **x**
Abbreviations ..... **xii**
Symbols and Notations ..... **xiv**

1 INTRODUCTION **1**
1.1 Objective 1
1.2 Motivation 2
1.3 Background 3
1.4 Organisation of the Report 5
2 DISSERTATION DESCRIPTION AND GOALS **7**
2.1 Problem Statement 7
2.2 Objectives 7
2.3 Scope of the Project 8
2.4 Proposed System 9
2.5 Literature Survey 10
2.6 Findings in Literature Survey 12
2.7 Goals and Success Criteria 13
2.8 Stakeholders and Usage Scenarios 13
2.9 Assumptions and Dependencies 14
3 TECHNICAL SPECIFICATION **15**
3.1 Functional Requirements 15
3.2 Non-Functional Requirements 16
3.3 Technology Stack 16
3.4 Hardware and Software Environment 17
3.5 Interface Specification 18
3.6 Data Model 18
3.7 Configuration Parameters 19
3.8 Error Vocabulary 20
3.9 Use Case Descriptions 20
3.10 Request and Response Formats 21
3.11 Security Requirements in Detail 22
4 DESIGN APPROACH AND DETAILS **23**

4.1 Design Approach / Materials and Methods....23
4.2 Constraints, Alternatives and Tradeoffs....36
4.3 Threat Model and Mitigations....37
4.4 Result Presentation and Diagnostics Design....38
4.5 Case-Insensitive Text Matching....38
4.6 Engine Abstraction and Retry Policy....39
4.7 Embedding Service....40
5 SCHEDULE, TASKS AND MILESTONES....41
5.1 Project Plan....41
5.2 Task Breakdown....41
5.3 Milestones....42
5.4 Risk Management....43
6 DISSERTATION DEMONSTRATION....44
6.1 Environment Setup....44
6.2 User Walkthrough....45
6.3 Sample Code....47
6.4 Testing Strategies....49
6.5 Deployment and Distribution....51
6.6 Worked Example: One Question End to End....51
7 COST ANALYSIS, RESULTS AND DISCUSSION....54
7.1 Test Results....54
7.2 Guardrail Latency....54
7.3 Data Exposure Reduction....55
7.4 Cost Analysis....56
7.5 Discussion....58
7.6 Comparison with Alternative Approaches....59
8 HELIXQL BETA VERSION....60
8.1 Motivation and Design Challenge....60
8.2 Guarantees....60
8.3 Components and Architecture....61
8.4 How a Turn Is Routed....62
8.5 The Write Path End to End....63
8.6 Gateway: The Write Planner....64
8.7 Client: Validating a Plan and Building the SQL....66
8.8 Preview and Confirmation....67
8.9 Execution....68
8.10 Schema Metadata Beta Depends On....69

8.11 Privacy: What Leaves the Machine....69
8.12 Error Codes....70
8.13 Limits and Configuration....70
8.14 Limitations of Beta....71
8.15 Testing the Beta Mode....71
8.16 Changing Beta Safely....72
9 SUMMARY....73
9.1 Findings....73
9.2 Recommendations and Future Work....74
REFERENCES....75
APPENDIX A ADDITIONAL MATERIAL....

LIST OF FIGURES

Figure No.	Title	Page No.
4.1	HelixQL System Architecture	24
4.2	Use Case Diagram of HelixQL	26
4.3	Class Diagram of HelixQL	27
4.4	Sequence Diagram of a Natural-Language Query	28
4.5	Activity Diagram of the Query Pipeline	29
6.1	Authentication Page of the Desktop Application	45
6.2	Home Page where the User Connects to the Database	46
6.3	Query Page with Generated SQL, Results and Diagnostics	47
8.1	HelixQL Beta System Architecture	62

LIST OF TABLES

Table No.	Title	Page No.
2.1	The Three Tiers of HelixQL	9
2.2	Summary of Literature Survey	10
2.3	Capability Comparison of HelixQL with Surveyed Approaches	12
2.4	Project Goals and Success Criteria	13
2.5	Stakeholders and Their Needs	13
3.1	Functional Requirements	15
3.2	Non-Functional Requirements	16
3.3	Technology Stack	16
3.4	Development and Deployment Environment	17
3.5	Gateway Endpoints	18
3.6	Control Plane Collections	18
3.7	Key Configuration Parameters	19
3.8	Principal Error Codes	20
3.9	Principal Use Case Descriptions	20
4.1	What Crosses the Privacy Boundary	25
4.2	Lexical Scoring Rules	31
4.3	Design Decisions, Alternatives and Trade-offs	36
4.4	Threats and Mitigations	37
5.1	Project Phases and Deliverables	41
5.2	Task Breakdown by Tier	42
5.3	Milestones and Reviews	42
5.4	Risks and Mitigations	43
6.1	Automated Test Suites by Tier	49
6.2	Guardrail Adversarial Catalogue	50
7.1	Goals Versus Verification Results	54
7.2	Guardrail Timing Measurement	55
7.3	Information Sent for the Sample Database	56
7.4	Operating Cost Components	56
7.5	Subscription Plans Defined in the Product	57
7.6	Qualitative Comparison with Alternatives	59
8.1	Beta Guarantees	60
8.2	Beta Components and Responsibilities	62
8.3	Stages of a Beta Delete	64
8.4	Write-Plan Parser Outcomes	65

8.5 Value Coercion by Column Type....66
8.6 Additional Schema Metadata....69
8.7 Beta Error Codes....70
8.8 Beta Limits....70
8.9 Beta Test Suites....71
9.1 Common Problems and Causes....78

LIST OF ABBREVIATIONS

AES	Advanced Encryption Standard
API	Application Programming Interface
AST	Abstract Syntax Tree
BGE	BAAI General Embedding
CRUD	Create, Read, Update, Delete
CSV	Comma-Separated Values
CTE	Common Table Expression
DB	Database
DBMS	Database Management System
DDL	Data Definition Language
DML	Data Manipulation Language
DoS	Denial of Service
FK	Foreign Key
FR	Functional Requirement
GCM	Galois/Counter Mode
HMAC	Hash-based Message Authentication Code
HTTP	Hypertext Transfer Protocol
HTTPS	Hypertext Transfer Protocol Secure
IPC	Inter-Process Communication
JSON	JavaScript Object Notation
LLM	Large Language Model
MTEB	Massive Text Embedding Benchmark
NFR	Non-Functional Requirement
NL	Natural Language
NLP	Natural Language Processing
ORM	Object-Relational Mapping
OWASP	Open Web Application Security Project
PK	Primary Key
RAG	Retrieval Augmented Generation
REST	Representational State Transfer
SMTP	Simple Mail Transfer Protocol
SQL	Structured Query Language
SRS	Software Requirements Specification
TLS	Transport Layer Security

TTL	Time To Live
UI	User Interface
UML	Unified Modeling Language
VPC	Virtual Private Cloud

SYMBOLS AND NOTATIONS

q	User question (natural-language query)
T	A table in the local schema blueprint
t	A token extracted from the question
w(t, T)	Lexical weight contributed by token t to table T
S_lex	Lexical score of a table
S_sem	Semantic points of a table
S	Final hybrid score of a table
s	Cosine similarity between question and table embeddings
f	Semantic floor (0.45)
W	Semantic weight (9 points)
a, b	Embedding vectors
k	Number of self-correction attempts
K	Maximum self-correction attempts (3)
B_data	Size of the database contents in bytes
B_sent	Size of the schema blueprint sent to the gateway in bytes
ρ	Data-exposure reduction ratio
T_total	End-to-end latency of one question
N_rows	Row count of a write preview
N_exp	Expected affected-row count recorded at preview time
N_aff	Affected-row count reported by the database on execution

CHAPTER 1
INTRODUCTION

Organisations today store the most valuable part of their operational knowledge in relational databases. Sales, inventory, payments, human resources and customer support records all live in tables that can be interrogated with the Structured Query Language (SQL). SQL is expressive and precise, but it is also a specialist skill. A regional manager who wants to know which state produced the most orders last quarter must usually wait for a data analyst to write, test and run a query on their behalf. That hand-off is slow, it consumes scarce analyst time, and it turns a simple question into a ticket in a queue.

Recent progress in Large Language Models (LLMs) has made it practical to remove that hand-off. A Natural Language to SQL (Text-to-SQL) system accepts a question written in ordinary English, reads a description of the database structure, and produces an executable query. Benchmarks and commercial products have shown that modern models can translate a surprisingly wide range of business questions correctly (Gao et al., 2023; Pourreza & Rafiei, 2023). However, the same capability introduces risks that matter greatly in enterprise settings. The model usually lives in a cloud service that the organisation does not control, so any data placed in the prompt leaves the organisation. The model is also a probabilistic text generator, so its output may be wrong, may refer to columns that do not exist, or, in the worst case, may contain a statement that deletes or alters data.

HelixQL is a Text-to-SQL platform designed around these two risks. Its central idea is that the language model should be given only what it needs to write a query, namely the question and the empty structure of the relevant tables, and that nothing the model returns should be trusted until it has been structurally verified. The real data never leaves the machine on which the database is reachable. This report describes the motivation, the design, the implementation and the evaluation of HelixQL, and it documents an experimental Beta mode that extends the system from read-only querying to carefully controlled data modification.

1.1 Objective

The primary objective of this project is to develop a secure, privacy-preserving natural-language interface for relational databases that utilises Large Language Models

and programmatic validation techniques to let non-technical users retrieve information safely. The project aims to deliver the following outcomes:

- A native desktop application that connects to MySQL and PostgreSQL databases from inside the organisation's network and presents results, SQL, execution plans and diagnostics to the user.
- A stateless cloud gateway that converts a question plus schema-only context into a single verified, read-only SQL statement.
- A control plane that handles account registration, email verification, API token issuance, subscription plans and monthly usage metering.
- A structural security layer, based on Abstract Syntax Tree analysis, that rejects every data-mutating or unsafe construct before a query is allowed to reach a database.
- A bounded self-correction loop that repairs queries rejected by the database without exposing data and without letting the model run indefinitely.
- An experimental Beta mode that supports insert, update and delete through a structured, confirmed and reversible-on-failure write path.

Beyond these functional outcomes, the project has a methodological objective: to show that privacy and safety in AI-assisted data access can be obtained by architecture and by deterministic code, rather than by trusting a model to behave. Each safety property in HelixQL is enforced by ordinary software that can be read, tested and audited.

1.2 Motivation

Three observations motivate the work. The first is the persistent gap between the people who need data and the people who can query it. Surveys of analytics teams routinely describe ad hoc query requests as a major source of delay, and every request answered by an analyst is time not spent on deeper analysis. A tool that lets a business user ask the question directly would shorten the path from question to decision.

The second observation is that existing cloud-hosted Text-to-SQL offerings generally ask the customer to share more than is comfortable. To improve accuracy, some systems send sample rows, value distributions or the full schema with comments to the model provider. For a bank, a hospital or any organisation under data-protection obligations, this is unacceptable regardless of how accurate the answers are. The

compliance review alone can prevent adoption. HelixQL is motivated by the question of how much accuracy can be preserved when the model is given the least possible information.

The third observation concerns trust in generated code. A language model can emit a syntactically valid but dangerous statement such as DELETE FROM payroll, or a seemingly harmless SELECT that calls a function which pauses the server or reads a file from disk. Prompt instructions that tell the model to write only SELECT statements reduce but do not eliminate this possibility, and a system whose safety depends on prompt compliance is only as safe as its worst response. The motivation here is to move the safety decision out of the probabilistic component and into a deterministic analysis of the generated query tree.

Finally, there is a practical motivation tied to usability. Many tools stop at generating SQL and leave users to deal with errors themselves. When a generated query fails because of a hallucinated column, a non-technical user has no way to recover. HelixQL therefore treats the database's own error message as feedback for the model, so the system can repair its own mistakes quietly and keep the conversation moving.

1.3 Background

1.3.1 Evolution of Text-to-SQL

Research on translating questions into database queries dates back several decades, but progress accelerated with large annotated datasets such as Spider (Yu et al., 2018), which pairs thousands of questions with SQL over hundreds of databases from different domains, and later BIRD (Li et al., 2023b), which emphasises larger, noisier and more realistic databases. Early neural systems encoded the question and schema jointly and decoded SQL with sequence models. RAT-SQL introduced relation-aware self-attention that links question words to tables and columns (Wang et al., 2020), and PICARD constrained the decoder so that only grammatically valid SQL tokens could be produced (Scholak et al., 2021). With the arrival of instruction-following LLMs, the field shifted towards prompting. Methods such as DIN-SQL decompose the task into schema linking, classification, generation and self-correction (Pourreza & Rafiei, 2023), while DAIL-SQL studies how question representation and example selection influence accuracy (Gao et al., 2023).

1.3.2 Large Language Models as Query Translators

An LLM is a neural network trained on very large text corpora to predict the next token. When prompted with a schema and a question, it can produce SQL because both SQL and the vocabulary of business questions are well represented in training data. The model does not execute anything. It only produces text, and that text must be parsed, validated and run by the surrounding system. This separation is important for HelixQL: the model is treated as an untrusted text producer, in the same way a web application treats user input.

Zero-shot prompting, in which the model receives instructions and a schema but no worked examples, is attractive in an enterprise setting because it needs no training data from the customer (Dong et al., 2023). HelixQL uses zero-temperature decoding so that the same question and schema produce the same query as far as the provider allows, which supports repeatability and testing.

1.3.3 Retrieval Augmented Generation and Schema Linking

Retrieval Augmented Generation (RAG) supplies a model with relevant external context at inference time instead of relying only on what it memorised during training (Lewis et al., 2020). In Text-to-SQL, the retrieved context is the part of the schema that is relevant to the question. Large production databases contain hundreds of tables, and including all of them wastes tokens, dilutes the prompt and, for a privacy-sensitive product, discloses far more structure than necessary. Schema linking is the task of choosing which tables and columns a question refers to. HelixQL performs this retrieval locally on the desktop, using a three-tier combination of model-based linking, embedding similarity and keyword matching, so that only the selected table structures are transmitted.

1.3.4 Abstract Syntax Tree Validation

A compiler or interpreter does not treat source code as a flat string. It first parses it into an Abstract Syntax Tree (AST) whose nodes represent statements, clauses, expressions and function calls. Analysing the tree rather than the text makes a security check robust to casing, whitespace, comments and string literals that merely contain suspicious words. HelixQL relies on SQLGlot, a SQL parser and transpiler for many dialects, to build the tree for MySQL and PostgreSQL queries. Every node is inspected,

and any node belonging to a forbidden class causes the whole query to be rejected. Because the tree is also used to regenerate the final SQL string, what is executed is exactly what was inspected.

1.3.5 Self-Correction with Execution Feedback

Even a strong model occasionally refers to a column that does not exist or misuses a dialect-specific function. Execution-guided correction takes the database's error message and asks the model to repair the query (Piao et al., 2026; Pourreza & Rafiei, 2023). HelixQL probes with the EXPLAIN statement, which asks the database optimiser to resolve every identifier and join without reading any rows, so mistakes surface cheaply. The number of correction attempts is bounded so that a confused model cannot loop forever.

1.3.6 Desktop Application Technology

The client is built with Electron, a framework that packages a Chromium renderer and a Node.js runtime into a cross-platform desktop application, and React for the user interface. Electron splits an application into a main process, which has access to the operating system and to network sockets, and one or more renderer processes, which display the interface. HelixQL keeps all credentials, tokens and database handles in the main process and exposes only narrow request and response channels to the renderer. This design means that a defect or compromise in the user-interface code cannot read a database password.

1.4 Organisation of the Report

The remainder of this report is organised as follows. Chapter 2 states the problem, objectives, scope and proposed system and reviews the literature. Chapter 3 gives the technical specification, including requirements, technology stack, interfaces and data model. Chapter 4 explains the design approach in detail, with architecture and UML diagrams, algorithms, and the constraints and trade-offs that shaped the system. Chapter 5 presents the schedule, tasks and milestones. Chapter 6 demonstrates the implementation, with sample code, screenshots and the testing strategy. Chapter 7 reports results, cost analysis and discussion. Chapter 8 documents the Beta version of the system, which adds

confirmed write operations. Chapter 9 summarises the work and recommends future directions. References and an appendix with additional material follow.

CHAPTER 2

DISSERTATION DESCRIPTION AND GOALS

This chapter defines the problem addressed by HelixQL, the objectives and scope of the project, the proposed system at a high level, and the research context established through a literature survey. It closes with the gap identified in existing work and the measurable goals set for the project.

2.1 Problem Statement

Existing Natural Language to SQL systems allow users to retrieve database information using natural language, but their integration with cloud-based Large Language Models can introduce significant privacy and security risks. Sending actual enterprise database records, or excessive schema information, to external AI services may expose confidential information. Furthermore, automatically generated SQL can contain syntactic errors, incorrect table or column references, or potentially destructive operations.

Therefore, there is a need for a Text-to-SQL system that can generate SQL from natural language while keeping actual database records within the organisation's local environment, programmatically validating generated SQL before execution, and automatically correcting runtime errors without exposing sensitive data.

The problem can be decomposed into four sub-problems, each of which has to be solved for the system to be acceptable in an enterprise:

1. **Data exposure.** Which information may be sent to the model provider, and how can the system guarantee that nothing else is sent?
2. **Unsafe output.** How can the system guarantee that no generated statement modifies data, alters structure, reads files or degrades the server?
3. **Unreliable output.** How can the system recover automatically when generated SQL is syntactically valid but semantically wrong for the connected schema?
4. **Operational control.** How can an operator authenticate users, limit consumption and distribute the client without placing database credentials in the cloud?

2.2 Objectives

The specific objectives derived from the problem statement are listed below.

- To develop a natural-language interface for querying relational databases.
- To generate SQL queries from natural-language user requests using an LLM.
- To provide database context to the LLM using schema-only metadata without transmitting actual database records.
- To validate generated SQL queries before execution.
- To prevent destructive database operations by enforcing a read-only query policy.
- To implement an automated error-feedback and self-correction mechanism for incorrect SQL queries.
- To provide authentication, token management and usage metering so that the service can be operated as a subscription product.
- To extend the system, in an isolated Beta mode, with confirmed insert, update and delete operations that preserve the read-path guarantees.

2.3 Scope of the Project

HelixQL is proposed as a secure Natural Language to SQL system that enables users to interact with relational databases using ordinary English queries. The system separates the database environment from the cloud-based AI processing layer to protect sensitive enterprise data. When a user enters a natural-language query, the desktop application locally analyses the database structure and identifies the relevant tables and their schema information. Only the required structural metadata, without actual database records, is sent to the FastAPI-based cloud gateway.

The gateway provides this schema context along with the user's query to the Large Language Model, which generates the corresponding SQL statement. The generated SQL is then analysed using SQLGlot to verify that it follows the system's read-only policy and does not contain destructive operations. After successful validation, the query is returned to the local application, where it is first checked using the database's EXPLAIN mechanism and then executed against the local database. If an error occurs during validation or execution, the error information is used to refine the generated query through a limited self-correction loop. Finally, the retrieved database results and execution information are presented to the user through the desktop interface.

The following items are explicitly **in scope**: MySQL and PostgreSQL support; English-language questions; single-statement SELECT queries including joins,

aggregates, subqueries and common table expressions; schema browsing; clarifying conversation (Agent talk); manual SQL editing under the same guardrail; account management and metering; installers for Windows, macOS and Linux; and the Beta write mode described in Chapter 8. The following are **out of scope**: sending result rows to the model for natural-language summaries, support for non-relational stores, multi-statement scripts, stored-procedure invocation, bulk data import, and automatic undo of committed writes.

2.4 Proposed System

HelixQL is organised into three tiers whose responsibilities are deliberately separated, as summarised in Table 2.1. The Control Plane owns identity and billing. The Server Gateway owns language-model access and the security guardrail. The Desktop Client is the only tier that ever touches real data.

Table 2.1 The Three Tiers of HelixQL

Tier	Technology	Responsibility	Sees real data?
Control Plane	Next.js, TypeScript, MongoDB (Mongoose)	Registration, email verification, login, api_token issuance, subscription plans, usage metering, download endpoint, marketing and documentation pages	No
Server Gateway	Python 3.12, FastAPI, SQLGlot, Pydantic	Authenticates tokens, meters usage, builds prompts, calls the LLM provider, repairs queries, enforces the AST guardrail, links schema, writes plans (Beta)	No
Desktop Client	Electron, React, TypeScript, mysql2, pg	Holds database credentials, introspects schema, selects relevant tables, calls the gateway, runs EXPLAIN and the final query, renders results	Yes (locally only)

The end-to-end flow for one question proceeds as follows. The user signs in and connects to a database. The client introspects the schema into an in-memory snapshot called the blueprint. For each question, the client selects the relevant tables, converts them into empty CREATE TABLE statements, and posts the question and those statements to the gateway. The gateway authenticates the token, meters the request, asks the model for SQL, folds string comparisons to be case-insensitive, validates the SQL with the AST guardrail, applies a row cap and returns the sanitised statement. The client then runs EXPLAIN. If the database rejects the statement, the error is sent back for

repair, up to three times. When EXPLAIN succeeds, the statement is executed in a read-only transaction and the rows are displayed locally alongside diagnostics.

Four properties make this design distinctive. **Schema-only context:** the gateway never receives rows, credentials or even row counts. **Structural verification:** every query is parsed and rejected unless it is a single SELECT free of forbidden nodes and functions. **Bounded self-healing:** the database's own error message drives at most three repairs, and repairs are not billed. **Defence in depth:** even if a mutating query somehow reached the client, the read path executes inside a READ ONLY transaction with a timeout.

2.5 Literature Survey

The literature relevant to HelixQL spans benchmark studies, schema linking, prompting strategies, constrained decoding, self-correction and structural evaluation of generated SQL. Table 2.2 summarises eighteen representative works together with their merits and the demerits that motivate the HelixQL design.

Table 2.2 Summary of Literature Survey

S.No	Title	Merits	Demerits
1	Next-generation Database Interfaces: A Survey of LLM-based Text-to-SQL (Hong et al., 2025)	Comprehensive survey of LLM-based Text-to-SQL methods, database interfaces and research challenges; gives a broad view of how LLMs convert questions into SQL.	Analyses approaches rather than proposing an implementation. Enterprise privacy and secure local execution are not the focus.
2	TACO: A Benchmark for Open-Domain Text-to-SQL with Ambiguous and Cross-Database Queries (Deng et al., 2026)	Benchmark for ambiguous and cross-database queries; evaluates systems in harder, more realistic scenarios.	Focused on benchmarking; offers no mechanism for protecting enterprise data or blocking unsafe SQL.
3	Semantic Captioning: Benchmark Dataset and Graph-Aware Few-Shot In-Context Learning for SQL2Text (Al-Lawati et al., 2025)	Graph-aware few-shot learning improves the link between SQL and language; highlights the value of structural information.	The task is SQL-to-text rather than text-to-SQL, so secure SQL generation is not addressed.
4	Enhanced Schema Linking with LLMs via Self-Verification and Value Hints (Ma et al., 2026)	Self-verification and value hints improve identification of relevant database elements.	Needs additional context such as values; does not address keeping sensitive information away from external AI services.
5	Text-to-SQL Meets the Real-World (Nascimento et al., 2024)	Studies practical challenges of applying Text-to-SQL to real databases beyond benchmarks.	Identifies challenges but gives no architecture combining privacy isolation, validation and local execution.

S.No	Title	Merits	Demerits
6	LitE-SQL: A Lightweight and Efficient Text-to-SQL Framework with Vector-based Schema Linking and Execution-Guided Self-Correction (Piao et al., 2026)	Vector-based schema retrieval and execution-guided self-correction; shows lightweight models can suit privacy-sensitive environments.	Requires model training; lacks HelixQL's split between cloud SQL generation and local execution.
7	DIN-SQL: Decomposed In-context Learning of Text-to-SQL with Self-Correction (Pourreza & Rafiei, 2023)	Decomposes generation into stages with self-correction, improving reliability on complex queries.	Relies on LLM reasoning and prompting; has no dedicated programmatic layer to block destructive SQL.
8	READ-SQL: A Reasoning Path Decomposer and Corrector for Self-Correction (Yang et al., 2025)	Reasoning-path decomposition and correction handle generation errors.	Extra stages add complexity; privacy and isolation of enterprise records are not addressed.
9	LLM-Based SQL Generation: Prompting, Self-Refinement, and Adaptive Weighted Majority Voting (Yang et al., 2026)	Studies prompting, self-refinement and candidate selection; iteration reduces errors.	Multiple candidates raise token cost; focuses on quality rather than database security.
10	SQLStructEval: Structural Evaluation of LLM Text-to-SQL Generation (Zhou et al., 2026)	Uses canonical ASTs to analyse reliability; shows structurally different SQL can be produced for the same input.	An evaluation work, not an execution system; no authentication, privacy isolation or protection against destructive operations.
11	RAT-SQL: Relation-Aware Schema Encoding and Linking for Text-to-SQL Parsers (Wang et al., 2020)	Relation-aware encoding of tables, columns and question tokens improves accuracy on complex schemas.	Needs a specialised model and training; targets accuracy, not privacy or runtime security.
12	PICARD: Parsing Incrementally for Constrained Auto-Regressive Decoding (Scholak et al., 2021)	Constrained decoding blocks invalid tokens and malformed SQL during generation.	Addresses syntactic validity only; no guarantee of semantic correctness, safety or privacy.
13	Text-to-SQL Empowered by LLMs: A Benchmark Evaluation (Gao et al., 2023)	Systematically evaluates prompting strategies; DAIL-SQL gives strong accuracy with good token efficiency.	Focuses on prompting efficiency; generated SQL can still reference wrong schema items and no security layer is provided.
14	C3: Zero-shot Text-to-SQL with ChatGPT (Dong et al., 2023)	Shows general-purpose LLMs can perform Text-to-SQL zero-shot with suitable prompts.	Can still fail on complex schemas; no mechanism for blocking unsafe queries or isolating data.
15	Evaluating the Text-to-SQL Capabilities of Large Language Models (Rajkumar et al., 2022)	Early systematic evaluation of LLM capabilities and limitations for SQL generation.	Evaluates models rather than designing a production system; privacy and validation are not the focus.
16	RESDSQL: Decoupling Schema Linking and Skeleton Parsing for Text-to-SQL (Li et al., 2023a)	Separates schema linking from skeleton parsing, ranking schema items before generation.	Requires trained ranking and parsing models; does not address privacy of enterprise data.
17	Can LLM Already Serve as a Database Interface? A Big Bench for Large-Scale Database Grounded Text-to-SQLs (Li et al., 2023b)	BIRD benchmark emphasises large, dirty, real-world databases and efficiency.	A benchmark; offers no secure execution architecture.

S.No	Title	Merits	Demerits
18	Retrieval-Augmented Generation for Text-to-SQL: A Survey and Evaluation (Gao et al., 2024)	Surveys retrieval of schema, examples and values to ground SQL generation.	Retrieval may include values or examples from the database, which conflicts with strict data isolation.

2.6 Findings in Literature Survey

The literature indicates that recent Text-to-SQL systems have significantly improved SQL generation through large language models, schema linking, retrieval-based context selection and self-correction mechanisms. However, many approaches primarily focus on generation accuracy rather than protecting enterprise database information during the generation process. Existing approaches may also rely on extensive schema information, sample values or execution feedback that contains data, and may not enforce a strict programmatic read-only policy before database execution.

Three recurring gaps can be identified. First, accuracy-oriented work treats privacy as outside its scope, so the amount of information given to the model is rarely minimised. Second, safety is usually delegated to the model through prompts or to the decoder through grammar constraints, which guarantees syntax at best and says nothing about whether a syntactically valid statement is harmful. Third, self-correction is evaluated for accuracy gains but not for the data it may expose, since execution feedback can contain row values.

Therefore, a gap exists for a Text-to-SQL architecture that combines schema-only context transmission, local database execution, structural SQL validation and bounded self-correction. HelixQL addresses this gap by separating AI-based translation from local data execution. Table 2.3 positions HelixQL against the capabilities observed across the surveyed work.

Table 2.3 Capability Comparison of HelixQL with Surveyed Approaches

Capability	Typical LLM prompting	Fine-tuned parsers	Self-correction methods	HelixQL
Schema-only context (no row values)	Sometimes	Yes	Rarely	Always
Local execution, data never leaves	No	Depends	No	Yes
Structural (AST) read-only enforcement	No	No	No	Yes

Capability	Typical LLM prompting	Fine-tuned parsers	Self-correction methods	HelixQL
Database-error repair loop	No	No	Yes	Yes, bounded to 3
Audit view of what was sent	No	No	No	Yes (Diagnostics)
Needs model training	No	Yes	Sometimes	No

2.7 Goals and Success Criteria

The goals are expressed as measurable success criteria against which the finished system is evaluated in Chapter 7.

Table 2.4 Project Goals and Success Criteria

ID	Goal	Success criterion
G-1	Privacy	No request accepted by the gateway can carry result rows, credentials or row counts; verified by request-schema tests.
G-2	Read-only safety	Every mutation, stacked statement, file access, sleep and sequence function in the adversarial catalogue is rejected, and legitimate SELECT queries still pass.
G-3	Reliability	Failed queries are repaired automatically in at most three attempts, and repairs are not metered.
G-4	Responsiveness	Structural validation adds negligible latency compared with the model call.
G-5	Operability	Users can register, verify, sign in, be metered and download installers without any manual intervention.
G-6	Quality	All automated suites pass; each tier has unit tests for its core logic.
G-7	Beta safety	No write executes without preview and confirmation; the committed row count equals the previewed count or the write is rolled back.

2.8 Stakeholders and Usage Scenarios

Four groups of people interact with HelixQL, and their needs shaped the requirements. Table 2.5 describes each group and the scenario that matters most to it.

Table 2.5 Stakeholders and Their Needs

Stakeholder	Need	How HelixQL responds
Business user (manager, sales lead, support lead)	Answers from data without learning SQL or waiting for an analyst	English questions, clarifying conversation, a results grid, plain-language errors
Data analyst	Fast first drafts of queries and a way to inspect and edit them	Generated SQL and EXPLAIN plan are shown; the Write SQL tab accepts edits under the same guardrail
Database administrator / security officer	Assurance that data stays inside the network and that nothing can be modified or degraded	Schema-only transmission, AST guardrail, read-only transactions, auditable list of tables sent

Stakeholder	Need	How HelixQL responds
Operator of the service	Authentication, fair-use limits, distribution of the client and observability	Control plane with plans and metering, rate limiting, installers through CI, structured logging

Three usage scenarios were used as acceptance stories throughout development. In the first, a sales manager asks which customer in a particular state placed the most orders; the answer depends on a join between customers and orders and a filter on the customer's state, so it checks both schema selection and translation quality. In the second, the same manager asks who the best customer is, which has several valid readings and therefore exercises the clarifying conversation. In the third, an analyst types a destructive statement into the manual editor, which must be refused without any consumption of allowance.

2.9 Assumptions and Dependencies

The design rests on a number of assumptions that should be stated plainly. The target database is MySQL or PostgreSQL and is reachable from the machine on which the desktop application runs. The database account used for reading has at least SELECT privilege on the tables to be queried and the ability to run EXPLAIN. The user has internet access to the gateway and control plane, unless a fully local gateway with the Ollama engine is deployed. Table and column names carry enough meaning for a language model to infer what they store; HelixQL does not read column comments. The model provider's availability and quota are outside the project's control, which is why the engine is swappable and failures are reported with a stable error code.

The principal external dependencies are the language-model providers (Google Gemini, Groq or a local Ollama server), the optional embedding service (Hugging Face Inference), MongoDB for the control plane, an SMTP provider for verification email, and open-source libraries including SQLGlot, FastAPI, Pydantic, Electron, React, mysql2 and pg. Each dependency was chosen so that its failure either degrades quality gracefully or produces an explicit, user-readable error and never an unsafe default.

CHAPTER 3

TECHNICAL SPECIFICATION

This chapter specifies what HelixQL must do and the technical environment in which it does it. It follows the structure of a Software Requirements Specification: functional and non-functional requirements, the technology stack, the interfaces exposed by each tier, the persistent data model, the configuration parameters and the error vocabulary.

3.1 Functional Requirements

Functional requirements describe the behaviour the system must exhibit. Table 3.1 lists them with identifiers that are referenced by tests and design discussions throughout this report.

Table 3.1 Functional Requirements

ID	Requirement	Tier
FR-1.1	User registration with name, email and password; passwords are stored only as bcrypt hashes.	Control Plane
FR-1.2	Email verification through a single-use, expiring link; verification activates the account and mints the api_token.	Control Plane
FR-1.3	Login that returns the api_token to the desktop client over HTTPS.	Control Plane
FR-1.4	API token generation, stored as a keyed hash for lookup and as AES-256-GCM ciphertext for recovery.	Control Plane
FR-2.1	Database connection configuration for MySQL and PostgreSQL held only in the client's main process.	Desktop
FR-2.2	Schema extraction of tables, views, columns, types, keys and foreign keys into an in-memory blueprint.	Desktop
FR-2.3	Natural-language input in the Ask in English, Agent talk and Beta modes.	Desktop
FR-2.4	Local pruning of the schema so that only relevant table structures are sent.	Desktop
FR-2.5	Schema-only context: only empty CREATE TABLE structures leave the machine.	Desktop
FR-3.1	Token authentication on every gateway request.	Gateway
FR-3.2	Atomic monthly usage metering before a paid model call.	Gateway / Control Plane
FR-3.3	SQL generation by an LLM with deterministic settings and a strict output contract.	Gateway
FR-3.4	AST validation that accepts only one SELECT statement.	Gateway
FR-3.5	Rejection of forbidden nodes and functions anywhere in the query tree, including CTEs and subqueries.	Gateway
FR-3.6	Row cap applied to queries without an adequate LIMIT.	Gateway
FR-4.1	EXPLAIN-based verification of every query before execution.	Desktop
FR-4.2	Execution of validated SELECT queries in a read-only transaction with timeout.	Desktop

ID	Requirement	Tier
FR-4.3	Error handling that maps failures to stable, user-readable codes.	All
FR-4.4	Result visualisation in a data grid with the SQL, plan, timings and tables sent.	Desktop
FR-4.5	Self-correction loop limited to three attempts, enforced on both client and gateway.	Desktop / Gateway
FR-5.1	Agent talk: clarifying questions grounded in the connected schema.	Desktop / Gateway
FR-5.2	Schema questions answered locally without a model call.	Desktop
FR-5.3	Query usage tracking shown in the desktop header and web dashboard.	All
FR-6.1	Beta write mode: structured plan, local validation, preview, confirmation and transactional execution.	Desktop / Gateway

3.2 Non-Functional Requirements

Table 3.2 Non-Functional Requirements

ID	Category	Requirement
NFR-1	Security	All model output is untrusted; mutation is blocked structurally; defence in depth through read-only transactions; secrets compared in constant time; tokens never logged.
NFR-2	Privacy	No row data, credentials or counts reach the gateway; the Diagnostics panel lets users audit exactly which table structures were sent.
NFR-3	Reliability	Optional services (embeddings, schema linker, clarifier) degrade accuracy but never fail a question.
NFR-4	Low latency	Local steps (validation, pruning) complete in milliseconds; total latency is dominated by the model call.
NFR-5	Scalability	Gateway is stateless and horizontally scalable; usage metering is atomic in MongoDB; rate limiting is shared across instances.
NFR-6	Maintainability	Strict typing in TypeScript and Pydantic; narrow modules with pure functions; every tier has an automated test suite.
NFR-7	Cross-platform	Desktop installers for Windows, macOS and Linux built by CI.
NFR-8	Fault tolerance	Retries with back-off for provider faults; the control plane being unavailable yields a clear error rather than an unsafe default.
NFR-9	Determinism	Temperature fixed at zero; the translator prompt forbids prose; output is regenerated from the AST.
NFR-10	Usability	Plain-language error banners, diagnostics available on demand, advisory versus error severity distinguished.

3.3 Technology Stack

Table 3.3 Technology Stack

Layer	Technology	Purpose
Desktop shell	Electron 37	Cross-platform application with isolated main and renderer processes

Layer	Technology	Purpose
Desktop UI	React 18, TypeScript, Tailwind CSS, Vite (electron-vite)	Component-based interface, styling and bundling
DB drivers	mysql2, pg (node-postgres)	Native MySQL and PostgreSQL connectivity with parameter binding
Gateway	Python 3.12, FastAPI, Uvicorn, Pydantic	Typed REST API with validation and async I/O
SQL analysis	SQLGlot	Dialect-aware SQL parser, AST and generator
LLM providers	Google Gemini, Groq (gpt-oss-120b), Ollama (qwen2.5-coder)	Swappable SQL synthesis engines, including a local engine
Embeddings	BAAI/bge-small-en-v1.5 via Hugging Face Inference	Semantic schema ranking (optional)
Control plane	Next.js, React, TypeScript, Mongoose	Web site, authentication, subscription and metering APIs
Persistence	MongoDB (Atlas or local)	Users, plans, subscriptions, verification logs, telemetry, rate limits
Mail	SMTP via Nodemailer	Verification emails (link logged to console if SMTP is unset)
Testing	pytest, Vitest	Unit and integration tests in all tiers
Delivery	Docker, Render blueprint, Vercel, GitHub Actions, electron-builder	Containerised gateway, hosted control plane, desktop installers

3.4 Hardware and Software Environment

The system was developed and verified on a Linux workstation. Because the heavy computation is performed by hosted language models, the hardware demands on the end-user machine are modest. Table 3.4 lists the environment used for development and the minimum environment expected for deployment.

Table 3.4 Development and Deployment Environment

Item	Development	Minimum for end users
Operating system	Linux (Ubuntu 24.04 class), kernel 7.x	Windows 10+, macOS 12+, or a recent Linux desktop
Processor / memory	Multi-core workstation, 16 GB RAM class	Dual-core CPU, 4 GB RAM
Runtime	Node.js 20, Python 3.12	Bundled in the installer (Electron)
Databases	MySQL 8 and PostgreSQL 16 in Docker containers	Any reachable MySQL or PostgreSQL server
Network	Localhost and internet access for model providers	HTTPS access to the gateway and control plane
Optional local model	Ollama with qwen2.5-coder:7b or qwen2.5:3b	Not required

3.5 Interface Specification

The gateway exposes a small set of authenticated REST endpoints, summarised in Table 3.5. All requests carry the user's api_token, and request and response bodies are validated by Pydantic models that reject unknown shapes with a uniform error payload of the form {error, code, details}.

Table 3.5 Gateway Endpoints

Endpoint	Purpose	Metered?
POST /v1/translate	Question plus schema blueprint to one verified SELECT; also performs repair when a repair block is supplied	Fresh translation only; repairs are free
POST /v1/validate	Run the guardrail on SQL written by hand in the Write SQL tab	No (no model involved)
POST /v1/clarify	Agent talk: decide whether to ask a clarifying question	Opening turn counted with the final translation; follow-ups bounded
POST /v1/link-schema	Model-based selection of tables from a catalogue of names and columns	No (supports a metered question)
POST /v1/embed	Embeddings for table descriptions and the question	No
POST /v1/beta/write-plan	Beta: structured write plan or a question for missing fields	Opening turn only
GET /health	Liveness probe used by the hosting platform	No

The control plane exposes user-facing routes under /api/auth (register, verify, login, logout), /api/account/me, /api/contact and /api/download/[platform], and two internal routes under /api/internal that are reachable only with a shared secret: tokens/verify and usage/increment. The shared secret is compared in constant time, and the two secrets configured on the gateway and the control plane must be identical.

3.6 Data Model

The control plane stores five collections in MongoDB. No customer database content is ever stored. Table 3.6 describes each collection and its key fields.

Table 3.6 Control Plane Collections

Collection	Key fields	Notes
users	name, email (unique), passwordHash, status (pending, active), apiTokenLookupHash, apiTokenEncrypted, apiTokenCreatedAt	Hash and encrypted token fields are excluded from queries by default

Collection	Key fields	Notes
subscriptionplans	key (unique), name, monthlyQueryLimit	Free plan allows 100 queries per month
usersubscriptions	userId (unique), planId, currentPeriodStart, currentPeriodEnd, queriesUsedThisPeriod	Updated by conditional atomic operations
emailverificationlogs	userId, tokenHash (unique), expiresAt, used	Raw token is never stored; only its SHA-256 hash
telemetrylogs / ratelimitevents	userId, action, metadata / key, windowStart, count	Rate-limit documents expire through a TTL index after one hour

On the desktop, the schema blueprint is an in-memory structure of TableInfo records, each with columns (name, type, nullability, key flags, and in Beta mode generated and default markers), foreign keys and an isView flag. It is never written to disk. This follows the project's deliberate decision that the application should leave no local artefacts that would need auditing.

3.7 Configuration Parameters

Table 3.7 Key Configuration Parameters

Parameter	Default	Meaning
LLM_PROVIDER	gemini	Selects gemini, groq or ollama as the synthesis engine
Temperature	0.0	Zero temperature for deterministic translation
max_repair_attempts	3	Ceiling for self-correction, enforced on client and gateway
max_clarify_turns	3	Questions Agent talk may ask before committing
max_write_turns	8	Questions the Beta planner may ask for one write
max_result_rows	1000	Row cap added to SELECTs without a smaller LIMIT
QUERY_TIMEOUT_MS	30,000	Per-query timeout on the desktop (MAX_EXECUTION_TIME or statement_timeout)
MAX_TABLES_SENT	12	Upper bound on table structures sent per question
MAX_CATALOG_TABLES	60	Schemas larger than this are prefiltered before schema linking
SEMANTIC_FLOOR / WEIGHT	0.45 / 9	Parameters of the embedding score rescaling
Embedding model	BAAI/bge-small-en-v1.5	384-dimension retrieval model

3.8 Error Vocabulary

Every failure in the system is mapped to a stable machine-readable code so that the client can show an appropriate message and tests can assert behaviour without matching free text. Table 3.8 lists the principal codes. Codes beginning with WRITE_ belong to the Beta mode and are described in Chapter 8.

Table 3.8 Principal Error Codes

Code	Raised when	Presentation
SECURITY_VIOLATION	Generated or hand-written SQL fails the AST guardrail	Error banner; no allowance is consumed for hand-written SQL
TRANSLATION_FAILED	The model returns unparseable or empty SQL	Error banner
QUESTION_UNANSWERABLE	The schema cannot answer the question	Advisory message
QUERY_LIMIT_EXCEEDED	Monthly allowance spent, or repair attempts exhausted	Advisory banner
SELF_HEAL_EXHAUSTED	Query still failing after three repair attempts	Error banner with last database error
LLM_UNAVAILABLE	Provider down, rate-limited or timing out	Error banner
CONTROL_PLANE_UNAVAILABLE	Gateway cannot reach the control plane (often mismatched secrets)	Error banner
INVALID_API_TOKEN	Token invalid or user inactive	Sign-in prompt
EMBEDDINGS_UNAVAILABLE	Embedding service not configured or down	Silent fallback to keyword matching
EMPTY_SCHEMA	The connected database has no tables	Advisory message

3.9 Use Case Descriptions

Table 3.9 gives structured descriptions of the principal use cases that correspond to the use case diagram presented in Chapter 4.

Table 3.9 Principal Use Case Descriptions

Use case	Actor	Main flow	Alternative flows
Register and verify	User	Submit name, email and password; receive a verification email; open the link; account becomes active and receives an api_token and the free plan	Expired or reused link is rejected; duplicate email is refused; mail not configured logs the link to the console in development
Connect to database	User	Choose engine; enter host, port, database, user and password; the client connects and builds the blueprint	Wrong credentials or unreachable host produce a connection error; credentials are never persisted

Use case	Actor	Main flow	Alternative flows
Ask in English	User	Type a question; the client selects tables; the gateway translates and validates; the client runs EXPLAIN and then the query; results are displayed	Unanswerable question yields an advisory; allowance exhausted yields QUERY_LIMIT_EXCEEDED; EXPLAIN error starts the repair loop
Agent talk	User	The clarifier asks one question grounded in the schema; the user replies; the resolved question is run through the pipeline	Clarifier unavailable falls through to a normal run; maximum of three questions
Write SQL	Analyst	Type SQL; the gateway validates it; the client runs EXPLAIN and the query	Any non-SELECT or unsafe construct is refused with SECURITY_VIOLATION and no allowance is used
Review diagnostics	User, security officer	Open the Diagnostics panel to see the SQL, plan, timings, tables sent and repairs	Not applicable
Beta write	User	Describe a change; the planner returns a plan; the client validates it and shows a preview; the user confirms; the write commits if the count matches	Missing fields produce questions; zero or too many rows produce a request to narrow; mismatch rolls back

3.10 Request and Response Formats

The translate endpoint is the central interface. Its request contains the question text, the list of schema statements, the dialect, and an optional repair object with the failed SQL, the driver error and the attempt number. Its response contains the sanitised SQL, the dialect, the attempt number, the list of tables the query touches, the row limit that was applied (if any), the columns whose comparisons were folded to be case-insensitive, and, for a fresh translation, the usage counters. Because every field of every request is declared in a Pydantic model, an unexpected field is rejected rather than ignored, which is also what keeps the privacy boundary honest.

Listing 3.1 Shape of a Translate Request and Response

```
POST /v1/translate
{ "question": "Who made the most orders from Gujarat?",
  "schema_ddl": ["CREATE TABLE customers (...)", "CREATE TABLE orders (...)"],
  "dialect": "postgres",
  "repair": null }                    // or {"sql": "...", "error": "...",
"attempt": 1}

200 OK
{ "sql": "SELECT ... LIMIT 1000",
  "dialect": "postgres", "attempt": 1,
  "tables": ["customers", "orders"],
  "limit_applied": 1000,
  "case_insensitive_columns": ["customers.state"],
  "usage": { "remaining": 97, "monthly_query_limit": 100 } }
```

3.11 Security Requirements in Detail

Security requirements deserve more detail than a single line in the non-functional table. Authentication: every gateway route requires a valid api_token, which the gateway verifies by calling the control plane; the token is never written to logs. Authorisation: a user can only affect their own subscription record, and internal routes accept only requests bearing the shared secret. Confidentiality: tokens are stored as a keyed hash and as authenticated ciphertext; verification tokens are stored only as hashes; passwords are stored only as bcrypt hashes. Integrity: all data-changing paths are structurally restricted, either by the guardrail on the read path or by the plan builder on the Beta path. Availability: rate limiting protects authentication endpoints, a row cap protects the client's memory, query timeouts protect the database and a bounded repair loop protects the model quota.

Operational security is addressed in deployment. The gateway container runs as an unprivileged user, secrets are supplied by the hosting platform and not by the repository, cross-origin access is disabled by default because the desktop client is not a browser, and the health route reveals nothing beyond a status string.

CHAPTER 4

DESIGN APPROACH AND DETAILS

This chapter explains how HelixQL is designed. It begins with the overall architecture and the privacy boundary, presents the UML models, and then describes each major mechanism in turn: schema extraction, hybrid table selection, prompt design, the AST guardrail, the EXPLAIN probe and self-correction loop, Agent talk, and the control plane's authentication and metering. It closes with a discussion of constraints, alternatives and trade-offs.

4.1 Design Approach / Materials and Methods

4.1.1 Design Philosophy

Four principles guided every design decision. The first is **least disclosure**: the model receives the minimum information needed to write a query. The second is **untrusted generation**: nothing produced by the model is executed or displayed to the database until deterministic code has inspected it. The third is **graceful degradation**: optional intelligence, such as embeddings, schema linking and clarification, may improve accuracy but its absence or failure must never prevent a question from being answered. The fourth is **defence in depth**: no single control is relied upon, so the prompt, the AST guardrail, the EXPLAIN probe and the read-only transaction each independently limit harm.

4.1.2 System Architecture

Figure 4.1 shows the architecture. The desktop application and the local database sit on the organisation's side of the network boundary. The FastAPI gateway and the language model sit outside it. Between them flows only the natural-language question and the schema blueprint, which is a set of empty CREATE TABLE statements. The validated SQL flows back. Rows flow only between the local database and the local user interface.




Fig. 4.1 HelixQL System Architecture

The desktop client contains a user interface, a schema manager, a query orchestrator and a local executor. The orchestrator drives the request and response flow, deciding at each stage whether to continue, to ask the gateway for a repair or to stop with a coded error. The gateway contains an API layer with authentication and request handling, an LLM integration layer that builds prompts and talks to the provider, an SQL validation layer based on SQLGlot, and a response layer. A self-correction module closes the loop between the local executor and the gateway: it receives an error and the failed SQL and returns a refined statement, bounded by three attempts.

4.1.3 Privacy Boundary

The privacy boundary is the most important structural property of the design and it is enforced in several places. At the request-schema level, the gateway's Pydantic

models contain no field that could carry a result row: a translate request has question, schema_ddl, dialect and an optional repair block that carries a failed SQL string and the driver's error text. At the code level, the client's pipeline never sends rows anywhere; the original specification contemplated sending rows back for a written summary, and that step was deliberately not implemented. At the test level, a dedicated suite pins the set of request fields and the set of routes, so that adding a field capable of carrying rows fails a test.

The boundary has one subtle point worth stating plainly. A driver error message can, in principle, quote a value (for example, a duplicate key message). For the read path this is not a concern because EXPLAIN reads no rows, and its errors describe identifiers and syntax. This is one more reason the probe is EXPLAIN and not the real query.

Table 4.1 What Crosses the Privacy Boundary

Sent to the gateway	**Never sent to the gateway**
The English question and clarification replies	Result rows of any query
Empty CREATE TABLE statements for the few selected tables	Row counts and value distributions
The SQL dialect name (mysql or postgres)	Database host, port, user or password
A failed SQL string and the driver's EXPLAIN error, when repairing	The full list of tables, unless the schema linker catalogue is requested (names and columns only)

4.1.4 Use Case Model

Figure 4.2 shows the use case diagram. The primary actor is the User, who can log in or register, connect to a database, enter a natural-language query and view the query results and execution information. Entering a query extends into generating SQL, which includes validating the SQL, which in turn includes executing it. Two secondary actors participate: the LLM service in the cloud, which generates SQL, and the local premises database, which executes queries. The Handle Query Error use case extends execution to model failure cases and triggers self-correction.




Fig. 4.2 Use Case Diagram of HelixQL

4.1.5 Class Model

Figure 4.3 presents the class diagram. A User owns zero or more DatabaseConnections, each of which refers to a Schema containing Tables, and each Table contains Columns. A user submits Queries; each Query produces an SQLQuery through the LLMService. An SQLQuery is checked by a ValidationResult, and a validated SQLQuery gives rise to an ExecutionPlan and a QueryResult, with ExecutionInfo carrying timings and row counts. The model is conceptual: in the implementation these roles are realised by TypeScript interfaces on the desktop (for example TableInfo, ColumnInfo and PipelineResult), Pydantic models on the gateway (TranslateRequest, TranslateResponse) and Mongoose schemas in the control plane.




Fig. 4.3 Class Diagram of HelixQL

4.1.6 Sequence Model

Figure 4.4 shows the interaction sequence for a typical question. The user enters a natural-language query in the desktop application. The application sends the query and schema context to the gateway, which prompts the LLM service for SQL. The generated SQL returns to the gateway, which validates syntax and read-only policy and, in the original design, calls EXPLAIN. The validated SQL is returned to the desktop application, which executes it against the local database and displays the result and execution information. In the failure branch, a validation or execution error triggers self-correction: the desktop application refines the SQL and retries, up to three attempts, and then executes the corrected query.




Fig. 4.4 Sequence Diagram of a Natural-Language Query

4.1.7 Activity Model

Figure 4.5 shows the activity flow. The user enters a natural-language query; the system collects schema context; the LLM generates SQL; the system validates syntax and read-only status. A decision node tests whether the SQL is valid and safe. If not, the flow returns an error and the self-correction loop refines the SQL. If so, the SQL executes on the local database, results and execution information are fetched and finally displayed to the user.




Fig. 4.5 Activity Diagram of the Query Pipeline

4.1.8 Schema Extraction and Blueprint

When the user connects, the driver reads the database's information schema in a single pass and builds the blueprint. For each table it records the name, whether it is a view, and each column's name, data type, nullability, primary-key membership and foreign-key reference. The blueprint lives only in memory and is refreshed when the user presses refresh in the Schema tab. Converting a table into a prompt-ready blueprint produces a statement such as the following, which contains structure but no data.

Listing 4.1 Example Blueprint Statement Sent to the Gateway

```
CREATE TABLE orders (
  id INT PRIMARY KEY,
  customer_id INT NOT NULL REFERENCES customers(id),
  status VARCHAR(20),
  total DECIMAL(10,2),
  created_at TIMESTAMP
);
```

4.1.9 Hybrid Table Selection

Selecting the right tables is the step that most influences both accuracy and privacy. HelixQL uses three tiers, each a fallback for the one above, so that no failure of an optional service can fail a question.

1. **Schema linking.** The client sends the gateway a compact catalogue with one line per table, containing the table name and its column names only, and asks the model to name the tables the question needs. The linker prompt tells the model to judge a table by what its columns show it stores, not by whether its name shares words with the question. For schemas larger than 60 tables, the catalogue is first prefiltered locally by embedding similarity.
2. **Embedding similarity.** Each table is described as a sentence, for example Table signup. Columns: email, password hash, full name. A retrieval-tuned embedding model turns descriptions and question into vectors, and the cosine similarity of the two ranks the tables.
3. **Keyword matching.** A deterministic, offline scoring function tokenises the question, removes stop words and scores tables by lexical overlap with table and column names. It is exact, predictable and always available.

The lexical score of a table T for a question q is the sum of the contributions of the question's tokens, as in Eqn. 4.1. A token that equals a whole word of the table name contributes 10 divided by the number of words in the name, so a hit on users outranks a hit on one word of ai_user_events (Eqn. 4.2). A substring of the table name contributes 5, a column-name word contributes 3, and a long partial column match contributes 1.

$$S_{lex}(T, q) = \sum_{t \in q} w(t, T) \tag{4.1}$$

$$w(t, T) = \frac{10}{\left| words(T) \right|} \tag{4.2}$$

Embedding similarity is rescaled into the same point scale. Raw cosine values for short strings are not centred on zero, so a floor is applied: in Eqn. 4.3 the variable s denotes the cosine similarity of the question and table vectors, f is the floor of 0.45 and W is the weight of 9 points. Because W is below the 10 points of an exact table-name hit, no embedding score can outrank a table that the user named outright. The cosine itself is

the dot product of two length-normalised vectors a and b (Eqn. 4.4), and the final hybrid score is the sum of both parts (Eqn. 4.5).

$$S_{sem} = \begin{cases} \frac{s-f}{1-f} \cdot W, s \geq f \\ 0, s < f \end{cases} \tag{4.3}$$

$$\cos(a,b) = \sum_i a_i b_i \tag{4.4}$$

$$S = S_{lex} + S_{sem} \tag{4.5}$$

After ranking, the top tables are selected up to a cap of 12, and the selection is expanded by one foreign-key hop in both directions. This expansion is essential: the question Who ordered the most? names orders but not customers, yet answering it requires both. Without the expansion the model could not reach the customer's name and would hallucinate a column. If nothing matches at all, a bounded slice of the first eight tables is used instead, so the model can still try and the gateway can report that the question is unanswerable.

Table 4.2 Lexical Scoring Rules

Match type	**Points**	**Example (question token: user)**
Whole word of table name	10 / words in name	users scores 10; ai_user_events scores 3.3
Substring of table name	5	superuser_log
Whole word of a column name	3	orders.user_id
Long partial match in a column name (over 4 characters)	1	username
Plural and singular folding	n/a	orders matches the table order

4.1.10 Prompt Design

The translator prompt is written as a contract, because its output goes straight into a parser and not to a human. It states that the model is a deterministic code translator and not an assistant, and it lists output rules: raw SQL only, exactly one statement, beginning with SELECT or WITH, no markdown fences, no trailing semicolon, and no top-level set operations. It forbids functions that read files, run commands, pause execution or advance sequences. Schema rules require the model to use only tables and columns present in the blueprint, to infer joins from declared keys, to qualify columns with aliases and to match identifier casing.

Result-shape rules improve usefulness. Computed columns receive readable aliases. A yes or no question about whether data exists is answered with a COUNT and a descriptive alias, because a lone 1 is easily misread as one. Rankings receive ORDER BY, and small-result questions receive a sensible LIMIT. When the blueprint genuinely lacks what is needed, the model emits a sentinel line, HELIXQL_UNANSWERABLE, followed by a short reason, which the gateway converts into a clean 422 response rather than letting the model invent a query over tables that do not exist. The comments in the prompt module state the design position explicitly: the prompt is the ergonomic layer, the guardrail is the security layer, and safety must never rely on the prompt.

Three engines implement the same interface. Gemini and Groq are hosted providers, with a retry policy for transient faults. Ollama runs a model on the local machine for development or fully offline deployment; it uses the native chat endpoint because only that endpoint accepts a context-size option, and the default context of a few thousand tokens would otherwise silently truncate a schema blueprint. The guardrail is indifferent to which engine produced the string.

4.1.11 AST Security Guardrail

The guardrail is the core security component. It receives the model's raw SQL string, the dialect and a row limit, and it returns either a sanitised statement or a coded rejection. The procedure is outlined in Listing 4.2 and consists of five stages: parse, single-statement check, root check, tree walk and row cap.

Listing 4.2 Guardrail Procedure (Pseudocode)

```
validate_sql(sql, dialect, max_rows):
    statements = parse(sql, dialect)            # SQLGlot
    if parse fails:        raise TRANSLATION_FAILED
    if len(statements)>1:  raise SECURITY_VIOLATION   # stacked statements
    root = statements[0]
    if root is not SELECT: raise SECURITY_VIOLATION
    for node in root.walk():                    # every node, incl. CTEs/subqueries
        if node is in FORBIDDEN_NODES:          raise SECURITY_VIOLATION
        if node is a function and name in FORBIDDEN_FUNCTIONS:
                                                raise SECURITY_VIOLATION
    tables = collect_tables(root)
    root = apply_row_cap(root, max_rows)        # add or clamp LIMIT
    return root.sql(dialect, comments=False)    # regenerate from the tree
```

The forbidden node classes cover data mutation (Insert, Update, Delete, Merge, Upsert), schema mutation (Create, Drop, Alter, Truncate, Rename), privilege and session control (Grant, Revoke, Set, Use, Transaction, Commit, Rollback), filesystem and

external I/O (Into, Copy, Export, Attach, Detach, LoadData), row locking (Lock) and the parser's catch-all Command class. The last is refused because an unmodelled statement is an uninspectable statement; it is better to fail closed. The forbidden function list covers MySQL functions such as LOAD_FILE, SLEEP, BENCHMARK and GET_LOCK, PostgreSQL functions such as PG_SLEEP, PG_READ_FILE, PG_LS_DIR, LO_IMPORT and DBLINK, and sequence mutators NEXTVAL and SETVAL, which are writes dressed up as reads.

Two design details deserve emphasis. First, the returned SQL is regenerated from the validated tree rather than echoed from the input. Whatever the parser skipped, such as a trailing comment or an odd whitespace construct, does not survive the round trip. Comments are explicitly removed because MySQL treats a comment of the form /*! 12345 ... */ as executable SQL, so an inert-looking comment could otherwise still run on the server. Second, the function check consults both the dedicated class name and the raw callee name of anonymous functions, because SQLGlot models well-known functions as classes and everything else as an Anonymous node whose name sits in a different attribute.

The row cap protects the client from questions such as show me the orders. If a query has no LIMIT, the configured maximum of 1,000 rows is added; if it has a literal LIMIT larger than the maximum, it is clamped down; a smaller LIMIT is respected.

4.1.12 EXPLAIN Probe and Self-Correction Loop

After the gateway returns a validated statement, the desktop client does not run it immediately. It first runs EXPLAIN, which asks the database optimiser to resolve every table, column and join without reading rows. A hallucinated column therefore fails cheaply, with a precise error message, before any expensive scan. The client never uses EXPLAIN ANALYZE, because that variant executes the query. When EXPLAIN fails, the client sends the failed SQL and the driver error back to the gateway through the repair path of the translate endpoint, and the model is asked to correct the specific fault without changing the question's intent. The loop is shown in Listing 4.3.

Listing 4.3 Self-Correction Loop on the Desktop (Simplified)

```
K = 3
translation = gateway.translate(question, schema_ddl, dialect)
for attempt in 0 .. K:
    try:
```

```
        plan = driver.explain(translation.sql)      # no rows read
        break
    except DatabaseError as e:
        if attempt >= K - 1:
            raise SELF_HEAL_EXHAUSTED(e)
        record_repair(attempt+1, translation.sql, e)
        translation = gateway.translate(question, schema_ddl, dialect,
                                        repair={sql: translation.sql,
                                                error: e, attempt: attempt+1})
rows = driver.execute(translation.sql)              # read-only transaction
```

Both tiers enforce the ceiling independently. If a modified client tried to loop indefinitely, the gateway would reject a repair whose attempt number exceeds the configured maximum. Repairs are not metered, because they exist to fix the model's own mistake; charging three queries for one question would penalise the user for the system's error. The attempt ceiling is what prevents the unmetered path from being abused. Every repair is recorded and displayed in the Diagnostics panel, so a user can see what the model first wrote, what the database said and how it was corrected.

The relationship between the stages gives the end-to-end latency in Eqn. 4.6, where each term is measured by the client and shown in the Diagnostics panel. Because the first two local terms and the guardrail are small, the translate term dominates in practice.

$$T_{total} = T_{schema} + T_{translate} + T_{explain} + T_{exec} \tag{4.6}$$

4.1.13 Read-Only Execution on the Desktop

The desktop driver is the last line of defence. For MySQL it sets a session execution timeout and starts a transaction with the READ ONLY characteristic; for PostgreSQL it sets a statement timeout and begins a transaction in READ ONLY mode. The server therefore refuses any write even if one reached it. The PostgreSQL driver uses the extended protocol with parameterised queries, which accepts exactly one statement, and the MySQL connection is created with multiple statements disabled. A thirty-second timeout stops a runaway query from holding a connection open.

4.1.14 Agent Talk and Local Schema Answers

Agent talk is a short conversation that pins down an ambiguous question before any SQL is written. Who is our best customer? can mean most orders or highest spend. Rather than let the translator guess, the clarifier asks, but only about readings the connected schema can answer: it is given the same pruned blueprint the translator would

receive, so it cannot offer highest spend to a database with no amount column. It asks at most three questions, enforced by the gateway because clarification is not metered. Clarification is advisory: if the clarifier is unavailable or confused, the turn falls through to an ordinary run on what the user has said so far.

Some questions never need a model at all. What columns does users have? is answered directly from the local blueprint, since the translator only sees the user's tables and cannot know. Such answers involve no model call and no database query, and the SQL pane states that fact.

4.1.15 Control Plane: Authentication and Metering

Registration creates a pending user and sends a verification email containing a high-entropy single-use token. Only the SHA-256 hash of the token is stored, so a database leak does not reveal usable links. Verification activates the user, mints the api_token, which carries the prefix hql_live_ and 32 random bytes, and attaches the free plan. The token has two stored representations because it must be both quickly verifiable and recoverable: an HMAC-SHA-256 lookup hash supports an indexed query on every request, and AES-256-GCM ciphertext lets the login endpoint return the plaintext token to the desktop client. Passwords are hashed with bcrypt.

Usage metering is designed to be race-free. When the gateway calls the internal increment endpoint, the control plane first rolls the billing period over if it has elapsed, using a conditional update on the old period end so that concurrent requests cannot roll over twice. It then increments the counter with a filter that requires the current count to be below the plan limit. If no document matches, the allowance is exhausted. Because the check and the increment are one atomic operation, concurrent requests from the same user cannot slip past the cap. A fixed-window rate limiter, also stored in MongoDB with a TTL index, protects registration and login and is correct across multiple serverless instances.

4.1.16 Desktop Process Isolation

The Electron application follows the recommended hardened layout. The renderer has no Node.js access. A preload script exposes a small typed API object, and every call travels over inter-process channels to handlers in the main process, which hold the token, the database handle and the blueprint. Handlers are wrapped so that they always resolve

with a result object rather than rejecting, because a rejected inter-process call loses its error code on the way across the bridge. The result is that the renderer can ask for work to be done but can never read a credential.

4.2 Constraints, Alternatives and Tradeoffs

Every significant decision in HelixQL was a choice among alternatives under constraints. The principal constraints were privacy (no data to the cloud), safety (no unreviewed mutation), cost (a student project operating on free tiers), portability (three operating systems) and the quality limits of hosted free-tier language models. Table 4.3 records the main decisions and the reasoning behind them.

Table 4.3 Design Decisions, Alternatives and Trade-offs

Decision	Alternative considered	Reason for choice and trade-off
Desktop client holds data access	Hosted SaaS that connects to the customer database	Keeps credentials and rows inside the firewall. Trade-off: installation is required and updates are distributed as installers.
Send schema-only blueprints	Send sample rows or value hints for better accuracy	Absolute data privacy. Trade-off: the model cannot see value spellings, so case-insensitive folding of text comparisons is applied afterwards.
AST validation with SQLGlot	Regex or keyword denylist; trusting the prompt; database permissions only	A tree walk is immune to comments, casing and string literals. Trade-off: depends on the parser's coverage, so unmodelled statements are refused.
EXPLAIN as the probe	Execute with LIMIT 0 or run the query directly	Validates identifiers and joins without reading rows. Trade-off: the optimiser may accept some queries that later fail at run time, which is handled by the error path.
Bounded repair, not metered	Unlimited retries; metering each repair	Fair to users, safe from abuse by a ceiling enforced twice. Trade-off: hard cases may end in SELF_HEAL_EXHAUSTED.
Three-tier model-based linking with fallbacks	Keyword matching only; embeddings only	Misleading names such as signup versus ai_user_events defeat both alternatives. Trade-off: one extra model call per question, bounded by a names-only catalogue.
Swappable LLM provider	Single provider (Gemini)	Gemini's free tier allows about 20 requests per day per model; Groq is far more generous; Ollama allows offline use. Trade-off: prompts must work across models of varying strength.
Control plane separate from gateway	Gateway queries MongoDB directly	One implementation of token validation; gateway stays stateless. Trade-off: an extra network hop and a shared secret that must match.
Electron	Native toolkits per OS; a web client	One code base, native drivers, process isolation. Trade-off: larger installers and a known Linux crash with newer Electron on kernel 7.x, so the project is pinned to Electron 37.
Write support deferred to Beta	Allow the model to emit INSERT, UPDATE, DELETE	The read guarantees stay intact. Writes follow a separate structured-plan path (Chapter 8). Trade-off: more limited expressiveness.

Two trade-offs deserve further comment. The first is the decision to omit natural-language summaries of results. Summaries are a popular feature of competing products, but producing one requires sending rows to the model, which is precisely what the architecture forbids. HelixQL chooses to present rows in a data grid and accepts a less conversational experience. The second is the use of a model call for schema linking. It adds latency and consumes provider quota, but measurements during development showed that, for the question how many users do we have, embedding similarity ranked a decoy telemetry table marginally above the real user table, because short identifiers are scored largely on literal token overlap. A model that reads columns reaches the right answer, so the added call buys accuracy where it matters.

4.3 Threat Model and Mitigations

A design that claims safety should be able to say what it defends against. Table 4.4 lists the principal threats considered, using the STRIDE categories as a checklist, and the mechanism that addresses each. The adversary model includes a user who types hostile text, a model that produces unsafe or wrong output, and an observer of network traffic. It does not include an attacker who has already compromised the user's operating system account, because such an attacker could read process memory regardless of design.

Table 4.4 Threats and Mitigations

Threat	Category	Mitigation
A prompt asks the model to drop or alter tables	Tampering	AST guardrail rejects any non-SELECT root and every forbidden node; read-only transaction as a second barrier
A stacked statement hides a mutation after a SELECT	Tampering	Only a single statement is accepted; multiple statements are refused; drivers refuse multiple statements
A mutation is buried in a CTE or subquery	Tampering	The whole tree is walked, not only the root
A comment such as /*!50000 DROP ... */ runs on MySQL	Tampering	Comments are stripped; SQL is regenerated from the validated tree
A SELECT calls SLEEP, BENCHMARK or pg_sleep to stall the server	Denial of service	Forbidden function list; query timeout of 30 seconds
A SELECT reads server files with LOAD_FILE or pg_read_file	Information disclosure	Forbidden function list; SELECT INTO and COPY nodes refused
A SELECT advances a sequence with nextval	Tampering	NEXTVAL and SETVAL are forbidden
A very large result exhausts desktop memory	Denial of service	Row cap of 1,000 rows applied by the gateway

Threat	Category	Mitigation
Rows or credentials are leaked to the model provider	Information disclosure	Schema-only request models; no endpoint accepts rows; privacy tests pin request fields and routes
A stolen database dump exposes verification links or API tokens	Information disclosure	Verification tokens stored as SHA-256 hashes; API tokens as HMAC lookup hash and AES-256-GCM ciphertext
Credential stuffing against login and registration	Spoofing	bcrypt hashing and a shared fixed-window rate limiter
A modified client loops the model indefinitely	Denial of service	Gateway enforces the repair attempt ceiling independently
A user bypasses metering by sending repairs as fresh queries	Elevation of privilege	Repairs require a repair block and respect the attempt ceiling; fresh translations are always metered first
A compromised renderer reads the token or database password	Elevation of privilege	Secrets live only in the Electron main process; the renderer has no Node access
The write path is abused to run arbitrary SQL (Beta)	Tampering	Model returns a plan, not SQL; allowlisted operators; bound parameters; typed confirmation; row-count check

The threat model also explains why the guardrail fails closed. Any statement that the parser cannot model is classified as a generic command, and commands are refused. A statement that cannot be understood cannot be proven safe, and the cost of refusing a harmless but exotic query is far lower than the cost of admitting a harmful one.

4.4 Result Presentation and Diagnostics Design

Presentation was treated as part of the security design and not only as polish. The data grid renders rows in the renderer process from data held in local memory. The Diagnostics panel is organised so that a non-expert can audit the system without reading code. It shows the generated SQL, because users should be able to see what is about to be run on their behalf; the EXPLAIN plan, because it explains the cost; stage timings, because they show where time goes; the tables sent, because that is the privacy audit; and the repair trail, because it shows what the model first got wrong. Error messages are mapped to titles that tell the user what to do next, and codes that mean the user has to act, such as an exhausted allowance or an unanswerable question, are shown as advisories in a calmer style than genuine failures.

4.5 Case-Insensitive Text Matching

A consequence of the schema-only design is that the model cannot see how values are capitalised. If a user asks about customers in gujarat, a literal comparison to the

lower-case string will miss rows stored as Gujarat. A repair retry cannot help either, because a query that returns zero rows is not an error and so there is nothing to repair. Rather than reveal values to the model, HelixQL closes the gap with a deterministic post-processing step in the gateway. After the model answers, every comparison between a text column and a string literal is rewritten to compare lower-cased values, for example the condition u.state = 'gujarat' becomes LOWER(u.state) = 'gujarat'.

The rewrite is applied only where it is both needed and safe. It affects text columns only, as judged from the blueprint's own types, because applying LOWER to a date or an enumeration would break the query on PostgreSQL, and a column that cannot be resolved to a known table is left alone. It is applied to PostgreSQL always and to MySQL only for case-sensitive collations, because the default MySQL collations already ignore case and wrapping an indexed column in LOWER would prevent index use. The index trade-off is real on PostgreSQL, where an expression index on the lower-cased column restores performance, but for an interactive analytics tool returning the right rows is worth more than returning none quickly. The step runs before the guardrail, so the guardrail inspects the SQL that will actually run, and the response lists the folded columns so that the Diagnostics panel can show what was changed. It runs only on model output: SQL typed into the manual editor is executed as written, because the operator chose their own comparison. This illustrates a design pattern used throughout HelixQL, in which a decision that the model cannot make from information it deliberately lacks is moved into a deterministic step after generation.

4.6 Engine Abstraction and Retry Policy

All language-model access goes through one engine interface with operations for translation, repair, clarification, schema linking and Beta planning. Three implementations exist: Gemini through Google's SDK, Groq through an OpenAI-compatible chat completion API, and Ollama through its native chat endpoint, which inherits most behaviour from the Groq engine. The engine is selected by configuration at startup, and the application fails fast with a readable message if the selected provider lacks its key. Provider faults such as timeouts, rate limits and temporary unavailability are retried with a short back-off, and a persistent failure is converted into the LLM_UNAVAILABLE error. Generation settings are fixed for determinism: temperature

zero, a bounded output length, a request timeout, and, for Gemini, the thinking setting appropriate to the model generation, because the two generations spell the option differently and each rejects the other's field.

4.7 Embedding Service

Embeddings are produced by a small retrieval-tuned model, BAAI/bge-small-en-v1.5, which has 384 dimensions and is accessed through the Hugging Face Inference API. A single request carries every table description plus the question, bounded by a maximum number of texts and characters so that one call cannot be made arbitrarily expensive. The route is authenticated but not metered, on the reasoning that a user's allowance counts questions answered and the embedding call serves a question that is already metered. If no token is configured, the route reports itself unavailable and the client falls back to keyword ranking, which is exactly how the system behaved before embeddings existed. The ranking therefore degrades instead of failing.

CHAPTER 5

SCHEDULE, TASKS AND MILESTONES

The project was carried out between 6 July 2026 and 3 November 2026 under the guidance of the project supervisor. Development followed an iterative approach in which the system was built tier by tier, integrated, and then hardened, with review milestones at the end of each phase. This chapter describes the phases, the tasks completed, the milestones reached and the way risks were managed.

5.1 Project Plan

HelixQL was built in five phases. The work followed the three-tier design: first the foundations, then each tier on its own, then integration, then hardening and the Beta extension. Table 5.1 summarises the phases and their outputs.

Table 5.1 Project Phases and Deliverables

Phase	Period	Principal tasks	Deliverables
1. Requirements and architecture	July 2026	Wrote the product specification and functional requirements; designed the three-tier architecture; defined the privacy boundary	Specification, architecture and UML models
2. Core development	July to August 2026	Control plane accounts, verification, tokens, metering and rate limiting; gateway translate endpoint, LLM integration and AST guardrail; desktop drivers, schema discovery, DDL building and pipeline; self-correction loop	Working end-to-end read pipeline
3. Retrieval and UX improvements	August to September 2026	RAG-based schema linking through embed and link-schema endpoints; Agent talk; schema questions; diagnostics panel; readability work	Improved accuracy and transparency
4. Deployment and distribution	September 2026	Docker build and Render blueprint for the gateway; GitHub Actions release workflow for desktop installers; download API on the control plane	Installable builds and hosted tiers
5. Refinement, Beta and stabilisation	September to October 2026	Case-insensitive text matching; TypeScript and module-resolution clean-up; Ollama engine; Beta write mode with tests; documentation; regression testing	Beta write path, 349 passing tests, architecture documentation

5.2 Task Breakdown

Within each phase, work was divided into tasks that could be completed and verified independently. The task list in Table 5.2 is organised by tier and shows the sequence in which the tasks were done. The repository history records the progression,

from the initial control plane and gateway scaffolding to the later commits that added the Ollama engine, schema questions, Beta write planning and the Beta architecture documentation.

Table 5.2 Task Breakdown by Tier

Tier	Tasks (in order of completion)
Control Plane	Data models; password hashing; registration and email verification; token minting and encryption; login and logout; usage metering and plan rollover; rate limiting; internal verification and increment endpoints; dashboard, pricing, documentation, contact and legal pages; download endpoint
Server Gateway	Configuration and error model; control-plane client; engine abstraction with Gemini; Groq engine; AST guardrail; translate and repair routes; case folding of text comparisons; embeddings endpoint; schema linker; clarifier; Ollama engine; write-plan endpoint
Desktop Client	Electron shell and secure preload; connection manager and drivers; schema introspection; DDL builder; keyword pruning; embeddings and linking; pipeline with EXPLAIN and repair; Dashboard, Schema browser, Data grid and Diagnostics; Agent talk; schema questions; Beta controller, plan checker and confirmation card
Quality and delivery	Unit tests per tier; adversarial guardrail suite; privacy tests; Dockerfile; Render blueprint; installer workflow; developer script that validates configuration; sample database generator; documentation

5.3 Milestones

Table 5.3 Milestones and Reviews

Milestone	Description	Evidence
M1	Architecture and privacy boundary approved	Specification and diagrams
M2	First end-to-end question answered (translate, validate, EXPLAIN, execute)	Pipeline test and screenshots
M3	Review 2: system architecture, UML diagrams, implementation and sample screenshots presented	Review 2 report
M4	Retrieval and Agent talk released with Diagnostics showing the tables sent	Schema linker and clarifier tests
M5	Desktop installers built by CI and gateway containerised	Release workflow, Dockerfile, Render blueprint
M6	Beta write mode with preview, confirmation and rollback complete	Beta test suites and architecture document
M7	Final report and demonstration	This report

5.4 Risk Management

Table 5.4 lists the main risks that were identified and the mitigation applied. Several of these risks materialised during development, which is why the mitigations appear in the final design.

Table 5.4 Risks and Mitigations

Risk	Impact	Mitigation
Free-tier model quota exhausted (Gemini about 20 requests per day per model)	Questions fail with LLM_UNAVAILABLE	Swappable engines; Groq as default for hosted deployment; Ollama for local use; clear error banner
Model hallucinates tables, columns or statements	Wrong results or unsafe SQL	Schema-only blueprint with exact identifiers; AST guardrail; EXPLAIN; bounded repair
Misleading table names defeat keyword matching	Wrong tables sent	Model-based schema linking over a names-and-columns catalogue, with embeddings and keywords as fallbacks
Mismatched shared secrets between control plane and gateway	Every query fails with an opaque error	Developer script verifies byte-for-byte equality before starting
Electron crash on newer versions with Linux kernel 7.x	Desktop app exits at start	Pin to Electron 37; documented in troubleshooting
Small local models give unreliable JSON for write plans	Beta turns could fail	Parser repairs a known quirk; plan validated on the client; never guesses on ambiguity
Scope growth from write support	Weakened read guarantees	Separate Beta path; the Driver write method is the only write route and is reachable only after confirmation

CHAPTER 6
DISSERTATION DEMONSTRATION

This chapter demonstrates the working system. It describes how the three tiers are started, walks through a complete user session with screenshots, presents representative source code for the most important components, and explains the multi-level testing strategy together with the security test catalogue.

6.1 Environment Setup

HelixQL can be run entirely on a developer workstation. The three tiers are installed with their package managers: npm for the control plane and the desktop client, and a Python virtual environment with pip for the gateway. Configuration is supplied through two environment files. Secrets are generated with a random generator, and one secret must be configured identically in both files: GATEWAY_INTERNAL_SECRET in the control plane and CONTROL_PLANE_INTERNAL_SECRET in the gateway. If they differ, every query fails with an opaque CONTROL_PLANE_UNAVAILABLE error, so the development script checks them before starting anything.

A MongoDB instance is required, either an Atlas connection string or a local container, together with an API key for the selected model provider. To exercise the system without touching real data, the repository contains a generator that produces a fifteen-table e-commerce database for either dialect, covering customers, orders, order items, payments, shipments, returns, reviews, inventory, suppliers, support tickets and a payroll table that should never be exposed to a sales question. The generated MySQL and PostgreSQL databases hold identical rows, which allows the two drivers to be compared fairly. One command then starts the control plane and the gateway in the background, waits for both to answer, and launches the desktop application in the foreground.

Listing 6.1 Starting a Sample Database and the Whole Stack

```
# PostgreSQL sample database in a throwaway container
docker run -d --name helixql-postgres -e POSTGRES_PASSWORD=helix \
  -e POSTGRES_USER=helix -e POSTGRES_DB=shopdb -p 55432:5432 postgres:16
python3 scripts/sample_db.py postgres | docker exec -i helixql-postgres \
  psql -q -U helix -d shopdb

# validate configuration, start control plane + gateway, then the desktop app
./scripts/dev.sh
```

6.2 User Walkthrough

6.2.1 Account Creation and Sign-in

The user opens the control plane website, registers with name, email and password and clicks the verification link. Verification is what creates the api_token and attaches the free plan, so the desktop application cannot be used before it. The user then signs in to the desktop application with the same credentials. The application calls the login endpoint and caches the returned token in its main process memory. Figure 6.1 shows the sign-in screen of the desktop application.




Fig. 6.1 Authentication Page of the Desktop Application

6.2.2 Connecting to a Database

After sign-in, the home page asks the user to connect to a database. The user selects the engine, enters host, port, database name, user and password and presses the connect button. The application connects through the native driver and maps the schema in a single pass. Figure 6.2 shows the connection form in the left sidebar. The Schema tab then lists every table, and expanding a table shows its columns, types and key markers.




Fig. 6.2 Home Page where the User Connects to the Database

6.2.3 Asking a Question

In the Ask in English tab the user types a question in ordinary language, for example: Who are the top 3 customers in Gujarat by delivered spend? The application shows progress events (matching the question against the local schema, translating, checking with the optimiser) and then displays the results grid. The Diagnostics panel shows the generated SQL, the EXPLAIN plan, stage timings, the tables whose structure was sent and the self-correction trail if one occurred. Figure 6.3 shows the query page with the generated query and its response.




Fig. 6.3 Query Page with Generated SQL, Results and Diagnostics

The diagnostics pane is the part of the interface that makes the privacy claim auditable. Before trusting the system, a user can confirm that a sales question never sent the payroll table, simply by reading the list of tables sent. This transparency is a deliberate product feature and not only a debugging aid.

6.2.4 Guardrail in Action

The Write SQL tab lets an advanced user type a query manually. Such queries pass through the same AST guardrail as generated SQL, so the editor is not a way around the policy. Typing DELETE FROM payroll is refused with a security violation banner, nothing reaches the database, and no part of the monthly allowance is consumed because no model was involved. Only English questions are metered.

6.3 Sample Code

The listings in this section show the essential logic of three components. Complete source files are available in the project repository and extracts are included in Appendix A.

6.3.1 AST Security Guardrail

Listing 6.2 Core of the Guardrail (server-gateway/app/services/guardrail.py)

```
def validate_sql(sql: str, dialect: str, max_rows: int = 0) -> GuardrailResult:
    read_dialect = _dialect_for(dialect)

    statement = _parse_single_statement(sql, read_dialect)   # one statement only
    select = _assert_select_root(statement)                  # root must be SELECT
```

```
    _assert_no_forbidden_nodes(select)                        # walk every node

    tables = _collect_tables(select)
    capped, limit_applied = _apply_row_cap(select, max_rows)

    # Regenerated from the validated tree: what runs is what was inspected.
    return GuardrailResult(
        sql=capped.sql(dialect=read_dialect, pretty=True, comments=False),
        tables=tables,
        limit_applied=limit_applied,
    )


def _assert_no_forbidden_nodes(expression):
    violations = []
    for node in expression.walk():
        if isinstance(node, FORBIDDEN_NODES):
            violations.append(node.key.upper())
            continue
        if isinstance(node, exp.Func):
            candidates = {(node.sql_name() or "").upper()}
            if isinstance(node, exp.Anonymous):
                candidates.add(str(node.name).upper())
            for name in candidates & FORBIDDEN_FUNCTIONS:
                violations.append(f"{name}()")
    if violations:
        raise SecurityViolationError(
            "Query rejected: it contains data-mutating or unsafe operations — "
            + ", ".join(dict.fromkeys(violations)) + ".")
```

6.3.2 Translate Endpoint

Listing 6.3 Metering, Translation and Validation (server-gateway/app/routers/translate.py)

```
@router.post("/translate", response_model=TranslateResponse)
async def translate(payload, user, llm, control_plane, settings):
    is_repair = payload.repair is not None
    if is_repair:
        if payload.repair.attempt > settings.max_repair_attempts:
            raise QueryLimitExceededError("Self-correction gave up ...")
    else:
        # Meter before invoking the model, so a user at the cap never
        # reaches the paid pipeline at all.
        metered = await control_plane.increment_usage(user.user_id)

    raw_sql = await (llm.repair(...) if is_repair else llm.translate(...))

    # The model cannot see value capitalisation, so fold text comparisons
    # *before* the guardrail: it must inspect the SQL that actually runs.
    raw_sql, folded = fold_text_comparisons(raw_sql, payload.dialect,
                                            payload.schema_ddl)
    result = validate_sql(raw_sql, payload.dialect,
                          max_rows=settings.max_result_rows)
    return TranslateResponse(sql=result.sql, tables=result.tables, ...)
```

6.3.3 Atomic Usage Metering

Listing 6.4 Conditional Increment in the Control Plane (usageService.ts)

```
// Increment only if the user is still under their plan limit.
// One conditional findOneAndUpdate: concurrent requests cannot race past the cap.
const updated = await UserSubscriptionModel.findOneAndUpdate(
  { userId, queriesUsedThisPeriod: { $lt: plan.monthlyQueryLimit } },
  { $inc: { queriesUsedThisPeriod: 1 } },
```

```
  { new: true },
);
if (!updated) {
  throw new ServiceError("QUERY_LIMIT_EXCEEDED",
                         "Monthly query allowance exceeded for this plan.");
}
return { allowed: true,
         remaining: plan.monthlyQueryLimit - updated.queriesUsedThisPeriod,
         monthlyQueryLimit: plan.monthlyQueryLimit };
```

6.3.4 Read-Only Transaction in the Desktop Driver

The MySQL driver sets a server-side execution limit and opens a transaction that the server itself will not allow to write. The PostgreSQL driver does the equivalent with a statement timeout and a read-only transaction. This is the defence-in-depth layer: even a statement that fooled both the prompt and the guardrail would be refused by the database.

Listing 6.5 Read-Only Execution (client-desktop/src/main/db/driver.ts, excerpt)

```
// MySQL
await connection.query(`SET SESSION MAX_EXECUTION_TIME = ${QUERY_TIMEOUT_MS}`);
await connection.query("START TRANSACTION READ ONLY");
// ... run the single parameterised statement ...

// PostgreSQL
await client.query("BEGIN TRANSACTION READ ONLY");
// statement_timeout is set on the connection (QUERY_TIMEOUT_MS = 30_000)
```

6.4 Testing Strategies

Testing works at several levels. Each level targets one of the system's core promises: correctness, security and privacy. The automated suites run with a single command per tier and are summarised in Table 6.1.

6.4.1 Unit Testing

Table 6.1 Automated Test Suites by Tier

Tier	Framework	Tests passing	Focus
Server Gateway	pytest	220	Guardrail, authentication, metering, LLM retry, output parsing, schema linking, clarifier, embeddings, text matching, Ollama and Groq engines, write planning, no-row-data privacy tests
Control Plane	Vitest	27	Password hashing, token issuance, usage limits, rate limiting, authentication service
Desktop Client	Vitest	102 (9 end-to-end tests skipped by default)	Schema pruning (RAG), DDL generation, Agent talk, schema questions, write-plan validation, Beta turn flow
Total		349	

The figures are those obtained when running the three suites on the final code base. The desktop package also carries an end-to-end suite that drives the real pipeline against a real database, the real gateway and the real model provider. It is skipped unless an environment flag is set, because it consumes provider quota and requires live services.

6.4.2 Security Testing: Adversarial Test Cases

The guardrail is tested against a catalogue of attack patterns, all of which must be rejected. The catalogue is summarised in Table 6.2, and the same suite includes a matching list of valid SELECT queries (joins, aggregates, subqueries, common table expressions and a UNION inside a derived table) that must pass, which guards against false positives.

Table 6.2 Guardrail Adversarial Catalogue

Attack class	Examples	Outcome
Direct mutations	DROP, DELETE, UPDATE, INSERT, TRUNCATE, ALTER, CREATE, GRANT	Rejected
Stacked statements	SELECT 1; DROP TABLE users	Rejected
Mutations hidden in CTEs and subqueries	WITH d AS (DELETE ... RETURNING *) SELECT * FROM d	Rejected
File-system access	LOAD_FILE, pg_read_file, SELECT ... INTO	Rejected
Denial-of-service functions	SLEEP, BENCHMARK, pg_sleep	Rejected
Writes that look like reads	nextval, SELECT ... FOR UPDATE	Rejected
Session control	SET GLOBAL, USE	Rejected
Legitimate reads	Joins, aggregates, subqueries, CTEs, UNION in a derived table	Accepted

6.4.3 Integration Testing

- **Gateway and control plane.** The control-plane client is tested for token validation, usage increments and failure handling, for example the control plane being unavailable.
- **Translate route end to end.** With a mocked model, tests cover fresh translations, repair attempts, the attempt limit and the rule that repairs are not metered.
- **Provider tests.** Gemini, Groq and Ollama engines are tested for configuration validation, retries and request shape.
- **Privacy surface tests.** One suite pins the set of request fields and the set of routes so that any change that could carry rows fails.

6.4.4 Configuration Validation

The development script validates the configuration before startup. For example, it verifies that the shared internal secrets on the gateway and the control plane match exactly, which prevents a whole class of hard-to-diagnose failures. It is the sort of check that costs little to add and removes a frequent source of confusion for anyone setting up the system.

Listing 6.6 Running the Tests

```
cd server-gateway && ./venv/bin/python -m pytest
cd control-plane  && npm test
cd client-desktop && npm test
```

6.5 Deployment and Distribution

The gateway is packaged in a two-stage Docker image: a builder stage creates a virtual environment with the dependencies, and the runtime stage copies only that environment and the application code. The container runs as an unprivileged user, because a translation service that never touches the filesystem has no reason to hold root. A Render blueprint declares the service, with secrets marked so that they are supplied in the dashboard and never stored in version control. The control plane is deployed separately on Vercel. The desktop installers for Windows, macOS and Linux are built by a GitHub Actions workflow triggered by version tags, and the control plane's download endpoint resolves the newest release at request time, so a new version appears on the website without a deployment of its own. The hosted deployment in this project is a sample deployment on free tiers and has not been scaled onto a production cloud account.

6.6 Worked Example: One Question End to End

This section traces one question through every stage to make the interaction of the components concrete. The question is taken from the project's own acceptance check on the sample database: Who made the most orders from Gujarat? The example is illustrative: the SQL shown is representative of what the pipeline produces and is not a recorded transcript of a particular model run, but the stages, checks and data flows are exactly those of the implementation.

1. **Local schema question check.** The client tests whether the question is about the schema itself, such as asking for the columns of a table. It is not, so the pipeline continues.

2. **Table selection.** The question contains the tokens orders and Gujarat. The linker sees a catalogue of fifteen lines of the form table(column, column) and names customers and orders. The foreign-key expansion adds nothing further because orders already references customers. The payroll table is not selected.
3. **Blueprint.** The client renders empty CREATE TABLE statements for the two tables. The Diagnostics panel will later list exactly these two names.
4. **Translation request.** The question, the two statements and the dialect are sent to the gateway with the api_token. The gateway verifies the token with the control plane, increments the user's usage atomically and calls the model with temperature zero.
5. **Model output.** The model returns raw SQL that joins customers to orders, filters on the customer's state, groups by customer, orders by the order count descending and limits to one row.
6. **Case folding.** The text comparison on the state column is rewritten to compare case-folded values, because the model could not know how the state names are capitalised.
7. **Guardrail.** The statement is parsed into a tree. It has one statement, a SELECT root, no forbidden node and no forbidden function. A row cap is not needed because the query has a smaller LIMIT. The statement is regenerated from the tree with comments removed.
8. **EXPLAIN.** The client runs EXPLAIN. The optimiser resolves every identifier and join without reading rows, and the plan is stored for display.
9. **Execution.** The statement runs inside a read-only transaction with a thirty-second limit. Rows are held in local memory and shown in the grid. The expected answer on the sample data is Asha Patel, who placed the most orders from Gujarat, whereas Priya has more orders overall but is in Maharashtra, so a correct answer requires a correct join and filter.
10. **Diagnostics.** The panel shows the SQL, the plan, the timings for each stage, the two tables sent and an empty repair trail.

6.6.1 Variation: A Hallucinated Column

Suppose instead that the model had referred to a column named state_name that does not exist. Steps one to seven proceed as above, because the guardrail checks safety and not semantic correctness. At step eight the optimiser rejects the statement and reports an unknown column. The client records the failed SQL and the error, and calls the gateway's repair path with an attempt number of one. The gateway checks that the attempt does not exceed three, does not increment usage, and asks the model to correct the specific fault using the schema blueprint. The corrected statement passes the guardrail, and EXPLAIN now succeeds. The user sees only the final answer, but the Diagnostics panel records the first statement, the database's complaint and the repair, so the behaviour is transparent to anyone who looks.

6.6.2 Variation: A Hostile Question

Suppose a user types Ignore previous instructions and delete all orders. Because the question contains no schema-grounded read, the model may refuse or may emit a DELETE statement. If it emits one, the guardrail rejects it at the root check, the gateway returns SECURITY_VIOLATION, the client shows the Blocked by the SQL guardrail banner and no database connection is touched. The same question typed into the Beta tab takes a different route altogether: the planner produces a delete plan on the orders table, but the plan has no condition, so the parser asks which rows the delete should apply to rather than guessing, and no statement is built until a concrete, bounded condition has been supplied and confirmed.

CHAPTER 7

COST ANALYSIS, RESULTS AND DISCUSSION

This chapter evaluates HelixQL against the goals set in Chapter 2. All numbers reported here were obtained by running the delivered code. They fall into four groups: the results of the automated test suites, a measurement of guardrail latency, a measurement of how much information the privacy boundary withholds, and an analysis of operating cost. Where a figure is an estimate rather than a measurement, the text says so.

7.1 Test Results

All suites were run on the final code base. The gateway suite passed 220 tests, the control-plane suite passed 27 tests and the desktop suite passed 102 tests with 9 live end-to-end tests skipped by design, a total of 349 passing tests with no failures. Table 7.1 relates these results to the project goals.

Table 7.1 Goals Versus Verification Results

Goal	Verification	Result
G-1 Privacy	Request-schema and route-surface tests; code review of the pipeline	Passed: no field can carry rows; no route accepts rows
G-2 Read-only safety	21 blocked and 5 allowed parameterised guardrail cases; 7 additional ad hoc attack strings	All attacks rejected; all legitimate queries accepted
G-3 Reliability	Translate route tests for repair, attempt limit and free repairs	Passed
G-4 Responsiveness	Latency measurement in Section 7.2	Validation averaged about 0.5 ms
G-5 Operability	Authentication, token, usage and rate-limit tests; install and run scripts	Passed
G-6 Quality	Three suites	349 passing, 0 failing
G-7 Beta safety	Beta turn-flow, plan-validation and parser tests; checks against MySQL 8 and PostgreSQL 16 containers	Passed (Chapter 8)

7.2 Guardrail Latency

To quantify the cost of structural validation, the guardrail was timed on three representative queries (a join with aggregation and ordering, a simple filter, and a query with a common table expression) in the MySQL dialect with the row cap enabled. Each query was validated 500 times, giving 1,500 measurements, on the development

workstation. The mean was 0.51 ms and the 95th percentile was 0.72 ms. Seven attack strings were also run through the guardrail as a separate smoke test, and every one was rejected: DROP TABLE, a stacked DROP, SLEEP, a data-modifying CTE, SELECT INTO OUTFILE, UPDATE and pg_read_file. The INTO OUTFILE statement was rejected at the parsing stage with a translation error and the rest with a security violation, which is acceptable because in both cases the statement is discarded and never leaves the gateway.

Table 7.2 Guardrail Timing Measurement

Measure	Value
Validations timed	1,500 (3 queries x 500 repetitions)
Mean latency	0.51 ms
95th percentile	0.72 ms
Attack strings tried / rejected	7 / 7

These figures are small compared with a model call, which takes from several hundred milliseconds to several seconds, so structural validation is effectively free. This supports goal G-4. It also means that there is no performance reason to weaken the check or to skip it for queries that look harmless.

7.3 Data Exposure Reduction

The privacy claim can be quantified. For the fifteen-table sample database generated by the project's own script, the full PostgreSQL dump with data is 3,549,301 bytes (about 3.4 MB). The CREATE TABLE statements of all fifteen tables together occupy 4,258 bytes, and the statements for a typical three-table question about customers, orders and order items occupy 441 + 446 + 318 = 1,205 bytes. Let B_data denote the size of the database contents and B_sent the size of the blueprint actually transmitted. The data-exposure reduction ratio is defined in Eqn. 7.1.

$$\rho = 1 - \frac{B_{sent}}{B_{data}} \tag{7.1}$$

In Eqn. 7.1 the variable ρ is the fraction of the data volume that never leaves the machine, and B_sent and B_data are as defined above. Using the figures above, a three-table question gives ρ = 1 − 1,205 / 3,549,301, which is approximately 0.99966, or 99.97 percent, while sending the entire schema still gives approximately 0.9988. The sample

database is small, and real databases contain far more rows per table while their table structures remain about the same size, so the ratio would only improve with scale. The more important point is qualitative: the numerator contains structure and the denominator contains data, and the system's guarantee is that no data bytes appear in B_sent at all.

Table 7.3 Information Sent for the Sample Database

Item	Size in bytes	Contains data values?
Full database dump (15 tables, thousands of rows)	3,549,301	Yes (never sent)
CREATE TABLE statements for all 15 tables	4,258	No
Blueprint for customers, orders and order items	1,205	No
Translator system instruction (fixed)	2,192 characters	No

A rough estimate of token cost follows from these sizes. Using the common approximation of four characters per token, a three-table blueprint is of the order of 300 tokens and the fixed system instruction is of the order of 550 tokens, so a typical translation prompt is around a thousand tokens before the question. This is an estimate and not a measurement of a particular provider's tokenizer, but it shows why pruning matters: sending the whole schema of a hundred-table database would multiply the blueprint portion many times over and would also disclose far more structure than the question needs.

7.4 Cost Analysis

7.4.1 Operating Cost of the Prototype

The prototype was designed to run at near-zero fixed cost so that it can be evaluated without a budget. Table 7.4 lists the components and the type of plan used. Prices change, so the table gives the plan type and not a dollar figure, except where the project itself defines the price.

Table 7.4 Operating Cost Components

Component	Hosting / plan used	Cost behaviour
Gateway	Render web service, free plan, Docker image	No fixed cost; free instances may sleep when idle
Control plane	Vercel serverless deployment	No fixed cost at prototype scale
Database	MongoDB Atlas free tier or local container	No fixed cost at prototype scale
Language model	Groq free tier (hosted default), Gemini free tier, or local Ollama	Free tier request limits apply; local model costs electricity only

Component	Hosting / plan used	Cost behaviour
Embeddings	Hugging Face Inference (optional)	Optional; absent token degrades to keyword ranking
Desktop distribution	GitHub Releases through GitHub Actions	No fixed cost for the project's scale
Email	Any SMTP provider; console logging in development	Free tiers suffice for verification mail

7.4.2 Subscription Model

The control plane implements the metering needed to turn the system into a product. The pricing page defines three plans: a Free plan with 100 queries per month and one database connection, a Pro plan with 2,000 queries per month priced at 49 US dollars per month (marked as coming soon), and an Enterprise plan with a custom allowance, single sign-on, audit logs and a private gateway deployment inside the customer's own network. Only English questions count against the allowance, whether or not they return rows. Self-correction retries, schema linking, embeddings, clarification follow-ups and hand-written SQL do not. This keeps billing aligned with the value delivered and not with internal mechanics.

Table 7.5 Subscription Plans Defined in the Product

Plan	Monthly queries	Connections	Price
Free	100	1	No charge
Pro (coming soon)	2,000	Unlimited	49 US dollars per month
Enterprise	Custom	Unlimited	Custom; private VPC gateway option

7.4.3 Cost of Alternatives

The main alternative to a hosted SQL model is a local model, which removes provider cost and also removes the need to send even the schema blueprint outside the organisation. The gateway supports this through the Ollama engine. The trade-off, observed during development, is that small local models such as qwen2.5:3b are weaker at following the output contracts: they occasionally ask for optional fields in Beta mode and produce stray tokens in JSON. A seven-billion-parameter coder model or a hosted model gives a smoother conversation. The system's client-side checks keep both safe, but quality differs.

7.5 Discussion

7.5.1 Achievement of Goals

The measurements and tests show that the goals were met. The privacy boundary is enforced by schema, code and test. The guardrail rejects the entire adversarial catalogue while accepting legitimate queries, at a latency negligible compared with the model. Repairs are bounded, free and visible. The control plane atomically enforces plan limits. The Beta mode extends capability without weakening the read path, as Chapter 8 explains.

7.5.2 Why Structural Validation Matters

A natural question is whether the additional machinery of an AST guardrail is necessary when the database user could simply be granted read-only privileges. Database permissions are an excellent control and are recommended as an additional layer, but they do not cover everything the guardrail covers. A read-only database account can still run SLEEP and BENCHMARK, which are denial-of-service vectors, can call file-reading functions if privileges allow, and cannot protect a deployment where the same account is also used by Beta writes. The guardrail is also applied before the statement reaches the customer's network at all, so a malicious or hallucinated statement is discarded in the cloud tier.

7.5.3 Limitations of the Approach

- **Accuracy depends on the model and on names.** With schema-only context, the model cannot see value spellings or distributions, so questions that depend on exact values may need clarification. Case folding mitigates one common case.
- **Blueprint quality matters.** Cryptic column names reduce accuracy. The system cannot read comments that a database may not provide.
- **Metadata is still sent.** Table and column names can themselves be sensitive. HelixQL minimises but does not eliminate this; the fully local Ollama option removes it.
- **Single statements only.** Questions that need multi-step scripts must be decomposed by the user.

- **Evaluation scope.** The evaluation here is a functional and safety evaluation on a purpose-built sample database. It is not a benchmark of translation accuracy on a public dataset such as Spider or BIRD, which would be a valuable extension.

7.5.4 Threats to Validity

The latency figures were measured on one workstation and would differ on other hardware, though the order of magnitude would not. The sample database is synthetic. The adversarial catalogue was written by the developer and, like any such list, cannot prove the absence of bypasses, which is why the guardrail fails closed on unmodelled statements and why the read-only transaction exists as a second barrier.

7.6 Comparison with Alternative Approaches

To place HelixQL in context, Table 7.6 compares it qualitatively with three common ways of giving non-technical users access to data. The comparison is about architecture and risk and not about translation accuracy, which this project did not benchmark.

Table 7.6 Qualitative Comparison with Alternatives

Aspect	Analyst on request	Cloud Text-to-SQL service with data access	HelixQL
Time to first answer	Hours to days	Seconds	Seconds
Data leaves the network	No	Yes (rows or samples are often sent)	No; only table structure is sent
Unsafe SQL prevented	By human judgement	Usually by prompt or permissions	Structurally, by AST analysis plus read-only transaction
Recovery from wrong SQL	Analyst iterates	User retries manually	Automatic, bounded repair using the database error
Audit of what was shared	Not applicable	Rarely provided	Diagnostics panel lists tables sent per question
Scaling with number of users	Poor	Good	Good; gateway is stateless
Installation effort	None	Low	Moderate (desktop installer)
Natural-language summaries of results	By analyst	Often provided	Deliberately not provided

The comparison shows that HelixQL trades some convenience, namely an installed client and the absence of generated prose summaries, for a stronger guarantee about data and a stronger guarantee about what can be executed. For organisations whose compliance position rules out sending data to an external model, this is the right trade.

CHAPTER 8

HELIXQL BETA VERSION

The first seven chapters describe a system that only reads. Beta mode is an experimental fourth tab in the desktop application that answers questions in the same way as Agent talk and can additionally insert, update and delete rows, with the user confirming each change before it runs. This chapter explains the Beta part of the system: what it guarantees, how a turn is routed, how a write is planned, validated, previewed, confirmed and executed, what leaves the machine, and what remains limited. It is based on the Beta architecture document maintained in the project repository.

The other three tabs (Ask in English, Agent talk and Write SQL) are unchanged. They still run every query in a read-only transaction, and the gateway's AST guardrail still rejects any write that the model writes as SQL. Beta adds a separate path for writes and leaves those controls alone. Beta is intended for trying things on non-critical data, and its limitations are listed in Section 8.14.

8.1 Motivation and Design Challenge

Allowing a language model to write data-changing SQL is dangerous for three reasons. The model may misinterpret which rows are meant. It may invent a column or a value. And a value supplied by a user, or hallucinated by the model, may be crafted to alter the shape of the statement. The straightforward solution of loosening the guardrail would defeat the safety properties established for reading. Beta takes a different route: the model is never allowed to write SQL for a write at all. It returns a small structured plan naming an operation, a table, values and conditions. The SQL is then built by local, deterministic code from allowlists, with every value bound as a parameter.

8.2 Guarantees

Every design decision in Beta supports one of the ten guarantees in Table 8.1. If a future change weakens one of them, it must be treated as a security change.

Table 8.1 Beta Guarantees

#	Guarantee	Enforced by
G1	The model never writes SQL for a write. It returns a structured plan; SQL is built by local, deterministic code.	WritePlan schema (gateway), checkPlan (client)

#	Guarantee	Enforced by
G2	Every identifier is real. Tables and columns are resolved against the live schema snapshot; unknown names are rejected.	checkPlan
G3	Every value fits its column. Values are type-checked and coerced per column type before binding.	coerceValue
G4	Values cannot change the statement's shape. Values are bound parameters, identifiers are quoted and operators come from a fixed allowlist.	writePlan builders, driver parameter binding
G5	No unbounded update or delete. Both require a WHERE, may touch at most 100 rows and must match at least one.	Gateway parser, checkPlan, runBetaTurn
G6	Nothing changes without confirmation. The user sees the rows affected; a delete also requires typing the word delete.	runBetaTurn, confirmWrite, ConfirmCard
G7	What runs is exactly what was previewed. The statement stays in the main process under a single-use id.	pending map in beta.ts
G8	It commits only if the affected-row count still matches the preview; otherwise it rolls back.	Driver.write
G9	Other tabs stay read-only. execute, explain and query keep their read-only transactions.	driver.ts
G10	No row data reaches the gateway, for writes or reads.	Request schemas, privacy tests

8.3 Components and Architecture

Figure 8.1 shows the Beta system architecture. The renderer contains the Beta chat component, which holds the conversation thread and the confirmation card, and the Dashboard, which hosts the amber Beta tab and the shared Results and Diagnostics panels. The Electron main process contains the inter-process handlers for beta:turn, beta:confirm and beta:cancel, the Beta controller that routes turns, previews writes and holds pending writes, the pure plan-validation module, the unchanged read path and the database driver. The gateway contains the write-plan router, the engines that implement plan generation and the parser that turns reply text into a typed response. The customer database sits outside both, reachable only through the driver.




Fig. 8.1 HelixQL Beta System Architecture

Table 8.2 Beta Components and Responsibilities

Layer	File	Responsibility
UI	BetaChat.tsx	Conversation thread, confirmation card, cancelling a preview the user walks away from
UI	Dashboard.tsx	Beta mode and amber tab, error titles for WRITE_ codes
Bridge	preload/index.ts, shared/types.ts	window.api.beta turn, confirm and cancel, plus the Beta and Write types
Main	ipc.ts	Registers the three beta handlers
Main	beta.ts	Routes turns, previews writes, holds pending writes, confirms or cancels
Main	db/writePlan.ts	Pure functions: checkPlan, coerceValue, writeBlueprintFor, followUpMessage
Main	db/driver.ts	query() (parameterised, read-only) and write() (the only write path)
Gateway	routers/beta.py	POST /v1/beta/write-plan and metering
Gateway	services/prompts.py	Write planner system instruction and prompt builder
Gateway	services/write_plan_output.py	parse_write_plan: reply text to a typed WritePlanResponse
Gateway	services/llm.py, groq.py	plan_write() on Gemini and Groq; Ollama inherits Groq's
Gateway	schemas.py	WritePlan, WhereCondition, WritePlanRequest, WritePlanResponse

8.4 How a Turn Is Routed

Each exchange in the Beta thread has a track, either read or write. The track is unset until the first reply decides it. After that, every later turn in the exchange stays on the same track. A new question is handled as follows. If the track is already read, it is

passed to the unchanged Agent talk path. If the track is write, it goes to the planner. If the track is unset, a deterministic gate decides whether the question might be a write.

The gate, mightWrite, splits the question into words and compares them to a fixed set of verbs that can mean changing data, such as add, insert, create, update, change, set, delete, remove and mark. Words must match exactly, so cancelled orders and new customers do not trigger it. If there is no write verb, the question goes straight to Agent talk, with no planner call and no extra metering. This gate exists because a small local model was seen sending how many customers are in Punjab down the write path. If there is a write verb, the planner still decides, and it can return read for questions such as show the price change by month.

Earlier finished exchanges are passed as context, the most recent three, so that follow-ups such as now change her phone can be resolved. A finished read contributes its resolved question. A finished write contributes the plan's summary, which is built from the plan, so it contains only values the user typed and never rows read back from the database.

8.5 The Write Path End to End

Consider the request: delete the customer with email a@x.com. The renderer sends the question, history and context to the main process. The main process confirms that a write verb is present, selects the schema and builds the write blueprint, which adds GENERATED and DEFAULT markers to columns. It posts the question and blueprint to the gateway. The gateway returns a ready plan naming a delete on customers with a condition on email. The main process runs checkPlan, which produces a parameterised DELETE, a COUNT statement and a preview SELECT. The COUNT and the preview run in a read-only transaction. The main process stores the pending write under a plan id, with the expected row count of one, and returns a confirm card with the preview. The user sees the rows, types delete and presses the Delete button. The renderer sends the plan id and the typed word. The main process checks the word and the connection, removes the pending entry and runs the write in a read-write transaction that commits only if exactly one row was affected. An insert follows the same path without the COUNT and preview queries: its preview is the row about to be inserted, and the expected row count is one.

Table 8.3 Stages of a Beta Delete

Step	Where	What happens
1	Renderer	User enters the request; beta:turn is sent with history and context
2	Main	mightWrite is true; schema selected; write blueprint built
3	Gateway	POST /v1/beta/write-plan returns status ready with a delete plan
4	Main	checkPlan builds parameterised DELETE, COUNT and preview SELECT
5	Database	COUNT and LIMIT 20 preview run in a read-only transaction
6	Main	pending[planId] stored with statement, expected rows and driver
7	Renderer	Confirmation card and affected rows shown; user types delete and confirms
8	Main	Word, connection and expiry checked; entry removed before running
9	Database	BEGIN READ WRITE; DELETE; commit only if affected rows equal expected
10	Renderer	Result shown: deleted 1 row in customers

8.6 Gateway: The Write Planner

8.6.1 Endpoint and Plan Schema

The planner is exposed as POST /v1/beta/write-plan and requires authentication. A request carries the question (1 to 2,000 characters), up to 80 schema statements, a history of at most 24 turns and at most 6 context entries. The response has one of four statuses. Read means the user only wants to see data. Ask carries a message and optional options and is used when a field or condition is missing. Unanswerable carries an explanation. Ready carries the plan, which names the operation (insert, update or delete), the table, the values (the row to insert or the SET clause of an update) and a list of AND-ed conditions, each with a column, an operator and a value.

The operator in a condition must be one of equals, not equals, less than, less than or equal, greater than, greater than or equal, like, in, is null and is not null. Because the schema type is a closed literal set, an operator such as OR 1=1 followed by a comment fails validation at the gateway and never reaches the client.

Listing 8.1 Shape of a Ready Write Plan

```
{ "status": "ready",
  "plan": {
    "operation": "update",                       // insert | update | delete
    "table": "customers",
    "values": { "phone": "+91 98765 43210" },    // unused for delete
    "where": [ { "column": "email", "op": "=", "value": "asha@example.com" } ]
  } }
```

8.6.2 Planner Prompt

The planner's system instruction follows a short list of rules. It must classify first, replying read if the user only wants to see data. It must never invent a value and uses only what the user typed; the current date is supplied so that today resolves without a guess. For inserts it asks for every missing required field in one question and does not ask for optional ones, and it never includes a generated column. For updates and deletes it needs a condition and asks if the condition is missing or vague, and it never widens what the user asked for. The scope is limited to AND-ed conditions on the target table; anything more is explained to the user and refused.

8.6.3 Parsing: Never Guess

Unlike the clarifier, the write parser never guesses. An unusable reply becomes an ask turn, because a write built from a misread plan cannot be undone. Table 8.4 lists the outcomes.

Table 8.4 Write-Plan Parser Outcomes

Model reply	**Result**
Not valid JSON	Ask the user to rephrase
Ready, but the plan fails schema validation	Ask the user to rephrase
Ready, but an update or delete lacks a where clause	Ask which rows the change applies to
Ask after the turn budget (8) is spent	Unanswerable: start again with all details
Unknown status	Ask the user to rephrase

JSON extraction is shared with the clarifier. If parsing fails, it removes a stray empty bracket pair directly after a closing brace or bracket and decodes the first complete object. This handles a quirk seen with the small local model during testing, and replies that already parse are unaffected.

8.6.4 Metering

The opening turn of a write conversation, with empty history and status ask or ready, is metered once, like a fresh translation. Follow-up turns are free and bounded by the write-turn budget. A turn that returns read is not metered here, because the client then runs it through the normal pipeline, which meters it there.

8.7 Client: Validating a Plan and Building the SQL

The function checkPlan is pure: it performs no input or output and does not throw for a bad plan. It returns either a built write or a list of problems and missing fields, and the second form becomes the assistant's next question. Resolution is strict. The table is matched case-insensitively and exactly; if there is no match, the request is refused, and a view is refused with the explanation that a view cannot be changed directly. Columns are matched the same way, and unknown columns become problems. Generated columns are dropped from inserts, with a note shown to the user, and refused in updates.

For inserts, a column is required when it is NOT NULL, has no default, is not generated and has no value yet. A value that was given but invalid counts as a problem and not as missing, so the user is told what is wrong rather than asked again. A typical message reads: I still need email (text) and joined on (date, YYYY-MM-DD).

8.7.1 Type Coercion

Every value is checked and converted according to the column's type before it is bound, as summarised in Table 8.5. Collation suffixes are removed before matching. A null, or an empty string for a non-text column, means empty and is allowed only on nullable columns.

Table 8.5 Value Coercion by Column Type

Column type	Accepts	Bound as	Rejects
TINYINT(1), BOOLEAN, BOOL, BIT(1)	true/false, yes/no, y/n, 1/0, on/off	MySQL 1 or 0; PostgreSQL true or false	Anything else
TINYINT to BIGINT, SERIAL family	Whole numbers	Number (string beyond 2^53)	Decimals, words, out of range, negatives if unsigned
DECIMAL(p,s), NUMERIC	Decimal text	String, to stay exact	More than s decimal places or p-s integer digits
FLOAT, DOUBLE, REAL	Numbers	Number	Non-numeric
DATE	YYYY-M-D	YYYY-MM-DD	Impossible dates such as 30 February
DATETIME, TIMESTAMP	Date, or date with time	YYYY-MM-DD HH:MM:SS	Invalid date or time
TIME	HH:MM[:SS]	HH:MM:SS	Out of range
ENUM(...)	Case-insensitive member	Canonical member	Non-members (the message lists allowed values)
JSON	Valid JSON text	String	Invalid JSON
UUID	Canonical UUID	String	Anything else

Column type	Accepts	Bound as	Rejects
VARCHAR(n), CHAR(n)	Text up to n characters	String	Longer than n
Anything else	Text	String	Nothing

8.7.2 Conditions and Built Statements

Operators are taken from an allowlist, and the not-equals operator is emitted as the standard form. An equality test against null is rewritten to IS NULL, because comparing to NULL with an equals sign never matches in SQL. The in operator coerces each element and rejects an empty list. The like operator binds its pattern as a string. Other values are coerced against the condition's own column, so comparing an integer column to the text abc is rejected. The same builder produces both the statement that runs and the statement that is displayed. The only difference is the bind function: a placeholder for execution and a literal with doubled quotes for display. The display statement is never executed. It exists only for the Show SQL disclosure on the confirmation card and for the Diagnostics panel.

Listing 8.2 Statements Built for Beta (MySQL and PostgreSQL)

```
-- MySQL (runs)
UPDATE `customers` SET `phone` = ? WHERE `email` = ?
-- PostgreSQL (runs); placeholders are numbered across SET and WHERE
UPDATE "customers" SET "phone" = $1, "first_name" = $2 WHERE "id" IN ($3, $4)
-- PostgreSQL insert asks for a single-column primary key back
INSERT INTO "customers" ("first_name", "email") VALUES ($1, $2) RETURNING "id"

-- Preview queries reuse the identical WHERE, with their own parameter list
SELECT COUNT(*) AS affected FROM `customers` WHERE `email` = ?
SELECT * FROM `customers` WHERE `email` = ? LIMIT 20
```

8.8 Preview and Confirmation

After checkPlan succeeds, the controller prepares a preview. For an insert, the preview is the new row and the affected count is one. For an update or delete, a COUNT statement runs through the read-only query path. If no rows match, the controller returns an ask turn and offers nothing for confirmation. If more than 100 rows match, it returns an ask turn asking the user to narrow the request. Otherwise it samples up to 20 rows and notes when there are more. Equation 8.1 states the acceptance condition for a preview, where N_rows is the number of rows matched and the limit is 100.

$$1 \le N_{rows} \le 100 \tag{8.1}$$

The preview is returned both as a structured preview for the confirmation card and as a pipeline result so that the shared Results and Diagnostics panels show the affected rows and the SQL. Preview rows are read from the user's database and shown locally. They never leave the machine.

8.8.1 Pending Writes

The pending write, held in a map keyed by plan id, stores the parameterised statement, the expected row count taken from the preview, the connection identity at preview time, the confirmation word for deletes and the creation time. It is stored only in the main process, so the renderer receives the plan id and nothing it could edit. Entries expire after ten minutes and are swept on each turn and each confirmation. The entry is removed before the statement runs, so a double click cannot run it twice. Abandoned previews are cancelled: asking a new question or starting a new conversation calls the cancel handler, so a stale card cannot be confirmed later.

8.8.2 Confirmation Checks

When the user confirms, the main process performs four checks in order. First, the entry must exist and not have expired, otherwise the result is WRITE_EXPIRED. Second, the active connection must be the same as at preview time, otherwise WRITE_EXPIRED, because a reconnect means the preview described a different database. Third, for a delete, the typed word must match, ignoring case and surrounding spaces, otherwise WRITE_NOT_CONFIRMED and the entry is kept so the user can retry. Fourth, the entry is removed and the write is executed. The interface mirrors the third check by keeping the Delete button disabled until the word is typed, but the main process enforces it independently, so a modified renderer gains nothing.

8.9 Execution

The driver's write method is the only place in the application that opens a read-write transaction. It starts a transaction, runs the single parameterised statement, compares the affected row count with the expected count, and either commits or rolls back. Equation 8.2 states the commit condition, where N_aff is the affected-row count reported by the database and N_exp is the count recorded at preview time. On any error, the transaction is rolled back and the error is rethrown.

$$commit \Leftrightarrow N_{aff} = N_{\exp} \tag{8.2}$$

For MySQL, the driver uses the library's query method with parameters, which escapes values on the client, with multiple statements disabled. The library sets the found-rows flag, so affected rows counts rows matched and not only rows whose value actually changed, which makes it comparable to the preview's COUNT. This was verified against MySQL 8 with an update in which one row already held the target value. The insert identifier comes from the result header. For PostgreSQL, a parameterised query uses the extended protocol, which accepts exactly one statement; the row count is compared with the expected count and the insert identifier comes from a RETURNING clause on the primary key. A mismatch surfaces as WRITE_ROWS_CHANGED with the advice that nothing was changed and the user should ask again for a fresh preview. Any other database error, such as a foreign-key violation or missing write privilege, surfaces as WRITE_FAILED with the driver's own message.

8.10 Schema Metadata Beta Depends On

To decide which fields are required and which columns the user must not set, Beta introspection gained three optional fields, listed in Table 8.6. They are optional so that existing code that builds column or table records is unaffected.

Table 8.6 Additional Schema Metadata

Field	MySQL source	PostgreSQL source
ColumnInfo.generated	EXTRA contains auto_increment, or ends in generated (virtual or stored)	is_identity is YES, is_generated is ALWAYS, or the default begins with nextval (serial)
ColumnInfo.hasDefault	COLUMN_DEFAULT is not null, or EXTRA contains DEFAULT_GENERATED	column_default is not null
TableInfo.isView	TABLE_TYPE is VIEW	table_type is VIEW

The snapshot is taken at connect time and refreshed by the Schema tab's refresh. If a table's structure changes during a session, the user should refresh before writing to it, or required-field detection will work from stale data.

8.11 Privacy: What Leaves the Machine

Beta keeps the same privacy position as the read path, with one clarification. The gateway receives the question and the user's replies, the empty table structure with

generated and default markers, and earlier questions with summaries of earlier writes. Those summaries are built from the plan and therefore contain the user's own values. It never receives rows read from the database (including preview rows), row counts, or credentials and connection details. The values to be written are the user's own typed input, the same class of content as the question itself. A privacy test pins the write-plan request's fields to the question, the schema statements, the history and the context, and lists the write-plan route in the expected route surface, so adding a field that could carry rows fails a test.

8.12 Error Codes

Table 8.7 Beta Error Codes

Code	Raised by	Meaning	User interface
WRITE_NOT_CONFIRMED	confirmWrite	Delete confirmation word missing or wrong; plan kept	Advisory banner: Not confirmed
WRITE_EXPIRED	confirmWrite	Plan unknown, used, expired or cancelled, or connection changed	Advisory banner: Change not made
WRITE_ROWS_CHANGED	confirmWrite	Row count differed from the preview; rolled back	Advisory banner: Change not made
WRITE_FAILED	confirmWrite	Database refused the statement (constraint, permission)	Error banner: The database refused the change
QUERY_LIMIT_EXCEEDED	Gateway metering	Allowance spent on the opening write turn	Existing advisory banner
LLM_UNAVAILABLE	Gateway engines	Provider down or rate-limited	Existing error banner

Planner faults such as an unknown column, a bad value, a missing field or no matching rows are not errors. They come back as an ask turn the user can answer, which keeps the experience conversational.

8.13 Limits and Configuration

Table 8.8 Beta Limits

Setting	Value	Where defined
Maximum rows per update or delete	100	MAX_WRITE_ROWS in writePlan.ts
Preview sample size	20	PREVIEW_ROWS in writePlan.ts
Pending write lifetime	10 minutes	PLAN_TTL_MS in beta.ts
Delete confirmation word	delete	DELETE_CONFIRM_WORD
Earlier exchanges sent as context	3	CONTEXT_WINDOW

Setting	Value	Where defined
Planner question budget per write	8	max_write_turns in the gateway configuration
History turns accepted	24	WritePlanRequest.history
Context entries accepted	6	WritePlanRequest.context

The database user with which the application connects needs INSERT, UPDATE and DELETE privileges for Beta writes. The other tabs work with a read-only user. With a read-only user, Beta still answers reads, and writes fail cleanly with WRITE_FAILED. This suggests a good deployment practice: use a read-only account for everyday use and a separate, limited write account only on non-critical databases where Beta is being tried.

8.14 Limitations of Beta

- **One table per write.** There are no joins, no conditions on other tables and no OR. The planner is told to say so.
- **No bulk import, upserts or multi-row inserts.** Each confirmed insert is a single row.
- **No undo.** Once committed, a change is final. The preview and confirmation are the only safeguards.
- **The schema snapshot can go stale.** Refresh before writing to a table whose structure changed.
- **Small local models are weaker planners.** A 3-billion-parameter model sometimes asks for optional fields and needs the JSON repair described above; client-side checks keep this safe, but a larger or hosted model gives a smoother conversation.
- **Unrecognised column types are treated as text,** with a length check where the type declares one. For example, PostgreSQL arrays and geometry types are not validated beyond that.

8.15 Testing the Beta Mode

Table 8.9 Beta Test Suites

Suite	Covers
Plan validation (desktop)	Coercion per type, required fields, generated columns, views, conditions, operator allowlist, placeholder numbering, injection stays a bound value

Suite	Covers
Turn flow (desktop)	Read routing (mightWrite), local follow-up asks, zero-row and over-100-row refusals, typed delete word, single use, cancellation, row-count mismatch
Gateway write planner	Parser outcomes, where required, operator rejection, junk-tolerant JSON, prompt contents, metering, authentication
Privacy	Route surface and request fields

The driver's write method was also verified against real databases, MySQL 8 and PostgreSQL 16 in throwaway containers. The checks covered the introspection flags for generated columns, defaults and views, the returned insert identifier, matched-row counting on an update where one row already held the target value, rollback on a count mismatch, deletion, a hostile value stored verbatim and the fact that the read-only execute method still refuses writes. There is not yet a committed integration suite for this, and anyone repeating the check should run the driver against a disposable database and never a real one.

8.16 Changing Beta Safely

The Beta design carries a short set of maintenance rules that protect its guarantees.

1. Never let the model's text reach the SQL string. New plan features belong in the WritePlan schema and in checkPlan as structured fields built from allowlists.
2. Keep the driver's write method the only write path and call it only from confirmWrite. Do not relax the read-only transactions in execute, explain or query.
3. Raising the maximum rows or removing the typed delete word changes guarantee G5 or G6, so it is a product decision and not a tweak.
4. A new request field on the write-plan endpoint must keep the privacy test honest: update its expected fields and confirm the new field cannot carry rows.
5. When adding a column type, add a branch to the coercion function, add a matching phrase to the type describer so the missing-field message names the right format, and add both an accepts and a rejects case to the plan-validation tests.

CHAPTER 9

SUMMARY

HelixQL is a secure Text-to-SQL system designed to simplify database querying through natural language while maintaining data privacy and database security. The system allows users to enter business-related questions in English and converts them into SQL queries using a Large Language Model. To protect sensitive information, HelixQL processes the actual database locally and sends only the required schema metadata to the cloud-based language model.

The generated SQL query is checked using SQLGlot-based AST validation to ensure that only safe, read-only operations are permitted. Before execution, the query is verified using the database EXPLAIN mechanism. If an error occurs during validation or execution, the system uses an automated self-correction mechanism to refine the generated query and retry it within a limited number of attempts. Thus, HelixQL combines natural language processing, schema-based retrieval, SQL validation, local database execution and self-correction to provide a practical and secure interface for accessing database information.

9.1 Findings

- A three-tier architecture separates identity and billing, language-model access and data access, so that only the desktop tier ever touches real data.
- Schema-only context is sufficient to drive translation. In the sample database, a three-table blueprint is 1,205 bytes against 3,549,301 bytes of data, and no data bytes are sent at all.
- Structural validation by AST analysis rejects every item in the adversarial catalogue, including mutations hidden in common table expressions, stacked statements, file access, sleep functions and sequence functions, while accepting legitimate reads. It averages about 0.5 ms per query.
- Hybrid table selection with model-based linking, embeddings and keywords tolerates misleading table names and degrades gracefully when optional services fail.
- Bounded, unmetered self-correction driven by EXPLAIN repairs hallucinated identifiers without exposing data and without runaway loops.

- Beta mode extends the system to confirmed writes by keeping the model out of SQL authorship and by combining validation, preview, confirmation and transactional row-count checking.
- All 349 automated tests across the three tiers pass.

9.2 Recommendations and Future Work

Several extensions would strengthen the system. A public-benchmark evaluation on Spider and BIRD would quantify translation accuracy under schema-only context and measure the effect of each selection tier. Support for additional databases such as Oracle, already listed on the product's Pro plan, would broaden adoption. A committed integration suite for the Beta driver against disposable MySQL and PostgreSQL containers would turn the manual verification into a regression test. Query history, CSV export and audit logs would address enterprise needs. A fully local deployment with a stronger open model would remove even the transmission of table names. Finally, user studies with non-technical staff would show how often clarification and self-correction change outcomes.

For organisations adopting such a system, the recommended practice is to connect with a read-only database account for everyday use, to enable Beta writes only on non-critical data with a separate limited account, to review the Diagnostics panel regularly to confirm which tables are being sent, and to keep the shared internal secrets under proper secret management. With these practices, HelixQL offers a pragmatic way to give business users direct access to data without giving a language model access to the data itself.

REFERENCES

Journal Articles, Conference Papers and Preprints

[1] Al-Lawati, A., Lucas, J., & Mitra, P. (2025, January). Semantic captioning: Benchmark dataset and graph-aware few-shot in-context learning for SQL2Text. In *Proceedings of the 31st International Conference on Computational Linguistics* (pp. 8026–8042).

[2] Deng, C., Fan, J., Luo, Y., Xue, Q., Fan, M., Zhang, Y., ... & Du, X. (2026). TACO: A benchmark for open-domain text-to-SQL with ambiguous and cross-database queries. *arXiv preprint arXiv:2606.14201*.

[3] Dong, X., Zhang, C., Ge, Y., Mao, Y., Gao, Y., Chen, L., Lin, J., & Lou, D. (2023). C3: Zero-shot text-to-SQL with ChatGPT. *arXiv preprint arXiv:2307.07306*.

[4] Gao, D., Wang, H., Li, Y., Sun, X., Qian, Y., Ding, B., & Zhou, J. (2023). Text-to-SQL empowered by large language models: A benchmark evaluation. *arXiv preprint arXiv:2308.15363*.

[5] Gao, Y., Fang, L., Wang, Y., & others. (2024). Retrieval-augmented generation for text-to-SQL: A survey and evaluation. *arXiv preprint*.

[6] Hong, Z., Yuan, Z., Zhang, Q., Chen, H., Dong, J., Huang, F., & Huang, X. (2025). Next-generation database interfaces: A survey of LLM-based text-to-SQL. *IEEE Transactions on Knowledge and Data Engineering*.

[7] Lewis, P., Perez, E., Piktus, A., Petroni, F., Karpukhin, V., Goyal, N., ... & Kiela, D. (2020). Retrieval-augmented generation for knowledge-intensive NLP tasks. *Advances in Neural Information Processing Systems, 33*, 9459–9474.

[8] Li, H., Zhang, J., Li, C., & Chen, H. (2023a). RESDSQL: Decoupling schema linking and skeleton parsing for text-to-SQL. *Proceedings of the AAAI Conference on Artificial Intelligence, 37*(11), 13067–13075.

[9] Li, J., Hui, B., Qu, G., Yang, J., Li, B., Li, B., Wang, B., Qin, B., Geng, R., Huo, N., Zhou, X., Chen, X., Li, G., Chang, J., Yang, Z., Zhang, Z., & others. (2023b). Can LLM already serve as a database interface? A big bench for large-scale database grounded text-to-SQLs. *Advances in Neural Information Processing Systems, 36*.

[10] Ma, L., Wei, D., Li, X., Wen, F., & Zhang, H. (2026). Enhanced schema linking with large language models via self-verification and value hints. *Big Data and Cognitive Computing, 10*(4), 104.

[11] Nascimento, E., García, G. M., Feijó, L., Victorio, W., Izquierdo, Y. T., de Oliveira, A. R., ... & Casanova, M. A. (2024). Text-to-SQL meets the real-world. In *ICEIS (1)* (pp. 61–72).

[12] Piao, S., Lee, J., & Park, S. (2026, March). LitE-SQL: A lightweight and efficient text-to-SQL framework with vector-based schema linking and execution-guided self-correction. In *Findings of the Association for Computational Linguistics: EACL 2026* (pp. 3593–3608).

[13] Pourreza, M., & Rafiei, D. (2023). DIN-SQL: Decomposed in-context learning of text-to-SQL with self-correction. *Advances in Neural Information Processing Systems, 36*, 36339–36348.

[14] Rajkumar, N., Li, R., Kalyan, A., Liang, P., & Manning, C. D. (2022). Evaluating the text-to-SQL capabilities of large language models. *arXiv preprint arXiv:2204.00498*.

[15] Scholak, T., Schucher, N., & Bahdanau, D. (2021). PICARD: Parsing incrementally for constrained auto-regressive decoding from language models. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing* (pp. 9895–9901).

[16] Wang, B., Shin, R., Liu, X., Polozov, O., & Richardson, M. (2020). RAT-SQL: Relation-aware schema encoding and linking for text-to-SQL parsers. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics* (pp. 7567–7578).

[17] Yang, H., Wang, K., & Zhou, X. (2025). READ-SQL: A reasoning path decomposer and corrector for self-correction. *OpenReview / International Conference on Learning Representations*.

[18] Yang, Y. J., Chang, H. F., & Chen, P. A. (2026). LLM-based SQL generation: Prompting, self-refinement, and adaptive weighted majority voting. *arXiv preprint arXiv:2601.17942*.

[19] Yu, T., Zhang, R., Yang, K., Yasunaga, M., Wang, D., Li, Z., ... & Radev, D. (2018). Spider: A large-scale human-labeled dataset for complex and cross-domain semantic parsing and text-to-SQL task. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing* (pp. 3911–3921).

[20] Zhou, Y., Zhang, F., Guo, Z., Chen, Y., Zhang, H., Nakov, P., & Xie, Z. (2026). SQLStructEval: Structural evaluation of LLM text-to-SQL generation. *arXiv preprint arXiv:2604.06736*.

Websites and Documentation

[21] Electron. (n.d.). *Electron documentation*. https://www.electronjs.org/docs

[22] FastAPI. (n.d.). *FastAPI documentation*. https://fastapi.tiangolo.com/

[23] MySQL. (n.d.). *MySQL 8.0 reference manual*. https://dev.mysql.com/doc/

[24] OWASP Foundation. (n.d.). *SQL injection*. https://owasp.org/www-community/attacks/SQL_Injection

[25] PostgreSQL Global Development Group. (n.d.). *PostgreSQL documentation*. https://www.postgresql.org/docs/

[26] Toby Mao. (n.d.). *SQLGlot: A SQL parser, transpiler and optimizer*. https://github.com/tobymao/sqlglot

[27] Vercel. (n.d.). *Next.js documentation*. https://nextjs.org/docs

APPENDIX A

ADDITIONAL MATERIAL

This appendix contains additional sample code, configuration, manuals and test material that support the main report. Only important extracts are included; the full source is available in the project repository. No page numbers are shown from this appendix onwards.

A.1 Quick-Start Manual (from README)

The following extract shows how the three tiers are installed and started locally, and how the sample database is created.

```
# 1. Dependencies
cd control-plane  && npm install && cd ..
cd client-desktop && npm install && cd ..
cd server-gateway && python3 -m venv venv && ./venv/bin/pip install -r
requirements.txt && cd ..

# 2. Configuration (generate each secret with: openssl rand -hex 32)
cp control-plane/.env.example  control-plane/.env
cp server-gateway/.env.example server-gateway/.env
# GATEWAY_INTERNAL_SECRET (control-plane) must equal
# CONTROL_PLANE_INTERNAL_SECRET (server-gateway), byte for byte.

# 3. Sample database (PostgreSQL) and the whole stack
python3 scripts/sample_db.py postgres | docker exec -i helixql-postgres psql -q -U
helix -d shopdb
./scripts/dev.sh
```

A.2 Troubleshooting Guide

Table 9.1 Common Problems and Causes

Symptom	Cause
CONTROL_PLANE_UNAVAILABLE on every query	The two shared secrets do not match.
Sign-in says no api_token yet	The account was never email-verified.
LLM_UNAVAILABLE after a few queries	Free-tier Gemini allows about 20 requests per day per model. Use Groq or change the model; restart the gateway after changing the environment file.
Gateway returns 400 on every translation	Both thinking level and thinking budget are set; set one and blank the other.
Desktop app exits instantly with SIGSEGV	Newer Electron segfaults on this Linux kernel; the project is pinned to Electron 37.
Desktop app exits with an isPackaged error	ELECTRON_RUN_AS_NODE is set in the shell; unset it.
Desktop window is blank	The preload script failed to load so window.api is missing; the terminal shows the underlying error.

A.3 Guardrail Test Catalogue (extract)

```
BLOCKED_QUERIES = [
    ("DROP TABLE users", "mysql"),
    ("DELETE FROM orders WHERE 1=1", "mysql"),
    ("UPDATE users SET role = 'admin'", "mysql"),
    ("INSERT INTO users (name) VALUES ('x')", "mysql"),
    ("TRUNCATE TABLE orders", "mysql"),
    ("ALTER TABLE users ADD COLUMN x INT", "mysql"),
    ("CREATE TABLE t (id INT)", "mysql"),
    ("GRANT ALL ON *.* TO 'x'@'%'", "mysql"),
    # Stacked statements — a SELECT root does not make the payload safe.
    ("SELECT 1; DROP TABLE users", "mysql"),
    ("SELECT * FROM users; DELETE FROM users", "postgres"),
    # Mutations buried inside an otherwise read-shaped query.
    ("WITH d AS (DELETE FROM orders RETURNING *) SELECT * FROM d", "postgres"),
    ("SELECT * FROM users WHERE id IN (SELECT id FROM (SELECT 1) t) AND sleep(5)",
"mysql"),
    # Filesystem and command execution dressed as a SELECT.
    ("SELECT LOAD_FILE('/etc/passwd')", "mysql"),
    ("SELECT pg_read_file('/etc/passwd')", "postgres"),
    ("SELECT * INTO exfil FROM users", "postgres"),
    # Denial of service.
    ("SELECT pg_sleep(30)", "postgres"),
    ("SELECT BENCHMARK(100000000, MD5('x'))", "mysql"),
```

A.4 Beta Write Plan Request and Response Examples

```
// Request: WritePlanRequest
{
  "question": "add a customer named Asha Rao",
  "schema_ddl": ["CREATE TABLE customers (...)"],
  "history": [{ "role": "assistant", "content": "..." }, { "role": "user", "content":
"..." }],
  "context": [{ "question": "...", "resolved_question": "..." }]
}

// Responses: WritePlanResponse
{ "status": "read" }
{ "status": "ask", "message": "What is Asha's email address?", "options": [] }
{ "status": "unanswerable", "message": "..." }
{ "status": "ready", "plan": {
    "operation": "update", "table": "customers",
    "values": { "phone": "+91 98765 43210" },
    "where": [ { "column": "email", "op": "=", "value": "asha@example.com" } ] } }
```