

EXPERIMENT NO. 9: AJAX

Name of Student	Ansh Sarfare
Class Roll No	D15A_49
D.O.P.	06/03/2025
D.O.S.	13/03/2025
Sign and Grade	

AIM : To study AJAX

PROBLEM STATEMENT :

Create a registration page having fields like **Name**, **College**, **Username**, and **Password** (password is to be entered twice). Validate the form by checking:

- Username is not same as existing entries
- Password and Confirm Password fields match
- Auto-suggest college names
- On successful registration, show the message "**Successfully Registered**" below the Submit button

Let all page updates be **asynchronously loaded**. Implement using **XMLHttpRequest Object**

THEORY :

1. How do Synchronous and Asynchronous Requests differ?

Synchronous Requests	Asynchronous Requests
Blocks the execution of code	Doesn't block the execution
Waits for the server response	Continues executing while waiting for response
Slower user experience	Faster, smoother user experience
Used less in modern web applications	Preferred in modern web applications

2. Describe various properties and methods used in XMLHttpRequest Object

Properties:

- readyState: Describes the state of the request (0 to 4)
- status: HTTP status code (e.g., 200 = OK)
- responseText: Gets the response data as a string
- responseXML: Gets the response data as XML


Methods:

- open(method, url, async): Initializes the request
- send(data): Sends the request
- setRequestHeader(header, value): Sets HTTP headers
- onreadystatechange: Event triggered when readyState changes

GITHUB LINK - https://github.com/Ansh476/Webx_Lab/tree/main/webx-9

CODE:

a) Folder structure



b) index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>AJAX Registration</title>
  <link rel="stylesheet" href="styles.css" />
</head>
<body>
  <div class="container">
    <h1>Register</h1>
    <form id="registerForm">
      <label for="name">Name</label>
      <input type="text" id="name" required />
```

```

<label for="college">College</label>
<input type="text" id="college" list="collegeList" required />
<datalist id="collegeList"></datalist>

<label for="username">Username</label>
<input type="text" id="username" required />

<label for="password">Password</label>
<input type="password" id="password" required />

<label for="confirmPassword">Retype Password</label>
<input type="password" id="confirmPassword" required />

<button type="submit">Register</button>
</form>
<div id="message"></div>
<button id="addNewBtn" style="display:none;">Add New</button>
</div>
<script src="script.js"></script>
</body>
</html>

```

c)script.js

```

function showMessage(text, color = 'red') {
  const messageBox = document.getElementById('message');
  messageBox.innerText = text;
  messageBox.style.color = color;
  messageBox.style.opacity = 1;

  if (messageBox.timeoutId) {
    clearTimeout(messageBox.timeoutId);
  }
  messageBox.timeoutId = setTimeout(() => {
    messageBox.innerText = "";
  }, 15000);
}

document.getElementById('registerForm').addEventListener('submit', function (e) {
  e.preventDefault();

  const name = document.getElementById('name').value.trim();
  const college = document.getElementById('college').value.trim();
  const username = document.getElementById('username').value.trim();
  const password = document.getElementById('password').value;
  const confirmPassword = document.getElementById('confirmPassword').value;

```

```

const addNewBtn = document.getElementById('addNewBtn');
addNewBtn.style.display = 'none';

if (!name) {
  showMessage('Name cannot be empty!');
  return;
}

if (password !== confirmPassword) {
  showMessage('Passwords do not match!');
  return;
}

const xhr = new XMLHttpRequest();
xhr.open('GET', 'http://localhost:3000/users', true);

xhr.onload = function () {
  if (xhr.status === 200) {
    const users = JSON.parse(xhr.responseText);
    const userExists = users.some(user => user.username === username);

    if (userExists) {
      showMessage('Username already exists!');
    } else {
      const newUser = {
        name,
        college,
        username,
        password
      };

      const xhrPost = new XMLHttpRequest();
      xhrPost.open('POST', 'http://localhost:3000/users', true);
      xhrPost.setRequestHeader('Content-Type', 'application/json');

      xhrPost.onload = function () {
        if (xhrPost.status === 201) {
          document.querySelectorAll('#registerForm input, #registerForm
button[type="submit"]').forEach(el => {
            el.disabled = true;
          });

          setTimeout(() => {
            showMessage('✅ Successfully Registered!', 'green');
            addNewBtn.style.display = 'inline-block';
          }, 100);
        }
      };
    }
  }
};

```

```

    } else {
      showMessage('Something went wrong!');
    }
  };

  xhrPost.send(JSON.stringify(newUser));
}
} else {
  showMessage('Failed to fetch users!');
}
};

xhr.onerror = function () {
  showMessage('Network error occurred!');
};

xhr.send();
});
document.getElementById('addNewBtn').addEventListener('click', function () {
  document.getElementById('registerForm').reset();
  document.getElementById('message').innerText = "";
  this.style.display = 'none';

  document.querySelectorAll('#registerForm input, #registerForm
button[type="submit"]').forEach(el => {
    el.disabled = false;
  });
});
const collegeNames = ["VESIT", "DJ Sanghvi", "Sardar Patel", "KJ Somaiya", "VJTI"];
const datalist = document.getElementById('collegeList');

collegeNames.forEach(college => {
  const option = document.createElement('option');
  option.value = college;
  datalist.appendChild(option);
});

```


c) users.json

```

{
  users:[]
}

```


a)Successful Registration Message



The screenshot displays a 'Register' form with the following fields and values: Name (Ansh Sarfare), College (VESIT), Username (Ansh), Password (masked with dots), and Retype Password (masked with dots). A blue 'Register' button is present. Below the button, a green checkmark icon is followed by the text 'Successfully Registered!'. At the bottom, there is a green 'Add New' button.

This screenshot shows the "Successfully Registered!" message, which appears after a successful registration.

b) Duplicate Username Validation



The screenshot displays the same 'Register' form as above, but with a red error message 'Username already exists!' shown below the blue 'Register' button. The form fields (Name, College, Username, Password, Retype Password) and the 'Add New' button remain visible.

This screenshot validates that the Username is not already in use, preventing duplicate entries.

c) Password Match Confirmation

Register

Name

College

Username

Password

Retype Password

Passwords do not match!

This screenshot confirms that the Password and Re-typed Password match, ensuring data integrity.

d) College Name Auto-suggestion

Register

Name

College

Username

Password

Retype Password

VESIT
DJ Sanghvi
Sardar Patel
KJ Somaiya
VJTI

This screenshot demonstrates the auto-suggestion feature for the College field, where users can choose from suggested college names.

Conclusion:

The experiment successfully demonstrated the use of the XMLHttpRequest object to implement AJAX-based asynchronous form submission and validation. Key features such as form field validation, duplicate username detection, password match checking, and college name auto-suggestions were efficiently implemented without reloading the page. This experiment highlighted the effectiveness of AJAX in enhancing user experience by allowing dynamic content updates and real-time feedback during user interaction.