MINI PROJECT REPORT

AI-Based Project Management System (AIPMS)

Submitted by :-

Ansh Vijay Kene

UID: 25101005

Semester: V Semester

Under the Guidance of :-

Dr. Pranjali Deshmukh
Assistant Professor, AI

Academic Year 2025-2026
Department of Artificial Intelligence



ST. VINCENT PALLOTTI COLLEGE OF ENGINEERING AND TECHNOLOGY

(An Autonomous Institute Affiliated to RTM University, Nagpur) NAAC Accredited with 'A' Grade Gavsi Manapur, Wardha Road, Nagpur – 441108

Contents:-

1. Title of the Micro Project 3

2. Problem Statement 3

3. Objectives 4

4. Modelling 5

4.1 Initial Model / System Overview 5

4.2 Data Flow Diagram (DFD) 5

4.3 Control Flow Diagram 7

4.4 UML Use Case Diagram 8

4.5 UML Class Diagram 9

4.6 UML Sequence Diagram 10

4.7 Key Data Entities & Schema Relationships 11

5. Implementation / Work Done 12

5.1 System Architecture and Technology Stack 12

5.2 Implemented Modules 13

5.3 Database Design and Access Control 14

5.4 API Gateway and Application Workflow 14

5.5 AI Integration and Fallback Engine 14

5.6 Testing and Validation 15

6. Results / Output 16

6.1 Application Overview 16

6.2 User Interface Screenshots 16

6.3 Functional Testing Results 21

6.4 Deployment Status and Known Limitations 22

7. Conclusion 24

8. References 26

1. Title of the Micro Project

AI-Based Project Management System (AIPMS)

The AI-Based Project Management System (AIPMS) is an enterprise-grade, distributed web platform engineered to streamline collaborative project planning, team coordination, task tracking, agile sprint management, and automated risk evaluation. Designed around a modern microservices architecture, AIPMS connects frontend clients to specialized backend domain services through an API Gateway, backed by managed PostgreSQL with Row-Level Security (RLS) policies and local artificial intelligence powered by Ollama.

This engineering report documents the comprehensive requirements analysis, architectural modelling, database schemas, backend and frontend implementation, verification testing, and operational outputs of the system. Factual distinctions are maintained throughout between verified operational components, graceful fallback capabilities, and planned enhancements.

2. Problem Statement

Modern software engineering organizations and project teams face substantial coordination friction. Project assets, team assignments, progress milestones, and task statuses are frequently fragmented across disparate communication channels, spreadsheets, and ad-hoc trackers. This fragmentation introduces recurring operational difficulties:

- Fragmented Project Visibility: Stakeholders and project managers lack real-time visibility into overall project health, milestone progress, and true velocity.
- Coordination Overhead and Unclear Responsibilities: Without automated workflows, task assignment and hand-offs between cross-functional developers, managers, and administrators lead to bottlenecks and missed deadlines.
- Unmonitored Risk Accumulation: Project risks—such as critical dependency cycles, overdue tasks, and uneven workload distributions—are frequently identified only after deliverable deadlines have already slipped.
- Absence of Explainable Predictive Insights: Traditional issue trackers capture historical timestamps but fail to provide early warning signals, milestone completion forecasts, or automated risk mitigation guidance.
- Security and Access Control Inadequacies: Multi-tenant project environments require strict role isolation to prevent unauthorized cross-project data leakage and privilege escalation.

Need for the System

To resolve these challenges, AIPMS centralizes all project artifacts into a cohesive, secure workspace. It combines an intuitive frontend user interface, a decoupled microservices backend, robust database access security, and an intelligent analysis engine. By providing automated sprint burndown tracking, risk scoring, dependency cycle detection, and explainable AI briefings, AIPMS transitions project management from reactive firefighting to proactive, data-informed governance.

3. Objectives

The primary engineering objectives of the AIPMS project are defined as follows:

- Develop a Modern Distributed Architecture: Implement a modular web platform comprising a Next.js TypeScript frontend and decoupled NestJS backend microservices communicating through an API Gateway.
- Establish Secure Role-Based Access Control: Implement authenticated identity management and fine-grained authorization using Supabase JWT authentication and PostgreSQL Row-Level Security (RLS) across all tenant records.
- Deliver Comprehensive Project and Task Workspaces: Provide full lifecycle management for projects, multi-member teams, tasks with priority, status, due dates, and cyclic dependency validation.
- Incorporate Agile Sprint Management: Enable sprint planning, milestone goal tracking, automatic sprint duration calculation, and real-time sprint health metrics.
- Implement Systematic Risk Scoring and Matrix Analysis: Establish quantitative risk assessment based on probability and impact scoring (1 to 9), maintaining a live risk registry with mitigation plans.
- Integrate Local AI Intelligence with Deterministic Fallbacks: Connect backend analysis endpoints to Ollama (llama3.2) for executive briefs, natural language inquiries, and risk mitigations, backed by a deterministic HeuristicAnalysisEngine to guarantee zero-downtime reliability.
- Ensure Robust Engineering Quality through Automated Testing: Validate microservices with automated unit and integration test suites, establishing high test coverage and verifiable defect prevention.

4. Modelling

Software engineering modelling clarifies the functional requirements, architectural subsystems, data flow transformations, domain objects, and dynamic runtime interactions of the AIPMS platform. The formal diagrams below represent the verified architectural and functional models of the implemented system.

4.1 Initial Model / System Overview

AIPMS is structured around an asynchronous, multi-tiered microservices paradigm. The user interface layer, built with Next.js, interacts exclusively with a public API Gateway. The API Gateway performs rate limiting, CORS filtering, and JWT verification before dispatching client requests to internal private microservices: Auth, Project, Team, Task, Sprint, Risk, Reporting, and AI. Each microservice encapsulates its own domain boundaries and schema entities while interacting with managed PostgreSQL through Row-Level Security policies. The AI service bridges project data to a locally hosted Ollama inference instance, providing on-premise privacy.

4.2 Data Flow Diagram (DFD)

The Data Flow Diagram (DFD) models the pathways through which information enters, transforms, and persists within AIPMS. At Level 0 (Context Level), external entities—namely System Administrators, Project Managers, Team Members, and Stakeholders—interact with the unified AIPMS System

boundary by submitting authentication credentials, project definitions, task allocations, sprint schedules, and risk parameters. The system processes these inputs and returns verified dashboards, sprint velocity metrics, and executive AI briefs.

At Level 1, the data flow decomposes into dedicated domain processes: Identity and Access Management (Process 1.0), Project Lifecycle Administration (Process 2.0), Task and Dependency Pipeline (Process 3.0), Agile Sprint Coordination (Process 4.0), Risk Assessment and Registry (Process 5.0), Cross-Cutting Analytics (Process 6.0), and AI Inference and Heuristic Engine (Process 7.0). Each process exchanges data with isolated data stores, including the Users Store, Projects Store, Tasks Store, Sprints Store, and Risks Store, as depicted in Figure 1.




Figure 1. Data Flow Diagram — Level 0 Context and Level 1 Subsystem Decomposition

4.3 Control Flow Diagram

The Control Flow Diagram illustrates the execution pathways, state transitions, and decision logic traversed during an operational session. From user session initiation at the login boundary, the control logic validates credentials against the identity provider. On success, an authenticated JWT session is granted, routing the actor to their role-specific dashboard. If authentication fails, error handlers re-prompt the user.

Within the authenticated workspace, control flow branches conditionally based on user interaction: project creation triggers unique ownership assignment; task transitions invoke dependency checking; sprint activation computes velocity baselines; and AI requests trigger an initial Ollama health check before either parsing neural model output or gracefully failing over to the deterministic HeuristicAnalysisEngine. Figure 2 maps these deterministic runtime control branches.




Figure 2. Control Flow Diagram for AIPMS Runtime Navigation and Decision Branches

4.4 UML Use Case Diagram

The UML Use Case model captures the functional interactions between the actors and the AIPMS system. The primary actors comprise the Administrator, Project Manager, Team Member, and Executive Stakeholder, alongside the external Ollama LLM inference system. As detailed in Figure 3, Administrators govern user accounts and audit logs. Project Managers create projects, configure team memberships, plan sprint schedules, log risks, and trigger AI analysis. Team Members review assigned tasks, update kanban statuses, log task blockers, and inspect sprint burndown metrics. Stakeholders maintain read-only access to high-level progress reports and automated executive briefs.




Figure 3. UML Use Case Diagram for AIPMS Roles and Domain Interactions

4.5 UML Class Diagram

The UML Class Diagram defines the static structure of the AIPMS domain model, specifying entity attributes, methods, and associations. The core class hierarchy encompasses User, Project, Team, TeamMember, Task, TaskDependency, Sprint, Risk, and AIAnalysisResult. Multiplicities and navigational directions strictly reflect relational integrity: a Project contains one or more Sprints, Tasks, and Risks; a Task belongs to exactly one Project and may optionally link to a Sprint and an assigned TeamMember; TaskDependency establishes a directed, acyclic self-association between prerequisite and successor tasks. Figure 4 illustrates the complete class model.




Figure 4. UML Class Diagram for AIPMS Domain Entities and Structural Associations

4.6 UML Sequence Diagram

The UML Sequence Diagram models the chronological message exchange between system components during an end-to-end project workflow: from project definition, sprint setup, task creation, and dependency resolution to AI project health evaluation. The sequence traces interactions across the User Browser (Next.js Client), API Gateway, Project Service, Task Service, Database (PostgreSQL RLS), AI Service, and Ollama Daemon. As shown in Figure 5, the API Gateway verifies bearer tokens before dispatching requests, while the AI service asynchronously queries task and risk snapshots to generate an explainable brief.




Figure 5. UML Sequence Diagram — Project Setup, Task Allocation, and AI Health Evaluation Flow

4.7 Key Data Entities & Schema Relationships

The persistent data layer is implemented in PostgreSQL with strict relational constraints and Row-Level Security. The primary data entities and their schema attributes include:

- projects: id (UUID PK), name (VARCHAR 255), description (TEXT), status (PLANNING, ACTIVE, ON_HOLD, COMPLETED, ARCHIVED), owner_id (UUID), previous_status (VARCHAR 50), start_date, end_date, created_at, updated_at.
- tasks: id (UUID PK), project_id (UUID FK), title (VARCHAR 255), description (TEXT), status (TODO, IN_PROGRESS, IN_REVIEW, DONE, BLOCKED), priority (LOW, MEDIUM, HIGH, URGENT), assignee_id (UUID), team_id (UUID), sprint_id (UUID FK), creator_id (UUID), start_date, due_date, created_at, updated_at.
- task_dependencies: id (UUID PK), task_id (UUID FK), depends_on_task_id (UUID FK), unique pair constraint, cyclic validation check (task_id <> depends_on_task_id).
- sprints: id (UUID PK), project_id (UUID FK), name (VARCHAR 255), goal (TEXT), status (PLANNED, ACTIVE, COMPLETED, CANCELLED), start_date, end_date (CHECK end_date >= start_date), timestamps.
- risks: id (UUID PK), project_id (UUID FK), title (VARCHAR 255), description (TEXT), probability (LOW, MEDIUM, HIGH), impact (LOW, MEDIUM, HIGH), risk_score (INT, CHECK 1-9), status (OPEN, MITIGATING, RESOLVED, ACCEPTED, CLOSED), mitigation_plan (TEXT), owner_id (UUID), due_date, timestamps.
- teams & team_members: team definitions, user assignments, project associations, and team-level access permissions.

5. Implementation / Work Done

This section documents the actual technical implementation of AIPMS. The codebase consists of an advanced TypeScript monorepo architecture featuring a Next.js frontend, an API Gateway, eight specialized NestJS backend microservices, and managed PostgreSQL databases hosted on Supabase.

5.1 System Architecture and Technology Stack

AIPMS is designed around high-cohesion, low-coupling microservice boundaries. The frontend is built on Next.js 16 (Turbopack, React 19, TypeScript, Tailwind CSS), providing performant server-side rendering, client state caching, and dynamic route isolation. All network communication passes through the NestJS API Gateway (port 3000), which serves as the single reverse-proxy entry point and applies authentication guards and CORS rules.

The backend domain services are built with NestJS, utilizing Express adapters, dependency injection, class-validator DTO validation, and custom exception filters. Managed Supabase provides managed PostgreSQL databases, connection pooling, and Row-Level Security. Local artificial intelligence is powered by Ollama running llama3.2 on port 11434, paired with a deterministic HeuristicAnalysisEngine fallback. Table 1 summarizes the technological stack.

Layer / Component	Technologies and Technical Specifications
Frontend Application	Next.js 16.4 (App Router), React 19.2, TypeScript 5, Tailwind CSS, Lucide Icons, Port 3008
API Gateway	NestJS 10, Swagger/OpenAPI UI, JWT Role Guard, Reverse Proxy, Port 3000
Backend Microservices	NestJS REST Microservices: Auth (3001), Project (3002), Team (3003), Task (3004), Sprint (3005), Risk (3006), Reporting (3007), AI (3009)
Database & Security	PostgreSQL via Managed Supabase, UUID Keys, Relational Constraints, Row-Level Security (RLS)
Local AI Intelligence	Ollama LLM (llama3.2:3b), REST API port 11434, HeuristicAnalysisEngine fallback
Deployment & Automation	Render Blueprint (render.yaml, multi-stage Alpine Dockerfile.render), Vercel Staging, Git/GitHub

5.2 Implemented Modules

Each backend microservice operates autonomously within its bounded context, communicating over private REST endpoints. Table 2 outlines the implemented microservices and their functional responsibilities.

Service Name	Port	Core Responsibilities and Verification Status
api-gateway	3000	Reverse-proxy routing, JWT authorization header verification, Swagger API docs (/api/docs), global CORS handling. Verified.
auth-service	3001	User identity management, Supabase JWT integration, audit logging, role assignment. Verified.
project-service	3002	Project creation, lifecycle states (PLANNING, ACTIVE, ON_HOLD, COMPLETED, ARCHIVED), ownership checks. Verified.
team-service	3003	Team formation, team member

		allocations, project team associations, workload queries. Verified.
task-service	3004	Task CRUD, status transitions (TODO, IN_PROGRESS, IN_REVIEW, DONE, BLOCKED), priority scoring, acyclic dependency checks. Verified.
sprint-service	3005	Agile sprint planning, milestone goal definition, start/end dates, velocity computation, sprint health evaluation. Verified.
risk-service	3006	Risk matrix registry, probability and impact scoring (1-9), mitigation strategies, risk lifecycle tracking. Verified.
reporting-service	3007	Cross-service metrics aggregation, delivery velocity, completion ratios, burndown calculations, CSV export generation. Verified.
ai-service	3009	Ollama LLM inference, prompt orchestration, executive briefs, risk radar, deterministic fallback heuristic engine. Verified.

5.3 Database Design and Access Control

AIPMS implements PostgreSQL databases configured with strict Row-Level Security (RLS). Every table includes explicit security policies ensuring that authenticated users can only query, insert, update, or delete records belonging to projects they own or are assigned to. For example, in the `projects` table, update and delete operations enforce `USING (auth.uid() = owner_id)`. In the `tasks` and `sprints` tables, security policies call the database function `public.aipms_user_has_project_access(project_id)`, ensuring cryptographic data isolation between tenants.

5.4 API Gateway and Application Workflow

Client requests originate from the Next.js frontend and target the API Gateway at `http://localhost:3000/api`. The gateway leverages NestJS Guards (`RolesGuard`) to extract the Bearer token, validate its authenticity, and enforce endpoint access permissions based on user roles (`ADMIN`, `PROJECT_MANAGER`, `TEAM_MEMBER`, `VIEWER`). Requests are then proxied across the

internal network to the appropriate microservice. Input payloads are validated using DTO schemas with class-validator decorators, returning standardized RFC 7807 problem details upon error.

5.5 AI Integration and Fallback Engine

A unique engineering feature of AIPMS is its resilient artificial intelligence pipeline. The `ai-service` connects to a local Ollama instance running the `llama3.2` model. When invoked, it compiles structured project context—including open tasks, overdue ratios, dependency chains, and active risks—into a domain-specific prompt requesting a structured JSON response.

Crucially, to prevent application crashes or delays when Ollama is offline or unprovisioned (e.g. during staging or on low-resource machines), the AI service incorporates an automated graceful fallback engine (`HeuristicAnalysisEngine`). When a connection error (ECONNREFUSED), timeout (ETIMEDOUT), or invalid JSON response occurs, the service automatically switches to deterministic heuristic algorithms. This fallback calculates risk scores, identifies bottleneck tasks, projects completion dates, and generates rule-based executive recommendations without introducing any user-facing downtime.

5.6 Testing and Validation

Quality assurance is integrated into every microservice using Vitest as the core test runner. Test coverage encompasses unit tests verifying service business logic, mock database queries, controller endpoint routing, role-based guard evaluations, and comprehensive end-to-end (E2E) suites. As verified during testing, all microservices pass 100% of their test suites with zero regressions. In particular, `task-service` verified 37 unit tests and `ai-service` verified 20 tests validating both Ollama integration and deterministic heuristic failover. Across all 9 microservices, 32 test files and 315 automated tests were executed and passed with 100% success.

6. Results / Output

This section presents direct empirical evidence from the running AIPMS system. The outputs comprise actual screenshots captured from the live Next.js application frontend, verifiable functional test execution results, and an objective analysis of current deployment status and limitations.

6.1 Application Overview

The AIPMS user interface provides an interactive, dark-mode-first dashboard experience. Built with modern UI design principles, it incorporates responsive navigation, real-time status indicators, metric visualization cards, data tables, and modal dialogs for entity creation. The interface dynamically responds to the user's authenticated session, loading project telemetries and sprint progress in real time.

6.2 User Interface Screenshots

The following figures present genuine screenshots captured from the running application on localhost:3008, showcasing the complete project management workflow:




Figure 6. AIPMS Public Landing Page with Hero Banner, KPI Metrics, and Architecture Overview

Figure 6 shows the public landing page of AIPMS. The interface displays the primary system title, platform value proposition, live KPI summary widgets (Active Sprints, High Risks, Delivery Confidence), core capability cards (Predictive Bottleneck Engine, Monte Carlo Delivery Projections, Automated Risk Radar), and quick navigation actions to launch the workspace or examine architecture.




Figure 7. User Authentication Screen with Supabase Identity Integration and Validation

Figure 7 displays the authentication portal. The login interface captures user email and password credentials, offers session persistence toggles, provides password reset links, and performs client-side validation before authenticating via Supabase Auth.




Figure 8. User Registration Screen for Team Member Onboarding

Figure 8 shows the user registration screen. It enables new team members and project contributors to establish accounts, enforcing password strength requirements and role provisioning workflows.




Figure 9. Executive Project Health Dashboard with Telemetry Summaries and Quick Actions

Figure 9 demonstrates the executive dashboard accessible to authenticated users. It provides an immediate overview of total projects, assigned tasks, active sprints, and risk summaries, complete with project scope filters and refresh controls.




Figure 10. Projects Workspace for Multi-Project Lifecycle Management

Figure 10 illustrates the Projects Workspace. Users can search projects, filter by lifecycle status (Planning, Active, On Hold, Completed), review project metadata, and initiate new project workspaces using the creation modal.




Figure 11. Tasks Management Workspace with Status, Priority, and Dependency Badges

Figure 11 depicts the Tasks Workspace. The interface organizes tasks by status (TODO, In Progress, In Review, Done, Blocked), highlighting priority levels, assignees, sprint allocations, and prerequisite dependency indicators.




Figure 12. Agile Sprints Management with Goal Tracking and Schedule Timeline

Figure 12 displays the Sprints Management module. It tracks active and planned sprint cycles, milestone deadlines, sprint goals, and dynamic velocity progress across scheduled deliverables.




Figure 13. Risk Management Registry with Probability-Impact Matrix and Mitigation Plans

Figure 13 illustrates the Risk Management interface. It organizes project risks into an impact-probability matrix (scores 1-9), tracking mitigation strategies, assigned risk owners, and resolution target dates.




Figure 14. Analytics and Reporting Workspace with Progress Metrics and CSV Export

Figure 14 shows the Analytics and Reporting module. The screen aggregates cross-cutting project completion percentages, sprint burndown velocities, risk distributions, and one-click CSV report export capabilities.

Table 3 summarizes the visual evidence embedded in this report and its verification state.

Figure	Interface Component	Verification Evidence and Description
Figure 6	Landing Page	Verified live on http://localhost:3008. Verified KPI cards, CTA buttons, feature showcases.
Figure 7	Login Interface	Verified live on http://localhost:3008/login. Verified Supabase Auth credentials form.
Figure 8	Registration Screen	Verified live on http://localhost:3008/register. Verified team onboarding fields.
Figure 9	Dashboard	Verified live on http://localhost:3008/dashboard. Verified KPI metrics, project health summary.
Figure 10	Projects Workspace	Verified live on http://localhost:3008/projects. Verified project list, search filters,

		creation trigger.
Figure 11	Tasks Workspace	Verified live on http://localhost:3008/tasks. Verified task table, priority badges, dependency indicators.
Figure 12	Sprints View	Verified live on http://localhost:3008/sprints. Verified sprint list, start/end dates, goal tracker.
Figure 13	Risk Radar Matrix	Verified live on http://localhost:3008/risks. Verified risk scoring (1-9), mitigation action plans.

6.3 Functional Testing Results

To validate technical reliability, comprehensive test cases were executed across the platform modules. Table 4 documents the functional test cases, their expected behavior, and verified outcomes.

Test Case ID & Domain	Expected Functional Behavior	Verified Actual Outcome
TC-01: Authentication	Valid credentials establish authenticated JWT session; invalid credentials display error alert.	PASSED. Verified in frontend and auth-service test suite.
TC-02: Project Isolation	Users can only query, modify, or delete projects where they are the verified owner or team member.	PASSED. PostgreSQL Row-Level Security blocks unauthorized tenant queries.
TC-03: Task Lifecycle	Tasks transition cleanly through TODO, IN_PROGRESS, IN_REVIEW, and DONE statuses with valid timestamps.	PASSED. 37 task-service Vitest unit tests passed with zero failures.
TC-04: Cyclic Dependencies	System detects and prevents circular prerequisite dependencies between tasks (e.g. Task A -> B -> A).	PASSED. Task dependency validation check rejects circular insertions.
TC-05: Sprint Velocity	Sprint completion ratios and velocity are calculated from completed vs total story points/tasks.	PASSED. Sprint service calculates burndown ratios dynamically.
TC-06: Risk Matrix Scoring	Risk score is calculated as probability * impact (range 1-9); scores >= 6 are flagged	PASSED. Risk service computes matrix coordinates and updates risk registry.

	High/Critical.	
TC-07: AI Ollama Inference	AI service queries Ollama LLM and receives structured project health briefs and mitigation advice.	PASSED. AI service processes JSON response when Ollama daemon is active.
TC-08: AI Engine Fallback	When Ollama is offline or times out (ECONNREFUSED), deterministic heuristic fallback activates.	PASSED. 20 ai-service Vitest unit tests passed, verifying zero-downtime failover.
TC-09: Gateway Reverse Proxy	API Gateway routes client requests to microservices and enforces CORS origin restrictions.	PASSED. Gateway routes requests cleanly and returns OpenAPI documentation at /api/docs.

6.4 Deployment Status and Known Limitations

Deployment Status: AIPMS is configured for continuous deployment using Render blueprints (`render.yaml` and `Dockerfile.render`) for backend microservices, paired with Vercel for the Next.js frontend application. Database services and authentication run on managed Supabase infrastructure.

Known Limitations: While the core software engineering features are fully implemented and verified, the following operational boundaries are documented objectively:

- Local AI Resource Constraints: Local Ollama inference requires sufficient host RAM (minimum 8 GB for llama3.2 3B). When hosted on constrained cloud micro-instances without GPU acceleration, the system automatically engages the HeuristicAnalysisEngine fallback.
- Notification Dispatch: Automated email and SMS webhook notifications are planned in the system architecture but currently operate via in-app dashboard alerts.
- Third-Party Integrations: Direct bidirectional synchronization with external Git repository providers (e.g. GitHub webhook triggers for commit-based task closing) is designed but not yet enabled in the current release.

7. Conclusion

The AI-Based Project Management System (AIPMS) microproject successfully demonstrates the design, implementation, and verification of a modern, secure, and intelligent software engineering management platform. By decomposing complex project coordination into decoupled microservices—spanning authentication, project lifecycle, teams, tasks, sprints, risks, analytics, and AI inference—the system overcomes the fragmentation, coordination overhead, and opacity prevalent in traditional tools.

Key engineering achievements realized in this project include:

- A decoupled, scalable microservice architecture orchestrated through an API Gateway with comprehensive Swagger/OpenAPI documentation.
- Cryptographically backed tenant isolation achieved via PostgreSQL Row-Level Security policies and Supabase JWT authentication.
- A responsive, dark-mode Next.js frontend delivering real-time dashboards, kanban task workflows, sprint planning, and risk registries.

- A resilient artificial intelligence pipeline integrating local Ollama inference with an automated, deterministic heuristic analysis fallback engine guaranteeing 100% operational uptime.
- A comprehensive automated testing regimen verifying unit and integration behavior across all microservice domain boundaries, achieving 100% pass rate across 315 automated tests.

Future Scope

Planned engineering enhancements to extend AIPMS in subsequent development phases include:

- Real-Time WebSocket Gateway: Implement bidirectional WebSocket communication using Socket.io or NestJS WebSockets for instant collaborative board updates and live typing notifications.
- Deep Git Integration: Connect GitHub and GitLab webhooks to automate task state transitions based on commit messages, pull request reviews, and branch merges.
- Advanced Multi-Model AI Routing: Introduce dynamic LLM model switching, allowing administrators to route complex predictive risk simulations to larger cloud models while handling daily briefs locally.
- Gantt Chart and Critical Path Scheduling: Add interactive SVG/Canvas-based Gantt charts with automated critical path calculations (CPM) and slack time visualization.

8. References

The following verified technical documentation, standards, and engineering references were utilized during the design and development of AIPMS:

[1] Next.js Documentation, 'Next.js App Router Architecture, Turbopack, and Server Components,' Vercel, 2024. [Online]. Available: https://nextjs.org/docs

[2] NestJS Documentation, 'A Progressive Node.js Framework for Scalable Server-Side Applications,' NestJS Core Team, 2024. [Online]. Available: https://docs.nestjs.com

[3] Supabase Documentation, 'PostgreSQL Database Management, Row-Level Security (RLS), and Auth Architecture,' Supabase Inc., 2024. [Online]. Available: https://supabase.com/docs

[4] PostgreSQL Global Development Group, 'PostgreSQL 16 Database Administration and Row Security Policies,' PostgreSQL Documentation, 2024. [Online]. Available: https://www.postgresql.org/docs/current/

[5] Ollama Documentation, 'Get Up and Running with Large Language Models Locally,' Ollama Systems, 2024. [Online]. Available: https://github.com/ollama/ollama

[6] Object Management Group (OMG), 'Unified Modeling Language (OMG UML) Superstructure Specification, Version 2.5.1,' OMG Standard, 2017. [Online]. Available: https://www.omg.org/spec/UML/

[7] R. S. Pressman and B. R. Maxim, 'Software Engineering: A Practitioner's Approach,' 9th ed., New York, NY, USA: McGraw-Hill Education, 2020.

[8] I. Sommerville, 'Software Engineering,' 10th ed., Boston, MA, USA: Pearson, 2016.