

## Spock Test

```
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 http://
maven.apache.org/xsd/maven-4.0.0.xsd">
  <modelVersion>4.0.0</modelVersion>

  <groupId>guru.springframework</groupId>
  <artifactId>mb2g-testing</artifactId>
  <version>1.0-SNAPSHOT</version>

  <properties>
    <project.build.sourceEncoding>UTF-8</project.build.sourceEncoding>
    <project.reporting.outputEncoding>UTF-8</
project.reporting.outputEncoding>
    <java.version>11</java.version>
    <maven.compiler.source>${java.version}</maven.compiler.source>
    <maven.compiler.target>${java.version}</maven.compiler.target>
  </properties>

  <dependencies>
    <dependency>
      <groupId>org.codehaus.groovy</groupId>
      <artifactId>groovy-all</artifactId>
      <version>3.0.8</version>
      <type>pom</type>
    </dependency>
    <dependency>
      <groupId>junit</groupId>
      <artifactId>junit</artifactId>
      <version>4.12</version>
      <scope>test</scope>
    </dependency>
    <dependency>
      <groupId>org.spockframework</groupId>
      <artifactId>spock-core</artifactId>
      <version>2.0-M5-groovy-3.0</version>
      <scope>test</scope>
    </dependency>
  </dependencies>

  <build>
    <plugins>
```

```

<plugin>
  <artifactId>maven-compiler-plugin</artifactId>
  <version>3.8.0</version><!-- 3.1 is the minimum -->
  <configuration>
    <compilerId>groovy-eclipse-compiler</compilerId>
    <compilerArguments>
      <indy/><!-- optional; supported by batch 2.4.12-04+ -->
      <configScript>config.groovy</configScript><!-- optional;
supported by batch 2.4.13-02+ -->
    </compilerArguments>
  </configuration>
  <dependencies>
    <dependency>
      <groupId>org.codehaus.groovy</groupId>
      <artifactId>groovy-eclipse-compiler</artifactId>
      <version>3.7.0</version>
    </dependency>
    <dependency>
      <groupId>org.codehaus.groovy</groupId>
      <artifactId>groovy-eclipse-batch</artifactId>
      <version>3.0.8-01</version>
    </dependency>
  </dependencies>
</plugin>
<plugin>
  <groupId>org.apache.maven.plugins</groupId>
  <artifactId>maven-surefire-plugin</artifactId>
  <version>2.22.0</version>
  <configuration>
    <argLine>
      --illegal-access=permit
    </argLine>
  </configuration>
</plugin>
</plugins>
</build>

</project>

```

We can write test using Spock

It is a .groovy file.

```
package guru.springframework
```

```
import spock.lang.Specification
```

```
/**
 * Created by jt on 2018-12-12.
 */
class JavaHelloWorldSpecTest extends Specification {

    def "GetHello"() {

        when:
        def foo = "123"

        then:
        true
    }
}
```

It needs groovy plugins to compile.

We are doing bdd, we are saying when called foo = "123" then I am saying evaluate to true.