

# Patterns and Matcher

The Java Class Library has two special classes possessing advanced features for work with regular

expressions: `java.util.regex.Pattern` and `java.util.regex.Matcher`

A `Matcher` object provides us with many useful methods to handle regexes, while a `Pattern` object represents a regular expression itself.

## Matching a regex

```
String text = "We use Java to write modern applications";
```

We want to use a regular expression to check whether the text contains substrings **"Java"** or **"java"**. We can carry this out in three simple steps with the `Pattern` and `Matcher` classes.

1. Create an object of the `Pattern` class by passing a regex string to the `compile` method:

```
Pattern pattern = Pattern.compile(".*[Jj]ava.*"); // regex to match "java" or "Java" in a text
```

2. Create a `Matcher` by invoking the `matcher` method of the `Pattern` and creating an object for the given string:

```
Matcher matcher = pattern.matcher(text); // it will match the passed text
```

3. Invoke the `matches` method of the `matcher` to match the string:

```
boolean matches = matcher.matches(); // true
```

The method `matches` of a `Matcher` works exactly the same way as the method `matches` of the `String`, with which we are already familiar.

## Advantages of Pattern and Matcher classes

- **Performance.** Actually, the `matches` method of the `String` internally invokes the `matches` method of the `Matcher`, but it also invokes `Pattern.compile(...)` every time it is executed. That's not efficient. If the same pattern is used multiple times, compiling it once will be more reasonable.
- **Rich API.** The `Matcher` class has more to offer than a single `matches` method: there are a lot of useful methods to process strings and a `Pattern` provides us with the opportunity to configure it in detail, for example, enabling case-insensitive matching.

So, if you plan on reusing your regex several times and/or need more elaborate methods for text and pattern comparison, it is preferable to use Pattern and Matcher rather than String.

## Patterns and Modes

A Pattern is used to create an object of Matcher. If we aren't going to reuse our regex, though, we can simply invoke the matches method of the Pattern class in a single line.

```
Pattern.matches(".*[Jj]ava.*", "We use Java to write modern applications"); // true
```

It is similar to invoking the matches method of a String but has the same performance problem.

It cannot match words like **"JAVA"** because it does not ignore the case, as all regular expressions do by default. Fortunately, there is a special mode Pattern.CASE\_INSENSITIVE that can be set during the compilation of the Pattern. It allows your regex to match strings without taking the case into account.

```
Pattern pattern = Pattern.compile(".*java.*", Pattern.CASE_INSENSITIVE);
```

```
String text = "We use Java to write modern applications";
```

```
Matcher matcher = pattern.matcher(text);
```

```
System.out.println(matcher.matches()); // true
```

Another mode you may want to remember is Pattern.DOTALL that makes the dot metacharacter . match all characters, including the line break \n.

```
Pattern.matches("(?is).*java.*", "\n\nJAVA\n\n"); // true
```

## The matches and find methods

Just as the matches method of the String, the method matches of the Matcher returns true only when the pattern matches the whole string, otherwise, it returns false. That's not very convenient in some situations.

For example, if we want to check whether there is a particular substring somewhere in our text, we have to add .\* at the beginning and at the end of the pattern.

Thanks to the Matcher , we can also apply the find method. It is similar to

the matches , but instead of checking the match with the whole string, it tries to find a substring that matches the pattern.

```
String text = "Regex is a powerful tool for programmers";
```

```
Pattern pattern = Pattern.compile("tool");  
Matcher matcher = pattern.matcher(text);
```

```
System.out.println(matcher.matches()); // false, the whole string does not  
match the pattern
```

```
System.out.println(matcher.find()); // true, there is a substring that matches the  
pattern
```

Remember the boundary characters we've learned before? They can be applied to modify the behavior of the find method to make it work somewhat similarly to the matches method. To make sure that the find method will match a substring located at the beginning of the string, we can add the hat character ^ at the start of the regex. To make it match a substring at the end of the string, we can add the dollar character \$ at the end of the regex.

By combining these symbols, we make out of find a copy of matches:

```
Pattern pattern = Pattern.compile("^tool$");  
Matcher matcher = pattern.matcher(text);
```

```
System.out.println(matcher.matches()); // false  
System.out.println(matcher.find()); // false
```

By default, both methods matches and find work with the whole string. It is possible, though, to narrow down their scope by invoking the region method that allows us to specify the first (inclusive) and the last (exclusive) indices of the substring that we want our methods to consider.

```
String text = "Regex is a powerful tool for programmers";  
Matcher matcher = Pattern.compile("tool").matcher(text);
```

```
matcher.region(10, 20); // start index = 10, end index = 20  
System.out.println(matcher.find()); // false  
matcher.region(20, 30); // start index = 20, end index = 30  
System.out.println(matcher.find()); // true
```

