

Domain2Vec: Domain Embedding for Unsupervised Domain Adaptation

Supplementary Material

Xingchao Peng^{*1}, Yichen Li^{*2}, and Kate Saenko^{1,3}

¹ Boston University, Boston, MA, USA

² Stanford University, Stanford, CA, USA

³ MIT-IBM Watson AI Lab, Boston, MA, USA

{xpeng,saenko}@bu.edu, liyichen@stanford.edu

The supplementary material is organized as follows: Section A shows the comparison of our two datasets with the state-of-the-art cross-domain datasets. Section B describes the details of generating the TINYDA dataset. Section C shows the detailed information about DOMAINBANK dataset. Section D introduces the detailed network framework for experiments on TINYDA dataset. Section E shows the additional experimental analysis. Section F shows the category information in the openset domain adaptation experiments.

A Comparison to modern datasets

| Dataset | Year | Images | Classes | Domains | Description |
|--------------------|------|----------|----------|---------|-----------------|
| Digit-Five | - | ~100,000 | 10 | 5 | digit |
| Office [1] | 2010 | 4,110 | 31 | 3 | office |
| Office-Caltech [2] | 2012 | 2,533 | 10 | 4 | office |
| CAD-Pascal [3] | 2015 | 12,000 | 20 | 6 | animal, vehicle |
| Office-Home [4] | 2017 | 15,500 | 65 | 4 | office, home |
| PACS [5] | 2017 | 9,991 | 7 | 4 | animal, stuff |
| Open MIC [6] | 2018 | 16,156 | - | - | museum |
| Syn2Real [7] | 2018 | 280,157 | 12 | 3 | animal, vehicle |
| DomainNet [8] | 2019 | 569,010 | 345 | 6 | clipart, sketch |
| TinyDA (Ours) | - | 965,619 | 10 or 26 | 54 | tiny images |
| DomainBank (Ours) | - | 339,772 | - | 55 | dataset |

Table 1. A collection of most notable datasets to evaluate domain adaptation methods. Specifically, ‘‘Digit-Five’’ dataset indicates five most popular digit datasets (MNIST [9], MNIST-M [10], Synthetic Digits [10], SVHN, and USPS) which are widely used to evaluate domain adaptation models. Our dataset is challenging as it contains more images and domains than other datasets.

B TinyDA Generation

The images from TINYDA dataset are generated by blending different foreground shapes over patches randomly extracted from background images. In the first step, we select a foreground shape from the following five MNIST-style datasets: MNIST [11], USPS [12], EMNIST [13], KMNIST [14], QMNIST [15], and Fashion-MNIST [16]. Secondly, we choose a background pattern from the CIFAR10 [17]

^{*} These authors contributed equally.

dataset or randomly cropped from BSD500 [18] dataset. Thirdly, we perform three different post-process to our rendered images: (1) replace the background with black patch, (2) replace the background with white path, (3) convert the generated images to grayscale images. These three post-processes, together with the original foreground images and the generated color images, form a dataset with five different modes, *i.e.* Black Background (*BB*), White Background (*WB*), GrayScale image (*GS*), Color (*Cr*) image, Original image (*Or*). In total, we generate a dataset with 54 domains and about one million MNIST-style training examples.

The image examples of our TINYDA dataset are shown in Table 2. Specifically, the upper and below table show the images generated with backgrounds from BSDS500 [18] and CIFAR10 [17], respectively. The image number of each domain in TINYDA dataset can be seen from Table 3.

| | Foreground | Background | Mode |
|---------------|------------|------------|-----------|
| MNIST | | | Black BG |
| USPS | | | White BG |
| EMNIST | | | Color |
| KMNIST | | | Grayscale |
| QMNIST | | | Original |
| Fashion Mnist | | | |
| | | | |
| CIFAR10 | | | |
| BSDS | | | |

Fig. 1. Generation configuration for TINYDA dataset. We create our TinyDA dataset with six foregrounds, two backgrounds and five modes. The foreground images are from MNIST [11], USPS [12], EMNIST [13], KMNIST [14], QMNIST [15], FashionMNIST [16]. The background images are randomly sampled from CIFAR10 [17] or randomly cropped from BSDS500 [18] dataset. The five modes include “Black Background”, “White Background”, “Color”, “GrayScale”, and “Original”.

| FG/Mode | Black BG | White BG | Color | Grayscale | Original |
|--------------|----------|----------|-------|-----------|----------|
| MNIST | | | | | |
| USPS | | | | | |
| FashionMNIST | | | | | |
| KMNIST | | | | | |
| QMNIST | | | | | |
| EMNIST | | | | | |
| MNIST | | | | | |
| USPS | | | | | |
| FashionMNIST | | | | | |
| KMNIST | | | | | |
| QMNIST | | | | | |
| EMNIST | | | | | |

Table 2. Illustration of TINYDA dataset. We create our TINYDA dataset with six foregrounds, two backgrounds, and five modes. The upper and below table show the images generated with backgrounds from BSDS500 [18] and CIFAR10 [17], respectively.

| FG/Mode | Black BG | White BG | Color | Grayscale | Original |
|--------------|----------|----------|--------|-----------|----------|
| MNIST | 40,000 | 40,000 | 40,000 | 40,000 | 20,000 |
| USPS | 14,582 | 14,582 | 14,582 | 14,582 | 7291 |
| FashionMNIST | 40,000 | 40,000 | 40,000 | 40,000 | 20,000 |
| KMNIST | 40,000 | 40,000 | 40,000 | 40,000 | 20,000 |
| QMNIST | 40,000 | 40,000 | 40,000 | 40,000 | 20,000 |
| EMNIST | 40,000 | 40,000 | 40,000 | 40,000 | 20,000 |

Table 3. Number of images in each domain of TINYDA dataset.

| ID | Image Samples | ID | Image Samples |
|----|---------------|----|---------------|
| 1 | | 2 | |
| 3 | | 4 | |
| 5 | | 6 | |
| 7 | | 8 | |
| 9 | | 10 | |
| 11 | | 12 | |
| 13 | | 14 | |
| 15 | | 16 | |
| 17 | | 18 | |
| 19 | | 20 | |
| 21 | | 22 | |
| 23 | | 24 | |
| 25 | | 26 | |
| 27 | | 28 | |
| 29 | | 30 | |
| 31 | | 32 | |
| 33 | | 34 | |
| 35 | | 36 | |
| 37 | | 38 | |
| 39 | | 40 | |
| 41 | | 42 | |
| 43 | | 44 | |
| 45 | | 46 | |
| 47 | | 48 | |
| 49 | | 50 | |
| 51 | | 52 | |
| 53 | | 54 | |
| 55 | | 56 | |

Table 4. Illustration of DOMAINBANK dataset. The ID is this table is corresponding to the ID in Table 5.

| ID | Dataset Name | Image# | Description | ID | Dataset Name | Image# | Description |
|----|---------------------|--------|--------------|----|------------------------|--------|-------------|
| 1 | CUFSF [19] | 1,194 | face_sketch | 2 | COCO [20] | 10,000 | real |
| 3 | PASCAL [21] | 10,000 | realm | 4 | DomainNet [8] | 10,000 | real |
| 5 | SYNTHIA [22] | 10,000 | street_syn | 6 | UIUC CAR [23] | 1,220 | car |
| 7 | ZuDuB [24] | 210 | building | 8 | Bark-101 [25] | 2,586 | bark |
| 9 | DomainNet [8] | 10,000 | sketch | 10 | Open-MIC [6] | 10,000 | indoor |
| 11 | DomainNet [8] | 10,000 | clipart | 12 | Caltech256 [26] | 10,000 | real |
| 13 | Ped. Detection [27] | 10,000 | pedestrian | 14 | Traffic Sign [28] | 4,053 | traffic |
| 15 | UKBench [29] | 10,000 | indoor_stuff | 16 | Oxford Flower [30] | 8,189 | flower |
| 17 | Caltech Games [31] | 7,660 | game_cover | 18 | Oxford Buildings [32] | 5,063 | building |
| 19 | GFW Face [33] | 3,236 | face | 20 | Driving [34] | 9,420 | road |
| 21 | MegaAge [35] | 10,000 | face | 22 | ADE20K [36] | 10,000 | indoor |
| 23 | Ped. Color [37] | 10,000 | pedestrian | 24 | LabelMeFacade [38] | 395 | building |
| 25 | UT Zappos50K [39] | 10,000 | shoes | 26 | TRANCOS [40] | 1,244 | traffic |
| 27 | FGVC [40] | 10,000 | aeroplane | 28 | Mall Dataset [41] | 2,000 | mall |
| 29 | Chars74K [42] | 7,705 | character | 30 | DomainNet [8] | 10,000 | painting |
| 31 | Paris Dataset [43] | 3,187 | street | 32 | DomainNet [8] | 10,000 | infograph |
| 33 | DroneDataset [44] | 400 | drone | 34 | Boxy [45] | 2,148 | road |
| 35 | Stanford Car [46] | 8,144 | car | 36 | DeepFashion2 [47] | 10,000 | fashion |
| 37 | ExDark [48] | 6,619 | dark | 38 | LaMem [49] | 10,000 | memorial |
| 39 | Stanford Dog [50] | 10,000 | dog | 40 | Cartoon Set [51] | 9,999 | cartoon |
| 41 | DomainNet [8] | 10,000 | quick_draw | 42 | Football [52] | 771 | football |
| 43 | Sketch Objects [53] | 10,000 | sketch | 44 | CUB200 [54] | 10,000 | bird |
| 45 | CITY-OSM [55] | 914 | drone_view | 46 | Arch Style [56] | 4,630 | building |
| 47 | UCM Land [57] | 2,100 | satellite | 48 | Privacy Attribute [58] | 4,157 | stuff |
| 49 | IMDB-WIKI [59] | 10,000 | face | 50 | Street View [60] | 6,594 | street |
| 51 | PPSS [61] | 1,458 | pedestrian | 52 | Sketch Retrieval [62] | 1,213 | sketch |
| 53 | VisDA [63] | 10,000 | syn | 54 | GTA [64] | 5,000 | syn |
| 55 | Youtube BBox [65] | 10,000 | real | 56 | Logo-2k+ [66] | 10,000 | logo |

Table 5. Detailed information about our DomainBank dataset.

C DomainBank Dataset

The images of DOMAINBANK dataset are sampled from 56 existing popular computer vision datasets. We choose the dataset with different image modalities, illuminations, camera perspectives *etc.* to increase the diversity of the domains. More details about our DOMAINBANK benchmark are shown in Table 4 and Table 5. In total, we collect 339,772 images with image-level and domain-level annotations. Different from TINYDA, the categories of different domains in DOMAINBANK are not identical. This property makes DOMAINBANK a good testbed for Openset Domain Adaptation and Partial Domain Adaptation.

D Model architecture

The detailed network architecture for TINYDA dataset is shown in Table 6.

| layer | configuration |
|------------------------------|---|
| Feature Generator | |
| 1 | Conv2D (3, 64, 5, 1, 2), BN, ReLU, MaxPool |
| 2 | Conv2D (64, 64, 5, 1, 2), BN, ReLU, MaxPool |
| 3 | Conv2D (64, 128, 5, 1, 2), BN, ReLU |
| Disentangler | |
| 1 | FC (8192, 3072), BN, ReLU |
| 2 | DropOut (0.5), FC (3072, 2048), BN, ReLU |
| Domain Classifier | |
| 1 | FC (2048, 256), LeakyReLU |
| 2 | FC (256, 56), LeakyReLU |
| Classifier | |
| 1 | FC (2048, 10 or 26), BN, Softmax |
| Reconstructor | |
| 1 | FC (4096, 8192) |
| Mutual Information Estimator | |
| fc1.x | FC (2048, 512) |
| fc1.y | FC (2048, 512), LeakyReLU |
| 2 | FC (512,1) |

Table 6. Model Architecture for experiments on TINYDA dataset. For each convolution layer, we list the input dimension, output dimension, kernel size, stride, and padding. For the fully-connected layer, we provide the input and output dimensions. For drop-out layers, we provide the probability of an element to be zeroed.

E Additional experimental results




Fig. 2. Deep domain embedding results of our DOMAIN2VEC model on TINYDA dataset: (a) t-SNE plot of the embedding result (color indicates different background); (b)t-SNE plot of the embedding result (color indicates different foreground); (c) t-SNE plot of the embedding result (color indicates different mode); (d) Deep embedding result. (Best viewed in color. Zoom in to see details.)

F Category information

For openset domain adaptation experiments, we choose the “aeroplane”, “bus”, “horse”, “motorcycle”, “plant”, “train”, and “truck” as the common categories




Fig. 3. Deep domain embedding results of our DOMAIN2VEC model on DOMAIN-BANK dataset: **(a)** t-SNE plot of the embedding result (color indicates different domain); **(d)** Deep embedding result. (Best viewed in color. Zoom in to see details.)

across the four domains. We set “bicycle”, “car” “knife”, “person”, “skateboard” as the unknown categories.

References

1. Saenko, K., Kulis, B., Fritz, M., Darrell, T.: Adapting visual category models to new domains. In: European conference on computer vision, Springer (2010) 213–226
 2. Gong, B., Shi, Y., Sha, F., Grauman, K.: Geodesic flow kernel for unsupervised domain adaptation. In: Computer Vision and Pattern Recognition (CVPR), 2012 IEEE Conference on, IEEE (2012) 2066–2073
 3. Peng, X., Sun, B., Ali, K., Saenko, K.: Learning deep object detectors from 3d models. In: Proceedings of the IEEE International Conference on Computer Vision. (2015) 1278–1286
 4. Venkateswara, H., Eusebio, J., Chakraborty, S., Panchanathan, S.: Deep hashing network for unsupervised domain adaptation. In: (IEEE) Conference on Computer Vision and Pattern Recognition (CVPR). (2017)
 5. Li, D., Yang, Y., Song, Y.Z., Hospedales, T.: Deeper, broader and artier domain generalization. In: International Conference on Computer Vision. (2017)
 6. Koniusz, P., Tas, Y., Zhang, H., Harandi, M., Porikli, F., Zhang, R.: Museum exhibit identification challenge for the supervised domain adaptation and beyond. In: The European Conference on Computer Vision (ECCV). (September 2018)
 7. Peng, X., Usman, B., Saito, K., Kaushik, N., Hoffman, J., Saenko, K.: Syn2real: A new benchmark for synthetic-to-real visual domain adaptation. CoRR [abs/1806.09755](#) (2018)
 8. Peng, X., Bai, Q., Xia, X., Huang, Z., Saenko, K., Wang, B.: Moment matching for multi-source domain adaptation. In: Proceedings of the IEEE International Conference on Computer Vision. (2019) 1406–1415

9. LeCun, Y., Bottou, L., Bengio, Y., Haffner, P.: Gradient-based learning applied to document recognition. *Proceedings of the IEEE* **86**(11) (1998) 2278–2324
10. Ganin, Y., Lempitsky, V.: Unsupervised domain adaptation by backpropagation. In Bach, F., Blei, D., eds.: *Proceedings of the 32nd International Conference on Machine Learning*. Volume 37 of *Proceedings of Machine Learning Research.*, Lille, France, PMLR (07–09 Jul 2015) 1180–1189
11. LeCun, Y., Boser, B., Denker, J., Henderson, D., Howard, R., Hubbard, W., Jackel, L.: Backpropagation applied to handwritten zip code recognition. *Neural Computation* (1989)
12. Hull, J.J.: A database for handwritten text recognition research. *IEEE Transactions on pattern analysis and machine intelligence* **16**(5) (1994) 550–554
13. Cohen, G., Afshar, S., Tapson, J., van Schaik, A.: Emnist: an extension of mnist to handwritten letters. *arXiv preprint arXiv:1702.05373* (2017)
14. Klanuwat, T., Bober-Irizar, M., Kitamoto, A., Lamb, A., Yamamoto, K., Ha, D.: Deep learning for classical japanese literature. *arXiv preprint arXiv:1812.01718* (2018)
15. Yadav, C., Bottou, L.: Cold case: The lost mnist digits. *arXiv preprint arXiv:1905.10498* (2019)
16. Xiao, H., Rasul, K., Vollgraf, R.: Fashion-mnist: a novel image dataset for benchmarking machine learning algorithms. *arXiv preprint arXiv:1708.07747* (2017)
17. Krizhevsky, A., Hinton, G., et al.: Learning multiple layers of features from tiny images. Technical report, Citeseer (2009)
18. Arbelaez, P., Maire, M., Fowlkes, C., Malik, J.: Contour detection and hierarchical image segmentation. *IEEE Trans. Pattern Anal. Mach. Intell.* **33**(5) (May 2011) 898–916
19. Zhang, W., Wang, X., Tang, X.: Coupled information-theoretic encoding for face photo-sketch recognition. In: *CVPR 2011*, IEEE (2011) 513–520
20. Lin, T.Y., Maire, M., Belongie, S., Hays, J., Perona, P., Ramanan, D., Dollár, P., Zitnick, C.L.: Microsoft COCO: Common objects in context. In: *European conference on computer vision*, Springer (2014) 740–755
21. Everingham, M., Van Gool, L., Williams, C.K.I., Winn, J., Zisserman, A.: The pascal visual object classes (voc) challenge. *International Journal of Computer Vision* **88**(2) (June 2010) 303–338
22. Zolfaghari Bengar, J., Gonzalez-Garcia, A., Villalonga, G., Raducanu, B., Aghdam, H.H., Mozerov, M., Lopez, A.M., van de Weijer, J.: Temporal coherence for active learning in videos. In: *The IEEE International Conference in Computer Vision, Workshops (ICCV Workshops)*. (2019)
23. UIUC: Uiuc car dataset, <http://l2r.cs.uiuc.edu/cogcomp/data/car/>
24. Shao, H., Svoboda, T., Van Gool, L.: Zubud: Zurich buildings database for image based recognition. (01 2003)
25. Ratajczak, R., Bertrand, S., Crispim-Junior, C., Tougne, L.: Efficient bark recognition in the wild. (02 2019)
26. Griffin, G., Holub, A., Perona, P.: Caltech-256 object category dataset. (2007)
27. Enzweiler, M., Gavrila, D.M.: Monocular pedestrian detection: Survey and experiments. *IEEE transactions on pattern analysis and machine intelligence* **31**(12) (2008) 2179–2195
28. Mathias, M., Timofte, R., Benenson, R., Van Gool, L.: Traffic sign recognition—how far are we from the solution? In: *The 2013 international joint conference on Neural networks (IJCNN)*, IEEE (2013) 1–8

29. Nister, D., Stewenius, H.: Scalable recognition with a vocabulary tree. In: 2006 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'06). Volume 2., Ieee (2006) 2161–2168
30. Nilsback, M.E., Zisserman, A.: A visual vocabulary for flower classification. In: 2006 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'06). Volume 2., IEEE (2006) 1447–1454
31. Aly, M., Welinder, P., Munich, M., Perona, P.: Towards automated large scale discovery of image families. In: 2009 IEEE Computer Society Conference on Computer Vision and Pattern Recognition Workshops, IEEE (2009) 9–16
32. Philbin, J., Chum, O., Isard, M., Sivic, J., Zisserman, A.: Object retrieval with large vocabularies and fast spatial matching. In: 2007 IEEE conference on computer vision and pattern recognition, IEEE (2007) 1–8
33. He, Y., Cao, K., Li, C., Loy, C.C.: Merge or not? learning to group faces via imitation learning. In: Thirty-Second AAAI Conference on Artificial Intelligence. (2018)
34. Udacity: <https://github.com/udacity/self-driving-car>
35. Zhang, Y., Liu, L., Li, C., Loy, C.C.: Quantifying facial age by posterior of age comparisons. In: British Machine Vision Conference (BMVC). (2017)
36. Zhou, B., Zhao, H., Puig, X., Xiao, T., Fidler, S., Barriuso, A., Torralba, A.: Semantic understanding of scenes through the ade20k dataset. International Journal of Computer Vision **127**(3) (2019) 302–321
37. Cheng, Z., Li, X., Loy, C.C.: Pedestrian color naming via convolutional neural network. In: Asian Conference on Computer Vision, Springer (2016) 35–51
38. Fröhlich, B., Rodner, E., Denzler, J.: A fast approach for pixelwise labeling of facade images. In: Proceedings of the International Conference on Pattern Recognition (ICPR 2010). (2010)
39. Yu, A., Grauman, K.: Fine-grained visual comparisons with local learning. In: Computer Vision and Pattern Recognition (CVPR). (Jun 2014)
40. Guerrero-Gómez-Olmedo, R.: Extremely overlapping vehicle counting. In: Iberian Conference on Pattern Recognition and Image Analysis (IbPRIA). (2015)
41. Change Loy, C., Gong, S., Xiang, T.: From semi-supervised to transfer counting of crowds. In: Proceedings of the IEEE International Conference on Computer Vision. (2013) 2256–2263
42. De Campos, T.E., Babu, B.R., Varma, M., et al.: Character recognition in natural images. VISAPP (2) **7** (2009)
43. Philbin, J., Chum, O., Isard, M., Sivic, J., Zisserman, A.: Lost in quantization: Improving particular object retrieval in large scale image databases. In: 2008 IEEE conference on computer vision and pattern recognition, IEEE (2008) 1–8
44. of Computer Graphics, I., Vision: <http://dronedataset.icg.tugraz.at/>
45. Behrendt, K.: Boxy vehicle detection in large images. In: Proceedings of the IEEE International Conference on Computer Vision. (2019)
46. Krause, J., Stark, M., Deng, J., Fei-Fei, L.: 3d object representations for fine-grained categorization. In: Computer Vision Workshops (ICCVW), 2013 IEEE International Conference on, IEEE (2013) 554–561
47. Ge, Y., Zhang, R., Wu, L., Wang, X., Tang, X., Luo, P.: A versatile benchmark for detection, pose estimation, segmentation and re-identification of clothing images. CVPR (2019)
48. Loh, Y.P., Chan, C.S.: Getting to know low-light images with the exclusively dark dataset. Computer Vision and Image Understanding **178** (2019) 30–42

49. Khosla, A., Raju, A.S., Torralba, A., Oliva, A.: Understanding and predicting image memorability at a large scale. In: International Conference on Computer Vision (ICCV). (2015)
50. Khosla, A., Jayadevaprakash, N., Yao, B., Fei-Fei, L.: Novel dataset for fine-grained image categorization. In: First Workshop on Fine-Grained Visual Categorization, IEEE Conference on Computer Vision and Pattern Recognition, Colorado Springs, CO (June 2011)
51. Royer, A., Bousmalis, K., Gouws, S., Bertsch, F., Mosseri, I., Cole, F., Murphy, K.: Xgan: Unsupervised image-to-image translation for many-to-many mappings. In: Domain Adaptation for Visual Understanding. Springer (2020) 33–49
52. Kazemi, V., Sullivan, J.: Using richer models for articulated pose estimation of footballers. In: BMVC. (2012)
53. Eitz, M., Hays, J., Alexa, M.: How do humans sketch objects? ACM Trans. Graph. (Proc. SIGGRAPH) **31**(4) (2012) 44:1–44:10
54. Welinder, P., Branson, S., Mita, T., Wah, C., Schroff, F., Belongie, S., Perona, P.: Caltech-ucsd birds 200. (2010)
55. Kaiser, P., Wegner, J.D., Lucchi, A., Jaggi, M., Hofmann, T., Schindler, K.: Learning aerial image segmentation from online maps. IEEE Transactions on Geoscience and Remote Sensing **55**(11) (2017) 6054–6068
56. Xu, Z., Tao, D., Zhang, Y., Wu, J., Tsoi, A.C.: Architectural style classification using multinomial latent logistic regression. In: European Conference on Computer Vision, Springer (2014) 600–615
57. Yang, Y., Newsam, S.: Bag-of-visual-words and spatial extensions for land-use classification. In: Proceedings of the 18th SIGSPATIAL international conference on advances in geographic information systems. (2010) 270–279
58. Orekondy, T., Schiele, B., Fritz, M.: Towards a visual privacy advisor: Understanding and predicting privacy risks in images. In: IEEE International Conference on Computer Vision (ICCV). (2017)
59. Rothe, R., Timofte, R., Gool, L.V.: Deep expectation of real and apparent age from a single image without facial landmarks. International Journal of Computer Vision **126**(2-4) (2018) 144–157
60. Zamir, A., Shah, M.: Image geo-localization based on multiple nearest neighbor feature matching using generalized graphs (2014)
61. Luo, P., Wang, X., Tang, X.: Pedestrian parsing via deep decompositional network. In: Proceedings of the IEEE international conference on computer vision. (2013) 2648–2655
62. Eitz, M., Hildebrand, K., Boubekeur, T., Alexa, M.: Sketch-based image retrieval: Benchmark and bag-of-features descriptors. IEEE Transactions on Visualization and Computer Graphics **17**(11) (2011) 1624–1636
63. Peng, X., Usman, B., Kaushik, N., Hoffman, J., Wang, D., Saenko, K.: Visda: The visual domain adaptation challenge. arXiv preprint arXiv:1710.06924 (2017)
64. Richter, S.R., Vineet, V., Roth, S., Koltun, V.: Playing for data: Ground truth from computer games. In Leibe, B., Matas, J., Sebe, N., Welling, M., eds.: European Conference on Computer Vision (ECCV). Volume 9906 of LNCS., Springer International Publishing (2016) 102–118
65. Real, E., Shlens, J., Mazzocchi, S., Pan, X., Vanhoucke, V.: Youtube-boundingboxes: A large high-precision human-annotated data set for object detection in video. In: Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition. (2017) 5296–5305

66. Wang, J., Min, W., Hou, S., Ma, S., Zheng, Y., Wang, H., Jiang, S.: Logo-2k+: A large-scale logo dataset for scalable logo classification. arXiv preprint arXiv:1911.07924 (2019)