Lab Exercise 7- Create Service in Kubernetes

Objective:

- Understand the syntax and structure of a Kubernetes Service definition file (YAML).
- Learn to create different types of Services: ClusterIP, NodePort, and LoadBalancer.
- Comprehend how Services operate independently of specific Pods.

Prerequisites

- Kubernetes Cluster: Have a running Kubernetes cluster (locally using Minikube or kind, or a cloud-based service).
- kubectl: Install and configure kubectl to interact with your Kubernetes cluster.
- Basic Knowledge of YAML: Familiarity with YAML format will be helpful for understanding Kubernetes resource definitions.

Step-by-Step Guide

NodePort Service

To expose the Service on a port on each Node in the cluster, modify the Service type to NodePort.

Create a YAML file named nodeport-service.yaml with the following content:

PS C:\Users\upes\docker> notepad nodeport-service.yaml

apiVersion: v1 kind: Service metadata:

```
name: nodeport-service
spec:
selector:
app: my-app
ports:
- protocol: TCP
port: 80
targetPort: 80
nodePort: 30007 # A specific port in the range 30000-32767
type: NodePort
```

Explanation:

- The primary difference from the ClusterIP Service is the addition of nodePort, which specifies the static port on each Node.
- type: Set to NodePort, exposing the Service on a specific port across all Nodes.

Apply this YAML to create the NodePort Service:

```
kubectl apply -f nodeport-service.yaml

PS C:\Users\upes\docker> kubectl apply -f nodeport-service.yaml
service/nodeport-service created
```

Verify the Service:

```
kubectl get services
PS C:\Users\upes\docker> kubectl get services
NAME
                   TYPE
                               CLUSTER-IP
                                                EXTERNAL-IP
                                                                             AGE
                                                              PORT(S)
kubernetes
                   ClusterIP
                               10.96.0.1
                                                              443/TCP
                                                                             12m
                                               <none>
nodeport-service NodePort
                               10.109.76.163
                                               <none>
                                                              80:30007/TCP
                                                                             24s
```

You should see the nodeport-service listed with a NodePort and details about the port exposed.