Lab Exercise 5- Building a Docker Image for an HTML App Using Nginx

1. Setup

You will need:

- Docker installed on your machine.
- A simple HTML file for the app.

2. Step 1: Create the HTML File

Create a directory for your HTML app and place an index.html file in it.

```
mkdir nginx-html-app
```

Inside the nginx-html-app directory, create the HTML file.

touch index.html

Edit the index.html file with the following content (or any custom HTML content you want):

```
<!DOCTYPE html>
<html>
<head>
<title>Welcome to My Nginx HTML App</title>
</head>
<body>
<h1>Hello, Nginx Docker!</h1>
This is a simple HTML app served by Nginx in a Docker container.
</body>
</html>
```

3. Step 2: Create a Dockerfile

In the same directory, create a Dockerfile. This file will define how to build the Docker image using Nginx as the base image.

```
touch Dockerfile
```

Edit the Dockerfile and add the following content:

```
FROM nginx:latest

COPY index.html /usr/share/nginx/html/

EXPOSE 80
```

4. Step 3: Build the Docker Image

Now that you have the Dockerfile and index.html, it's time to build the Docker image. Run the following command to build the image, giving it a tag (e.g., nginx-html-app):

Docker will use the Nginx base image, copy your index.html into the appropriate directory, and build the image.

5. Step 4: Run the Docker Container

After building the image, you can run the container with the following command:

```
docker run -d -p 8080:80 nginx-html-app


C:\Users\Vibhav Khaneja\OneDrive\Desktop\nginx-html-app>docker run -d -p 8080:80 nginx-html-app
a7712577b64c1a8139e803e35a4fae3687b24b16f352831f6d71f216cf90d7f4

C:\Users\Vibhav Khaneja\OneDrive\Desktop\nginx-html-app>
```

This command runs the container in detached mode (-d) and maps port 8080 on your host machine to port 80 inside the container, where Nginx is serving your HTML app.

6. Step 5: Verify

Open a browser and go to http://localhost:8080. You should see your HTML page with the message "Hello, Nginx Docker!".



Hello, Nginx Docker!

This is a simple HTML app served by Nginx in a Docker container.

7. Step 6: Stop and Remove the Container

Once you're done, you can stop and remove the container:

```
docker ps # to see running containers

docker stop <container-id>

docker rm <container-id>
```

```
C:\Users\Vibhav Khaneja\OneDrive\Desktop\nginx-html-app>docker ps
CONTAINER ID IMAGE COMMAND CREATED
a7712577b64c nginx-html-app "/docker-entrypoint..." 2 minute
                                                                       STATUS
                                                                                      PORTS 0.0.0:8080->80/tcp
                                                                                                            NAMES
                                                                       Up 2 minutes
C:\Users\Vibhav Khaneja\OneDrive\Desktop\nginx-html-app>docker stop a7712577b64c
C:\Users\Vibhav Khaneja\OneDrive\Desktop\nginx-html-app>
C:\Users\Vibhav Khaneja\OneDrive\Desktop\nginx-html-app>docker rm a7712577b64c
a7712577b64c
C:\Users\Vibhav Khaneja\OneDrive\Desktop\nginx-html-app>docker ps
CONTAINER ID
                   IMAGE
                                COMMAND
                                             CREATED
                                                                                   NAMES
                                                        STATUS
                                                                      PORTS
C:\Users\Vibhav Khaneja\OneDrive\Desktop\nginx-html-app>
```