● **Anshu Kumar Sharma · 22322008** github.com/Anshu2003-commits/Kuku_assignment

Kuku AI Generalist · Problem 1 · Find the promos

the model picks the moment. code owns every timestamp.

An editor watches **all 50 episodes** of every show by hand, and Kuku ships a show a week, so the work grows with the catalogue while the editor's hours don't. This tool reads the timestamped screenplay and hands back a **ranked shortlist of 20 promos** for the editor to approve.

50 episodes
watched by hand per show, today

→

20 clips
ranked, every one 20–60 s, ready for approval

RULE 1
20–60 s
Inclusive. A continuous stretch preferred; multi-segment allowed.

RULE 2
hook ≤ 3 s
The hook has to land in the first three seconds.

RULE 3
cut on a beat
Never mid-line. Must make sense on its own, judged on the clip alone.

DOES IT WORK? · I LABELLED 30 CLIPS BY HAND

Each clip judged by reading its actual beats, never the model's description of its own pick.


Top 10 · n 10 — **60% clean · 90% usable**



Whole slate · n 18 — **44% clean · 89% usable**



Rejects · n 12 — **67% correctly dropped**



good · borderline · bad

MECHANICAL CHECKS · TRUST NOTHING THE PIPELINE SAYS

100%
timestamps are real beat boundaries

100%
promos within 20–60 s

200/200
candidates judged

0
API failures, 0 parse warnings

`eval/verify_outputs.py` re-parses the scripts independently.

HOW IT WORKS · THE MODEL NEVER EMITS A TIMESTAMP, SO A HALLUCINATED TIME IS IMPOSSIBLE BY CONSTRUCTION

01 · parse — CODE
3,727 beats
Every scene, line and action gets an id and exact times. 50 episodes, 0 warnings.

›

02 · candidates — CODE
200 candidates
Heuristics keep 4 per episode. Cost control: the per-show bill is fixed before the run.

›

03 · judge — AI
118 of 200 tightened
Gemini 3.1 Flash Lite picks beat ids and writes prose. 8 bad ids caught and logged.

›

04 · rank — CODE
20 shortlisted
Ranking, diversity and dedupe stay in code, so a human can read and argue with the policy.

›

05 · approve — EDITOR
3 output formats
md / csv / json. A shortlist for the editor, not a publishing decision.

WHO DOES WHAT · CODE IS DETERMINISTIC, AI ONLY JUDGES DRAMA

KEPT AS CODE
- Parsing, timestamps, beat ids
- 20–60 s limits, boundary snapping
- Candidate generation and pruning
- Ranking, diversity, dedupe

GIVEN TO THE AI
- Is this actually a hook?
- Does it cut on something unresolved?
- Would a stranger follow it?
- The hook / cliffhanger / why lines

WHY THIS PROBLEM

- The only one of the three with a **real input pack** and an output you can check against a stated definition.
- The pain is **concrete and recurring**: a new show every week.
- **Narrow enough to finish**: find moments and boundaries, not cut video.

Run on all 50 episodes of the input pack. Every number comes from `outputs/` and `run_report.json`.

● **Anshu Kumar Sharma · 22322008** github.com/Anshu2003-commits/Kuku_assignment

where it breaks · and what i fixed

ASSUMPTIONS · THE BRIEF WAS SILENT ON ALL SIX

01 Screenplay timestamps match the rendered video 1:1.

02 20–60 s inclusive; hook lands in the first 3 s.

03 Clips cut on beat boundaries, never mid-line.

04 "Makes sense on its own" is judged on the clip alone.

05 Multi-segment allowed; a continuous stretch preferred.

06 Spoiler risk rises with episode number (no audience data).

MEASURE, FIX, MEASURE AGAIN

Labelling found three defects. I fixed them and re-measured (`eval/before_after.md`).

Top-10 clean

~~30%~~ → **60%**

Reject precision (the cost)

~~77%~~ → **67%**

WHERE IT PICKS BADLY

6/30 **Soft endings.** The model scores cliffhanger 4/5 and the clip still cuts on a resolution; #3 ends on a flirt. Absolute 1–5 scoring is the cause.

4/12 **Too harsh at the gate.** Sampled rejects that were postable, one ending on the word "Arsenic."

198 **Spoiler risk is dead weight.** 198 of 200 scored 1 or 2. Standalone has sd 0.66; no clip scored below 2.

Reads prose, not frames. A striking image with no dialogue is underrated. A ceiling on any text-only approach, not a tunable bug.

Stitched promos ship flagged `stitch_unverified_continuity` since the tool can't confirm two shots cut together cleanly.

SCALE AND COST

200
calls per show

~230k
tokens per show

FREE-TIER LIMITS THAT BIND

15 / min
sets ~16 min wall time

500 / day
caps ~2.5 shows/day. I hit it in testing.

Paid tier: under a minute, cents per show. Cost scales with `--per-episode` , not episode length, so the budget is known before the run.

RUN IT

```
python run.py --input "<pack>"
  --out outputs/
```

`--provider` gemini | openai | groq | anthropic. Swap the model with one flag.

`--reuse-judgements` re-rank a past run for free. How the ranking was tuned without spending quota.

`--no-llm` runs with no API key.

WHERE AI TOOLS MISLED ME · ALL CAUGHT BY TESTS

Claude used a retired model id (404). So I list models from the API, not memory.

It assumed beats were time-ordered; tracks step back up to 1.0 s in 8 places. A test caught it.

My lexicon read "crackling hearth fire" as violence, a bandaging scene ranked 19th.

One run hung two hours on 2.2 s of CPU. The SDK has no default HTTP timeout.

Tools: Claude (Claude Code) for building · Gemini 3.1 Flash Lite as the judge inside the tool

BIGGER MODEL, SAME ANSWER

Seconds per judgement, identical scores



100× the time for no gain, so the light model judges.

WHAT I'D DO NEXT

Pairwise comparison instead of absolute 1–5 scores; both failures point there.

Learn ranking weights from real watch-through data.

Sample keyframes for top candidates to close the text-only gap.

Sources: outputs/ · run_report.json · eval/test_parse.py · eval/verify_outputs.py · eval/before_after.md