

SQL Project on Pizza Sales



Hello !

My name is Anshul Sharma and this is a project on pizza sales and in this I have utilized SQL queries to solve various questions that are related to pizza sales

Dataset

The name of this dataset is pizza sales and I have picked this dataset from github. This dataset basically involve 4 csv files they are:

1. order_detail.csv
2. orders.csv
3. pizza_types.csv
4. pizzas.csv

The Question we are going to solve in this project they are below:


1. Retrieve the total number of orders placed.
2. Calculate the total revenue generated from pizza sales.
3. Identify the highest-priced pizza.
4. Identify the most common pizza size ordered.
5. List the top 5 most ordered pizza types along with their quantities.
6. Join the necessary tables to find the total quantity of each pizza category ordered.
7. Determine the distribution of orders by hour of the day.
8. Join relevant tables to find the category-wise distribution of pizzas.
9. Group the orders by date and calculate the average number of pizzas ordered per day.
10. Determine the top 3 most ordered pizza types based on revenue.
11. Calculate the percentage contribution of each pizza type to total revenue.
12. Analyze the cumulative revenue generated over time.
13. Determine the top 3 most ordered pizza types based on revenue for each pizza category.

LETS
BEGIN.....



Retrieve the total number of orders placed.

```
SELECT
    COUNT(order_id) AS total_orders
FROM
    orders
```

Result Grid 	
	total_orders
▶	21350

Calculate the total revenue generated from pizza sales.

```
SELECT
    ROUND(SUM(order_details.quantity * pizzas.price),
          2) AS total_sales
FROM
    order_details
    JOIN
    pizzas ON pizzas.pizza_id = order_details.pizza_id
```

Result Grid	
	total_sales
▶	817860.05

Identify the highest-priced pizza.

```
SELECT
    pizza_types.name, pizzas.price
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
ORDER BY pizzas.price DESC
LIMIT 1;
```

Result Grid			Filter Rows:
	name	price	
▶	The Greek Pizza	35.95	



Identify the most common pizza size ordered.

```
SELECT
    pizzas.size,
    COUNT(order_details.order_details_id) AS order_count
FROM
    pizzas
    JOIN
    order_details ON pizzas.pizza_id = order_details.pizza_id
GROUP BY pizzas.size
ORDER BY order_count DESC
LIMIT 1;
```

Result Grid			File
	size	order_count	
▶	L	18526	

List the top 5 most ordered pizza types along with their quantities.

```
SELECT
    pizza_types.name, SUM(order_details.quantity) AS quantity
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
    JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY quantity DESC
LIMIT 5
```

Result Grid   Filter Rows: <input type="text"/>		
	name	quantity
▶	The Classic Deluxe Pizza	2453
	The Barbecue Chicken Pizza	2432
	The Hawaiian Pizza	2422
	The Pepperoni Pizza	2418
	The Thai Chicken Pizza	2371



Join the necessary tables to find the total quantity of each pizza category ordered.

```
SELECT
    pizza_types.category,
    SUM(order_details.quantity) AS quantity
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
    JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.category
ORDER BY quantity DESC;
```

Result Grid			Filter
	category	quantity	
▶	Classic	14888	
	Supreme	11987	
	Veggie	11649	
	Chicken	11050	



Determine the distribution of orders by hour of the day.

```
SELECT
    HOUR(order_time), COUNT(order_id)
FROM
    orders
GROUP BY HOUR(order_time);
```

Result Grid   Filter Rows: <input type="text"/>		
	HOUR(order_time)	COUNT(order_id)
▶	11	1231
	12	2520
	13	2455
	14	1472
	15	1468
	16	1920
	17	2336
	18	2399
	19	2009
	20	1642
	21	1198
	22	663
	23	28




Join relevant tables to find the category-wise distribution of pizzas.

```
SELECT
    category, COUNT(name)
FROM
    pizza_types
GROUP BY category
```

Result Grid   Filter Rows		
	category	COUNT(name)
▶	Chicken	6
	Classic	8
	Supreme	9
	Veggie	9



Group the orders by date and calculate the average number of pizzas ordered per day.

```
SELECT
    ROUND(AVG(quantity), 0)
FROM
    (SELECT
        orders.order_date, SUM(order_details.quantity) AS quantity
    FROM
        orders
    JOIN order_details ON orders.order_id = order_details.order_id
    GROUP BY orders.order_date) AS order_quantity;
```

Result Grid			 Filter Rows
	ROUND(AVG(quantity), 0)		
	138		



Determine the top 3 most ordered pizza types based on revenue.

```
SELECT
    pizza_types.name,
    SUM(order_details.quantity * pizzas.price) AS revenue
FROM
    pizza_types
    JOIN
    pizzas ON pizzas.pizza_type_id = pizza_types.pizza_type_id
    JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY revenue DESC
LIMIT 3 ;
```

Result Grid   Filter Rows: <input type="text"/>		
	name	revenue
▶	The Thai Chicken Pizza	43434.25
	The Barbecue Chicken Pizza	42768
	The California Chicken Pizza	41409.5



Calculate the percentage contribution of each pizza type to total revenue.

```
SELECT
    pizza_types.category,
    (SUM(order_details.quantity * pizzas.price) / (SELECT
        ROUND(SUM(order_details.quantity * pizzas.price),
            2) AS total_sales
    FROM
        order_details
        JOIN
        pizzas ON pizzas.pizza_id = order_details.pizza_id)) * 100 AS revenue
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
    JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.category
ORDER BY revenue DESC;
```

Result Grid   Filter Rows: <input type="text"/>		
	category	revenue
▶	Classic	26.90596025566967
	Supreme	25.45631126009862
	Chicken	23.955137556847287
	Veggie	23.682590927384577



Analyze the cumulative revenue generated over time.

```
select order_date ,  
sum(revenue) over(order by order_date) as cum_revenue  
from  
(select orders.order_date,  
sum(order_details.quantity * pizzas.price ) as revenue  
from order_details join pizzas  
on order_details.pizza_id = pizzas.pizza_id  
join orders  
on orders.order_id = order_details.order_id  
group by orders.order_date) as sales ;
```

Result Grid   Filter Rows: <input type="text"/>		
	order_date	cum_revenue
▶	2015-01-01	2713.8500000000000004
	2015-01-02	5445.75
	2015-01-03	8108.15
	2015-01-04	9863.6
	2015-01-05	11929.55
	2015-01-06	14358.5
	2015-01-07	16560.7

Determine the top 3 most ordered pizza types based on revenue for each pizza category.

```
select name, revenue
from
(select category ,name, revenue ,
rank() over(partition by category order by revenue desc) as rn
from
(select pizza_types.category, pizza_types.name,
sum((order_details.quantity)*pizzas.price) as revenue
from pizza_types join pizzas
on pizza_types.pizza_type_id= pizzas.pizza_type_id
join order_details
on order_details.pizza_id = pizzas.pizza_id
group by pizza_types.category, pizza_types.name) as a) as b
where rn <= 3 ;
```

Result Grid   Filter Rows: <input type="text"/>		
	name	revenue
▶	The Thai Chicken Pizza	43434.25
	The Barbecue Chicken Pizza	42768
	The California Chicken Pizza	41409.5
	The Classic Deluxe Pizza	38180.5
	The Hawaiian Pizza	32273.25
	The Pepperoni Pizza	30161.75
	The Spicy Italian Pizza	34831.25

THANK

YOU.....