



COB LIGHTS



Application :-

- Retail Stores
- Hotel Lobbies / Waiting Area
- Restaurants
- Museum
- Airport Lounges
- Modern gym / Spa

Features & Benefits

- High quality COB gives excellent quality of light distribution.
- No harmful UV & IR radiations.
- Environment-friendly as it does not contain Mercury.
- Optimal Thermal Management- Effective heat dissipation is critical for long term Led performance.
- Interchangeable Led optics.


Housing & Finish

Pressure Die- cast Aluminium Housing (Heat sink) with Power coated White Finish.

Electronic Driver

Powered by an built-in isolated electronic LED driver.

COB Lights



COB Downlighter Series

Ordering Code	System Power	Lumen (lm)	Dimension (mm) {Dia x (H)}
JVSLD 3(COB) DL	03W	300	63 x 50 x 40
JVSLD 6(COB) DL	06W	600	90 x 75 x 60
JVSLD 10(COB) DL	10W	1000	90 x 75 x 75
JVSLD 18(COB) DL	18W	1800	115 x 95 x 85
JVSLD 24(COB) DL	24W	2400	135 x 115 x 100
JVSLD 30(COB) DL	30W	3000	160 x 140 x 110
JVSLD 40(COB) DL	40W	4000	160 x 40 x 120
JVSLD 50(COB) DL	50W	5000	160 x 40 x 120



COB Downlighter Series (Zoom)

Ordering Code	System Power	Lumen (lm)	Dimension (mm) {Dia x (Cutout)}
JVSLDZ 12(COB)	12W	1200	87 x 75
JVSLDZ 20(COB)	20W	2000	145 x 130
JVSLDZ 25(COB)	25W	2500	125 x 115
JVSLDZ 30(COB)	30W	3000	190 x 160
JVSLDZ 40(COB)	40W	4000	185 x 150



COB Downlighter Series

Ordering Code	System Power	Lumen (lm)	Dimension (mm) {Size x (H)}
JVSLD 3RSM(COB)	03W	300	64 x 26
JVSLD 3SQSM(COB)	03W	300	58 x 26




COB Downlighter Series

Ordering Code	System Power	Lumen (lm)	Dimension (mm) {Dia x (H)}
JVSLD 2R(COB) DL	02W	200	30 x 25 x 20
JVSLD 2SQ(COB) DL	02W	200	30 x 25 x 20

Recessed movable cob spot light made up of aluminium die casted housing with Industrial Grade Constant Current Constant Voltage Led Driver.

COB Lights



COB Zoomer

Ordering Code	System Power	Lumen (lm)	Size(mm)	Cut Out(mm)
JVSRLDZ 12 x 2 (COB)	24W	2400	103 x 225	90 x 195
JVSRLDZ 25 x 2 (COB)	50W	5000	125 x 275	115 x 245
JVSRLDZ 30 x 2 (COB)	60W	6000	160 x 350	145 x 325
JVSRLDZ 12 x 3 (COB)	36W	3600	103 x 325	90 x 290
JVSRLDZ 25 x 3 (COB)	75W	7500	125 x 405	115 x 375
JVSRLDZ 30 x 3 (COB)	90W	9000	160 x 520	145 x 490



COB Exotica Series

Ordering Code	System Power	Lumen (lm)	Dimension (mm) {Size x Cutout x (H)}
JVSLD NT 10SQ / RD	10W	1000	90 x 82 x 85
JVSLDOV 10(COB)	10W	1000	90 x 80 x 90
JVSLDDEEP 10(COB)	10W	1000	90 x 80 x 90
JVSLDPH 10(COB)	10W	1000	90 x 80 x 90
JVSLDHM 10(COB)	10W	1000	90 x 80 x 90



COB BOXER

Ordering Code	System Power	Lumen (lm)	Dimension (mm) {Size x Cutout x (H)}
JVSLDBLW 12(COB)	12W	1200	134 x 120 x 85
JVSLDBLW 25(COB)	25W	2500	155 x 140 x 115
JVSLDBLW 12x2(COB)	24W	2400	134 x 120 x 85
JVSLDBLW 25x2(COB)	50W	5000	155 x 140 x 115
JVSLDBLW 12x3(COB)	36W	3600	164 x 120 x 85
JVSLDBLW 25x3(COB)	75W	7500	155 x 140 x 115



COB STYLUS

Ordering Code	System Power	Lumen (lm)	Dimension (mm) {Size x Cutout}
JVSTRR 25(COB)	25W	2500	160 x 145

Professional Series: Recessed cob spot light made up of aluminium caste housing rim with Industrial Grade Constant Current Constant Voltage Led Driver.

Life - ≥ 50,000 Hrs, Working Humidity - 10% to 90% R.H. , Working Temperature - 10° to 50°

COB Lights



COB Focus Lighting

Ordering Code	System Power	Lumen (lm)	Dimension (mm) {DIA x (H)}
JVSTR 10 W COB(TL)	10W	1000	60 x 105
JVSTR 18 W COB(TL)	18W	1800	78 x 150
JVSTR 30 W COB(TL)	30W	3000	98 x 175
JVSTR 50 W COB(TL)	50W	5000	120 x 200

Available in Black & White Body.



SPOTLIGHT

Ordering Code	System Power	Lumen (lm)	Dimension (mm) {Cutout x (H)}
JVSTR 10 W COB(SL)	10W	1000	60 x 105
JVSTR 15 W COB(SL)	15W	1500	78 x 150
JVSTR 30 W COB(SL)	30W	3000	98 x 175
JVSTR 50 W COB(SL)	50W	5000	120 x 200
JVSTR Track Patti (Track per Meter)			

Available in Black & White Body.



Ordering Code	System Power	Lumen (lm)	Dimension (mm) {Dia x (H)}
JVSLD 10RSM (COB)	10W	1000	100 x 120
JVSLD 18RSM (COB)	18W	1800	100 x 150
JVSLD 30RSM (COB)	30W	3000	110 x 170

Available in Black & White Body.



Cob based track light made up of aluminium casted housing & aluminium extrusion based heat sink complete with Industrial Grade Constant Current Constant Voltage Led Driver.